



# SAFETY DATA SHEET

MULTIBASE, INC.

Product name: MOLYKOTE® D-321 R Anti-Friction Coating

Issue Date: 05/22/2020

Print Date: 07/03/2020

MULTIBASE, INC. encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

---

## 1. IDENTIFICATION

---

Product name: MOLYKOTE® D-321 R Anti-Friction Coating

Recommended use of the chemical and restrictions on use

Identified uses: Lubricants and lubricant additives

### COMPANY IDENTIFICATION

MULTIBASE, INC.  
3835 COPLEY RD  
COPLEY OH 44321  
UNITED STATES

Customer Information Number:

833-338-7668

SDSQuestion-NA@dupont.com

### EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1-800-424-9300

Local Emergency Contact: 800-424-9300

---

## 2. HAZARDS IDENTIFICATION

---

### Hazard classification

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids - Category 3

Eye irritation - Category 2A

Specific target organ toxicity - single exposure - Category 3

Specific target organ toxicity - repeated exposure - Category 1

Aspiration hazard - Category 1

### Label elements

#### Hazard pictograms



Signal word: **DANGER!**

**Hazards**

Flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

**Precautionary statements****Prevention**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

**Response**

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/ attention if you feel unwell.

Do NOT induce vomiting.

If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Storage**

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

**Disposal**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

Static-accumulating flammable liquid.

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

**Chemical nature:** Inorganic and organic compounds, in mineral oil

This product is a mixture.

---

**Component****CASRN****Concentration**

---

n-Butyl Acetate	123-86-4	>= 30.0 - <= 40.0 %
Naphtha (petroleum), hydrodesulfurized heavy	64742-82-1	>= 30.0 - <= 40.0 %
Molybdenum disulfide	1317-33-5	>= 10.0 - <= 20.0 %
Polybutyl titanate	9022-96-2	>= 10.0 - <= 20.0 %
Graphite	7782-42-5	>= 1.0 - <= 5.0 %
Butanol	71-36-3	>= 1.0 - <= 5.0 %

---

## 4. FIRST AID MEASURES

---

### Description of first aid measures

#### General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

**Inhalation:** Move person to fresh air. If not breathing, give artificial respiration; if by mouth to mouth use rescuer protection (pocket mask, etc). If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

**Skin contact:** Wash off with plenty of water. Suitable emergency safety shower facility should be available in work area.

**Eye contact:** Immediately flush eyes with water; remove contact lenses, if present, after the first 5 minutes, then continue flushing eyes for at least 15 minutes. Obtain medical attention without delay, preferably from an ophthalmologist. Suitable emergency eye wash facility should be immediately available.

**Ingestion:** Do not induce vomiting. Call a physician and/or transport to emergency facility immediately.

#### Most important symptoms and effects, both acute and delayed:

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

#### Indication of any immediate medical attention and special treatment needed

**Notes to physician:** Maintain adequate ventilation and oxygenation of the patient. Because rapid absorption may occur through the lungs if aspirated and cause systemic effects, the decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient. Skin contact may aggravate preexisting dermatitis.

---

## 5. FIREFIGHTING MEASURES

---

**Suitable extinguishing media:** Water spray Alcohol-resistant foam Carbon dioxide (CO<sub>2</sub>) Dry chemical

**Unsuitable extinguishing media:** High volume water jet Do not use direct water stream.

**Special hazards arising from the substance or mixture**

**Hazardous combustion products:** Carbon oxides Sulphur oxides

**Unusual Fire and Explosion Hazards:** Flash back possible over considerable distance. Exposure to combustion products may be a hazard to health. Vapours may form explosive mixtures with air.

**Advice for firefighters**

**Fire Fighting Procedures:** Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Contain fire water run-off if possible. Fire water run-off, if not contained, may cause environmental damage. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Do not use a solid water stream as it may scatter and spread fire.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

**Special protective equipment for firefighters:** In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

**Personal precautions, protective equipment and emergency procedures:** Remove all sources of ignition. Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

**Environmental precautions:** Do not release the product to the aquatic environment above defined regulatory levels. Prevent further leakage or spillage if safe to do so. Prevent spreading over a wide area (e.g. by containment or oil barriers). Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

**Methods and materials for containment and cleaning up:** Non-sparking tools should be used. Soak up with inert absorbent material. Suppress (knock down) gases/vapours/mists with a water spray jet. Clean up remaining materials from spill with suitable absorbant. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

See sections: 7, 8, 11, 12 and 13.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Do not get on skin or clothing. Do not breathe vapours or spray mist. Do not swallow. Do not get in eyes. Keep container tightly closed. Keep away from heat and sources of ignition. Take precautionary measures against static discharges. Take care to prevent spills, waste and minimize release to the environment. Non-sparking tools should be used. Handle in accordance with good industrial hygiene and safety practice.

Use with local exhaust ventilation. Use only in an area equipped with explosion proof exhaust ventilation. Ensure all equipment is electrically grounded before beginning transfer operations. This material can accumulate static charge due to its inherent physical properties and can therefore cause an electrical ignition source to vapors. In order to prevent a fire hazard, as bonding and grounding may be insufficient to remove static electricity, it is necessary to provide an inert gas purge before beginning transfer operations. Restrict flow velocity in order to reduce the accumulation of static electricity. Ground and bond container and receiving equipment.

**Conditions for safe storage:** Keep in properly labelled containers. Store locked up. Keep tightly closed. Keep in a cool, well-ventilated place. Store in accordance with the particular national regulations. Keep away from heat and sources of ignition.

Do not store with the following product types: Strong oxidizing agents. Organic peroxides. Flammable solids. Pyrophoric liquids. Pyrophoric solids. Self-heating substances and mixtures. Substances and mixtures, which in contact with water, emit flammable gases. Explosives. Gases. Unsuitable materials for containers: None known.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value
n-Butyl Acetate	Dow IHG	TWA	75 ppm
	Dow IHG	STEL	150 ppm
	OSHA Z-1	TWA	710 mg/m3 150 ppm
	Further information: (b): The value in mg/m3 is approximate.		
	CAL PEL	PEL	710 mg/m3 150 ppm
	CAL PEL	STEL	950 mg/m3 200 ppm
	ACGIH	TWA	50 ppm
	Further information: URT irr: Upper Respiratory Tract irritation; eye irr: Eye irritation		
	ACGIH	STEL	150 ppm
	Further information: URT irr: Upper Respiratory Tract irritation; eye irr: Eye irritation		
	OSHA Z-1	TWA	2,000 mg/m3 500 ppm
	Further information: (b): The value in mg/m3 is approximate.		
Naphtha (petroleum), hydrodesulfurized heavy	OSHA P0	TWA	1,600 mg/m3 400 ppm
	OSHA Z-1	TWA total dust	15 mg/m3 , Molybdenum
	ACGIH	TWA Inhalable particulate matter	10 mg/m3 , Molybdenum
	ACGIH	TWA Respirable particulate matter	3 mg/m3 , Molybdenum

	CAL PEL	PEL Total dust	10 mg/m3 , Molybdenum
	CAL PEL	PEL respirable dust fraction	3 mg/m3 , Molybdenum
	Further information: (n): The concentration and percentage of the particulate used for this limit are determined from the fraction passing a size selector with the following characteristics: Aerodynamic Diameter in Micrometers (unit density sphere)..... Percent Passing Selector 0 ..... 100 1 ..... 97 2 ..... 91 3 ..... 74 4 ..... 50 5 ..... 30 6 ..... 17 7 ..... 9 8 ..... 5 10 ..... 1		
Graphite	OSHA Z-1		See Further information
	Further information: (3): See table Z-3		
	OSHA Z-3	TWA Dust	15 Million particles per cubic foot
	Further information: a: Based on impinger samples counted by light-field techniques.; mppcf X 35.3 = million particles per cubic meter = particles per c.c		
	OSHA Z-1	TWA total dust	15 mg/m3
	OSHA Z-1	TWA respirable fraction	5 mg/m3
	ACGIH	TWA Respirable particulate matter	2 mg/m3
	Further information: pneumoconiosis: Pneumoconiosis		
	CAL PEL	PEL Total dust	10 mg/m3
	CAL PEL	PEL respirable dust fraction	5 mg/m3
	Further information: (n): The concentration and percentage of the particulate used for this limit are determined from the fraction passing a size selector with the following characteristics: Aerodynamic Diameter in Micrometers (unit density sphere)..... Percent Passing Selector 0 ..... 100 1 ..... 97 2 ..... 91 3 ..... 74 4 ..... 50 5 ..... 30 6 ..... 17 7 ..... 9 8 ..... 5 10 ..... 1		
	CAL PEL	PEL Respirable dust	2.5 mg/m3
	NIOSH REL	TWA Respirable	2.5 mg/m3
	Further information: Also see specific listing for Graphite (synthetic).		
Butanol	ACGIH	TWA	20 ppm
	Further information: URT irr: Upper Respiratory Tract irritation; eye irr: Eye irritation		
	OSHA Z-1	TWA	300 mg/m3 100 ppm
	Further information: (b): The value in mg/m3 is approximate.		
	CAL PEL	C	150 mg/m3 50 ppm
	Further information: S: Skin		
	NIOSH REL	C	150 mg/m3 50 ppm
	Further information: skin: Potential for dermal absorption		

The following substance(s), which have Occupational Exposure Limit(s) (OEL), may be formed during handling or processing:  
butanol

**Exposure controls**

**Engineering controls:** Use engineering controls to maintain airborne level below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use only with adequate ventilation. Local exhaust ventilation may be necessary for some operations.

#### Individual protection measures

**Eye/face protection:** Use chemical goggles.

#### Skin protection

**Hand protection:** Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Chlorinated polyethylene. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Examples of acceptable glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

**Other protection:** Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

**Respiratory protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, use an approved respirator. Selection of air-purifying or positive-pressure supplied-air will depend on the specific operation and the potential airborne concentration of the material. For emergency conditions, use an approved positive-pressure self-contained breathing apparatus. The following should be effective types of air-purifying respirators: Organic vapor cartridge with a particulate pre-filter.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### Appearance

Physical state	liquid
Color	dark grey
Odor	solvent-like
Odor Threshold	No data available
pH	No data available
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	> 100 °C (> 212 °F)
Flash point	closed cup 23 °C (73 °F)
Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not applicable
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	No data available
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	1.07
Water solubility	No data available

<b>Partition coefficient: n-octanol/water</b>	No data available
<b>Auto-ignition temperature</b>	No data available
<b>Decomposition temperature</b>	No data available
<b>Kinematic Viscosity</b>	< 20.5 mm <sup>2</sup> /s at 25 °C (77 °F)
<b>Explosive properties</b>	Not explosive
<b>Oxidizing properties</b>	The substance or mixture is not classified as oxidizing.
<b>Molecular weight</b>	No data available
<b>Particle size</b>	Not applicable

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** Not classified as a reactivity hazard.

**Chemical stability:** Stable under normal conditions.

**Possibility of hazardous reactions:** Can react with strong oxidizing agents. Vapours may form explosive mixture with air. Flammable liquid and vapour.

**Conditions to avoid:** Heat, flames and sparks.

**Incompatible materials:** Oxidizing agents

**Hazardous decomposition products:** Butanol.

---

## 11. TOXICOLOGICAL INFORMATION

---

*Toxicological information appears in this section when such data is available.*

### **Acute toxicity**

#### **Acute oral toxicity**

Product test data not available. Refer to component data.

#### **Acute dermal toxicity**

Product test data not available. Refer to component data.

#### **Acute inhalation toxicity**

Product test data not available. Refer to component data.

### **Skin corrosion/irritation**

Product test data not available. Refer to component data.

### **Serious eye damage/eye irritation**



Product test data not available. Refer to component data.

**Sensitization**

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Product test data not available. Refer to component data.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Product test data not available. Refer to component data.

**Carcinogenicity**

Product test data not available. Refer to component data.

**Teratogenicity**

Product test data not available. Refer to component data.

**Reproductive toxicity**

Product test data not available. Refer to component data.

**Mutagenicity**

Product test data not available. Refer to component data.

**Aspiration Hazard**

Aspiration into the lungs may occur during ingestion or vomiting, resulting in rapid absorption and injury to other body systems.

**COMPONENTS INFLUENCING TOXICOLOGY:**

**n-Butyl Acetate**

**Acute oral toxicity**

LD50, Rat, male, 12,789 mg/kg

LD50 Oral, Rat, female, 10,760 mg/kg

**Acute dermal toxicity**

LD50, Rabbit, male and female, > 14,112 mg/kg

**Acute inhalation toxicity**

The LC50 has not been determined.

**Skin corrosion/irritation**

Brief contact is essentially nonirritating to skin.  
Prolonged contact may cause severe skin irritation with local redness and discomfort.  
May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

May cause moderate eye irritation.  
Corneal injury is unlikely.  
Vapor may cause eye irritation experienced as mild discomfort and redness.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause drowsiness or dizziness.

Route of Exposure: Inhalation  
Target Organs: Nervous system

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In animals, effects have been reported on the following organs:  
Nasal tissue.

**Carcinogenicity**

No relevant data found.

**Teratogenicity**

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

**Reproductive toxicity**

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals. In animal studies, did not interfere with fertility.

**Mutagenicity**

In vitro genetic toxicity studies were negative.

**Naphtha (petroleum), hydrodesulfurized heavy**

**Acute oral toxicity**

Based on data from similar materials LD50, Rat, male and female, > 5,000 mg/kg

**Acute dermal toxicity**

Based on data from similar materials LD50, Rat, male and female, > 4,000 mg/kg No deaths occurred at this concentration.

**Acute inhalation toxicity**

Based on data from similar materials LC50, Rat, 4 Hour, vapour, > 13.1 mg/l

**Skin corrosion/irritation**

Brief contact may cause slight skin irritation with local redness.  
Prolonged or repeated skin contact can cause the following:  
May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

May cause slight temporary eye irritation.  
Corneal injury is unlikely.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause drowsiness or dizziness.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

For similar material(s):  
In humans, effects have been reported on the following organs:  
Central nervous system.

**Carcinogenicity**

No relevant data found.

**Teratogenicity**

For similar material(s): Has caused birth defects in laboratory animals only at doses toxic to the mother. Has been toxic to the fetus in laboratory animals at doses toxic to the mother.

**Reproductive toxicity**

For similar material(s): In animal studies, did not interfere with fertility.

**Mutagenicity**

For similar material(s): In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Molybdenum disulfide**

**Acute oral toxicity**

LD50, Rat, > 2,000 mg/kg No deaths occurred at this concentration.

**Acute dermal toxicity**

LD50, Rat, male and female, > 2,000 mg/kg No deaths occurred at this concentration.

**Acute inhalation toxicity**

LC50, Rat, 4 Hour, dust/mist, > 2.82 mg/l No deaths occurred at this concentration.

**Skin corrosion/irritation**

Brief contact is essentially nonirritating to skin.

Prolonged contact may cause slight skin irritation with local redness.

**Serious eye damage/eye irritation**

May cause slight temporary eye irritation.

Corneal injury is unlikely.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

No relevant data found.

**Carcinogenicity**

No relevant data found.

**Teratogenicity**

No relevant data found.

**Reproductive toxicity**

No relevant data found.

**Mutagenicity**

For similar material(s): In vitro genetic toxicity studies were negative.

**Polybutyl titanate**

**Acute oral toxicity**

LD50, Rat, > 2,000 mg/kg

**Acute dermal toxicity**

LD50, Rat, > 5,000 mg/kg

**Acute inhalation toxicity**

The LC50 has not been determined.

**Skin corrosion/irritation**

Essentially nonirritating to skin.

**Serious eye damage/eye irritation**

May cause severe eye irritation.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

No relevant data found.

**Carcinogenicity**

No relevant data found.

**Teratogenicity**

No relevant data found.

**Reproductive toxicity**

No relevant data found.

**Mutagenicity**

No relevant data found.

**Graphite**

**Acute oral toxicity**

LD50, Rat, > 2,000 mg/kg OECD Test Guideline 401 No deaths occurred at this concentration.

**Acute dermal toxicity**

The dermal LD50 has not been determined.

**Acute inhalation toxicity**

LC50, Rat, 4 Hour, dust/mist, > 2 mg/l OECD Test Guideline 403 No deaths occurred at this concentration.

**Skin corrosion/irritation**

Essentially nonirritating to skin.

**Serious eye damage/eye irritation**

May cause slight temporary eye irritation.

May cause slight temporary corneal injury.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs.

**Carcinogenicity**

No relevant data found.

**Teratogenicity**

Did not cause birth defects or any other fetal effects in laboratory animals.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction.

**Mutagenicity**

In vitro genetic toxicity studies were negative.

**Butanol**

**Acute oral toxicity**

LD50, Rat, female, 2,292 mg/kg OECD 401 or equivalent

**Acute dermal toxicity**

LD50, Rabbit, male, 3,430 mg/kg OECD Test Guideline 402

**Acute inhalation toxicity**

LC50, Rat, male and female, 4 Hour, vapour, > 17.76 mg/l OECD Test Guideline 403 No deaths occurred at this concentration.

**Skin corrosion/irritation**

Brief contact may cause skin irritation with local redness.  
Prolonged contact may cause severe skin irritation with local redness and discomfort.  
May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

May cause severe eye irritation.  
May cause moderate corneal injury.  
Vapor may cause eye irritation experienced as mild discomfort and redness.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause drowsiness or dizziness.

Route of Exposure: Inhalation

Target Organs: Nervous system

May cause respiratory irritation.

Route of Exposure: Inhalation

Target Organs: Respiratory Tract

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Butanol has been reported to cause eye effects (tearing, blurred vision, sensitivity to light, temporary corneal effects), hearing loss and vertigo.

**Carcinogenicity**

No relevant data found.

**Teratogenicity**

n-Butanol has caused birth defects and has been toxic to the fetus in laboratory animals at doses nontoxic to the mother. Dose levels producing these effects were many times higher than any dose levels expected from exposure due to use.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction.

**Mutagenicity**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Carcinogenicity****Component**

Naphtha (petroleum),  
hydrodesulfurized heavy

**List**

IARC

**Classification**

Group 2B: Possibly carcinogenic to  
humans

---

## 12. ECOLOGICAL INFORMATION

---

*Ecotoxicological information appears in this section when such data is available.*

**Toxicity****n-Butyl Acetate****Acute toxicity to fish**

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 18 mg/l

**Acute toxicity to aquatic invertebrates**

LC50, Daphnia magna (Water flea), 48 Hour, 44 mg/l

**Acute toxicity to algae/aquatic plants**

ErC50, Desmodesmus subspicatus (green algae), 72 Hour, Growth rate inhibition, 648 mg/l

**Toxicity to bacteria**

EC50, Bacteria, 16 Hour, > 1,000 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), 21 d, 23 mg/l

**Naphtha (petroleum), hydrodesulfurized heavy****Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

Based on data from similar materials

LL50, Oncorhynchus mykiss (rainbow trout), 96 Hour, 10 - 30 mg/l, OECD Test Guideline 203

**Acute toxicity to aquatic invertebrates**

Based on data from similar materials

EL50, Daphnia magna (Water flea), 48 Hour, 10 - 22 mg/l, OECD Test Guideline 202

**Acute toxicity to algae/aquatic plants**

Based on data from similar materials

EL50, Pseudokirchneriella subcapitata (green algae), 72 Hour, 4.6 - 10 mg/l, OECD Test Guideline 201

Based on data from similar materials

NOELR, Pseudokirchneriella subcapitata (green algae), 72 Hour, 0.22 mg/l, OECD Test Guideline 201

**Chronic toxicity to aquatic invertebrates**

Based on data from similar materials  
NOELR, Daphnia magna (Water flea), 21 d, 0.097 mg/l

**Molybdenum disulfide**

**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).  
For similar material(s):  
LC50, Fish, 96 Hour, > 100 mg/l

**Acute toxicity to aquatic invertebrates**

Based on data from similar materials  
EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l

**Acute toxicity to algae/aquatic plants**

Based on data from similar materials  
ErC50, algae, 72 Hour, Growth rate, > 100 mg/l

**Toxicity to bacteria**

EC50, 30 Hour, Respiration rates., > 100 mg/l

**Chronic toxicity to fish**

Based on data from similar materials  
NOEC, Fish, 34 d, > 10 mg/l

**Chronic toxicity to aquatic invertebrates**

Based on data from similar materials  
NOEC, Daphnia magna, 21 d, > 10 mg/l

**Polybutyl titanate**

**Acute toxicity to fish**

Not expected to be acutely toxic to aquatic organisms.

**Graphite**

**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).  
LC50, Danio rerio (zebra fish), 96 Hour, > 100 mg/l, OECD Test Guideline 203

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, > 100 mg/l, OECD Test Guideline 202

**Acute toxicity to algae/aquatic plants**

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 100 mg/l, OECD Test Guideline 201

**Toxicity to bacteria**

EC50, 3 Hour, > 1,012.5 mg/l, OECD Test Guideline 209

**Butanol**

**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 1,376 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), static test, 48 Hour, 1,328 mg/l, OECD Test Guideline 202 or Equivalent

**Acute toxicity to algae/aquatic plants**

EC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate inhibition, 225 mg/l, OECD Test Guideline 201 or Equivalent

**Toxicity to bacteria**

EC50, Pseudomonas putida, static test, 17 Hour, Growth inhibition, > 1,000 mg/l, DIN 38412

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), semi-static test, 21 d, number of offspring, 4.1 mg/l

**Toxicity to Above Ground Organisms**

Material is practically non-toxic to birds on an acute basis (LD50 > 2000 mg/kg).

**Persistence and degradability**

**n-Butyl Acetate**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 83 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301D or Equivalent

**Theoretical Oxygen Demand:** 2.20 mg/mg Estimated.

**Photodegradation**

**Sensitization:** OH radicals

**Atmospheric half-life:** 2.32 d

**Method:** Estimated.

**Naphtha (petroleum), hydrodesulfurized heavy**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

Based on data from similar materials 10-day Window: Pass

**Biodegradation:** 74.7 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301F

**Molybdenum disulfide**

**Biodegradability:** Biodegradability is not applicable to inorganic substances.

**Polybutyl titanate**

**Biodegradability:** Biodegradability is not applicable to inorganic substances.

**Graphite**

**Biodegradability:** Biodegradation is not applicable.



**Butanol**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 98 %

**Exposure time:** 19 d

**Method:** OECD Test Guideline 301E or Equivalent

**Theoretical Oxygen Demand:** 2.59 mg/mg Estimated.

**Chemical Oxygen Demand:** 2.45 mg/mg Estimated.

**Photodegradation**

**Test Type:** Half-life (indirect photolysis)

**Sensitization:** OH radicals

**Atmospheric half-life:** 55.9 Hour

**Method:** Estimated.

**Bioaccumulative potential****n-Butyl Acetate**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** Pow: 3.2 at 25 °C Measured

**Bioconcentration factor (BCF):** 15 Fish Estimated.

**Naphtha (petroleum), hydrodesulfurized heavy**

**Bioaccumulation:** Based on data from similar materials

**Partition coefficient: n-octanol/water(log Pow):** > 4

**Molybdenum disulfide**

**Bioaccumulation:** Partitioning from water to n-octanol is not applicable.

**Polybutyl titanate**

**Bioaccumulation:** No relevant data found.

**Graphite**

**Bioaccumulation:** No relevant data found.

**Butanol**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 1 at 25 °C OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

**Bioconcentration factor (BCF):** 3.16 Fish Estimated.

**Mobility in soil****n-Butyl Acetate**

Potential for mobility in soil is very high (Koc between 0 and 50).

**Partition coefficient (Koc):** 19 - 70 Estimated.

**Naphtha (petroleum), hydrodesulfurized heavy**

No relevant data found.

**Molybdenum disulfide**

No relevant data found.

**Polybutyl titanate**

No relevant data found.

**Graphite**

No relevant data found.

**Butanol**

Potential for mobility in soil is very high (Koc between 0 and 50).

**Partition coefficient (Koc):** 2.4 Estimated.

---

## 13. DISPOSAL CONSIDERATIONS

---

**Disposal methods:** DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

**Treatment and disposal methods of used packaging:** Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

---

## 14. TRANSPORT INFORMATION

---

**DOT**

<b>Proper shipping name</b>	Flammable liquids, n.o.s.(n-Butyl acetate, Naphtha (petroleum), hydrodesulfurized heavy)
<b>UN number</b>	UN 1993
<b>Class</b>	3
<b>Packing group</b>	III
<b>Marine pollutant</b>	Naphtha (petroleum), hydrodesulfurized heavy, Zinc oxide
<b>Reportable Quantity</b>	n-Butyl acetate

**Classification for SEA transport (IMO-IMDG):**

<b>Proper shipping name</b>	FLAMMABLE LIQUID, N.O.S.(n-Butyl acetate, Naphtha (petroleum), hydrodesulfurized heavy)
<b>UN number</b>	UN 1993
<b>Class</b>	3
<b>Packing group</b>	III

**Marine pollutant** Naphtha (petroleum), hydrodesulfurized heavy, Zinc oxide  
**Transport in bulk** Consult IMO regulations before transporting ocean bulk  
**according to Annex I or II**  
**of MARPOL 73/78 and the**  
**IBC or IGC Code**

**Classification for AIR transport (IATA/ICAO):**

**Proper shipping name** Flammable liquid, n.o.s.(n-Butyl acetate, Naphtha (petroleum), hydrodesulfurized heavy)  
**UN number** UN 1993  
**Class** 3  
**Packing group** III

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

**15. REGULATORY INFORMATION**

---

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312**

Flammable (gases, aerosols, liquids, or solids)  
 Hazard not otherwise classified (physical hazards)  
 Serious eye damage or eye irritation  
 Specific target organ toxicity (single or repeated exposure)  
 Aspiration hazard

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313**

The following components are subject to reporting levels established by SARA Title III, Section 313:

<b>Components</b>	<b>CASRN</b>
Butanol	71-36-3
Zinc 5-nitroisophthalate	60580-61-2
Zinc oxide	1314-13-2

**Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103**

Calculated RQ exceeds reasonably attainable upper limit.

<b>Components</b>	<b>CASRN</b>	<b>RQ (RCRA Code)</b>
Butanol	71-36-3	5000 lbs RQ
Butanol	71-36-3	100 lbs RQ (F003)
n-Butyl Acetate	123-86-4	5000 lbs RQ

**Pennsylvania Right To Know**

The following chemicals are listed because of the additional requirements of Pennsylvania law:

**Components**

n-Butyl Acetate  
 Naphtha (petroleum), hydrodesulfurized heavy  
 Molybdenum disulfide  
 Polybutyl titanate  
 Graphite  
 Butanol

**CASRN**

123-86-4  
 64742-82-1  
 1317-33-5  
 9022-96-2  
 7782-42-5  
 71-36-3

**California Prop. 65**

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

**United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**16. OTHER INFORMATION****Hazard Rating System****NFPA**

Health	Flammability	Instability
2	3	0

**HMIS**

Health	Flammability	Physical Hazard
3*	3	0

\* = Chronic Effects (See Hazards Identification)

**Revision**

Identification Number: 2287978 / A734 / Issue Date: 05/22/2020 / Version: 11.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

**Legend**

ACGIH	USA. ACGIH Threshold Limit Values (TLV)
C	Ceiling value not be exceeded at any time.
CAL PEL	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
Dow IHG	Dow Industrial Hygiene Guideline
NIOSH REL	USA. NIOSH Recommended Exposure Limits
OSHA P0	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
PEL	Permissible exposure limit
STEL	Short Term Exposure Limit (STEL):
TWA	Time Weighted Average (TWA):

**Full text of other abbreviations**

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

#### Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

MULTIBASE, INC. urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US