# **Material Safety Data Sheet**





Revision Number: 002.1 Issue date: 03/21/2011

# 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:Moly PasteIDH number:226696Product type:LubricantItem number:51049Region:United States

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Region: United S Contact information: Telephone: 860.571.5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

Physical state:pasteHEALTH:1Color:grey, to, blackFLAMMABILITY:1Odor:Mild, PetroleumPHYSICAL HAZARD:0

Personal Protection: See MSDS Section 8

CAUTION: MAY CAUSE EYE AND SKIN IRRITATION.

Relevant routes of exposure: Skin, Eyes

**Potential Health Effects** 

Inhalation: May cause respiratory tract irritation. This product has low volatility and is not expected to

cause respiratory tract irritation during normal conditions of use.

**Skin contact:** Prolonged or repeated contact may cause irritation.

**Eye contact:** Contact with eyes will cause irritation.

**Ingestion:** Principal hazard of ingestion is aspiration into the lungs and subsequent pneumonitis. Ingestion

may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Molybdenum disulphide	1317-33-5	60 - 100
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	1 - 5
Mineral oil light naphthenic hydrotreat. <3% DMSO	64742-53-6	1 - 5

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Wash with soap and water. If symptoms develop and persist, get medical

attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: Aspiration may cause pulmonary edema and pneumonitis. Do not induce

vomiting. Get medical attention.

## 5. FIRE FIGHTING MEASURES

Flash point: 160 °C (320°F)

Autoignition temperature: Not determined

Flammable/Explosive limits - lower: Not determined

Flammable/Explosive limits - upper: Not determined

Extinguishing media: foam Carbon dioxide. Dry chemical. Water spray or fog.

Special firefighting procedures: None

Unusual fire or explosion hazards: None

**Hazardous combustion products:** Oxides of carbon.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow material to contaminate ground water system.

Clean-up methods: Follow all local, state, federal and provincial regulations for disposal. Scrape

up as much material as possible. Clean residue with soap and water.

## 7. HANDLING AND STORAGE

Handling: Wash thoroughly after handling. Keep container closed. Avoid contact with

eyes, skin and clothing.

Storage: Keep in a cool, well ventilated area.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Molybdenum disulphide	10 mg/m3 TWA (as Mo) Inhalable fraction. 3 mg/m3 TWA (as Mo) Respirable fraction.	15 mg/m3 TWA (as Mo) Total dust.	None	None
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA mist 10 mg/m3 STEL mist 5 mg/m3 TWA Inhalable fraction.	5 mg/m3 TWA mist 500 ppm (2,000 mg/m3) TWA 5 mg/m3 TWA Mist.	None	None
Mineral oil light naphthenic hydrotreat. <3% DMSO	5 mg/m3 TWA Inhalable fraction.	500 ppm (2,000 mg/m3) TWA 5 mg/m3 TWA Mist.	None	None

Engineering controls: Use only with adequate ventilation. Local exhaust ventilation is recommended

when general ventilation is not sufficient to control airborne contamination

below occupational exposure limits.

Respiratory protection: No personal respiratory protective equipment normally required. Use NIOSH

approved respirator if there is potential to exceed exposure limit(s). Observe

OSHA regulations for respiratory use (29 CFR 1910.134).

**Eye/face protection:** Safety glasses with side-shields. Goggles.

Skin protection: Cover as much of the exposed skin area as possible with appropriate clothing.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: paste Color: grey, to, black Odor: Mild, Petroleum Odor threshold: Not available pH: Not applicable . Vapor pressure: Not available Boiling point/range: Not available Melting point/ range: Not available Specific gravity: 1.9614 Vapor density: Heavier than air. 160 °C (320°F) Flash point: Flammable/Explosive limits - lower: Not determined Flammable/Explosive limits - upper: Not determined

Autoignition temperature:

Evaporation rate:

Not determined
Less than butyl acetate.

Solubility in water: Slight

Partition coefficient (n-octanol/water): Not determined

**VOC content:** 5.08 %; 102.3 g/l EPA Method 24

### 10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

**Hazardous decomposition products:** Oxides of carbon. Hydrocarbons.

Incompatible materials: Oxidizing agents.

Conditions to avoid: None known

## 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Molybdenum disulphide	No	No	No
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Mineral oil light naphthenic hydrotreat. <3% DMSO	No	No	No

Hazardous components	Health Effects/Target Organs
Molybdenum disulphide	No Target Organs
Distillates (petroleum), hydrotreated heavy naphthenic	Irritant
Mineral oil light naphthenic hydrotreat. <3% DMSO	Irritant

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

#### **U.S. Department of Transportation Ground (49 CFR)**

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

# International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None
None

## Water Transportation (IMO/IMDG)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

# 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA 313: None above reporting de minimus

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

#### **Canada Regulatory Information**

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.B

### 16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.