

Revision Number: 003.0 Issue date: 08/28/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE LB 8012 LOW FRICTION IDH number: 226801

LUBRICANT known as Moly Paste

 Product type:
 Lubricant
 Item number:
 51145

 Restriction of Use:
 None identified
 Region:
 United States

 Company address:
 Contact information:

Henkel Corporation

One Henkel Way

MEDICAL EMERGENCY Phone: Poison Control Center
Rocky Hill, Connecticut 06067

1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

Telephone: (860) 571-5100

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW NOT CLASSIFIED. READ ENTIRE SAFETY DATA SHEET.

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)	
None	

Precautionary Statements

IDH number: 226801

Prevention: Not prescribed Response: Not prescribed Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Molybdenum disulphide	1317-33-5	60 - 100
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	1 - 5
Petroleum distillates, hydrotreated, light naphthenic	64742-53-6	1 - 5
Tristearate-Al	637-12-7	0.1 - 1
Barium dinonylnaphthalenesulfonate	25619-56-1	0.1 - 1
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	0.1 - 1

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

Product name: LOCTITE LB 8012 LOW FRICTION LUBRICANT known as Moly Paste

Page 1 of 6

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, give oxygen. Get medical attention.

Skin contact: Remove contaminated clothing and footwear. Immediately flush skin with

plenty of water (using soap, if available). If symptoms develop and persist, get

medical attention. Wash clothing before reuse.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. If eye irritation persists, consult a specialist.

Ingestion: Aspiration may cause pulmonary edema and pneumonitis. Do not induce

vomiting. Get medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus. In case of fire, keep containers cool

with water spray.

Unusual fire or explosion hazards: None

IDH number: 226801

Hazardous combustion products: Oxides of carbon.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow material to contaminate ground water system.

Clean-up methods: Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

Scrape up as much material as possible. Clean residue with soap and water.

Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling: Use only with adequate ventilation. Prevent contact with eyes, skin and

clothing. Do not breathe vapor and mist. Wash thoroughly after handling.

Keep container closed.

Storage: Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Molybdenum disulphide	10 mg/m3 TWA (as Mo) Inhalable fraction. 3 mg/m3 TWA (as Mo) Respirable fraction.	15 mg/m3 PEL (as Mo) Total dust.	None	None
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist 500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Petroleum distillates, hydrotreated, light naphthenic	None	500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Tristearate-Al	1 mg/m3 TWA Respirable fraction. 10 mg/m3 TWA	None	None	None
Barium dinonylnaphthalenesulfonate	0.5 mg/m3 TWA (as Ba)	0.5 mg/m3 PEL (as Ba)	None	None
Distillates (petroleum), hydrotreated heavy paraffinic	5 mg/m3 TWA mist 10 mg/m3 STEL mist	5 mg/m3 TWA mist	None	None

Engineering controls: Use only with adequate ventilation. Local exhaust ventilation is recommended

when general ventilation is not sufficient to control airborne contamination

below occupational exposure limits.

Use NIOSH approved respirator if there is potential to exceed exposure Respiratory protection:

limit(s). Observe OSHA regulations for respirator use (29 CFR 1910.134).

Eye/face protection: Safety goggles or safety glasses with side shields. Safety showers and eye

wash stations should be available.

Skin protection: Chemical resistant, impermeable gloves. Use of Butyl or Nitrile Rubber gloves

is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste

Color: Gray, to, black Mild, Petroleum Odor: Odor threshold: Not available. pH: Not applicable Vapor pressure: Not available. Boiling point/range: Not available. Melting point/ range: Not available. Specific gravity: 1.9614 Vapor density: Heavier than air.

Flash point: 160 °C (320°F) Flammable/Explosive limits - lower: Not determined Flammable/Explosive limits - upper: Not determined Autoignition temperature: Not determined Evaporation rate:

Less than butyl acetate.

Solubility in water: Slight

IDH number: 226801

Partition coefficient (n-octanol/water): Not determined

VOC content: 5.08 %; 102.3 g/I EPA Method 24

Viscosity: Not available. **Decomposition temperature:** Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 226801

Oxides of carbon. Hydrocarbons.

Incompatible materials: Oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Eyes

Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation.

Skin contact: May cause skin irritation. **Eye contact:** May cause irritation.

Ingestion: May cause gastrointestinal disturbances.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Molybdenum disulphide	None	No Target Organs
Distillates (petroleum), hydrotreated heavy naphthenic	None	Irritant
Petroleum distillates, hydrotreated, light naphthenic	None	Irritant
Tristearate-Al	None	Lung
Barium dinonylnaphthalenesulfonate	None	No Records
Distillates (petroleum), hydrotreated heavy paraffinic	None	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Molybdenum disulphide	No	No	No
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Petroleum distillates, hydrotreated, light naphthenic	No	No	No
Tristearate-Al	No	No	No
Barium dinonylnaphthalenesulfonate	No	No	No
Distillates (petroleum), hydrotreated heavy paraffinic	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: D005. Barium.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:
Not regulated
None
None

International Air Transportation (ICAO/IATA)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis
None above reporting de minimis

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

IDH number: 226801

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Lou Fabrizio, Regulatory Affairs Specialist

Issue date: 08/28/2014

Product name: LOCTITE LB 8012 LOW FRICTION LUBRICANT known as Moly Paste Page 5 of 6

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 226801