Safety Data Sheet



Revision Number: 003.1

Issue date: 10/04/2019

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Product type/use: Adhesive/Sealant Restriction of Use: None identified Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE 567 TB 250ML EN

IDH number: 2087069 Item number: 2087069 Region: United States Contact information: Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT ENERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

WARNING:

EMERGENCY OVERVIEW CAUSES SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION. CAUSES SERIOUS EYE IRRITATION.

| HAZARD CLASS | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN IRRITATION | 2 |
| EYE IRRITATION | 2A |
| SKIN SENSITIZATION | 1 |



Precautionary Statements

| Prevention: | Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eve protection, and face protection. |
|-------------|--|
| Response: | IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. |
| Storage: | Not prescribed |
| Disposal: | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations. |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* | |
|------------------------|------------|-------------|--|

| 3,3,5 Trimethylcyclohexyl methacrylate | 7779-31-9 | 10 - 30 | |
|--|-------------|---------|--|
| Ethene, homopolymer | 9002-88-4 | 5 - 10 | |
| Ethene, tetrafluoro-, homopolymer | 9002-84-0 | 5 - 10 | |
| Titanium dioxide | 13463-67-7 | 1 - 5 | |
| Silica, amorphous, fumed, crystal-free | 112945-52-5 | 1 - 5 | |
| Propane-1,2-diol | 57-55-6 | 1 - 5 | |
| Cumene hydroperoxide | 80-15-9 | 0.1 - 1 | |
| Cumene | 98-82-8 | 0.1 - 1 | |

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

| 4. | FIRST AID MEASURES |
|------------------------------------|---|
| Inhalation: | If inhaled, immediately remove the affected person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention. |
| Skin contact: | IF ON SKIN: Wash with plenty of soap and water. If skin irritation persists, ca a physician. |
| Eye contact: | IF IN EYES: Rinse cautiously with water for several minutes. Remove contac lenses, if present and easy to do. Continue rinsing. If eye irritation persists, consult a specialist. |
| Ingestion: | DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention. |
| Symptoms: | See Section 11. |
| 5. FI | RE FIGHTING MEASURES |
| Extinguishing media: | Water spray (fog), foam, dry chemical or carbon dioxide. |
| Special firefighting procedures: | Wear self-contained breathing apparatus and full protective clothing, such a turn-out gear. In case of fire, keep containers cool with water spray. |
| Unusual fire or explosion hazards: | Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers. |
| Hazardous combustion products: | Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics Toxic fluorine compounds. Ketones. |

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

| Environmental precautions: | Do not allow product to enter sewer or waterways. |
|----------------------------|---|
| Clean-up methods: | Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during clean- up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. |

7. HANDLING AND STORAGE

Handling:

Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. Refer to Section 8.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use. Store frost-free.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|--|--|---|----------------------------------|--|
| 3,3,5 Trimethylcyclohexyl methacrylate | None | None | None | None |
| Ethene, homopolymer | 10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles. | 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust. | None | None |
| Ethene, tetrafluoro-, homopolymer | None | None | None | 10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction. |
| Titanium dioxide | 10 mg/m3 TWA | 15 mg/m3 PEL Total dust. 15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. | None | None |
| Silica, amorphous, fumed, crystal-free | 10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction. | 20 MPPCF TWA 0.8 mg/m3 TWA | None | None |
| Propane-1,2-diol | None | None | 10 mg/m3 TWA Aerosol. | None |
| Cumene hydroperoxide | None | None | 1 ppm (6 mg/m3) TWA (SKIN) | None |
| Cumene | 50 ppm TWA | 50 ppm (245 mg/m3) PEL (SKIN) | None | None |

Engineering controls:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Respiratory protection:

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

Eye/face protection:

Skin protection:

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: . Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: **Evaporation rate:** Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature:

Not available. Not available. Not available. Not available. Not available. Not available. > 149 °C (> 300.2 °F)no method Not available. 1.15 Not available. > 93 °C (> 199.4 °F) Not available. Not available. Not available. Not applicable Not available. Not available. Not available. 0.13 % (ASTM D5403) Not available. Not available.

| | | 10. STABILITY AND REACTIVITY |
|------------------------------|-----------|--|
| Stability: | | Stable under normal conditions of storage and use. |
| Hazardous reaction | ons: | None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials. |
| Hazardous decon products: | nposition | Oxides of carbon and nitrogen, aldehydes, acids and undetermined organics. Toxic fluorine compounds. Ketones. |
| Incompatible mat | erials: | Strong oxidizing agents. Strong reducing agents. Free radical initiators. Inert gases. Oxygen scavengers. |
| Reactivity: | | Not available. |
| Conditions to avo | oid: | Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials. |
| | 1 | 1. TOXICOLOGICAL INFORMATION |

10 STADILITY AND DEACTIVITY

Relevant routes of exposure: Skin, Inha

Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

| Inhalation: | Inhalation of vapors or mists of the product may be irritating to the respiratory system. |
|---------------|---|
| Skin contact: | Causes skin irritation. May cause allergic skin reaction. |
| Eye contact: | Causes serious eye irritation. |
| Ingestion: | May cause gastrointestinal tract irritation if swallowed. |

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|--|--|---|
| 3,3,5 Trimethylcyclohexyl methacrylate | None | No Records |
| Ethene, homopolymer | None | No Target Organs |
| Ethene, tetrafluoro-, homopolymer | None | No Target Organs |
| Titanium dioxide | None | Irritant, Respiratory, Some evidence of carcinogenicity |
| Silica, amorphous, fumed, crystal-free | None | Nuisance dust |
| Propane-1,2-diol | Oral LD50 (Rabbit) = 18 g/kg Oral LD50 (Mouse) = 23.9 g/kg Oral LD50 (Rat) = 30 g/kg | Irritant |
| Cumene hydroperoxide | None | Allergen, Central nervous system, Corrosive, Irritant, Mutagen |
| Cumene | Oral LD50 (Rat) = 2.91 g/kg Oral LD50 (Rat) = 1,400 mg/kg | Central nervous system, Irritant, Lung |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|--|-----------------|---|
| 3,3,5 Trimethylcyclohexyl methacrylate | No | No | No |
| Ethene, homopolymer | No | No | No |
| Ethene, tetrafluoro-, homopolymer | No | No | No |
| Titanium dioxide | No | Group 2B | No |
| Silica, amorphous, fumed, crystal-free | No | No | No |
| Propane-1,2-diol | No | No | No |
| Cumene hydroperoxide | No | No | No |
| Cumene | Reasonably Anticipated to be a Human Carcinogen. | Group 2B | No |

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number:

Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

| Proper shipping name: |
|-----------------------------|
| Hazard class or division: |
| Identification number: |
| Packing group: |
| DOT Hazardous Substance(s): |

RQ, Énvironmentally hazardous substance, liquid, n.o.s. 9 UN 3082 III alpha,alpha-Dimethylbenzylhydroperoxide

| International Air Transportation (ICAO/IATA) | |
|--|---|
| Proper shipping name: | RQ, Environmentally hazardous substance, liquid, n.o.s. |
| Hazard class or division: | 9 |
| Identification number: | UN 3082 |
| Packing group: | III |
| Water Transportation (IMO/IMDG) | |
| Proper shipping name: | RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. |
| Hazard class or division: | 9 |
| Identification number: | UN 3082 |
| Packing group: | III |
| | |

15. REGULATORY INFORMATION

United States Regulatory Information

| TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification: | All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory. None above reporting de minimis |
|--|---|
| CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313: | None above reporting de minimis. Immediate Health, Delayed Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cumene (CAS# 98-82-8). |
| CERCLA Reportable quantity: | Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg) |
| California Proposition 65: | This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. |
| Canada Regulatory Information | |
| CEPA DSL/NDSL Status: | Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. |

16. OTHER INFORMATION

Please contact Regulatory Affairs for additional details.

This safety data sheet contains changes from the previous version in sections: 4

Prepared by: Product Safety and Regulatory Affairs

Issue date: 10/04/2019

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.