



Revision Number: 007.0

Issue date: 03/22/2017

**1. PRODUCT AND COMPANY IDENTIFICATION**

|                               |   |                     |               |
|-------------------------------|---|---------------------|---------------|
| <b>Product name:</b>          | <b>LOCTITE SI 587 known as LOCTITE<br/>587 300ML EN</b> | <b>IDH number:</b>  | 234590        |
| <b>Product type:</b>          | Silicone Sealant  | <b>Item number:</b> | 58775         |
| <b>Restriction of Use:</b>    | None identified   | <b>Region:</b>      | United States |
| <b>Company address:</b>       | <b>Contact information:</b>                             |                     |               |
| Henkel Corporation            | Telephone: (860) 571-5100                               |                     |               |
| One Henkel Way                | MEDICAL EMERGENCY Phone: Poison Control Center          |                     |               |
| Rocky Hill, Connecticut 06067 | 1-877-671-4608 (toll free) or 1-303-592-1711            |                     |               |
|                               | TRANSPORT EMERGENCY Phone: CHEMTREC                     |                     |               |
|                               | 1-800-424-9300 (toll free) or 1-703-527-3887            |                     |               |
|                               | Internet: www.henkelna.com                              |                     |               |

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**WARNING:** CAUSES SKIN IRRITATION.  
MAY CAUSE AN ALLERGIC SKIN REACTION.  
CAUSES SERIOUS EYE IRRITATION.

| HAZARD CLASS       | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN IRRITATION    | 2               |
| EYE IRRITATION     | 2A              |
| SKIN SENSITIZATION | 1               |

**PICTOGRAM(S)**



**Precautionary Statements**

|                    |  |
|--------------------|--|
| <b>Prevention:</b> | Avoid breathing dust or fumes. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.   |
| <b>Response:</b>   | IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing. |
| <b>Storage:</b>    | Not prescribed   |
| <b>Disposal:</b>   | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.  |

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

| Hazardous Component(s)                           | CAS Number | Percentage* |
|--|------------|-------------|
| Limestone  | 1317-65-3  | 30 - 40     |
| Siloxanes and Silicones, di-Me                   | 63148-62-9 | 10 - 20     |
| Butan-2-one O,O',O"-<br>(vinylsilyldyne)trioxime | 2224-33-1  | 1 - 5       |
| Aluminum   | 7429-90-5  | 0.1 - 1     |
| aluminium tristearate                            | 637-12-7   | 0.1 - 1     |
| Quartz (SiO2)                                    | 14808-60-7 | 0.1 - 1     |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

|                      |  |
|----------------------|--|
| <b>Inhalation:</b>   | Move to fresh air in case of accidental inhalation of vapours or decomposition products. If symptoms develop and persist, get medical attention.   |
| <b>Skin contact:</b> | Wipe off paste with paper towel or cloth. Wash with soap and water. If skin irritation persists, call a physician.                                 |
| <b>Eye contact:</b>  | Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If adverse health effects develop seek medical attention. |
| <b>Ingestion:</b>    | Do not induce vomiting. In case of adverse health effects seek medical advice.   |
| <b>Symptoms:</b>     | See Section 11.  |

#### 5. FIRE FIGHTING MEASURES

|   |   |
|---|---|
| <b>Extinguishing media:</b>               | Foam, dry chemical or carbon dioxide.   |
| <b>Special firefighting procedures:</b>   | Prevent inhalation of fumes and gases. Wear self-contained breathing apparatus. |
| <b>Unusual fire or explosion hazards:</b> | None  |
| <b>Hazardous combustion products:</b>     | Oxides of carbon. Oxides of silicon. Formaldehyde. Irritating organic vapours.  |

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |   |
|-----------------------------------|---|
| <b>Environmental precautions:</b> | Do not allow product to enter sewer or waterways.   |
| <b>Clean-up methods:</b>          | Scrape up as much material as possible. Maintain good ventilation for large spills. Place scrap material in a well ventilated area and allow to cure to rubber. |

#### 7. HANDLING AND STORAGE

|                  |  |
|------------------|--|
| <b>Handling:</b> | Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation. |
| <b>Storage:</b>  | For safe storage, store at or below 32 °C (89.6 °F)<br>Keep container closed.  |

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                        | ACGIH TLV  | OSHA PEL  | AIHA WEEL | OTHER |
|---|--|---|-----------|-------|
| Limestone                                     | 10 mg/m <sup>3</sup> TWA Total dust.                                     | 5 mg/m <sup>3</sup> PEL Respirable fraction.<br>15 mg/m <sup>3</sup> PEL Total dust.  | None      | None  |
| Siloxanes and Silicones, di-Me                | None   | None  | None      | None  |
| Butan-2-one O,O',O''-(vinylsilyldyne)trioxime | None   | None  | None      | None  |
| Aluminum                                      | 1 mg/m <sup>3</sup> TWA Respirable fraction.                             | 15 mg/m <sup>3</sup> PEL (as Al) Total dust.<br>5 mg/m <sup>3</sup> PEL (as Al) Respirable fraction.<br>15 MPPCF TWA Respirable fraction.<br>50 MPPCF TWA Total dust.<br>5 mg/m <sup>3</sup> TWA Respirable fraction.<br>15 mg/m <sup>3</sup> TWA Total dust. | None      | None  |
| aluminium tristearate                         | 1 mg/m <sup>3</sup> TWA Respirable fraction.<br>10 mg/m <sup>3</sup> TWA | None  | None      | None  |
| Quartz (SiO <sub>2</sub> )                    | 0.025 mg/m <sup>3</sup> TWA Respirable fraction.                         | 2.4 MPPCF TWA Respirable.<br>0.1 mg/m <sup>3</sup> TWA Respirable.<br>0.05 mg/m <sup>3</sup> TWA (Respirable dust.)<br>(Respirable dust.)<br>0.025 mg/m <sup>3</sup> OSHA_ACT (Respirable dust.)<br>0.05 mg/m <sup>3</sup> PEL Respirable dust.               | None      | None  |

**Engineering controls:**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:**

Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Safety showers and eye wash stations should be available.

**Skin protection:**

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical state:**

Paste

**Color:**

Blue

**Odor:**

Mild, Petroleum

**Odor threshold:**

Not available.

**pH:**

Not applicable

**Vapor pressure:**

< 5 mm hg (20 °C (68°F))

**Boiling point/range:**

Not available.

**Melting point/ range:**

Not available.

**Specific gravity:**

1.31 at 20 °C (68°F)

|   |   |
|---|---|
| <b>Vapor density:</b>                           | Not available.                            |
| <b>Flash point:</b>                             | > 93 °C (> 199.4 °F) Tagliabue closed cup |
| <b>Flammable/Explosive limits - lower:</b>      | Not available.                            |
| <b>Flammable/Explosive limits - upper:</b>      | Not available.                            |
| <b>Autoignition temperature:</b>                | Not available.                            |
| <b>Flammability:</b>                            | Not applicable                            |
| <b>Evaporation rate:</b>                        | Not available.                            |
| <b>Solubility in water:</b>                     | Polymerises in presence of water.         |
| <b>Partition coefficient (n-octanol/water):</b> | Not available.                            |
| <b>VOC content:</b>                             | 3.33 %; 43.09 g/l                         |
| <b>Viscosity:</b>                               | Not available.                            |
| <b>Decomposition temperature:</b>               | Not available.                            |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Stability:</b>                        | Stable at normal conditions.   |
| <b>Hazardous reactions:</b>              | None under normal processing.  |
| <b>Hazardous decomposition products:</b> | Oxides of carbon. Oxides of silicon. Methyl ethyl ketoxime formed during cure. Formaldehyde. |
| <b>Incompatible materials:</b>           | Oxidizing agents. Acids and bases.   |
| <b>Reactivity:</b>                       | Not available.   |
| <b>Conditions to avoid:</b>              | Exposure to moisture.  |

## 11. TOXICOLOGICAL INFORMATION

|                                     |                                   |
|-------------------------------------|-----------------------------------|
| <b>Relevant routes of exposure:</b> | Skin, Inhalation, Eyes, Ingestion |
|-------------------------------------|-----------------------------------|

## Potential Health Effects/Symptoms

|                      |  |
|----------------------|--|
| <b>Inhalation:</b>   | Overexposure to methanol formed during cure may cause drowsiness, nausea, and vomiting. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit. Harmful if inhaled. Contains crystalline silica (quartz), which is classified as a possible carcinogen. However, the crystalline silica present in this product is encapsulated in the liquid and will only be liberated if the product is sanded or abraded, and even then what is liberated will not be pure crystalline silica. Appropriate precautions, however, should be taken if the product is sanded or abraded to prevent personnel from breathing the dust. |
| <b>Skin contact:</b> | Causes skin irritation. May cause allergic skin reaction.  |
| <b>Eye contact:</b>  | Causes serious eye irritation.   |
| <b>Ingestion:</b>    | Not expected under normal conditions of use. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.   |

| Hazardous Component(s)                         | LD50s and LC50s | Immediate and Delayed Health Effects                  |
|--|-----------------|---|
| Limestone                                      | None            | Nuisance dust   |
| Siloxanes and Silicones, di-Me                 | None            | Irritant  |
| Butan-2-one O,O',O''-(vinylsilylidyne)trioxime | None            | Irritant, Allergen                                    |
| Aluminum                                       | None            | Central nervous system, Irritant, Lung                |
| aluminium tristearate                          | None            | Lung  |
| Quartz (SiO2)                                  | None            | Immune system, Lung, Some evidence of carcinogenicity |

| Hazardous Component(s)                         | NTP Carcinogen                | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|-------------------------------|-----------------|--|
| Limestone                                      | No                            | No              | No                                       |
| Siloxanes and Silicones, di-Me                 | No                            | No              | No                                       |
| Butan-2-one O,O',O''-(vinylsilylidyne)trioxime | No                            | No              | No                                       |
| Aluminum                                       | No                            | No              | No                                       |
| aluminium tristearate                          | No                            | No              | No                                       |
| Quartz (SiO2)                                  | Known To Be Human Carcinogen. | Group 1         | Yes                                      |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Cured rubber can be incinerated or landfilled following EPA and local regulations.

**Hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

|                                  |               |
|----------------------------------|---------------|
| <b>Proper shipping name:</b>     | Not regulated |
| <b>Hazard class or division:</b> | None          |
| <b>Identification number:</b>    | None          |
| <b>Packing group:</b>            | None          |

**International Air Transportation (ICAO/IATA)**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

**Water Transportation (IMO/IMDG)**

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None  
**Exceptions:** None

**15. REGULATORY INFORMATION****United States Regulatory Information**

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.

**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health

**CERCLA/SARA Section 313:** None above reporting de minimis.

**California Proposition 65:** This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**Canada Regulatory Information**

**CEPA DSL/NDL Status:** All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

**16. OTHER INFORMATION**

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format.

**Prepared by:** Regulatory Affairs

**Issue date:** 03/22/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.