

Revision Number: 002.0

# 1. PRODUCT AND COMPANY IDENTIFICATION

**IDH number:** 

Product name:

Product type/use:

Restriction of Use:

Company address: Henkel Corporation

Rocky Hill, Connecticut 06067

One Henkel Way

BONDERITE L-MR CR 20 METAL REMOVAL LUBRICANT known as MULTAN CR 20 Lubricant None identified

Region:United StatesContact information:Telephone: +1 (860) 571-5100MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

594248

## 2. HAZARDS IDENTIFICATION

 EMERGENCY OVERVIEW

 DANGER:
 MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

HAZARD CLASS	HAZARD CATEGORY
ASPIRATION HAZARD	1
PICTOGRAM(S)	

**Precautionary Statements** 

Prevention: Response:

Storage:

Disposal:

Not prescribed IF SWALLOWED: Immediately call a physician or poison control center. Do NOT induce vomiting. Store locked up. Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO	64742-65-0	60 - 80
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO	64742-65-0	10 - 30
Hydrocarbon Mix		5 - 10

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

	4. FIRST AID MEASURES
Inhalation:	If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.
Skin contact:	Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention.
Eye contact:	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. If symptoms develop and persist, get medical attention.
Ingestion:	Immediate medical treatment necessary. DO NOT induce vomiting unless directed to do so by medical personnel.
Symptoms:	See Section 11.
Notes to physician:	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

5. FIR	E FIGHTING MEASURES
Extinguishing media:	carbon dioxide, foam, powder, water spray jet, fine water spray
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
Unusual fire or explosion hazards:	This product is combustible at high temperatures.
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

# 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** 

Clean-up methods:

Prevent further leakage or spillage if safe to do so. Wear suitable protective clothing, gloves and eye/face protection. Remove all sources of ignition.

Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

### 7. HANDLING AND STORAGE

Handling:Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of<br/>this product. Remove all sources of ignition. Do not take internally. For<br/>industrial use only. Launder work clothes frequently.Storage:For safe storage, store between 5 °C (41°F) and 30 °C (86°F)<br/>Keep container tightly closed and in a cool, well-ventilated place away from<br/>incompatible materials. Manufacturer recommends storing above 4.4 °C (40<br/>°F). If stored outside of this range, mix well before using. Do not pressurize,<br/>cut, heat or weld containers. Empty product containers may contain product<br/>residue. Do not reuse empty containers.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist. 500 ppm (2,000 mg/m3) PEL	None	None
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO	5 mg/m3 TWA Inhalable fraction.	5 mg/m3 PEL Mist. 500 ppm (2,000 mg/m3) PEL	None	None
Hydrocarbon Mix	None	None	None	None

**Engineering controls:** 

**Respiratory protection:** 

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

If mist is generated (heating, spraying) and engineering controls are not sufficient, wear approved organic vapor respirator suitable for oil mist. When workplace hazards warrant the use of a respirator, appropriate respirators must be used, and a program that follows 29 CFR 1910.134 must be followed.

Eye/face protection:

Skin protection:

Wear safety glasses; chemical goggles (if splashing is possible).

Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Amber
Odor:	Petroleum
Odor threshold:	Not available.
pH:	Not applicable
Vapor pressure:	Not determined
Boiling point/range:	260 °C (500°F)
Melting point/ range:	Not determined
Specific gravity:	0.86 - 0.89
Vapor density:	Not determined
Flash point:	210 °C (410°F)
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not available.
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Partially soluble
Partition coefficient (n-octanol/water):	Not available.
VOC content:	Not applicable
Viscosity:	40 - 50 mPa.s
Decomposition temperature:	Not available.

## **10. STABILITY AND REACTIVITY**

Stability:	Stable at normal conditions.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Incompatible materials:	Strong oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

# **11. TOXICOLOGICAL INFORMATION**

Relevant routes of exposure: Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

Inhalation:	Inhalation of vapors or mists of the product may be irritating to the respiratory system. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.
Skin contact:	May cause skin irritation.
Eye contact:	This product may cause irritation to the eyes.
Ingestion:	Ingestion of this product may cause nausea, vomiting and diarrhea. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO	Inhalation LC50 (Rat, 4 h) = $10.5 \text{ mg/l}$ Inhalation LC50 (Rat, 4 h) = $> 4.026 \text{ mg/l}$ Inhalation LC50 (Rat, 4 h) = $2.18 \text{ mg/l}$	Irritant	
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO	Inhalation LC50 (Rat, 4 h) = $10.5 \text{ mg/l}$ Inhalation LC50 (Rat, 4 h) = $> 4.026 \text{ mg/l}$ Inhalation LC50 (Rat, 4 h) = $2.18 \text{ mg/l}$	No Data	
Hydrocarbon Mix	None	No Data	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO	No	No	No
Distillates (petroleum), solvent-dewaxed heavy paraffinic < 3%DMSO	No	No	No
Hydrocarbon Mix	No	No	No

#### **ECOLOGICAL INFORMATION** 12.

**Ecological information:** 

No data available.

### **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

#### 14. **TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	
Hazard class or division:	
Identification number:	
Packing group:	

Not regulated None None None

### International Air Transportation (ICAO/IATA)

Proper shipping name: Hazard class or division: Identification number: Packing group:

Not regulated None None None

Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated None None None

### **15. REGULATORY INFORMATION**

### United States Regulatory Information

Cana

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. None above reporting de minimis
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health None above reporting de minimis.
California Proposition 65:	This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.
ada Regulatory Information	
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

# 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Regulatory Affairs

Issue date: 08/23/2022

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.