



Revision Number: 004.2

Issue date: 10/30/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE S-ST 6776 THIN AERO
 known as TURCO 6776 THIN
Product type: Paint stripping agents
Restriction of Use: None identified
Company address: Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number: 597019

Region: United States

Contact information:
 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
 MAY CAUSE AN ALLERGIC SKIN REACTION.
 HARMFUL IF INHALED.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY INHALATION	4
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Benzyl alcohol	100-51-6	10 - 30
Formic acid	64-18-6	10 - 30
Sodium xylene sulfonate	1300-72-7	10 - 30
Petroleum distillates, hydrotreated, light naphthenic	64742-53-6	10 - 30
2-Mercaptobenzothiazole	149-30-4	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.
Skin contact:	For skin contact flush with large amounts of water. Obtain medical attention if irritation persists.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Get medical attention. DO NOT induce vomiting unless directed to do so by medical personnel. Give one to two glasses of water or milk. Never give anything by mouth to a victim who is unconscious or is having convulsions.
Symptoms:	See Section 11.
Notes to physician:	This material, if aspirated into the lungs, may cause lipoid pneumonitis. Treat affected person appropriately.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Use media appropriate for surrounding material.
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	This product is an aqueous mixture which will not burn.
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Contain spill. Ventilate area. Do not allow product to enter sewer or waterways. Isolate area. Keep unnecessary personnel away.
Clean-up methods:	Collect spilled material with an inert absorbent such as sand or vermiculite. Place in properly labeled closed container. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Provide adequate ventilation. Avoid breathing vapors or mists of this product. Wash thoroughly after handling. Do not reuse the empty container.

Storage: Store in a cool, dry, well-ventilated area. Store between 40°F and 100°F. (5° and 38°C).
For safe storage, store between 32 °F (0°C) and 122 °F (50°C)
Keep the container tightly closed and in a cool, well-ventilated place.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Benzyl alcohol	None	None	10 ppm (44.20 mg/m3) TWA	None
Formic acid	10 ppm STEL 5 ppm TWA	5 ppm (9 mg/m3) PEL	None	None
Sodium xylene sulfonate	None	None	None	None
Petroleum distillates, hydrotreated, light naphthenic	5 mg/m3 TWA Inhalable fraction.	500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
2-Mercaptobenzothiazole	None	None	5 mg/m3 TWA (SKIN) (Skin sensitizer)	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Amber
Odor:	Sharp
Odor threshold:	Not available.
pH:	< 2
pH:	1.5
Vapor pressure:	17 mm hg
Boiling point/range:	> 101 °C (> 213.8 °F)None
Melting point/ range:	Not determined
Specific gravity:	1.04 - 1.07 at 25 °C (77°F)
Vapor density:	Not determined
Flash point:	> 200 °F (> 93.33 °C) Cleveland open cup > 93 °C (> 199.4 °F) HST-US E38F; Cleveland Open Cup (Coc) Flash Point
Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Autoignition temperature:	Not determined
Flammability:	Not applicable
Evaporation rate:	Not available.
Solubility in water:	Appreciable

Partition coefficient (n-octanol/water): Not determined
VOC content: 315 g/l Estimated
Viscosity: Not available.
Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.
Hazardous reactions: Will not occur.
Hazardous decomposition products: Upon decomposition, this product may yield sulfur dioxide, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
Incompatible materials: May react with strong bases or oxidizing agents.
Reactivity: Not available.
Conditions to avoid: Avoid excessive heat and ignition sources.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: This product is irritating to the respiratory system. Inhalation of high vapor concentrations may produce respiratory irritation, and may cause central nervous system (CNS) depression. Chronic inhalation overexposure may produce kidney or bladder damage.
Skin contact: Contact with liquid may produce severe skin irritation including redness, inflammation and chemical burns. This product may cause an allergic skin reaction.
Eye contact: This product is severely irritating to the eyes and may cause irreversible damage including burns and blindness.
Ingestion: Ingestion may produce burns to the lips, oral cavity, upper airway, esophagus and possibly the digestive tract.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Benzyl alcohol	Oral LD50 (Rabbit) = 1,940 mg/kg Oral LD50 (Rat) = 1,230 - 3,100 mg/kg Oral LD50 (Mouse) = 1,580 mg/kg Oral LD50 (Rat) = 3,100 mg/kg Dermal LD50 (Rabbit) = 2,000 mg/kg	Allergen, Central nervous system, Corrosive, Irritant
Formic acid	Oral LD50 (Mouse) = 700 mg/kg Oral LD50 (Rat) = 730 mg/kg	Central nervous system, Corrosive, Irritant, Kidney, Metabolic
Sodium xylene sulfonate	None	Irritant
Petroleum distillates, hydrotreated, light naphthenic	None	Irritant
2-Mercaptobenzothiazole	Oral LD50 (Mouse) = 3,148 mg/kg Oral LD50 (Mouse) = 1,558 mg/kg Oral LD50 (Mouse) = 1,490 mg/kg	Allergen, Kidney, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Benzyl alcohol	No	No	No
Formic acid	No	No	No
Sodium xylene sulfonate	No	No	No
Petroleum distillates, hydrotreated, light naphthenic	No	No	No
2-Mercaptobenzothiazole	No	Group 2A	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: This product, if discarded, may be characterized as a RCRA corrosive waste, D002. Wastes must be tested using methods described in 40 CFR Part 261 to determine if it meets applicable definitions of hazardous wastes. U123: Formic acid.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Formic acid solution
Hazard class or division: 8
Identification number: UN 3412
Packing group: II
DOT Hazardous Substance(s): Formic acid

International Air Transportation (ICAO/IATA)

Proper shipping name: Formic acid solution
Hazard class or division: 8
Identification number: UN 3412
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: FORMIC ACID solution
Hazard class or division: 8
Identification number: UN 3412
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Formic acid (CAS# 64-18-6).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2

Prepared by: Product Safety and Regulatory Affairs

Issue date: 10/30/2018

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.