# SAFETY DATA SHEET

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: TFL50 WET LUBE (non-aerosol) Product Code: 60128

Product Number: #60128 – 1 gallon cans

MANUFACTURER'S NAME: Business US50, LLC.

ADDRESSS: 3260 Industry Drive, Unit 5

North Charleston, SC 29414

EMERGENCY PHONE: CHEMTREC 800-424-9300

INFORMATION PHONE: 843-438-1720
Product Use: Lubricant

#### 2. HAZARDS IDENTIFICATION

# **CLASSIFICATION**

Flammable liquid 2
Skin Corrosion/Irritation 3
Eye Damage/Irritation 2B
Aspiration hazard 1



SIGNAL WORD: Danger

#### **Hazard Statements**

Highly flammable liquid and vapor

May be fatal if swallowed and enters airways

Causes mild skin irritation

Causes eye irritation

# **Precautionary Statements**

Keep away from heat/sparks/open flames/hot surfaces - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Wash hands thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

Do NOT induce vomiting

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

If skin irritation occurs: Get medical advice/attention

If eye irritation persists: Get medical advice/attention

SDS for: TFL50 Wet Lube (non-aerosol)

Page 1 of 4

Printed: 7/22/2015

In case of fire: Use ... for extinction

Store locked up

Store in a well ventilated place. Keep cool

Dispose of contents/container to comply with all local, state, and federal regulations

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Percent
PETROLEUM DISTILLATE	8052-41-3	72.70
PETROLEUM OIL	64742-52-5	1.30

#### 4. FIRST AID MEASURES

**INHALATION:** Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breating has stopped. Get medical attention.

EYE CONTACT: Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

INGESTION: If swallowed, do not induce vomiting. Get immediate medical attention.

Most important symptoms/effects, acute and delayed: Repeated exposure may cause skin dryness or cracking.

Indication of immediate medical attention and special treatment needed: None known.

#### 5. FIRE FIGHTING MEASURES

Suitable and unsuitable extinguising media: Foam, Alcohol foam, CO2, Dry chemical, Water fog. Water spray may be ineffective.

Specific hazards arising from the chemical: Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes.

Special equipment and precautions for fire-fighters: Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. Wear goggles and use self-contained breathing apparatus. If water is used, fog nozzles are preferred.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

Methods and materials for containment and cleaning up: Clean up with absorbent material and place in closed containers for disposal.

## 7. HANDLING AND STORAGE

SDS for: TFL50 Wet Lube (non-aerosol)

Precautions for safe handling: Keep closure tight and container upright to prevent leakage. Open container slowly. Do not get in eyes. Avoid skin contact and contact with clothing. Do not take internally.

Conditions for safe storage, including any incompatibilities: Store and use in cool, dry, well-ventilated areas. Keep containers closed when not in use. Keep away from excessive heat or open flame.

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
PETROLEUM DISTILLATE 8052-41-3	Not established	TLV-TWA: 400 ppm	
PETROLEUM OIL 64742-52-5	PEL: Mist 5 mg/m3, 8 hrs	TLV: Mist 5 mg/m3, 8 hrs	

**Appropriate engineering controls:** Ventilation should be sufficient to prevent inhalation of any vapors. General dilution and/or local exhoust ventilation in volume to keep PEL/TLV of most hazardous ingredient below acceptable limit and lel below stated limit.

## Individual protection measures:

**Respiratory protection:** None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination or particles and vapor. In confined areas, use an approved air line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Protective gloves: None under normal use. Use solvent-resistant for prolonged or repeated contact.

**Eye protection:** None under normal use. However, use of safety glasses with splash guards or full face shield should be used if indicated.

Other protective clothing or equipment: None under normal use. However, use of solvent- resitant aprons or other clothing is recommended. Eye washes and safety showers in the workplace are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	SI. Hazy liquid	Odor:	Solvent
Vapor Pressure:	Not determined	Odor threshold:	Not determined
Vapor Density:	Heavier than air	pH:	Not applicable
Density:	0.81458835	Melting point:	Not determined
Freezing point:	Not determined	Solubility:	Not determined
Boiling point:	N/A	Flash point:	>105 F
Evaporation rate:	Slower than ether	Flammability:	Combustible
Explosive Limits:	Not determined	Partition coefficient (n- octanol/water):	
Autoignition temperature:	Not determined	Decomposition temperature:	Not determined
Viscosity:	Not determined		

# 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions of use.

Chemical stability: Stable under normal storage and handling conditions.

Possibility of hazardous reactions: None known.

Incompatible materials: Strong oxidizing agents.

SDS for: TFL50 Wet Lube (non-aerosol)

Page 3 of 4

Hazardous decomposition products: Carbon monoxide and other hazardous fumes.

## 11. TOXICOLOGICAL INFORMATION

Long-term toxicological studies have not been conducted for this product.

## 12. ECOLOGICAL INFORMATION

Long-term ecological studies have not been conducted for this product.

# 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations. Before attempting clean up, refer to other sections of this document for hazard cautionary information.

## 14. TRANSPORT INFORMATION

By Land: Not regulated

By Water: DOT Proper Shipping Name: UN1993, FLAMMABLE LIQUID, n.o.s., (Petroleum distillates), 3, III

By Air: DOT Proper Shipping Name: UN1993, FLAMMABLE LIQUID, n.o.s., (Petroleum distillates), 3, III

## 15. REGULATORY INFORMATION

All ingredients are either listed on the TSCA inventory or are exempt.

#### 16. OTHER INFORMATION

Date revised: 2016-11-22 Revision 0

Date Printed: 2016-11-22

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.

SDS for: TFL50 Wet Lube (non-aerosol)

Page 4 of 4