

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Name : Magnolia 6398-A  
Product code : 6398-A

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Industrial use  
Adhesives, sealants  
Epoxy resin  
Recommended use : Adhesives, sealants

#### 1.3. Supplier

##### Manufacturer

Magnolia Advanced Materials, Inc.  
4360 Northeast Expressway  
Atlanta, GA , 30340  
USA  
T 770-451-2777 [8:00 am - 4:30 pm US eastern time zone]  
[SDS@magnolia-adv-mat.com](mailto:SDS@magnolia-adv-mat.com) - [www.magnolia-adv-mat.com](http://www.magnolia-adv-mat.com)

#### 1.4. Emergency telephone number

Emergency number : INFOTRAC 1-352-323-3500 (International) | 1-800-535-5053 (North America) | Account 79439

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture


##### GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) : 

Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction.  
H319 - Causes serious eye irritation

Precautionary statements (GHS US) : P261 - Avoid breathing fume.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear protective gloves.  
P302+P352 - If on skin: Wash with plenty of water.  
P305+P351+P338 - If in eyes: rinse cautiously with water for several minutes. remove contact

# Magnolia 6398-A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

lenses, if present and easy to do. continue rinsing  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Epoxy resin	CAS-No.: 28768-32-3	40-50	Skin Sens. 1, H317
Epoxy resin	CAS-No.: 25068-38-6	5-15	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice. If medical advice is needed, have product container or label at hand.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Gently wash with plenty of soap and water. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a POISON CENTER or doctor/physician if you feel unwell. Call a poison center/doctor/physician if you feel unwell.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.

Symptoms/effects after eye contact : Causes eye irritation. Eye irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

# Magnolia 6398-A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 5: Fire-fighting measures

#### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : dry extinguishing powder. Water spray. Dry powder. Foam. Carbon dioxide.

#### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes.

#### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Wear suitable protective clothing, gloves and eye/face protection. Self contained breathing apparatus. Wear respiratory protection. Wear fire/flame resistant/retardant clothing. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

##### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Ventilate area. Avoid contact with skin and eyes. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

##### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Wear suitable protective clothing, gloves and eye/face protection. Use personal protective equipment as required. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Avoid release to the environment.

#### 6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Take up liquid spill into absorbent material. Clean up any spills as soon as possible, using an absorbent material to collect it.

Other information : Dispose of contents/container to {0}message=<specify in accordance with local/regional/national/international regulations>|default=...|filter=^(\_)DISPOSAL\_+}. Dispose of materials or solid residues at an authorized site.

#### 6.4. Reference to other sections

For further information refer to section 13.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Use personal protective equipment as required. Use only in well-ventilated areas. Avoid contact with skin and eyes. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing dust/fume/gas/mist/vapors/spray.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

# Magnolia 6398-A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide local exhaust or general room ventilation. Ensure good ventilation of the work station.  
Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

protective gloves. Wear protective gloves/protective clothing/eye protection/face protection.

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Paste. gel.  
Color : Gray  
Odor : slightly ethereal  
Odor threshold : No data available  
pH : No data available  
Melting point : Not applicable  
Freezing point : No data available  
Boiling point : > 107.3 °C  
Flash point : > 93.4 °C  
Relative evaporation rate (butyl acetate=1) : No data available  
Flammability (solid, gas) : Not applicable.  
Vapor pressure : No data available  
Relative vapor density at 20 °C : No data available  
Relative density : ≈ 1.25  
Solubility : No data available

# Magnolia 6398-A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

VOC content : Negligible

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes eye irritation. Eye irritation.

# Magnolia 6398-A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 12: Ecological information

#### 12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.

Epoxy resin (28768-32-3)	
LC50 - Fish [1]	1 – 10 mg/l
EC50 - Crustacea [1]	6.7 mg/l
Epoxy resin (25068-38-6)	
ErC50 algae	11 mg/l (EPA 660/3 - 75/009, 72 h, Scenedesmus sp., Static system, Fresh water, Experimental value)

#### 12.2. Persistence and degradability

Epoxy resin (28768-32-3)	
Persistence and degradability	Biodegradability in soil: no data available. Inherently biodegradable.
Epoxy resin (25068-38-6)	
Persistence and degradability	Not readily biodegradable in water.

#### 12.3. Bioaccumulative potential

Epoxy resin (28768-32-3)	
Partition coefficient n-octanol/water (Log Pow)	2.12
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Epoxy resin (25068-38-6)	
BCF - Other aquatic organisms [1]	31 (Estimated value, Fresh weight)
Partition coefficient n-octanol/water (Log Pow)	3 (Estimated value, 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

#### 12.4. Mobility in soil

Epoxy resin (28768-32-3)	
Ecology - soil	Highly mobile in soil.
Epoxy resin (25068-38-6)	
Surface tension	59 mN/m (20 °C, 0.09 g/l)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	2.65 (log Koc, SRC PCKOCWIN v2.0, QSAR)
Ecology - soil	Low potential for adsorption in soil.

#### 12.5. Other adverse effects

No additional information available

# Magnolia 6398-A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 13: Disposal considerations

#### 13.1. Disposal methods

Waste treatment methods : Must follow special treatment according to local regulation. Dispose of contents/container in accordance with licensed collector's sorting instructions.

### SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

#### 14.1. UN number

DOT NA No : UN3082  
UN-No. (TDG) : Not applicable  
UN-No. (IMDG) : 3082  
UN-No. (IATA) : 3082

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Environmentally hazardous substances, liquid, n.o.s. (Epoxy resin)  
Proper Shipping Name (TDG) : Not applicable  
Proper Shipping Name (IMDG) : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)  
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin)  
Transport document description (DOT) : UN3082 Environmentally hazardous substances, liquid, n.o.s. (Epoxy resin), 9, III  
Transport document description (IMDG) : UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin), 9, III  
Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s. (Epoxy resin), 9, III

#### 14.3. Transport hazard class(es)

##### DOT

Transport hazard class(es) (DOT) : 9  
Hazard labels (DOT) : 9



##### TDG

Transport hazard class(es) (TDG) : Not applicable

##### IMDG

Transport hazard class(es) (IMDG) : 9  
Hazard labels (IMDG) : 9



##### IATA

Transport hazard class(es) (IATA) : 9  
Hazard labels (IATA) : 9

# Magnolia 6398-A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations



### 14.4. Packing group

Packing group (DOT)	: III
Packing group (TDG)	: Not applicable
Packing group (IMDG)	: III
Packing group (IATA)	: III

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### DOT

UN-No.(DOT)	: UN3082
DOT Special Provisions (49 CFR 172.102)	: 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies. 146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination. 173 - An appropriate generic entry may be used for this material. 335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leak-proof when used as bulk packaging. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 155
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: No limit
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: No limit
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

#### TDG

Emergency Response Guide (ERG) Number : 171



# Magnolia 6398-A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### IMDG

Special provision (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP2, TP29
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-F - SPILLAGE SCHEDULE Foxtrot - WATER-SOLUBLE MARINE POLLUTANTS
Stowage category (IMDG)	: A

### IATA

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provision (IATA)	: A97, A158, A197
ERG code (IATA)	: 9L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

### 15.2. International regulations

#### CANADA

##### Magnolia 6398-A

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

##### Epoxy resin (28768-32-3)

Listed on the Canadian DSL (Domestic Substances List)

##### Epoxy resin (25068-38-6)

Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

No additional information available

### National regulations

No additional information available

# Magnolia 6398-A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 08/31/2022

Other information : © 2020 Magnolia Advanced Materials Inc. All rights reserved.

Full text of H-phrases	
H315	Causes skin irritation
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation
H411	Toxic to aquatic life with long lasting effects

Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit

# Magnolia 6398-A

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Abbreviations and acronyms	
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Safety Data Sheet (SDS), USA

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

© 2018 Magnolia Advanced Materials Inc. All rights reserved.

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Name : Magnolia 6398-B  
Product code : 6398-B

#### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Adhesives, sealants  
Industrial use  
Epoxy resin: hardener  
Recommended use : Adhesives, sealants

#### 1.3. Supplier

##### Manufacturer

Magnolia Advanced Materials, Inc.  
4360 Northeast Expressway  
Atlanta, GA , 30340  
USA  
T 770-451-2777 [8:00 am - 4:30 pm US eastern time zone]  
[SDS@magnolia-adv-mat.com](mailto:SDS@magnolia-adv-mat.com) - [www.magnolia-adv-mat.com](http://www.magnolia-adv-mat.com)

#### 1.4. Emergency telephone number

Emergency number : INFOTRAC 1-352-323-3500 (International) | 1-800-535-5053 (North America) | Account 79439

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Acute toxicity (dermal) Category 4	H312	Harmful in contact with skin
Skin corrosion/irritation Category 1B	H314	Causes severe skin burns and eye damage.
Serious eye damage/eye irritation Category 1	H318	Causes serious eye damage
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.

Full text of H statements : see section 16

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H312 - Harmful in contact with skin  
H314 - Causes severe skin burns and eye damage.  
H317 - May cause an allergic skin reaction.  
H318 - Causes serious eye damage

Precautionary statements (GHS US) :

P260 - Do not breathe vapors.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P280 - Wear protective gloves.  
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting.

# Magnolia 6398-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - If in eyes: rinse cautiously with water for several minutes. remove contact lenses, if present and easy to do. continue rinsing  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Amine curing agent	CAS-No.: 140-31-8	40-50	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Cycloaliphatic Amine	CAS-No.: 4246-51-9	20-30	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call a physician immediately.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.  
First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth. Do not induce vomiting. Call a physician immediately.

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Burns. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Causes serious eye damage. Serious damage to eyes.  
Symptoms/effects after ingestion : Burns.

# Magnolia 6398-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : dry extinguishing powder. Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes.

### 5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Self contained breathing apparatus. Wear suitable protective clothing, gloves and eye/face protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Ventilate area. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Wear suitable protective clothing, gloves and eye/face protection. Use personal protective equipment as required. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Clean up any spills as soon as possible, using an absorbent material to collect it.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Wear personal protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

# Magnolia 6398-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Appropriate engineering controls

Appropriate engineering controls : Provide adequate ventilation to minimize dust concentrations. Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

<b>Hand protection:</b>
Protective gloves
<b>Eye protection:</b>
Safety glasses
<b>Skin and body protection:</b>
Wear suitable protective clothing
<b>Respiratory protection:</b>
In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Paste. gel.
Color	: Off-white to amber
Odor	: Amine-like
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: > 107.3 °C
Flash point	: > 93.4 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: ≈ 1

# Magnolia 6398-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

VOC content : Negligible

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Harmful in contact with skin.
Acute toxicity (inhalation)	: Not classified

Magnolia 6398-B	
ATE US (dermal)	1855.768 mg/kg body weight
Amine curing agent (140-31-8)	
LD50 oral rat	2097 mg/kg body weight (Rat, Male, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	866 mg/kg bw/day (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s))
Cycloaliphatic Amine (4246-51-9)	
LD50 oral rat	3160 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral)



# Magnolia 6398-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

<b>Cycloaliphatic Amine (4246-51-9)</b>	
LD50 dermal rat	> 2150 mg/kg (Equivalent or similar to OECD 402, 24 h, Rat, Male / female, Experimental value, Dermal)
Skin corrosion/irritation	: Causes severe skin burns.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Causes serious eye damage. Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

<b>Amine curing agent (140-31-8)</b>	
LC50 - Fish [1]	2190 mg/l (96 h, Pimephales promelas, Static system, Fresh water, Experimental value)
EC50 - Crustacea [1]	58 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Experimental value, GLP)
ErC50 algae	1000 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Fresh water, Experimental value, GLP)

<b>Cycloaliphatic Amine (4246-51-9)</b>	
LC50 - Fish [1]	215 – 464 mg/l (DIN 38412-15, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 - Crustacea [1]	218.16 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)

### 12.2. Persistence and degradability

<b>Amine curing agent (140-31-8)</b>	
Persistence and degradability	Not readily biodegradable in water.
Chemical oxygen demand (COD)	0.56 g O <sub>2</sub> /g substance

<b>Cycloaliphatic Amine (4246-51-9)</b>	
Persistence and degradability	Not readily biodegradable in water.

### 12.3. Bioaccumulative potential

<b>Amine curing agent (140-31-8)</b>	
BCF - Fish [1]	0.3 – 6.3 (OECD 305: Bioconcentration: Flow-Through Fish Test, 6 week(s), Cyprinus carpio, Flow-through system, Fresh water, Read-across)

# Magnolia 6398-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Amine curing agent (140-31-8)	
Partition coefficient n-octanol/water (Log Pow)	-1.48 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Cycloaliphatic Amine (4246-51-9)	
BCF - Other aquatic organisms [1]	0.07 (Calculated value)
Partition coefficient n-octanol/water (Log Pow)	-1.25 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)
Bioaccumulative potential	Not bioaccumulative.

### 12.4. Mobility in soil

Amine curing agent (140-31-8)	
Surface tension	No data available in the literature
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	4.57 (log Koc, Read-across, GLP)
Ecology - soil	Low potential for mobility in soil.
Cycloaliphatic Amine (4246-51-9)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	1.2 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

### 14.1. UN number

DOT NA No : UN3267  
UN-No. (TDG) : Not applicable  
UN-No. (IMDG) : 3267  
UN-No. (IATA) : 3267

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquid, basic, organic, n.o.s. (AMINOETHYLPIPERAZINE SOLUTION)  
Proper Shipping Name (TDG) : Not applicable  
Proper Shipping Name (IMDG) : CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (AMINOETHYLPIPERAZINE SOLUTION)  
Proper Shipping Name (IATA) : Corrosive liquid, basic, organic, n.o.s. (AMINOETHYLPIPERAZINE SOLUTION)  
Transport document description (DOT) : UN3267 Corrosive liquid, basic, organic, n.o.s. (AMINOETHYLPIPERAZINE SOLUTION), 8, III

# Magnolia 6398-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transport document description (IMDG) : UN 3267 CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (AMINOETHYLPIPERAZINE SOLUTION), 8, III  
Transport document description (IATA) : UN 3267 Corrosive liquid, basic, organic, n.o.s. (AMINOETHYLPIPERAZINE SOLUTION), 8, III

### 14.3. Transport hazard class(es)

#### DOT

Transport hazard class(es) (DOT) : 8  
Hazard labels (DOT) : 8



#### TDG

Transport hazard class(es) (TDG) : Not applicable

#### IMDG

Transport hazard class(es) (IMDG) : 8  
Hazard labels (IMDG) : 8



#### IATA

Transport hazard class(es) (IATA) : 8  
Hazard labels (IATA) : 8



### 14.4. Packing group

Packing group (DOT) : III  
Packing group (TDG) : Not applicable  
Packing group (IMDG) : III  
Packing group (IATA) : III

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

#### DOT

UN-No.(DOT) : UN3267

# Magnolia 6398-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx)	: 154
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other	: 40 - Stow "clear of living quarters",52 - Stow "separated from" acids

### TDG

Emergency Response Guide (ERG) Number : 153

### IMDG

Special provision (IMDG)	: 223, 274
Packing instructions (IMDG)	: P001, LP01
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T7
Tank special provisions (IMDG)	: TP1, TP28
EmS-No. (Fire)	: F-A - FIRE SCHEDULE Alfa - GENERAL FIRE SCHEDULE
EmS-No. (Spillage)	: S-B - SPILLAGE SCHEDULE Bravo - CORROSIVE SUBSTANCES
Stowage category (IMDG)	: A
Properties and observations (IMDG)	: Reacts violently with acids. Causes burns to skin, eyes and mucous membranes.

### IATA

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y841
PCA limited quantity max net quantity (IATA)	: 1L
PCA packing instructions (IATA)	: 852
PCA max net quantity (IATA)	: 5L
CAO packing instructions (IATA)	: 856
CAO max net quantity (IATA)	: 60L
Special provision (IATA)	: A3, A803
ERG code (IATA)	: 8L

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

# Magnolia 6398-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

#### 15.2. International regulations

##### CANADA

##### Magnolia 6398-B

Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)

##### Amine curing agent (140-31-8)

Listed on the Canadian DSL (Domestic Substances List)

##### Cycloaliphatic Amine (4246-51-9)

Listed on the Canadian DSL (Domestic Substances List)

##### EU-Regulations

No additional information available

##### National regulations

##### Amine curing agent (140-31-8)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

#### 15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

Component	State or local regulations
Amine curing agent(140-31-8)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 02/03/2023

Other information : © 2020 Magnolia Advanced Materials Inc. All rights reserved.

Full text of H-phrases	
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage

# Magnolia 6398-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases	
H412	Harmful to aquatic life with long lasting effects

Abbreviations and acronyms	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified

# Magnolia 6398-B

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

---

Abbreviations and acronyms	
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

Safety Data Sheet (SDS), USA

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

© 2018 Magnolia Advanced Materials Inc. All rights reserved.