

## Safety Data Sheet dated 10/22/2019, version 1

#### 1. IDENTIFICATION

#### **Product identifier**

Mixture identification:

Trade name: Prekote

Other means of identification:

MSDS code: 9241000

#### Recommended use of the chemical and restrictions on use

Recommended use:

Non-chromated surface pretreatment

Professional uses Industrial uses

Restrictions on use:

No uses advised against are identified.

# Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

#### Manufacturers:

Dysol Inc. - 791 Westport Parkway - Forth Worth, TX 76177 / Phone: 1-817-335-1826 / csr-na@socomore.com/ Fax Number: 817-335-2405

Pantheon Enterprises, Inc. - 225 West Deer Valley Road - Phoenix, AZ 85027 / Phone:

1-817-335-1826 / csr-na@socomore.com / Fax Number: 817-335-2405

Sea to Sky Innovations Limited - Unit 204, 6741 Cariboo Road, Burnaby V3N 4A3, British Columbia, Canada / Email: csr-sts@socomore.com / Phone: +1 604 420 7707 / Fax: +1 604 420 7701

#### Distributors:

SOCOMORE S.A.S.

Zone Industrielle du Prat - CS 23707 - 56037 VANNES CEDEX - France

Tel: +33 (0)2 97 43 76 83 - Fax: +33 (0)2 97 54 50 26

Socomore Ireland Ltd. - Meenane, Watergrasshill, Co. Cork, Ireland - Tel +353 21 4889922 / Fax +353 21 4889923 / ireland@socomore.com

Socomore GmbH - c/o MAZARS GmbH - Theodor-Stern-Kai 1 - 60596 Frankfurt am Main -

Deutschland - Tel: +49 (0)89 20 70 28 83 - Fax: +49 (0) 89 88 91 98 16

Socomore Iberia - Calle Diputacio, 260 - 08007 Barcelona - Espana - Tel: +34 917 693 962 - Fax: +34 902 908 966

SOCOMORE SPzoo - Ul. Piekna 18, 00-549 Warszawa Polska - Tel : +48 608 454 114 - Fax : +48 (22) 621 61 09

Dysol Inc. - 791 Westport Parkway - Forth Worth, TX 76177 / Phone: 1-817-335-1826 / csr-na@socomore.com/ Fax Number: 817-335-2405

Pantheon Enterprises, Inc. - 225 West Deer Valley Road - Phoenix, AZ 85027 / Phone:

1-817-335-1826 / csr-na@socomore.com / Fax Number: 817-335-2405

Sea to Sky Innovations Limited - Unit 204, 6741 Cariboo Road, Burnaby V3N 4A3, British Columbia, Canada / Email: csr-sts@socomore.com / Phone: +1 604 420 7707 / Fax: +1 604 420 7701

## Competent person responsible for the safety data sheet:

 $tech dirso comore @\, so comore.com\\$ 

### **Emergency phone number:**

CHEMTEL: I+1-813-248-0585 (International); 1-800-255-3924 (USA); CANUTEC: 1-613-996-6666 (CANADA)



## 2. HAZARD(S) IDENTIFICATION

#### Classification of the chemical

- Warning, Skin Irrit. 2, Causes skin irritation.
- Warning, Eye Irrit. 2A, Causes serious eye irritation.
- Warning, Skin Sens. 1A, May cause an allergic skin reaction.

#### Label elements

Hazard pictograms:



Warning

Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash Hands and Eyes Thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see ... On this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents/container in accordance with applicable regulations.

**Special Provisions:** 

None

## Hazards not otherwise classified identified during the classification process:

None

#### Ingredient(s) with unknown acute toxicity:

None.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substances

N.A.

## Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

>= 3% - < 5% 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether

REACH No.: 01-2119475104-44, Index number: 603-096-00-8, CAS: 112-34-5, EC: 203-961-6



A.3/2A Eye Irrit. 2A H319

>= 3% - < 5% 3-METHOXY-3-METHYL-1-BUTANOL

REACH No.: 01-2119976333-33, CAS: 56539-66-3, EC: 260-252-4

A.3/2A Eye Irrit. 2A H319

>= 1% - < 3% 2-(2-heptadec-8-en-1-yl-4,5-dihydro-1H-imidazol-1-yl)ethanol

CAS: 21652-27-7

4.2/1A Skin Corr. 1A H314

>= 0.3% - < 0.5% Capryloamphopropionate

CAS: 68877-55-4

A.4.2/1A Skin Sens. 1A H317

#### 4. FIRST-AID MEASURES

#### **Description of necessary measures**

#### In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

#### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Protect uninjured eye.

## In case of Ingestion:

Do not induce vomiting. Obtain a medical examination.

## In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

## Most important symptoms/effects, acute and delayed

## Indication of immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

No particular treatment.

## 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media:

Water.

Carbon dioxide (CO<sub>2</sub>).

## Unsuitable extinguishing media:

None in particular.

## Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

#### **Hazardous combustion products:**

None



Explosive properties: Not available Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains

Move undamaged containers from immediate hazard area if it can be done safely.

#### **6. ACCIDENTAL RELEASE MEASURES**

## Personal precautions, protective equipment, and emergency procedures

Wear personal protection equipment.

Remove persons to safety.

See protective measures under point 7 and 8.

#### Methods and materials for containment and cleaning up

Wash with plenty of water.

#### 7. HANDLING AND STORAGE

#### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Do not use on extensive surface areas in premises where there are occupants.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

See also section 8 for recommended protective equipment.

Advice on general occupational hygiene:

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

#### Conditions for safe storage, including any incompatibilities

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

Storage temperature:

Store at ambient temperature.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

- OEL Type: National TWA(8h): 67.5 mg/m3 Notes: Germany
- OEL Type: National TWA(8h): 67.5 mg/m3, 10 ppm STEL: 101.2 mg/m3, 15 ppm Notes: France VLEI
- OEL Type: National TWA(8h): 67.5 mg/m3, 10 ppm STEL: 101.2 mg/m3, 15 ppm Notes: UK
- OEL Type: EU TWA(8h): 67.5 mg/m3, 10 ppm STEL: 101.2 mg/m3, 15 ppm
- OEL Type: ACGIH TWA(8h): 10 ppm Notes: (IFV) Hematologic, liver and kidney eff
- OEL Type: National TWA(8h): 50 mg/m3, 9 ppm STEL: 100 mg/m3, 18 ppm Notes: Netherlands
- OEL Type: National TWA: 67.5 mg/m3, 10 ppm STEL: 101.2 mg/m3, 15 ppm Notes: Belgium
- OEL Type: National TWA: 67.5 mg/m3, 10 ppm STEL(15min (Miw)): 101.2 mg/m3, 15 ppm Notes: Osterreich

## **DNEL Exposure Limit Values**



2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Worker Industry: 101 mg/m3 - Consumer: 7.5 mg/m3 - Exposure: Human Inhalation -

Frequency: Short Term, local effects

Worker Industry: 20 mg/kg bw/day - Consumer: 10 mg/kg bw/day - Exposure: Human

Dermal - Frequency: Long Term, systemic effects

Worker Industry: 10 ppm - Consumer: 5 mg/kg bw/day - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Worker Industry: 10 ppm - Consumer: 5 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, local effects

Consumer: 1.25 - Exposure: Human Oral - Frequency: Long Term, systemic effects

3-METHOXY-3-METHYL-1-BUTANOL - CAS: 56539-66-3

Worker Industry: 5.9 mg/m3 - Consumer: 1.7 mg/m3 - Exposure: Human Inhalation -

Frequency: Long Term, systemic effects

Worker Industry: 2 mg/kg - Consumer: 1.2 mg/kg bw/day - Exposure: Human Dermal -

Frequency: Long Term, systemic effects

Consumer: 0.5 mg/kg bw/day - Exposure: Human Oral - Frequency: Long Term,

systemic effects

#### **PNEC Exposure Limit Values**

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Target: Fresh Water - Value: 1 mg/l Target: Marine water - Value: 0.1 mg/l

Target: Freshwater sediments - Value: 4 mg/l Target: Marine water sediments - Value: 0.4 mg/l

Target: Soil (agricultural) - Value: 0.4 mg/l

Target: Microorganisms in sewage treatments - Value: 200 mg/l

#### Appropriate engineering controls:

None

## Individual protection measures

Eye protection:

Safety goggles (EN 166)

Face protection shield. (EN 166)

Use closed fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Use respiratory protection where ventilation is insufficient or exposure is prolonged such as Mask with filter "A1" brown color(NF EN 14387)

Thermal Hazards:

None

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Properties	Value	Method:	Notes	
Appearance and colour:	Clear Amber	Clear Amber		
Odour:	None			
Odour threshold:	Not available			
pH:	10.5			
Melting point / freezing point:	28 deg F			
Initial boiling point and boiling	219 deg F, 104 deg C			



range:			
range:	400.4		
Flash Point (deg F):	>199.4		
Flash point (deg C):	>93		
Evaporation rate:	<1 But		Butyl acetate = 1
Solid/gas flammability:	Not applicable		
Upper/lower flammability or	Not applicable		
explosive limits:			
Vapour pressure:	17.3 mm Hg at 20 deg C		DGBE = 0.02
			mmHg at 20
			degC
Vapour density:	Not available		
Relative density:	0.96 - 1.04		Water Based
Solubility in water:	Completely soluble		
Solubility in oil:	Not available		
Partition coefficient	Not available		
(n-octanol/water):			
Auto-ignition temperature:	Not available		
Decomposition temperature:	Not available		
Viscosity:	Not available	Not available	
Explosive properties:	Not available		
Oxidizing properties:	Not available		

#### 9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.		
Fat Solubility:	N.A.		
Conductivity:	N.A.		
Substance Groups	N.A.		
relevant properties			

## 10. STABILITY AND REACTIVITY

Reactivity

Stable under normal conditions

**Chemical stability** 

Stable under normal conditions

Possibility of hazardous reactions

None

Conditions to avoid

Stable under normal conditions.

Incompatible materials

None in particular.

**Hazardous decomposition products** 

None.

## 11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

a) acute toxicity:



Test: LD50 - Route: Oral - Species: Mouse = 2410 mg/kg bw Test: LD50 - Route: Skin - Species: Rabbit = 2764 mg/kg bw Route: Inhalation - Species: Rat > 29 ppm - Duration: 2h - Notes: IRT (inhalation risk test) g) reproductive toxicity: Test: NOAEL - Species: Mouse = 720 MGKGBWDAY - Notes: 14 weeks 3-METHOXY-3-METHYL-1-BUTANOL - CAS: 56539-66-3 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat = 4300 mg/kg Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg i) STOT-repeated exposure: Test: NOAEL - Route: Oral - Species: Rabbit = 60 MGKGBWDAY Test: LOAEL - Route: Oral - Species: Rat = 250 mg/kg - Duration: 28 days Test: NOAEL - Route: Oral - Species: Rat = 60 mg/kg - Duration: 28 days Test: LOAEL - Route: Inhalation - Species: Rat = 0.53 mg/l - Duration: 28 days

## Substance(s) listed on the NTP report on Carcinogens:

None

Substance(s) listed on the IARC Monographs:

None.

Substance(s) listed as OSHA Carcinogen(s):

None.

Substance(s) listed as NIOSH Carcinogen(s):

None.

## 12. ECOLOGICAL INFORMATION

## **Ecotoxicity**

Adopt good working practices, so that the product is not released into the environment.

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 1300 mg/l - Duration h: 96 - Notes: Lepomis macrochirus

Endpoint: EC50 - Species: Daphnia = 4950 mg/l - Duration h: 48

Endpoint: LC50 - Species: Daphnia = 13415 mg/l - Duration h: 96 - Notes:

Americamysis bahia

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 96 - Notes: Desmodesmus subspicatus

Endpoint: EC10 - Species: Microorganisms > 1995 mg/l - Duration h: 0.5

c) Bacteria toxicity:

Endpoint: EC50 - Species: bacteria > 100 mg/l

3-METHOXY-3-METHYL-1-BUTANOL - CAS: 56539-66-3

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 100 mg/l - Duration h: 96 - Notes: Oryzias latipes Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: Daphnia magna

Endpoint: NOEC - Species: Algae = 1000 mg/l - Duration h: 72 - Notes: green algae(Selenastrum (Selenastrum capricornutum (green algae))

Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72 - Notes: (Selenastrum capricornutum (green algae))

Endpoint: EC50 - Species: bacteria > 1000 mg/l - Duration h: 3

Endpoint: IC50 - Species: aquatic plants > 1000 mg/l - Duration h: 72

b) Aquatic chronic toxicity:



Endpoint: NOEC - Species: Daphnia = 100 mg/l - Notes: 21 days, Daphnia magna

## Persistence and degradability

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Biodegradability: Photodegradation (in air) - Test: DT50 - Duration: 3-4 hours - Notes:

1.5x10^6 /cm?, AOPWIN

Biodegradability: Biodegradation in water - Test: MITI modif(I) - Duration: 28 days - %:

>80 - Notes: OECD 301C

3-METHOXY-3-METHYL-1-BUTANOL - CAS: 56539-66-3

Biodegradability: Readily biodegradable - Duration: 28 days

#### Bioaccumulative potential

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Log Pow 1 - Notes: 20?C

#### Mobility in soil

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether - CAS: 112-34-5

Volality (H: Henry's Law Constant) 0 atm m?/mol - Notes: 25?C

Surface tension 0.0069 N/m - Notes: 20?C

#### Other adverse effects

No harmful effects expected.

#### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment and disposal methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

Additional disposal information:

Disposal should be in accordance with applicable regional, national and local laws and regulations. Please consult Technical Data Sheet for details.

## 14. TRANSPORT INFORMATION

**UN** number

Not classified as dangerous in the meaning of transport regulations.

UN proper shipping name

N.A.

Transport hazard class(es)

N.A.

Packing group

N.A.

Environmental hazards

ADR-Enviromental Pollutant: No IMDG-Marine pollutant: No

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code)

N.A.

The product is transported in conditions that comply with exemption criteria for ADR transport.

Special precautions

N.A.

#### 15. REGULATORY INFORMATION

## **USA - Federal regulations**

TSCA - Toxic Substances Control Act

List of substances included in the TSCA inventory: 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether, 3-METHOXY-3-METHYL-1-BUTANOL.



List of substances not included in the TSCA inventory:

2-(2-heptadec-8-en-1-yl-4,5-dihydro-1H-imidazol-1-yl)ethanol,

Capryloamphopropionate.

TSCA sections for substances listed in section 3:

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether is listed in TSCA Section 8b

3-METHOXY-3-METHYL-1-BUTANOL is listed in TSCA Section 8b.

SARA - Superfund Amendments and Reauthorization Act

Section 302 Extremely Hazardous Substances: no substances listed.

Section 304 Hazardous substances: no substances listed.

Section 313 Toxic chemical list: no substances listed.

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act No substances listed.

CAA - Clean Air Act

CAA listed substances:

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether is listed in CAA Section 111, Section 112(b) - HON, Section 112(b) - HAP.

CWA - Clean Water Act

CWA listed substances:

None.

#### **USA - State specific regulations**

California Proposition 65

Substance(s) listed under California Proposition 65:

None.

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

No substances listed.

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

No substances listed.

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

No substances listed.

The following substance(s) in this product has/have an identification by CAS number either in countries not affected by the REACH regulation or in regulations not yet updated to reflect the new naming convention for hydrocarbon solvents:

### **16. OTHER INFORMATION**

Full text of phrases referred to in Section 3:

H319 Causes serious eye irritation.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Safety Data Sheet dated 10/22/2019, version 1

Disclaimer:

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. The information relates only to the specific material and may not be valid for such material used in combination with any other material or in any process.

This Safety Data Sheet cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of



Dangerous Goods by Road.

ATE: Acute Toxicity Estimate

ATEmix: Acute toxicity Estimate (Mixtures)

CAS: Chemical Abstracts Service (division of the American Chemical

Society).

CLP: Classification, Labeling, Packaging.

DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.
GHS: Globally Harmonized System of Classification and Labeling of

Chemicals.

HMIS: Hazardous Materials Identification System IARC: International Agency for Research on Cancer IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport

Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization"

(ICAO).

IMDG: International Maritime Code for Dangerous Goods. INCI: International Nomenclature of Cosmetic Ingredients.

KSt: Explosion coefficient.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PNEC: Predicted No Effect Concentration.

RID: Regulation Concerning the International Transport of Dangerous Goods

by Rail.

STEL: Short Term Exposure limit.
STOT: Specific Target Organ Toxicity.
TLV: Threshold Limiting Value.
TWA: Time-weighted average