HUNTSMAN

Enriching lives through innovation

P.O. Box 4980 The Woodlands, TX 77387-4980

8 am to 5 pm Phone: (800) 257-5547 24-Hour Emergency Phone: (800) 328-8501 International Emergency Phone: (409) 727-0831 Asia Pacific Emergency Phone: (65) 6336-8011

Effective Date: 4/7/10

Material Safety Data Sheet

MSDS No: 6335

1. PRODUCT IDENTIFICATION

Trade Name: Hardener 8579 US

Chemical Family: Amine

3 1 0

Health: 3*

Flammability: 1

Reactivity: 0

Personal Protection:

NFPA RATING

HMIS RATING

Synonyms:

LSA 642-03 Hardener XMH 8579 Hardener

Intended Use or Product Type: Epoxy adhesive hardener

2. COMPOSITION / INFORMATION ON INGREDIENTS

0 8	CAS No.	CHEMICAL IDENTITY	EXPOSURE LIMITS					CARCINOGEN STATUS		
Н			ACGIH		OSHA		MFR.	IARC	NTP	OSHA
A			TWA	STEL	PEL	STEL	_		1	
*	10563-29-8 Соттоп Name:	1,3-Propanediamine, N'-(3- aminopropy!)-N,N-dimethyl- Dimethylene Propylene Triamine	NE	NE	NE	NE	NE	NR	NR	NR
İ	Concentration	5.00 - 10.00 % by wt	İ					1	ļ	
+	111-40-0 Common Name: Concentration	1.2-Ethanediamine, N-(2- aminoethyl)- Diethylenetriamine	1 ppm	NE	NE	NE	NE	NR	NR	NR
*	112-24-3	1,2-Ethanediamine, N,N'-bis(2-	NE	NE	NE	NE NE	NE	NR	NR	NR
	Common Name: Concentration	aminoethyl)- Triethylenetetramine		112			2			
*	14808-60-7	Quartz (SiO2)	0.05	NE	0.1	NE	NE	Yes	Yes	NR
	Common Name: Concentration	Crystalline silica 0.10 - 0.30 % by wt	mg/m3		mg/m3					
•	68082-29-1 Common Name: Concentration	Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine Polyamide Resin 30.00 - 60.00 % by wt	NE	NE	NE	NE	NE	NR	NR	NR

Printed: 4/14/2010

Page 1 of 8

Hardener 8579 US Huntsman Advanced Materials Americas LLC (EL)

*	7727-43-7	Sulfuric acid, barium salt (1:1)	10 mg/m3	NE	5 mg/m3	NE	NE	NR	NR	NR
	Common	Barium Sulfate						!		!
ł	Name:	1	1 1	'	i i	ł	ł	l	ł	ł
	Concentration	30.00 - 60.00 % by wt	J							
-	80-05-7	Phenol, 4,4'-(1- methylethylidene)bis-	NE	NE	NE	NE	TLV 5 mg/m3	NR	NR	NŘ
	Common	Bisphenol A					ļ		ł	
	Name:							İ		
	Concentration	1.00 - 5.00 % by wt	1				ŀ			
	1302-78-9	Bentonite	NE	NE	NE	NE	NE	NR	NR	NR
	Concentration	5.00 - 10.00 % by wt						:		

NE = Not Established NR = Not Reviewed * = OSHA Hazardous Ingredient

3. HAZARDS IDENTIFICATION

Effective Date: 4/7/10

Emergency Overview: Corrosive - causes skin and eye burns. Causes irritation if inhaled and can cause allergic respiratory reaction and allergic skin reaction. Can be harmful if absorbed through skin and may be harmful if swallowed.

Primary Route(s) of Entry: Dermal; heated product may produce inhalable vapors.

Carcinogenicity (NTP, IARC, OSHA): This product contains crystalline silica. Repeated inhalation of respirable free crystalline silica dust may cause delayed lung injury (silicosis) and cancer.

Acute Exposure: Corrosive. Causes skin and eye burns.

Chronic: Overexposure may have effects on kidney and liver.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Skin: Immediately wash with soap and water. Remove contaminated clothing and launder before reuse. Destroy contaminated shoes. Seek immediate medical attention.

Inhalation: Remove to fresh air. Seek immediate medical attention.

Eyes: Immediately flush eyes with water for at least 15 minutes. Seek immediate medical attention.

Overexposure Effects: Corrosive - causes skin and eye burns. Causes irritation if inhaled and can cause allergic respiratory reaction and allergic skin reaction. Can be harmful if absorbed through skin and may be harmful if swallowed.

Medical Conditions Aggravated by Exposure: Skin, eye and pulmonary conditions.

Additional Information: Referral to a physician is recommended if there is any question about the seriousness of any injury.

5. FIRE FIGHTING MEASURES

Printed: 4/14/2010 Page 2 of 8

Hardener 8579 US Huntsman Advanced Materials Americas LLC (EL)

Flash Point: > 200°F (> 93 °C)

Flash Point Method Used: Estimated
Flammable Limits in Air (Lower - % by volume): Not established
Flammable Limits in Air (Upper - % by volume): Not established

Fire Fighting Extinguishing Media: Carbon dioxide, dry chemical, foam, water.

Fire Fighting Equipment: Use self-contained breathing apparatus.

Fire and Explosion Hazards: Decomposition and combustion products may be toxic.

6. ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Remove spillage by absorbing in absorbent material.

7. HANDLING AND STORAGE

Signal Word: Danger!

Effective Date: 4/7/10

Precautions: Corrosive - causes skin and eye burns. Causes irritation if inhaled and can cause allergic respiratory reaction and allergic skin reaction. Can be harmful if absorbed through skin and may be harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid breathing vapor or mist. Avoid tasting or swallowing. Keep container closed when not in use. Use with adequate ventilation. Wash thoroughly after handling. Notice! Overexposure may have effects on developing fetus.

Other Handling Information: Nuisance dust may be generated when sanding or sawing cured material.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Skin Protection: Wear impermeable gloves.

Respiratory Protection: Use NIOSH approved organic vapor cartridge respirator when vapor/mist exposure is likely.

Eye Protection: Wear splash-proof chemical goggles.

Engineering Controls: General mechanical and local exhaust in accordance with ACGIH recommendations.

9. PHYSICAL AND CHEMICAL PROPERTIES

Grey Color: Paste Physical State: Moderate Solubility in Water: Vapor Pressure: Not Determined Specific Gravity: 1.65 (water = 1) **Boiling Point:** Not Determined **Melting Point:** Not Determined Not Determined **Evaporation Rate:** Not Determined Density: Not Determined Vapor Density:

Printed: 4/14/2010 Page 3 of 8

Hardener 8579 US Huntsman Advanced Materials

Effective Date: 4/7/10

Americas LLC (EL)

pH:

Not Determined Not Determined

Coefficient of water/oil:

Percent Volatile: Not determined.

10. STABILITY AND REACTIVITY

Conditions to Avoid: Excessive heat for prolonged periods of time.

Stability: Stable.

Incompatibility: Strong oxidizers, acids and bases.

Hazardous Decomposition Products: Combustion may form toxic materials, such as carbon dioxide, carbon monoxide.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute Oral Effects (LD50): Component(s) are slightly toxic, 500 - 5000 mg/kg (rat). Diethylenetriamine= 1080 - 2330 mg/kg (rat)
Dimethylene propylene triamine= 1670 mg/kg (rat)
Triethylenetetramine= 2500 - 4340 mg/kg (rat)

Acute Dermal Toxicity (LD50): Component(s) are toxic, 200 - 1000 mg/kg (rabbit).

Triethylenetetramine= 550 - 800 mg/kg (rabbit)
Diethylenetriamine= 672 - 1240 mg/kg (rabbit)
Dimethylene propylene triamine= 1310 mg/kg (rabbit).

Acute Inhalation Exposure Effects: Respiratory irritant.

Sensitization: Causes allergic skin and respiratory sensitivity in some people.

Carcinogenicity: This product contains crystalline silica. Repeated inhalation of respirable free crystalline silica dust may cause delayed lung injury (silicosis) and cancer.

Skin Irritation: Corrosive. Causes burns.

Eye Irritation: Corrosive. Causes burns.

Reproduction: A recent study (October 2000) has shown that orally administered bisphenol A (BPA) in rats, can cross the placental barrier. Peak concentrations were achieved in most tissues within approximately 20 minutes and were reduced by 95 to 98% within 6 hours. A second study, "Three Generation Reproductive Toxicity Evaluation" in rats, yielded the following no observed adverse effect levels (NOAELs): adult systemic toxicity= 75 ppm or approximately 5 mg/kg/day; reproductive toxicity= 750 ppm or approximately 50 mg/kg/day; and postnatal toxicity= 750 ppm or approximately 50 mg/kg/day. These results suggest that Bisphenol A crosses the placental barrier and at high doses (greater than 50 mg/kg/day at or near the maximum tolerated dose) may be a mild reproductive and/or postnatal toxicant.

12. ECOLOGICAL INFORMATION

Printed: 4/14/2010 Page 4 of 8

Effective Date: 4/7/10

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Consult qualified local or corporate personnel for method that will comply with local, state and federal health and environmental regulations.

14. TRANSPORT INFORMATION

DOT: Non-Bulk

Proper Shipping Name: Polyamines, liquid, corrosive, N.O.S.

Technical Shipping Name (If n.o.s.): Dimethyl dipropyl triamine, Diethylene triamine

Hazard Class:

ID Number: UN 2735
Packing Group: PG II
Label: Corrosive

IATA: Non-Bulk

Proper Shipping Name: Polyamines, liquid, corrosive, N.O.S.

Technical Shipping Name (If n.o.s.): Dimethyl dipropyl triamine, Diethylene triamine

Hazard Class: 8
ID Number: UN 2735

Packing Group: PG II
Label: Corrosive

IMDG: Non-Bulk

Proper Shipping Name: Polyamines, liquid, corrosive, N.O.S.

Technical Shipping Name (If n.o.s.): Dimethyl dipropyl triamine, Diethylene triamine

Hazard Class: 8
ID Number: U

ID Number: UN 2735
Packing Group: PG II
Label: Corrosive

Label: TDG: Non-Bulk

Proper Shipping Name: Polyamines, liquid, corrosive, N.O.S.

Technical Shipping Name (If n.o.s.): Dimethyl dipropyl triamine, Diethylene triamine

Hazard Class:

ID Number: UN 2735
Packing Group: PG II

Label: PG II
Corrosive

15. REGULATORY INFORMATION

US Federal Regulations:

8

Occupational Safety and Health Act (OSHA): This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is considered to be a hazardous chemical under that standard.

Resource Conservation and Recovery Act (RCRA): Not a hazardous waste under RCRA (40 CFR 261) but handle with care due to corrosive effect on skin and eyes.

SARA Title III: Section 313 Toxic Chemical List (TCL): This product contains a toxic chemical(s) for routine annual toxic chemical release reporting under section 313 (40 CFR 372). This information must be included in all MSDS's copied or distributed for this material.

Printed: 4/14/2010 Page 5 of 8

Hardener 8579 US

Huntsman Advanced Materials Americas LLC (EL)

Effective Date: 4/7/10

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-

Common Name: Bisphenol A
Percent in Composition: 1 - 5 % by wt

Comment:

TSCA Section 8(b) - Inventory Status: All chemical components of this product are in compliance with TSCA inventory requirements.

TSCA Section 12(b) - Export Notification: This product does not contain any chemical(s) that are subject to a Section 12(b) export notification.

International Regulations:

Australian Inventory Status: This product contains only chemicals which are currently listed on the Australian Inventory of Chemical Substances.

Canadian Inventory Status: This product contains only chemicals that are currently listed on the Canadian Domestic Substance List.

Canadian WHMIS: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. D1B D2A D2B E

European Inventory Status (EINECS): This product contains only chemicals that are currently listed on the European Inventory of Existing Commercial Chemical Substances (EINECS).

State Regulations:

California Proposition 65: The following is required composition information. This product contains the following chemical(s) which are currently listed on the California list of Known Carcinogens and Reproductive Toxins:

Chemical Name: Quartz (SiO2)
Common Name: Crystalline silica
CAS Number: 14808-60-7

Percent in Composition: 0.1 - 0.3 % by wt

Comment: Warning! This chemical is known to the State of California to cause cancer.

Pennsylvania Right-to-Know: The following is required composition information:

Chemical Name: Sulfuric acid, barium salt (1:1)

Common Name: Barium Sulfate CAS Number: 7727-43-7 Comment: Hazardous Substance

Chemical Name: Fatty acids, C18-unsatd., dimers, polymers with tall-oil fatty acids and triethylenetetramine

Common Name: Polyamide Resin

CAS Number: 68082-29-1

Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: Bentonite CAS Number: 1302-78-9

Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: 1,3-Propanediamine, N'-(3-aminopropyl)-N,N-dimethyl-

Printed: 4/14/2010 Page 6 of 8

Hardener 8579 US

Huntsman Advanced Materials Americas LLC (EL)

Effective Date: 4/7/10

Common Name: Dimethylene Propylene Triamine

CAS Number: 10563-29-8

Comment: Not on Pennsylvania Hazardous Substance List

Chemical Name: 1,2-Ethanediamine, N-(2-aminoethyl)-

Common Name: Diethylenetriamine

CAS Number: 111-40-0

Comment: Hazardous Substance

Chemical Name: Phenol, 4,4'-(1-methylethylidene)bis-

Common Name: Bisphenol A CAS Number: 80-05-7

Comment: Environmental Hazardous Substance

Chemical Name: 1,2-Ethanediamine, N,N'-bis(2-aminoethyl)-

Common Name: Triethylenetetramine

CAS Number: 112-24-3

Comment: Hazardous Substance

16. OTHER INFORMATION

MSDS No:

Reason Issued:

4/10 update haz - 10/09 rename

Approved By:

Matt Austin

Title:

EHS Chemist

Other Information: BLW/Si/KL/CA1 (B12121031) [B20]

Disclaimer: The information and recommendations contained herein are based upon tests in controlled laboratory conditions, are believed to be correct, and are provided for the sole purpose of hazard communication as part of Huntsman's product safety program. This product has not been tested for, and therefore is not recommended or suitable for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended or likely, or for uses for which implantation within the human body is intended, and Huntsman assumes no liability for any such uses.

The information and recommendations contained herein are not intended to constitute performance information concerning the product, which is available in separate technical data sheets available from Huntsman upon request. Users are urged, and are urged to urge others who may come in contact with the product, to obtain and consult data sheets prior to purchase, use, transportation or storage of the product.

HUNTSMAN MAKES NO REPRESENTATION OR WARRANTY, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY, QUALITY, OR FITNESS FOR A PARTICULAR PURPOSE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED TO REIMBURSEMENT OF BUYER'S PURCHASE PRICE, OR IN HUNTSMAN'S DISCRETION REPLACEMENT, OF THE PRODUCT IN RESPECT OF WHICH SUCH CLAIM IS MADE. HUNTSMAN'S LIABILITY IS STRICTLY LIMITED BY LEGAL NOTICES IN TECHNICAL DATA SHEETS, PRODUCT LITERATURE, AND/OR SALE DOCUMENTS. The foregoing DISCLAIMERS and LIMITATION OF LIABILITY supercede inconsistent or contradictory provisions in Buyer's documents.

USER SHOULD CONSULT A LEGAL ADVISOR OR THE APPROPRIATE GOVERNMENTAL AGENCY TO DETERMINE THE APPLICABILITY OR EFFECT OF ANY LAW OR REGULATION WITH RESPECT TO THE PRODUCT. HUNTSMAN DOES NOT UNDERTAKE TO FURNISH ADVICE ON SUCH MATTERS.

Page 7 of 8 Printed: 4/14/2010

Hardener 8579 US

Huntsman Advanced Materials
Americas LLC (EL)

Effective Date: 4/7/10

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO HUNTSMAN, MANAGER, PRODUCT SAFETY AT THE ABOVE ADDRESS.

Printed: 4/14/2010 Page 8 of 8