

## 1. Identification

**Product identifier** 0165JC51

**Other means of identification**

**Synonyms** Goodrich Kit Components: 74-451-156, 74-451-167 (Contained in Goodrich Kits: 74-451-S, 74-451-S-2)

**Recommended use** Aerospace Coating

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Supplier**

**Company name** Goodrich Corporation  
UTC Aerospace Systems Sensors and Integrated Systems (Formerly De-icing and Specialty Systems)

**Address** 1555 Corporate Woods Parkway  
Uniontown, Ohio 44685  
US

**E-mail** Terry.Sluss@utas.utc.com

**Contact name** EH&S Manager

**Telephone number** (330)374-4011

**Emergency telephone number** (800)424-9300

## 2. Hazard(s) identification

**Physical hazards** Flammable liquids Category 2

**Health hazards**

Acute toxicity, oral	Category 4
Acute toxicity, dermal	Category 3
Acute toxicity, inhalation	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity, single exposure	Category 3 narcotic effects

**OSHA defined hazards** Not classified.

### Label elements



**Signal word** Danger

**Hazard statement**

Highly flammable liquid and vapor. Harmful if swallowed. Toxic in contact with skin. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Suspected of causing cancer. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness.

## Precautionary statement

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.

### Response

In case of fire: Use appropriate media to extinguish. If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse.

### Storage

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

### Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

### Hazard(s) not otherwise classified (HNOC)

None known.

### Supplemental information

None.

## 3. Composition/information on ingredients

### Mixtures

Chemical name	CAS number	%
Methyl ethyl ketone	78-93-3	40 - 60
Cyclohexanone	108-94-1	25 - 45
Tetrahydrofuran	109-99-9	3 - 5
Aluminium	7429-90-5	1 - 3
2-Methoxy-1-methylethyl acetate	108-65-6	<1
Toluene	108-88-3	< 1
Antimony trioxide	1309-64-4	< 0.2

### Composition comments

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

## 4. First-aid measures

### Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a POISON CENTER or doctor/physician if you feel unwell.

### Skin contact

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical advice/attention if you feel unwell. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

### Ingestion

Rinse mouth. Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Get medical advice/attention if you feel unwell.

### Most important symptoms/effects, acute and delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

<b>General information</b>	Take off immediately all contaminated clothing. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.
<b>5. Fire-fighting measures</b>	
<b>Suitable extinguishing media</b>	Water fog. Foam. Dry chemical. Carbon dioxide (CO <sub>2</sub> ).
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire. Carbon Dioxide may be ineffective on large fires, due to lack of cooling capacity.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. The product can accumulate electrostatic charges, which may cause an electrical spark (ignition source). Use proper grounding procedures. During fire, gases hazardous to health may be formed such as: Carbon monoxide. Carbon dioxide. Smoke. Aliphatic hydrocarbons.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. If a leak or spill has not ignited, use water spray to disperse the vapors and to protect men attempting to stop a leak.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.
<b>6. Accidental release measures</b>	
<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. This product is miscible in water.  Large Spills: Stop the flow of material, if this is without risk. Use water spray to reduce vapors or divert vapor cloud drift. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.
<b>7. Handling and storage</b>	
<b>Precautions for safe handling</b>	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.
<b>Conditions for safe storage, including any incompatibilities</b>	Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep out of the reach of children. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	PEL	5 mg/m <sup>3</sup> 15 mg/m <sup>3</sup>	Respirable dust. Total dust.
Antimony trioxide (CAS 1309-64-4)	PEL	0.5 mg/m <sup>3</sup>	
Cyclohexanone (CAS 108-94-1)	PEL	200 mg/m <sup>3</sup>	
Methyl ethyl ketone (CAS 78-93-3)	PEL	50 ppm 590 mg/m <sup>3</sup>	
Tetrahydrofuran (CAS 109-99-9)	PEL	200 ppm 590 mg/m <sup>3</sup>	
		200 ppm	

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling TWA	300 ppm 200 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m <sup>3</sup>	Respirable fraction.
Antimony trioxide (CAS 1309-64-4)	TWA	0.5 mg/m <sup>3</sup>	
Cyclohexanone (CAS 108-94-1)	STEL	50 ppm	
Methyl ethyl ketone (CAS 78-93-3)	TWA STEL	20 ppm 300 ppm	
Tetrahydrofuran (CAS 109-99-9)	TWA STEL	200 ppm 100 ppm	
Toluene (CAS 108-88-3)	TWA TWA	50 ppm 20 ppm	

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m <sup>3</sup> 5 mg/m <sup>3</sup> 10 mg/m <sup>3</sup>	Welding fume or pyrophoric powder. Respirable. Total
Antimony trioxide (CAS 1309-64-4)	TWA	0.5 mg/m <sup>3</sup>	
Cyclohexanone (CAS 108-94-1)	TWA	100 mg/m <sup>3</sup>	
Methyl ethyl ketone (CAS 78-93-3)	STEL	25 ppm 885 mg/m <sup>3</sup>	
	TWA	300 ppm 590 mg/m <sup>3</sup> 200 ppm	
Tetrahydrofuran (CAS 109-99-9)	STEL	735 mg/m <sup>3</sup>	
	TWA	250 ppm 590 mg/m <sup>3</sup> 200 ppm	
Toluene (CAS 108-88-3)	STEL	560 mg/m <sup>3</sup>	

## US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
	TWA	150 ppm 375 mg/m <sup>3</sup> 100 ppm	

## US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	50 ppm

## Biological limit values

### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Cyclohexanone (CAS 108-94-1)	80 mg/l	1,2-Cyclohexanediol, with hydrolysis	Urine	*
	8 mg/l	Cyclohexanol, with hydrolysis	Urine	*
Methyl ethyl ketone (CAS 78-93-3)	2 mg/l	MEK	Urine	*
Tetrahydrofuran (CAS 109-99-9)	2 mg/l	Tetrahydrofuran	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

\* - For sampling details, please see the source document.

## Exposure guidelines

### US - California OELs: Skin designation

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	Can be absorbed through the skin.
Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.
Toluene (CAS 108-88-3)	Can be absorbed through the skin.

### US - Minnesota Haz Subs: Skin designation applies

Cyclohexanone (CAS 108-94-1)	Skin designation applies.
Toluene (CAS 108-88-3)	Skin designation applies.

### US - Tennessee OELs: Skin designation

Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.
------------------------------	-----------------------------------

### US ACGIH Threshold Limit Values: Skin designation

Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.
Tetrahydrofuran (CAS 109-99-9)	Can be absorbed through the skin.

## US. NIOSH: Pocket Guide to Chemical Hazards

Cyclohexanone (CAS 108-94-1)	Can be absorbed through the skin.
------------------------------	-----------------------------------

### Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

## Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

### Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

### Skin protection

**Other** Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

### Respiratory protection

When engineering controls are not sufficient to lower exposure levels below the applicable exposure limit, use a NIOSH approved respirator.

<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using, do not eat, drink or smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical surveillance requirements.

## 9. Physical and chemical properties

<b>Appearance</b>	Silver liquid.
<b>Physical state</b>	Liquid.
<b>Form</b>	Thin liquid.
<b>Color</b>	Silver.
<b>Odor</b>	Sharp.
<b>Odor threshold</b>	1 - 5 ppm
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	Not available.
<b>Initial boiling point and boiling range</b>	151 - 410 °F (66.11 - 210 °C)
<b>Flash point</b>	6.0 °F (-14.4 °C) (TCC)
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1.1 %
<b>Flammability limit - upper (%)</b>	12.7 %
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	> 1 (Air = 1)
<b>Relative density</b>	0.88
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Appreciable (20°C)
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>VOC (Weight %)</b>	98 %

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Strong acids. Ammonia. Amines. Alkanolamines. Aldehydes. Isocyanates. Caustics.
<b>Hazardous decomposition products</b>	Carbon monoxide. Carbon dioxide. Aliphatic hydrocarbons.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Harmful if inhaled. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May be irritating to the respiratory tract.
<b>Skin contact</b>	Toxic in contact with skin. Causes skin irritation. Prolonged skin contact may cause dermatitis.
<b>Eye contact</b>	Causes serious eye irritation. Risk of corneal damage.
<b>Ingestion</b>	Harmful if swallowed. Swallowing or vomiting of the liquid may result in aspiration into the lungs. Aspiration may cause pulmonary edema and pneumonitis.

### Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity** Toxic in contact with skin. Harmful if inhaled. Harmful if swallowed.

Components	Species	Test Results
------------	---------	--------------

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)

#### Acute

##### Dermal

LD50	Rabbit	> 5000 mg/kg
------	--------	--------------

Antimony trioxide (CAS 1309-64-4)

#### Acute

##### Oral

LD50	Rat	> 20 g/kg
------	-----	-----------

Methyl ethyl ketone (CAS 78-93-3)

#### Acute

##### Dermal

LD50	Rabbit	5000 mg/kg
------	--------	------------

##### Inhalation

LC50	Rat	35.3 mg/l
------	-----	-----------

##### Oral

LD50	Rat	3000 mg/kg
------	-----	------------

Tetrahydrofuran (CAS 109-99-9)

#### Acute

##### Dermal

LD50	Rat	> 2000 mg/kg, 24 Hours
------	-----	------------------------

##### Oral

LD50	Rat	1650 mg/kg
------	-----	------------

Toluene (CAS 108-88-3)

#### Acute

##### Dermal

LD50	Rabbit	14.1 ml/kg
------	--------	------------

##### Inhalation

LC50	Rat	49000 mg/m <sup>3</sup> , 4 Hours
------	-----	-----------------------------------

##### Oral

LD50	Rat	5580 mg/kg
------	-----	------------

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

### Respiratory or skin sensitization

**Respiratory sensitization** Not available.

**Skin sensitization** Prolonged skin contact may cause dermatitis.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Suspected of causing cancer.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

Antimony trioxide (CAS 1309-64-4) 2B Possibly carcinogenic to humans.  
Cyclohexanone (CAS 108-94-1) 3 Not classifiable as to carcinogenicity to humans.  
Toluene (CAS 108-88-3) 3 Not classifiable as to carcinogenicity to humans.

**NTP Report on Carcinogens**

Not listed.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not regulated.

**Reproductive toxicity** Suspected of damaging fertility or the unborn child.

MEK - Embryo/fetotoxic effects have been observed in laboratory rats exposed to over 1000 ppm MEK for most of gestation period.

**Specific target organ toxicity - single exposure** May cause drowsiness and dizziness.

**Specific target organ toxicity - repeated exposure** Not classified.

**Aspiration hazard** Not available.

**Chronic effects** Prolonged skin contact may cause dermatitis. Repeated or prolonged exposure may cause kidney and liver damage. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

**12. Ecological information**

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Antimony trioxide (CAS 1309-64-4)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) 361.5 - 496 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas) > 80 mg/l, 96 hours
Methyl ethyl ketone (CAS 78-93-3)		
<b>Aquatic</b>		
Crustacea	LC50	Daphnia magna 12600 mg/l, 24 Hours
Fish	LC50	Goldfish (Carassius auratus) > 5000 mg/l, 24 Hours
Tetrahydrofuran (CAS 109-99-9)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas) 2160 mg/l, 96 Hours
Toluene (CAS 108-88-3)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia magna) 5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Pink salmon (Oncorhynchus gorbuscha) 6.86 - 8.48 mg/l, 96 hours

**Persistence and degradability** Methyl ethyl ketone: Readily biodegradable. Rapidly decomposed by photochemical processes in air.

**Bioaccumulative potential** Methyl ethyl ketone: Low bioaccumulation is expected.

**Partition coefficient n-octanol / water (log Kow)**

Cyclohexanone (CAS 108-94-1) 0.81  
Methyl ethyl ketone (CAS 78-93-3) 0.29  
Tetrahydrofuran (CAS 109-99-9) 0.46  
Toluene (CAS 108-88-3) 2.73

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.



### 13. Disposal considerations

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

### 14. Transport information

<b>DOT</b>	
<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint related material including paint thinning, drying, removing, or reducing compound
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	II
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	149, B52, IB2, T4, TP1, TP8, TP28
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	173
<b>Packaging bulk</b>	242
<b>IATA</b>	
<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint related material (including paint thinning or reducing compounds)
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>IMDG</b>	
<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound)
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-E, <u>S-E</u>
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not established.

### 15. Regulatory information

<b>US federal regulations</b>	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
<b>TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)</b>	Not regulated.
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)</b>	Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Antimony trioxide (CAS 1309-64-4)	LISTED
Cyclohexanone (CAS 108-94-1)	LISTED
Methyl ethyl ketone (CAS 78-93-3)	LISTED
Tetrahydrofuran (CAS 109-99-9)	LISTED
Toluene (CAS 108-88-3)	LISTED

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

<b>Hazard categories</b>	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No
--------------------------	---

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Aluminium	7429-90-5	1 - 3
Toluene	108-88-3	< 1

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**Antimony trioxide (CAS 1309-64-4)  
Toluene (CAS 108-88-3)**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**Methyl ethyl ketone (CAS 78-93-3) 6714  
Toluene (CAS 108-88-3) 6594**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**Methyl ethyl ketone (CAS 78-93-3) 35 %WV  
Toluene (CAS 108-88-3) 35 %WV**DEA Exempt Chemical Mixtures Code Number**Methyl ethyl ketone (CAS 78-93-3) 6714  
Toluene (CAS 108-88-3) 594**US state regulations****US. Massachusetts RTK - Substance List**Aluminium (CAS 7429-90-5)  
Antimony trioxide (CAS 1309-64-4)  
Cyclohexanone (CAS 108-94-1)  
Methyl ethyl ketone (CAS 78-93-3)  
Tetrahydrofuran (CAS 109-99-9)  
Toluene (CAS 108-88-3)**US. New Jersey Worker and Community Right-to-Know Act**Aluminium (CAS 7429-90-5)  
Antimony trioxide (CAS 1309-64-4)  
Methyl ethyl ketone (CAS 78-93-3)  
Tetrahydrofuran (CAS 109-99-9)  
Toluene (CAS 108-88-3)**US. Pennsylvania Worker and Community Right-to-Know Law**Aluminium (CAS 7429-90-5)  
Antimony trioxide (CAS 1309-64-4)  
Cyclohexanone (CAS 108-94-1)  
Methyl ethyl ketone (CAS 78-93-3)  
Tetrahydrofuran (CAS 109-99-9)  
Toluene (CAS 108-88-3)

## US. Rhode Island RTK

Aluminium (CAS 7429-90-5)  
Antimony trioxide (CAS 1309-64-4)  
Cyclohexanone (CAS 108-94-1)  
Methyl ethyl ketone (CAS 78-93-3)  
Tetrahydrofuran (CAS 109-99-9)  
Toluene (CAS 108-88-3)

## US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

### US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Antimony trioxide (CAS 1309-64-4)  
Arsenic (CAS 7440-38-2)  
Lead (CAS 7439-92-1)  
Toluene (CAS 108-88-3)

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

Issue date	05-January-2016
Revision date	-
Version #	01
HMIS® ratings	Health: 3* Flammability: 3 Physical hazard: 0

### NFPA ratings



### Disclaimer

Goodrich Corporation cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.