



# SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY\*

Product name: THIXON™ P-6-EF

Issue Date: 05/15/2017  
Print Date: 05/16/2017

THE DOW CHEMICAL COMPANY\* encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

---

## 1. IDENTIFICATION

---

Product name: THIXON™ P-6-EF

### Recommended use of the chemical and restrictions on use

Identified uses: Rubber to metal bonding

### COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY\*  
Agent for Rohm and Haas Chemicals LLC  
100 INDEPENDENCE MALL WEST  
PHILADELPHIA PA 19106-2399  
UNITED STATES

Customer Information Number:

215-592-3000  
SDSQuestion@dow.com

### EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: 1 800 424 9300

Local Emergency Contact: 800-424-9300

---

## 2. HAZARDS IDENTIFICATION

---

### Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Flammable liquids - Category 2

Acute toxicity - Category 3 - Inhalation

Skin irritation - Category 2

Serious eye damage - Category 1

Skin sensitisation - Category 1

Carcinogenicity - Category 2

Reproductive toxicity - Category 2

Specific target organ toxicity - single exposure - Category 3

Specific target organ toxicity - repeated exposure - Category 1 - Inhalation

Specific target organ toxicity - repeated exposure - Category 2 - Inhalation

Aspiration hazard - Category 1

**Label elements****Hazard pictograms**

Signal word: **DANGER!**

**Hazards**

Highly flammable liquid and vapour.

May be fatal if swallowed and enters airways.

Causes skin irritation.

May cause an allergic skin reaction.

Causes serious eye damage.

Toxic if inhaled.

May cause respiratory irritation.

May cause drowsiness or dizziness.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

May cause damage to organs through prolonged or repeated exposure if inhaled.

**Precautionary statements****Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Wear protective gloves/ eye protection/ face protection.

Use personal protective equipment as required.

**Response**

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

IF exposed or concerned: Get medical advice/ attention.  
 Do NOT induce vomiting.  
 If skin irritation or rash occurs: Get medical advice/ attention.  
 Take off contaminated clothing and wash before reuse.  
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

**Storage**

Store in a well-ventilated place. Keep container tightly closed.  
 Store in a well-ventilated place. Keep cool.  
 Store locked up.

**Disposal**

Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

No data available

---

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

**Chemical nature:** Polymers, solvent based  
 This product is a mixture.

Component	CASRN	Concentration
Methyl isobutyl ketone	108-10-1	25.0 - 27.0 %
Toluene	108-88-3	22.0 - 24.0 %
Chlorinated polymer	Not Hazardous	12.0 - 14.0 %
Mineral Spirits	8052-41-3	9.0 - 11.0 %
Methyl ethyl ketone	78-93-3	6.0 - 8.0 %
Hexamethylenetetramine	100-97-0	3.0 - 5.0 %
Resorcinol	108-46-3	3.0 - 5.0 %
Solvent naphtha, petroleum, light aromatic	64742-95-6	2.0 - 4.0 %
Zinc Oxide	1314-13-2	2.0 - 4.0 %
1,2,4-Trimethylbenzene	95-63-6	2.0 - 4.0 %
Titanium dioxide	13463-67-7	1.0 - 2.0 %
1,3,5-Trimethylbenzene	108-67-8	< 1.0 %
Hexachlorocyclopentadiene	77-47-4	< 0.4 %

Carbon black

1333-86-4

&lt; 0.4 %

---

## 4. FIRST AID MEASURES

---

**Description of first aid measures**

**Inhalation:** Move to fresh air. Give artificial respiration if breathing has stopped. Get prompt medical attention. In case of shortness of breath, give oxygen.

**Skin contact:** Remove contaminated clothing. Wash off with soap and plenty of water. Wash contaminated clothing before re-use. Do not take clothing home to be laundered. Consult a physician.

**Eye contact:** Rinse immediately with plenty of water for at least 15 minutes. Get prompt medical attention.

**Ingestion:** Drink 1 or 2 glasses of water. Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. Careful gastric lavage may be indicated. IMMEDIATELY see a physician. If vomiting occurs spontaneously, keep airway clear. Never give anything by mouth to an unconscious person.

**Most important symptoms and effects, both acute and delayed:** Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

**Indication of any immediate medical attention and special treatment needed**

**Notes to physician:** Acute massive exposure to toluene can cause transient hematuria and albuminuria. Cardiac arrhythmias can occur after massive inhalation. In acute cases of naphtha overexposure or ingestion, patients should be evaluated for signs of respiratory distress. Massive ingestion of methyl ethyl ketone may cause gastric irritation with absorption leading to metabolic acidosis with an anion gap. CNS narcosis and cardiac arrhythmias effects may be similar to other organic solvents.

---

## 5. FIREFIGHTING MEASURES

---

**Suitable extinguishing media:** Water spray Foam Carbon dioxide (CO2) Dry chemical

**Unsuitable extinguishing media:** No data available

**Special hazards arising from the substance or mixture**

**Hazardous combustion products:** No data available

**Unusual Fire and Explosion Hazards:** Vapors can travel to a source of ignition and flash back. Heated material can form flammable or explosive vapors with air. Closed containers may rupture via pressure build-up when exposed to fire or extreme heat. During a fire, irritating and highly toxic gases and/or fumes may be generated during combustion or decomposition.

**Advice for firefighters**

**Fire Fighting Procedures:** EXPLOSION HAZARD. Fight advanced fires from a protected location. Cool closed containers exposed to fire with water spray. Remain upwind. Avoid breathing smoke. Contain run-off.

**Special protective equipment for firefighters:** In the event of fire, wear self-contained breathing apparatus.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

**Personal precautions, protective equipment and emergency procedures:** Appropriate protective equipment must be worn when handling a spill of this material. See SECTION 8, Exposure Controls/Personal Protection, for recommendations. MATERIAL IS A POTENTIAL SENSITIZER. If exposed to material during clean-up operations, IMMEDIATELY remove all contaminated clothing and wash exposed skin areas with soap and water. See SECTION 4, First Aid Measures, for further information. Wash contaminated clothing before re-use. Do not take clothing home to be laundered.

**Environmental precautions:** CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

**Methods and materials for containment and cleaning up:** Eliminate all ignition sources. Evacuate personnel to safe areas. Ventilate the area. Floor may be slippery; use care to avoid falling. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Sweep up or vacuum up spillage and collect in suitable container for disposal. No sparking tools should be used. Avoid all contact. Avoid breathing vapor. NOTE: Spills on porous surfaces can contaminate groundwater.

---

## 7. HANDLING AND STORAGE

---

**Precautions for safe handling:** Vapors can be evolved when material is heated during processing operations. See SECTION 8, Exposure Controls/Personal Protection, for types of ventilation required. Ground all metal containers during storage and handling. Use non-sparking tools and grounding cables when transferring. This material is a potential sensitizer. See SECTION 8, Exposure Controls/Personal Protection, prior to handling. Wash after handling and shower at end of work period.

**Conditions for safe storage:** Residual vapors in empty containers may explode on ignition. DO NOT cut, drill, grind or weld on or near container. Avoid temperature extremes during storage; ambient temperature preferred. Store away from excessive heat (e.g. steampipes, radiators), from sources of ignition and from reactive materials. Keep away from direct sunlight. Store in a cool and shaded area. Keep container tightly closed. Keep away from heat, sparks, flame, and other sources of ignition.

**Other data:** CONTAINERS MAY BE HAZARDOUS WHEN EMPTY. Since emptied containers retain product residue follow all (M)SDS and label warnings even after container is emptied. Improper disposal or re-use of this container may be dangerous and illegal. Refer to applicable local, state and federal regulations.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### Control parameters

Exposure limits are listed below, if they exist.

Component	Regulation	Type of listing	Value/Notation
-----------	------------	-----------------	----------------

Methyl isobutyl ketone	ACGIH	TWA	20 ppm
	ACGIH	STEL	75 ppm
	OSHA Z-1	TWA	410 mg/m3 100 ppm
	ACGIH	TWA	BEI
	ACGIH	STEL	BEI
Toluene	ACGIH	TWA	20 ppm
	OSHA Z-2	TWA	200 ppm
	ACGIH	TWA	BEI
	OSHA Z-2	CEIL	300 ppm
	OSHA Z-2	Peak	500 ppm
Mineral Spirits	ACGIH	TWA	100 ppm
	OSHA Z-1	TWA	2,900 mg/m3 500 ppm
	OSHA P0	TWA	525 mg/m3 100 ppm
Methyl ethyl ketone	Dow IHG	TWA	50 ppm
	Dow IHG	STEL	100 ppm
	ACGIH	TWA	200 ppm
	ACGIH	STEL	300 ppm
	OSHA Z-1	TWA	590 mg/m3 200 ppm
	ACGIH	TWA	BEI
	ACGIH	STEL	BEI
Hexamethylenetetramine	Dow IHG	TWA	10 mg/m3
	Resorcinol	ACGIH	TWA
Solvent naphtha, petroleum, light aromatic	ACGIH	STEL	20 ppm
	OSHA P0	TWA	45 mg/m3 10 ppm
	OSHA P0	STEL	90 mg/m3 20 ppm
	Dow IHG	TWA	100 mg/m3
	Dow IHG	STEL	300 mg/m3
Zinc Oxide	OSHA Z-1	TWA	2,000 mg/m3 500 ppm
	ACGIH	TWA	200 mg/m3 , total hydrocarbon vapor
	ACGIH	TWA Respirable fraction	2 mg/m3
	ACGIH	STEL Respirable fraction	10 mg/m3
	OSHA Z-1	TWA total dust	15 mg/m3
1,2,4-Trimethylbenzene	OSHA Z-1	TWA respirable fraction	5 mg/m3
	OSHA Z-1	TWA	5 mg/m3
	ACGIH	TWA	25 ppm
	Dow IHG	TWA	2.4 mg/m3
	OSHA Z-1	TWA total dust	15 mg/m3
Titanium dioxide	ACGIH	TWA	10 mg/m3 , Titanium dioxide
	ACGIH	TWA	25 ppm
1,3,5-Trimethylbenzene	Dow IHG	TWA	0.005 ppm
	Dow IHG	TWA	SKIN, DSEN
	ACGIH	TWA	0.01 ppm
Hexachlorocyclopentadiene	ACGIH	TWA Inhalable fraction	3 mg/m3
	OSHA Z-1	TWA	3.5 mg/m3

**Exposure controls**

**Engineering controls:** Use explosion-proof local exhaust ventilation with a minimum capture velocity of 100 ft/min (0.5 m/sec) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

**Protective measures:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

#### Individual protection measures

**Eye/face protection:** Use chemical splash goggles (ANSI Z87.1 or approved equivalent). Eye protection worn must be compatible with respiratory protection system employed.

#### Skin protection

**Hand protection:** Chemical-resistant gloves should be worn whenever this material is handled. The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): Norfoil (Trademark of Siebe North, Inc.) 4H Glove (Trademark of Safety 4 A/S of Denmark) Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. Rinse and remove gloves immediately after use. Wash hands with soap and water.

**Other protection:** Use chemically resistant apron or other impervious clothing to avoid prolonged or repeated skin contact. Where splashing is possible, full chemically resistant protective clothing (e.g. acid suit) and boots are required.

**Respiratory protection:** A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Up to 1000 ppm organic vapor: Wear a properly fitted NIOSH approved (or equivalent) full-facepiece, air-purifying respirator, OR full facepiece, airline respirator in the pressure demand mode. Above 1000 ppm organic vapor or Unknown: Wear a properly fitted NIOSH approved (or equivalent) self-contained breathing apparatus in the pressure demand mode, OR full-facepiece, airline respirator in the pressure demand mode with emergency escape provision.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### Appearance

Physical state	liquid opaque
Color	grey
Odor	solvent-like
Odor Threshold	No data available
pH	Not applicable
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	80 °C ( 176 °F)
Flash point	-4 °C ( 25 °F) <i>PENSKY MARTENS CLOSED CUP</i>
Evaporation Rate (Butyl Acetate = 1)	No data available
Flammability (solid, gas)	Not Applicable
Lower explosion limit	1.00 % vol Toluene

Upper explosion limit	No data available
Vapor Pressure	24.0000000 mmHg at 20.00 °C (68.00 °F) Toluene
Relative Vapor Density (air = 1)	3.5000 Methyl isobutyl ketone
Relative Density (water = 1)	0.95
Water solubility	insoluble
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	475.00 °C (887.00 °F) Methyl isobutyl ketone
Decomposition temperature	>205 °C (401 °F)
Dynamic Viscosity	50 - 300 mPa.s
Kinematic Viscosity	No data available
Explosive properties	No data available
Oxidizing properties	No data available
Molecular weight	No data available
Percent volatility	73 - 76 %

NOTE: The physical data presented above are typical values and should not be construed as a specification.

---

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** No data available

**Chemical stability:** No data available

**Possibility of hazardous reactions:** Product will not undergo polymerization.

**Conditions to avoid:** No data available

**Incompatible materials:** Avoid contact with the following: Strong Oxidizers Acids Bases

**Hazardous decomposition products:** There are no known hazardous decomposition products for this material.

---

---

## 11. TOXICOLOGICAL INFORMATION

---

*Toxicological information appears in this section when such data is available.*

### Acute toxicity

#### Acute oral toxicity

Product test data not available. Refer to component data.

#### Acute dermal toxicity

Product test data not available. Refer to component data.

#### Acute inhalation toxicity



Product test data not available. Refer to component data.

**Skin corrosion/irritation**

Product test data not available. Refer to component data.

**Serious eye damage/eye irritation**

Product test data not available. Refer to component data.

**Sensitization**

Product test data not available. Refer to component data.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Product test data not available. Refer to component data.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Product test data not available. Refer to component data.

**Carcinogenicity**

Product test data not available. Refer to component data.

**Teratogenicity**

Product test data not available. Refer to component data.

**Reproductive toxicity**

Product test data not available. Refer to component data.

**Mutagenicity**

Product test data not available. Refer to component data.

**Aspiration Hazard**

Product test data not available. Refer to component data.

**COMPONENTS INFLUENCING TOXICOLOGY:**

**Methyl isobutyl ketone**

**Acute oral toxicity**

LD50, Rat, 2,080 mg/kg OECD Test Guideline 401

**Acute dermal toxicity**

LD50, Rabbit, > 2,000 mg/kg No deaths occurred at this concentration.

**Acute inhalation toxicity**

LC50, Rat, male, 4 Hour, vapour, 8.2 - 16.4 mg/l

**Skin corrosion/irritation**

Prolonged contact may cause slight skin irritation with local redness.

May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

May cause moderate eye irritation.

May cause slight corneal injury.

Vapor may cause eye irritation experienced as mild discomfort and redness.

**Sensitization**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause respiratory irritation.  
Route of Exposure: Inhalation  
Target Organs: Respiratory Tract

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Excessive exposure to methyl isobutyl ketone may cause respiratory irritation, gastrointestinal distress, anesthesia, kidney and liver effects.

**Carcinogenicity**

Has caused cancer in some laboratory animals. However, the relevance of this to humans is unknown. Kidney effects and/or tumors have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans.

**Teratogenicity**

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction.

**Mutagenicity**

In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

May be harmful if swallowed and enters airways.

**Toluene****Acute oral toxicity**

LD50, Rat, 5,580 mg/kg

**Acute dermal toxicity**

LD50, Rabbit, 12,267 mg/kg

**Acute inhalation toxicity**

LC50, Rat, male and female, 4 Hour, vapour, > 20 mg/l

**Skin corrosion/irritation**

Brief contact may cause slight skin irritation with local redness.  
Prolonged contact may cause moderate skin irritation with local redness.  
May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

May cause slight eye irritation.  
May cause slight temporary corneal injury.  
Vapor may cause eye irritation experienced as mild discomfort and redness.

Vapor may cause lacrimation (tears).

**Sensitization**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause drowsiness or dizziness.

Route of Exposure: Inhalation

Target Organs: Central nervous system

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In animals, effects have been reported on the following organs:

central nervous system (CNS) effects

Excessive exposure may cause neurologic signs and symptoms.

Toluene has caused hearing loss in laboratory animals upon exposure to high concentrations.

Intentional misuse by deliberately inhaling toluene may cause nervous system damage, hearing loss, liver and kidney effects and death.

**Carcinogenicity**

Did not cause cancer in laboratory animals.

**Teratogenicity**

In laboratory animals, toluene has been toxic to the fetus at doses toxic to the mother; it has caused birth defects in mice when administered orally, but not by inhalation.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction.

**Mutagenicity**

The majority and most reliable of the many genetic toxicity studies on toluene, both in vitro and in animals, indicate that it is not genetically toxic.

**Aspiration Hazard**

May be fatal if swallowed and enters airways.

**Mineral Spirits****Acute oral toxicity**

LD50, Rat, > 5,000 mg/kg

**Acute dermal toxicity**

LD50, Rabbit, > 2,000 mg/kg

**Acute inhalation toxicity**

Prolonged excessive exposure may cause adverse effects. Excessive exposure may cause irritation to upper respiratory tract (nose and throat). May cause central nervous system effects.

LC50, Rat, vapour, > 14 mg/l

**Skin corrosion/irritation**

Prolonged contact may cause slight skin irritation with local redness.

Repeated contact may cause skin irritation with local redness.  
May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

Essentially nonirritating to eyes.

**Sensitization**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In humans, effects have been reported on the following organs:

Bone Marrow

Liver

In animals, effects have been reported on the following organs:

central nervous system damage

Kidney.

Kidney effects and/or tumors have been observed in male rats. These effects are believed to be species specific and unlikely to occur in humans.

**Carcinogenicity**

No specific, relevant data available for assessment.

**Teratogenicity**

For similar material(s): Did not cause birth defects or any other fetal effects in laboratory animals.

**Reproductive toxicity**

For similar material(s): In animal studies, did not interfere with reproduction.

**Mutagenicity**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

May be fatal if swallowed and enters airways.

**Methyl ethyl ketone**

**Acute oral toxicity**

LD50, Rat, 2,657 - 5,554 mg/kg

**Acute dermal toxicity**

LD50, Rabbit, > 5,000 mg/kg

**Acute inhalation toxicity**

LC50, Rat, 4 Hour, vapour, 34.5 mg/l

**Skin corrosion/irritation**

Brief contact is essentially nonirritating to skin.

Prolonged contact may cause moderate skin irritation with local redness.

Repeated contact may cause moderate skin irritation with local redness.  
May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

May cause pain disproportionate to the level of irritation to eye tissues.  
May cause moderate eye irritation which may be slow to heal.  
May cause moderate corneal injury.  
Vapor may cause eye irritation experienced as mild discomfort and redness.

**Sensitization**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause drowsiness or dizziness.  
Route of Exposure: Inhalation  
Target Organs: Nervous system

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In animals, effects have been reported on the following organs:  
Liver.  
Methyl ethyl ketone has caused liver effects in laboratory animals exposed by inhalation to high concentrations.  
Methyl ethyl ketone is probably not neurotoxic in itself but it potentiates the neurotoxicity of methyl-n-butyl ketone and n-hexane.

**Carcinogenicity**

Available data are inadequate to evaluate carcinogenicity.

**Teratogenicity**

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Has caused birth defects in laboratory animals only at doses toxic to the mother.

**Reproductive toxicity**

For similar material(s): In animal studies, did not interfere with reproduction.

**Mutagenicity**

In vitro genetic toxicity studies were predominantly negative. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

May be harmful if swallowed and enters airways.

**Hexamethylenetetramine**

**Acute oral toxicity**

LD50, Rat, > 2,000 mg/kg No deaths occurred at this concentration.

**Acute dermal toxicity**

LD50, Rat, male and female, > 2,000 mg/kg No deaths occurred at this concentration.

**Acute inhalation toxicity**

As product: The LC50 has not been determined.

**Skin corrosion/irritation**

Prolonged contact may cause skin irritation with local redness.

**Serious eye damage/eye irritation**

May cause slight temporary eye irritation.  
Corneal injury is unlikely.

**Sensitization**

Has caused allergic skin reactions in humans.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Available data are inadequate to determine single exposure specific target organ toxicity.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

**Carcinogenicity**

Did not cause cancer in laboratory animals.

**Teratogenicity**

Did not cause birth defects or any other fetal effects in laboratory animals.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction.

**Mutagenicity**

In vitro genetic toxicity studies were inconclusive.

**Aspiration Hazard**

Based on available information, aspiration hazard could not be determined.

**Resorcinol**

**Acute oral toxicity**

Low toxicity if swallowed. Small amounts swallowed incidentally as a result of normal handling operations are not likely to cause injury; however, swallowing larger amounts may cause injury. In animals, effects have been reported on the following organs: Central nervous system. Blood Respiratory tract.

LD50, Rat, 510 mg/kg

**Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

LD50, Rabbit, 2,830 mg/kg

**Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility; single exposure is not likely to be hazardous.

LC0, Rat, female, 1 Hour, dust/mist, > 7.8 mg/l No deaths occurred at this concentration.

**Skin corrosion/irritation**

Prolonged contact may cause skin irritation with local redness.

Repeated contact may cause skin burns. Symptoms may include pain, severe local redness, swelling, and tissue damage.

May cause more severe response if skin is abraded (scratched or cut).

**Serious eye damage/eye irritation**

May cause severe irritation with corneal injury which may result in permanent impairment of vision, even blindness. Chemical burns may occur.

**Sensitization**

Has demonstrated the potential for contact allergy in mice.

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Causes damage to organs.

Route of Exposure: Oral

Target Organs: Central nervous system, Blood

May cause damage to organs.

Route of Exposure: Oral

Target Organs: Respiratory Tract

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

May cause methemoglobinemia, thereby impairing the blood's ability to transport oxygen.

May cause central nervous system effects.

In humans, effects have been reported on the following organs:

Heart.

Kidney.

Liver.

Spleen.

In animals, effects have been reported on the following organs:

Central nervous system.

Thyroid.

**Carcinogenicity**

Did not cause cancer in laboratory animals.

**Teratogenicity**

Did not cause birth defects or any other fetal effects in laboratory animals.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction.

**Mutagenicity**

In vitro genetic toxicity studies were negative in some cases and positive in other cases.

Animal genetic toxicity studies were negative.

**Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

**Solvent naphtha, petroleum, light aromatic**

**Acute oral toxicity**

LD50, Rat, 3,500 mg/kg

**Acute dermal toxicity**

LD50, Rabbit, > 3,160 mg/kg

**Acute inhalation toxicity**

Vapor concentrations are attainable which could be hazardous on single exposure. May cause respiratory irritation and central nervous system depression. Symptoms may include headache, dizziness and drowsiness, progressing to incoordination and unconsciousness.

LC50, Rat, 4 Hour, vapour, > 10.2 mg/l

**Skin corrosion/irritation**

May cause drying and flaking of the skin.

Prolonged contact may cause slight skin irritation with local redness.

Repeated contact may cause skin irritation with local redness.

**Serious eye damage/eye irritation**

May cause moderate eye irritation which may be slow to heal.

Corneal injury is unlikely.

Vapor may cause eye irritation experienced as mild discomfort and redness.

**Sensitization**

Did not cause allergic skin reactions when tested in guinea pigs.

**Carcinogenicity**

Did not show carcinogenic effects in animal experiments.

**Teratogenicity**

Developmental effects were seen in laboratory animals only at dose levels that were maternally toxic.

**Reproductive toxicity**

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

**Aspiration Hazard**

May be fatal if swallowed and enters airways.

**Zinc Oxide**

**Acute oral toxicity**

LD50, Rat, > 5,000 mg/kg

**Acute dermal toxicity**

The dermal LD50 has not been determined.

**Acute inhalation toxicity**

Exposure to metal oxide fumes may cause metal fume fever, characterized by influenza-like symptoms. Dust may cause irritation to upper respiratory tract (nose and throat).



LC50, Rat, 4 Hour, dust/mist, > 5 mg/l No deaths occurred at this concentration.

**Skin corrosion/irritation**

Prolonged contact is essentially nonirritating to skin.

**Serious eye damage/eye irritation**

May cause slight temporary eye irritation.

Corneal injury is unlikely.

**Sensitization**

For skin sensitization:

No relevant data found.

For respiratory sensitization:

No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Available data are inadequate to determine single exposure specific target organ toxicity.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In animals, effects have been reported on the following organs:

Lung.

In humans, effects have been reported on the following organs:

Respiratory tract.

**Carcinogenicity**

Available data are inadequate to evaluate carcinogenicity.

**Teratogenicity**

No relevant data found.

**Reproductive toxicity**

In animal studies, did not interfere with reproduction. In animal studies, did not interfere with fertility.

**Mutagenicity**

In vitro genetic toxicity studies were negative in some cases and positive in other cases.

**1,2,4-Trimethylbenzene****Acute oral toxicity**

LD50, Rat, > 3,400 mg/kg

**Acute dermal toxicity**

LD50, Rabbit, > 3,160 mg/kg

**Acute inhalation toxicity**

Prolonged excessive exposure may cause serious adverse effects, even death. Excessive exposure may cause irritation to upper respiratory tract (nose and throat) and lungs. May cause central nervous system effects. Symptoms of excessive exposure may be anesthetic or narcotic effects; dizziness and drowsiness may be observed.

LC50, Rat, 4 Hour, vapour, 18 mg/l

**Skin corrosion/irritation**

Brief contact may cause moderate skin irritation with local redness.  
May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

May cause eye irritation.  
Vapor may cause eye irritation experienced as mild discomfort and redness.

**Sensitization**

For similar material(s):  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause respiratory irritation.  
Route of Exposure: Inhalation  
Target Organs: Respiratory Tract

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

In animals, effects have been reported on the following organs:  
Respiratory tract.

**Carcinogenicity**

No relevant data found.

**Teratogenicity**

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

**Reproductive toxicity**

For similar material(s): In animal studies, did not interfere with reproduction.

**Mutagenicity**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

May be fatal if swallowed and enters airways.

**Titanium dioxide**

**Acute oral toxicity**

LD50, Rat, > 10,000 mg/kg

**Acute dermal toxicity**

LD50, Rabbit, 10,000 mg/kg

**Acute inhalation toxicity**

LC50, Rat, male, 4 Hour, dust/mist, > 6.82 mg/l No deaths occurred at this concentration.

**Skin corrosion/irritation**

Essentially nonirritating to skin.

**Serious eye damage/eye irritation**

Solid or dust may cause irritation due to mechanical action.

**Sensitization**

Did not demonstrate the potential for contact allergy in mice.  
Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Repeated excessive inhalation exposures to dusts may cause respiratory effects.  
In animals, effects have been reported on the following organs:  
Lung.

**Carcinogenicity**

Lung fibrosis and tumors have been observed in rats exposed to titanium dioxide in two lifetime inhalation studies. Effects are believed to be due to overloading of the normal respiratory clearance mechanisms caused by the extreme study conditions. Workers exposed to titanium dioxide in the workplace have not shown an unusual incidence of chronic respiratory disease or lung cancer. Titanium dioxide was not carcinogenic in laboratory animals in lifetime feeding studies.

**Teratogenicity**

No relevant data found.

**Reproductive toxicity**

No relevant data found.

**Mutagenicity**

In vitro genetic toxicity studies were negative in some cases and positive in other cases.  
Animal genetic toxicity studies were negative.

**Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

**1,3,5-Trimethylbenzene****Acute oral toxicity**

LD50, Rat, male, 6,000 mg/kg

**Acute dermal toxicity**

LD50, Rat, male and female, > 3,440 mg/kg No deaths occurred at this concentration.

**Acute inhalation toxicity**

Vapor may cause irritation of the upper respiratory tract (nose and throat). LC50, Rat, male and female, 4 Hour, vapour, > 10.2 mg/l

**Skin corrosion/irritation**

Brief contact may cause slight skin irritation with local redness.  
Prolonged contact may cause moderate skin irritation with local redness.  
May cause drying and flaking of the skin.

**Serious eye damage/eye irritation**

May cause eye irritation.  
Vapor may cause eye irritation experienced as mild discomfort and redness.

**Sensitization**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

May cause respiratory irritation.  
Route of Exposure: Inhalation  
Target Organs: Respiratory Tract

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Based on available data, repeated exposures are not anticipated to cause additional significant adverse effects.

**Carcinogenicity**

No relevant data found.

**Teratogenicity**

Has been toxic to the fetus in laboratory animals at doses toxic to the mother. Did not cause birth defects in laboratory animals.

**Reproductive toxicity**

In laboratory animal studies, effects on reproduction have been seen only at doses that produced significant toxicity to the parent animals.

**Mutagenicity**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Aspiration Hazard**

May be fatal if swallowed and enters airways.

**Hexachlorocyclopentadiene**

**Acute oral toxicity**

LD50, Rat, 315 mg/kg

**Acute dermal toxicity**

LD50, Rabbit, <200 mg/kg

**Acute inhalation toxicity**

LC50, Rat, male, 4 Hour, vapour, 0.018 mg/l

LC50, Rat, female, 4 Hour, vapour, 0.040 mg/l

**Skin corrosion/irritation**

Brief contact may cause skin burns. Symptoms may include pain, severe local redness and tissue damage.

**Serious eye damage/eye irritation**

May cause severe corneal injury.

**Sensitization**

Has caused allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Carcinogenicity**

Did not cause cancer in laboratory animals.

**Teratogenicity**

Did not cause birth defects in laboratory animals.

**Reproductive toxicity**

No relevant data found.

**Mutagenicity**

In vitro genetic toxicity studies were negative.

Animal genetic toxicity studies were negative.

**Aspiration Hazard**

Based on available information, aspiration hazard could not be determined.

**Carbon black**

**Acute oral toxicity**

LD50, Rat, > 8,000 mg/kg

**Acute dermal toxicity**

LD50, Rabbit, > 3,000 mg/kg No deaths occurred at this concentration.

**Acute inhalation toxicity**

LC50, Rat, 1 Hour, dust/mist, 27 mg/l No deaths occurred at this concentration.

**Skin corrosion/irritation**

Prolonged exposure not likely to cause significant skin irritation.

**Serious eye damage/eye irritation**

Solid or dust may cause irritation or corneal injury due to mechanical action.

**Sensitization**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:  
No relevant data found.

**Specific Target Organ Systemic Toxicity (Single Exposure)**

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

**Specific Target Organ Systemic Toxicity (Repeated Exposure)**

Dust may cause irritation of the upper respiratory tract (nose and throat) and lungs.  
Repeated exposures to very fine dusts may cause lung injury.

**Carcinogenicity**

Lung fibrosis and tumors have been observed in rats exposed to high concentrations of very fine carbon black particles for their lifetime. Effects are believed to be due to overloading of the normal respiratory clearance mechanisms caused by the extreme study conditions. Rats may be particularly susceptible to particle clearance overload, resulting in lung injury and tumors. No increases in tumors were observed in male or female mice exposed under the same conditions.

**Teratogenicity**

No relevant data found.

**Reproductive toxicity**

No relevant data found.

**Mutagenicity**

Animal genetic toxicity studies were negative in some cases and positive in other cases. Positive findings were observed only at doses which produced significant inflammation.

**Aspiration Hazard**

Based on physical properties, not likely to be an aspiration hazard.

**Carcinogenicity****Component****Methyl isobutyl ketone****List**

IARC

ACGIH

**Classification**

Group 2B: Possibly carcinogenic to humans

A3: Confirmed animal carcinogen with unknown relevance to humans.

**Solvent naphtha, petroleum, light aromatic**

ACGIH

A3: Confirmed animal carcinogen with unknown relevance to humans.

**Titanium dioxide**

IARC

Group 2B: Possibly carcinogenic to humans

**Carbon black**

IARC

Group 2B: Possibly carcinogenic to humans

ACGIH

A3: Confirmed animal carcinogen with unknown relevance to humans.

---

**12. ECOLOGICAL INFORMATION**

---

*Ecotoxicological information appears in this section when such data is available.*

**General Information**

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**Toxicity****Methyl isobutyl ketone****Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

LC50, Danio rerio (zebra fish), static test, 96 Hour, > 179 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, > 200 mg/l, OECD Test Guideline 202 or Equivalent

**Acute toxicity to algae/aquatic plants**

EC50, Pseudokirchneriella subcapitata (green algae), static test, 96 Hour, Growth rate inhibition, 400 mg/l, OECD Test Guideline 201 or Equivalent

EC50, Lemna minor (duckweed), semi-static test, 7 d, Growth rate inhibition, > 146 mg/l, OECD 221.

**Chronic toxicity to fish**

NOEC, Pimephales promelas (fathead minnow), 31 d, weight, 57 mg/l

LOEC, Pimephales promelas (fathead minnow), 31 d, weight, 105 mg/l

MATC (Maximum Acceptable Toxicant Level), Pimephales promelas (fathead minnow), 31 d, weight, 77.4 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), 21 d, 30 mg/l

**Toluene**

**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), semi-static test, 96 Hour, 5.8 mg/l

LC50, Fish, flow-through test, 96 Hour, 5.5 mg/l

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), static test, 24 Hour, 7 mg/l, OECD Test Guideline 202

LC50, water flea Ceriodaphnia dubia, semi-static test, 48 Hour, 3.78 mg/l

**Acute toxicity to algae/aquatic plants**

EbC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, Biomass, 12.5 mg/l, OECD Test Guideline 201

**Toxicity to bacteria**

IC50, Bacteria, 16 Hour, 29 mg/l

**Chronic toxicity to fish**

NOEC, Fish, flow-through test, 40 d, growth, 1.4 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Ceriodaphnia dubia (water flea), 7 d, number of offspring, 0.74 mg/l

NOEC, Daphnia magna (Water flea), 21 day, number of offspring, 2 mg/l

**Toxicity to soil-dwelling organisms**

LC50, Eisenia fetida (earthworms), 150 - 280 mg/kg

**Mineral Spirits**

**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

**Acute toxicity to aquatic invertebrates**

LC50, crustacean Chaetogammarus marinus, 96 Hour, 3.5 mg/l

**Acute toxicity to algae/aquatic plants**

ErC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, 1.2 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), 21 d, 0.1 mg/l

**Methyl ethyl ketone**

**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).  
LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, 2,993 mg/l, OECD Test Guideline 203

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), static test, 48 Hour, 308 mg/l, OECD Test Guideline 202

**Acute toxicity to algae/aquatic plants**

ErC50, Pseudokirchneriella subcapitata (microalgae), static test, 96 Hour, Growth rate inhibition, 2,029 mg/l, OECD Test Guideline 201

**Toxicity to bacteria**

EC50, Bacteria, 96 Hour, > 1,000 mg/l, hUCC

**Hexamethylenetetramine**

**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).  
LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 49,800 mg/l, OECD Test Guideline 203

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), static test, 48 Hour, 36,000 mg/l, OECD Test Guideline 202

**Resorcinol**

**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).  
LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 29.5 mg/l

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, 1.00 mg/l

**Acute toxicity to algae/aquatic plants**

ErC50, Pseudokirchneriella subcapitata (green algae), Static, 72 Hour, Growth rate inhibition, > 97 mg/l  
NOEC, Pseudokirchneriella subcapitata (green algae), Static, 72 Hour, Growth rate inhibition, 97 mg/l

**Toxicity to bacteria**

EC50, activated sludge, 3 Hour, Respiration rates., 7.3 mg/l



**Chronic toxicity to fish**

LOEC, Oncorhynchus mykiss (rainbow trout), 60 d, survival, 320 mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), flow-through test, 21 d, number of offspring,  $\geq 0.172$  mg/l

**Solvent naphtha, petroleum, light aromatic**

**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 9.22 mg/l, OECD Test Guideline 203

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna, 48 Hour, 6.14 mg/l

**Acute toxicity to algae/aquatic plants**

EC50, Marine algae (Skeletonema costatum), 72 Hour, Growth rate, 3.29 mg/l

**Toxicity to Above Ground Organisms**

Material is practically non-toxic to birds on an acute basis (LD50 > 2000 mg/kg).

Material is practically non-toxic to birds on a dietary basis (LC50 > 5000 ppm).

dietary LC50, Other, 8 d, > 6500mg/kg diet.

oral LD50, Other, 21 d, > 2150mg/kg bodyweight.

**Zinc Oxide**

**Acute toxicity to fish**

Material is very highly toxic to aquatic organisms on an acute basis (LC50/EC50 <0.1 mg/L in the most sensitive species).

LC50, Oncorhynchus mykiss (rainbow trout), static test, 96 Hour, 0.14 - 1.1 mg/l

LC50, Danio rerio (zebra fish), 96 Hour, 1 - 10 mg/l

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, 1 - 10 mg/l

**Acute toxicity to algae/aquatic plants**

IC50, Selenastrum capricornutum (green algae), 72 Hour, Growth rate, 0.136 mg/l

**Chronic toxicity to fish**

NOEC, Danio rerio (zebra fish), 32 d, mortality,  $\geq 0.540$  mg/l

**Chronic toxicity to aquatic invertebrates**

NOEC, Daphnia magna (Water flea), 21 d, number of offspring, 0.04 mg/l

**1,2,4-Trimethylbenzene**

**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).

LC50, Pimephales promelas (fathead minnow), flow-through test, 96 Hour, 7.7 mg/l

**Acute toxicity to aquatic invertebrates**

EC50, Daphnia magna (Water flea), 48 Hour, 3.6 mg/l

**Titanium dioxide**

**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).  
NOEC mortality, *Leuciscus idus* (Golden orfe), static test, 48 Hour, > 1,000 mg/l

**Acute toxicity to aquatic invertebrates**

EC50, *Daphnia magna* (Water flea), static test, 48 Hour, > 1,000 mg/l

**1,3,5-Trimethylbenzene**

**Acute toxicity to fish**

Material is moderately toxic to aquatic organisms on an acute basis (LC50/EC50 between 1 and 10 mg/L in the most sensitive species tested).  
LC50, *Carassius auratus* (goldfish), flow-through test, 96 Hour, 12.5 mg/l, Method Not Specified.

**Acute toxicity to aquatic invertebrates**

EC50, *Daphnia magna* (Water flea), Static, 48 Hour, 6 mg/l, OECD Test Guideline 202 or Equivalent

**Acute toxicity to algae/aquatic plants**

EbC50, *Desmodesmus subspicatus* (green algae), 48 Hour, Biomass, 25 mg/l, OECD Test Guideline 201 or Equivalent

**Chronic toxicity to aquatic invertebrates**

NOEC, *Daphnia magna* (Water flea), semi-static test, 21 d, number of offspring, 0.4 mg/l

**Hexachlorocyclopentadiene**

**Acute toxicity to fish**

Material is very highly toxic to aquatic organisms on an acute basis (LC50/EC50 <0.1 mg/L in the most sensitive species).  
LC50, Fathead minnow (*Pimephales promelas*), static test, 96 Hour, 0.007 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

EC50, *Daphnia magna*, static test, 48 Hour, 0.0522 mg/l, Method Not Specified.

**Acute toxicity to algae/aquatic plants**

LC50, Algae (*Selenastrum capricornutum*), 96 Hour, Growth rate, 0.19 mg/l, OECD Test Guideline 201

**Carbon black**

**Acute toxicity to fish**

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).  
LC50, *Leuciscus idus* (Golden orfe), static test, 96 Hour, > 1,000 mg/l, OECD Test Guideline 203 or Equivalent

**Acute toxicity to aquatic invertebrates**

EC50, *Daphnia magna* (Water flea), 24 Hour, > 5,600 mg/l, OECD Test Guideline 202 or Equivalent

**Persistence and degradability**

**Methyl isobutyl ketone**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Pass

**Biodegradation:** 83 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301F or Equivalent

**Theoretical Oxygen Demand:** 2.72 mg/mg

**Photodegradation**

**Test Type:** Half-life (indirect photolysis)

**Sensitizer:** OH radicals

**Atmospheric half-life:** 14.5 Hour

**Method:** Estimated.

**Toluene**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

**Biodegradation:** 100 %

**Exposure time:** 14 d

**Method:** OECD Test Guideline 301C or Equivalent

**Theoretical Oxygen Demand:** 3.13 mg/mg Calculated.

**Photodegradation**

**Test Type:** Half-life (indirect photolysis)

**Sensitizer:** OH radicals

**Atmospheric half-life:** 2 d

**Method:** Estimated.

**Mineral Spirits**

**Biodegradability:** Material is expected to be readily biodegradable.

**Theoretical Oxygen Demand:** 3.49 mg/mg

**Methyl ethyl ketone**

**Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

**Biodegradation:** 98 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301D or Equivalent

**Theoretical Oxygen Demand:** 2.44 mg/mg

**Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	71 - 76 %
10 d	71 - 82 %

20 d	71 - 89 %
------	-----------

**Photodegradation****Test Type:** Half-life (indirect photolysis)**Sensitizer:** OH radicals**Atmospheric half-life:** 8 d**Method:** Estimated.**Hexamethylenetetramine****Biodegradability:** Material is readily biodegradable. Passes OECD test(s) for ready biodegradability.

10-day Window: Not applicable

**Biodegradation:** 54 - 97 %**Exposure time:** 28 d**Method:** OECD Test Guideline 301C or Equivalent**Theoretical Oxygen Demand:** 3.2 mg/mg**Resorcinol****Biodegradability:** Material is expected to be readily biodegradable.

10-day Window: Not applicable

**Biodegradation:** 66.7 %**Exposure time:** 14 d**Method:** OECD Test Guideline 301C or Equivalent

10-day Window: Not applicable

**Biodegradation:** 97 %**Exposure time:** 4 d**Method:** OECD Test Guideline 302B or Equivalent

10-day Window: Not applicable

**Biodegradation:** 90 - 95 %**Exposure time:** 7 - 15 d**Method:** OECD Test Guideline 302B or Equivalent**Theoretical Oxygen Demand:** 1.89 mg/mg**Biological oxygen demand (BOD)**

Incubation Time	BOD
5 d	75.000 %
10 d	79.000 %
20 d	90.000 %

**Solvent naphtha, petroleum, light aromatic****Biodegradability:** For the major component(s): Biodegradation under aerobic static laboratory conditions is high (BOD20 or BOD28/ThOD > 40%). For some component(s): Biodegradation under aerobic static laboratory conditions is low (BOD20 or BOD28/ThOD between 2.5 and 10%).

For the major component(s): Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability. For some component(s): Based on stringent OECD test guidelines, this material cannot be considered

as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

#### Zinc Oxide

**Biodegradability:** Biodegradation is not applicable.

#### 1,2,4-Trimethylbenzene

**Biodegradability:** Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Not applicable

**Biodegradation:** 4 - 18 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301C or Equivalent

**Theoretical Oxygen Demand:** 3.19 mg/mg

#### **Photodegradation**

**Test Type:** Half-life (indirect photolysis)

**Sensitizer:** OH radicals

**Atmospheric half-life:** 0.641 d

**Method:** Estimated.

#### Titanium dioxide

**Biodegradability:** Biodegradation is not applicable.

#### 1,3,5-Trimethylbenzene

**Biodegradability:** Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

10-day Window: Fail

**Biodegradation:** 0 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 301C or Equivalent

10-day Window: Not applicable

**Biodegradation:** 50 %

**Exposure time:** 4.4 d

**Method:** Calculated.

#### Hexachlorocyclopentadiene

**Biodegradability:** Material is inherently biodegradable (reaches > 20% biodegradation in OECD test(s) for inherent biodegradability).

10-day Window: Fail

**Biodegradation:** 67 %

**Exposure time:** 28 d

**Method:** OECD Test Guideline 302B or Equivalent

#### Carbon black

**Biodegradability:** Biodegradation is not applicable.

#### **Bioaccumulative potential**

#### Methyl isobutyl ketone

**Partition coefficient: n-octanol/water(log Pow):** 1.9 Measured

**Toluene**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 2.73 Measured

**Bioconcentration factor (BCF):** 13.2 - 90 Fish Measured

**Mineral Spirits**

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

**Partition coefficient: n-octanol/water(log Pow):** 5.01 Measured

**Bioconcentration factor (BCF):** 140 Fish Estimated.

**Methyl ethyl ketone**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 0.29 Measured

**Hexamethylenetetramine**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** -4.15 Estimated.

**Resorcinol**

**Bioaccumulation:** Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

**Partition coefficient: n-octanol/water(log Pow):** 0.8 Estimated.

**Solvent naphtha, petroleum, light aromatic**

**Partition coefficient: n-octanol/water(log Pow):** 3.3

**Zinc Oxide**

**Bioaccumulation:** Partitioning from water to n-octanol is not applicable.

**1,2,4-Trimethylbenzene**

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

**Partition coefficient: n-octanol/water(log Pow):** 3.63 Measured

**Bioconcentration factor (BCF):** 33 - 275 Cyprinus carpio (Carp) 56 d Measured

**Titanium dioxide**

**Bioaccumulation:** Partitioning from water to n-octanol is not applicable.

**1,3,5-Trimethylbenzene**

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

**Partition coefficient: n-octanol/water(log Pow):** 3.42 Measured

**Bioconcentration factor (BCF):** 161 Pimephales promelas (fathead minnow) Measured

**Hexachlorocyclopentadiene**

**Bioaccumulation:** Bioconcentration potential is moderate (BCF between 100 and 3000 or Log Pow between 3 and 5).

**Partition coefficient: n-octanol/water(log Pow):** 3.99 Method Not Specified.

**Bioconcentration factor (BCF):** 1,297 Carassius auratus (goldfish)

**Carbon black**

**Bioaccumulation:** No relevant data found.

**Mobility in soil**

**Methyl isobutyl ketone**

Potential for mobility in soil is high (Koc between 50 and 150).  
**Partition coefficient (Koc):** 101 Estimated.

**Toluene**

Potential for mobility in soil is very high (Koc between 0 and 50).  
**Partition coefficient (Koc):** 37 - 178 Estimated.

**Mineral Spirits**

Potential for mobility in soil is low (Koc between 500 and 2000).  
**Partition coefficient (Koc):** 1700 Estimated.

**Methyl ethyl ketone**

Potential for mobility in soil is very high (Koc between 0 and 50).  
**Partition coefficient (Koc):** 3.8 Estimated.

**Hexamethylenetetramine**

Potential for mobility in soil is very high (Koc between 0 and 50).  
**Partition coefficient (Koc):** < 1 Estimated.

**Resorcinol**

Potential for mobility in soil is very high (Koc between 0 and 50).  
**Partition coefficient (Koc):** 10.35 Measured

**Solvent naphtha, petroleum, light aromatic**

**Partition coefficient (Koc):** > 60.7 - < 229.2 Estimated.

**Zinc Oxide**

No data available.

**1,2,4-Trimethylbenzene**

Potential for mobility in soil is low (Koc between 500 and 2000).  
**Partition coefficient (Koc):** 720 Estimated.

**Titanium dioxide**

No data available.

**1,3,5-Trimethylbenzene**

Potential for mobility in soil is low (Koc between 500 and 2000).  
**Partition coefficient (Koc):** 741.65 Estimated.

**Hexachlorocyclopentadiene**

No data available.

**Carbon black**

No relevant data found.

---

**13. DISPOSAL CONSIDERATIONS**

---

**Disposal methods:** For disposal, incinerate this material at a facility that complies with local, state, and federal regulations. (See 40 CFR 268)

**Contaminated packaging:** Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

**14. TRANSPORT INFORMATION**

---

**DOT**

<b>Proper shipping name</b>	Adhesives
<b>UN number</b>	UN 1133
<b>Class</b>	3
<b>Packing group</b>	II
<b>Reportable Quantity</b>	Toluene, Methyl isobutyl ketone

**Classification for SEA transport (IMO-IMDG):**

<b>Proper shipping name</b>	ADHESIVES
<b>UN number</b>	UN 1133
<b>Class</b>	3
<b>Packing group</b>	II
<b>Marine pollutant</b>	Hexachlorocyclopentadiene
<b>Transport in bulk according to Annex I or II of MARPOL 73/78 and the IBC or IGC Code</b>	Consult IMO regulations before transporting ocean bulk

**Classification for AIR transport (IATA/ICAO):**

<b>Proper shipping name</b>	Adhesives
<b>UN number</b>	UN 1133
<b>Class</b>	3
<b>Packing group</b>	II

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

**15. REGULATORY INFORMATION**

---

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312**



Acute Health Hazard  
Chronic Health Hazard  
Fire Hazard

**Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313**

The following components are subject to reporting levels established by SARA Title III, Section 313:

<b>Components</b>	<b>CASRN</b>
Methyl isobutyl ketone	108-10-1
Toluene	108-88-3
1,2,4-Trimethylbenzene	95-63-6
Zinc Oxide	1314-13-2

**Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103**

<b>Components</b>	<b>CASRN</b>	<b>RQ (RCRA Code)</b>
Hexachlorocyclopentadiene	77-47-4	10 lbs RQ
Methyl isobutyl ketone	108-10-1	5000 lbs RQ
Methyl isobutyl ketone	108-10-1	100 lbs RQ (F003)
Toluene	108-88-3	1000 lbs RQ
Toluene	108-88-3	100 lbs RQ (F005)
Methyl ethyl ketone	78-93-3	5000 lbs RQ
Methyl ethyl ketone	78-93-3	100 lbs RQ (F005)

**Pennsylvania**

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

**California (Proposition 65)**

This product contains a component or components known to the state of California to cause birth defects or other reproductive harm:

<b>Components</b>	<b>CASRN</b>
Toluene	108-88-3

**California (Proposition 65)**

This product contains a component or components known to the state of California to cause cancer and birth defects or other reproductive harm:

<b>Components</b>	<b>CASRN</b>
Methyl isobutyl ketone	108-10-1

**California (Proposition 65)**

This product contains trace levels of a component or components known to the state of California to cause cancer and birthdefects or other reproductive harm:

<b>Components</b>	<b>CASRN</b>
Benzene	71-43-2
Epichlorohydrin	106-89-8

**California (Proposition 65)**

This product contains trace levels of a component or components known to the state of California to cause cancer:

Components	CASRN
Cumene	98-82-8
Ethylbenzene	100-41-4
Dichloro-2-propanol	96-23-1

**United States TSCA Inventory (TSCA)**

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

---

## 16. OTHER INFORMATION

---

**Hazard Rating System****HMIS**

Health	Flammability	Physical Hazard
2*	3	0

\* = Chronic Effects (See Hazards Identification)

**Revision**

Identification Number: 101102242 / 1001 / Issue Date: 05/15/2017 / Version: 5.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

**Legend**

ACGIH	USA. American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Values (TLV)
BEI	Biological Exposure Indices
CEIL	Acceptable ceiling concentration
Dow IHG	Dow Industrial Hygiene Guideline
OSHA P0	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	USA. Occupational Exposure Limits (OSHA) - Table Z-2
Peak	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift
SKIN, DSEN	Absorbed via Skin, Skin Sensitizer
STEL	Short term exposure limit
TWA	Time weighted average

**Information Source and References**

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY\* urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that

his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.