

## 1. Identification

<b>Product identifier</b>	<b>FASTboot® Adhesive Primer</b>
<b>Other means of identification</b>	
<b>Product code</b>	0500KS2
<b>Synonyms</b>	Goodrich Kit Components: 74-451-190; 74-451-206; 74-451-207; 74-451-228. Goodrich Kits: 74-451-S; 74-451-S-1; 74-451-AA; 74-451-AH; 74-451-AJ; 74-451-AN
<b>Recommended use</b>	Adhesive Primer.
<b>Recommended restrictions</b>	None known.
<b>Manufacturer/Importer/Supplier/Distributor information</b>	
<b>Supplier</b>	
<b>Company name</b>	Goodrich Corporation Collins Aerospace, Interiors - Evacuation, Water & Lighting (Formerly De-icing and Specialty Systems)
<b>Address</b>	1555 Corporate Woods Parkway Uniontown, Ohio 44685 USA
<b>E-mail</b>	Terry.Sluss@utas.utc.com
<b>Contact name</b>	EH&S Manager
<b>Telephone number</b>	(330)374-4011
<b>Emergency telephone number</b>	(800)424-9300/ 1-703-741-5970

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 2
<b>Health hazards</b>	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, skin	Category 1
	Carcinogenicity	Category 2
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 1 (central nervous system, optic nerve)
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (hearing organs)
	Aspiration hazard	Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 1
	Hazardous to the aquatic environment, long-term hazard	Category 1
<b>OSHA defined hazards</b>	Not classified.	

### Label elements



**Signal word**

Danger

**Hazard statement** Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. Suspected of causing cancer. Suspected of damaging the unborn child. Causes damage to organs (central nervous system, optic nerve). May cause respiratory irritation. May cause drowsiness or dizziness. May cause damage to organs (hearing organs) through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Very toxic to aquatic life with long lasting effects.

**Precautionary statement**

**Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment.

**Response**

In case of fire: Use appropriate media to extinguish. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If exposed or concerned: Get medical advice/attention. Wash contaminated clothing before reuse. Collect spillage.

**Storage**

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)**

None known.

**Supplemental information**

None.

**3. Composition/information on ingredients**

**Mixtures**

Chemical name	CAS number	%
Cyclohexane	110-82-7	30 - 60
Xylene	1330-20-7	20 - 35
Ethyl alcohol	64-17-5	5 - 10
Ethylbenzene	100-41-4	< 11
Acrylate polymer (NJTS Reg No 04499600-5984P)	Trade Secret	1 - 5
Ethyl acetate	141-78-6	1 - 5
Chlorinated polyolefin	68609-36-9	< 2
Methyl alcohol	67-56-1	0.1 - 1
Epoxy resin	25068-38-6	< 0.5
Toluene	108-88-3	< 0.5
Chlorobenzene	108-90-7	<= 0.11

**Composition comments**

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard Communication Standard.

**4. First-aid measures**

**Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.

<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Never give anything by mouth to a victim who is unconscious or is having convulsions.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. Containers may rupture or explode if exposed to heat. During fire, gases hazardous to health may be formed such as: Carbon oxides. Hydrogen chloride. Aldehydes. Formaldehyde. Hydrocarbons.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
<b>Environmental precautions</b>	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Chlorobenzene (CAS 108-90-7)	PEL	350 mg/m3 75 ppm
Cyclohexane (CAS 110-82-7)	PEL	1050 mg/m3 300 ppm
Ethyl acetate (CAS 141-78-6)	PEL	1400 mg/m3 400 ppm
Ethyl alcohol (CAS 64-17-5)	PEL	1900 mg/m3 1000 ppm
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3 100 ppm
Methyl alcohol (CAS 67-56-1)	PEL	260 mg/m3 200 ppm
Xylene (CAS 1330-20-7)	PEL	435 mg/m3 100 ppm

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

#### US. ACGIH Threshold Limit Values

Components	Type	Value
Chlorobenzene (CAS 108-90-7)	TWA	10 ppm
Cyclohexane (CAS 110-82-7)	TWA	100 ppm
Ethyl acetate (CAS 141-78-6)	TWA	400 ppm
Ethyl alcohol (CAS 64-17-5)	STEL	1000 ppm
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
Methyl alcohol (CAS 67-56-1)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Cyclohexane (CAS 110-82-7)	TWA	1050 mg/m3
		300 ppm
Ethyl acetate (CAS 141-78-6)	TWA	1400 mg/m3
		400 ppm
Ethyl alcohol (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
	TWA	435 mg/m3
Methyl alcohol (CAS 67-56-1)		100 ppm
	STEL	325 mg/m3
	TWA	260 mg/m3
Toluene (CAS 108-88-3)		200 ppm
	STEL	560 mg/m3
	TWA	375 mg/m3
Xylene (CAS 1330-20-7)		100 ppm
	STEL	655 mg/m3
	TWA	435 mg/m3
		100 ppm

**Biological limit values****ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
Chlorobenzene (CAS 108-90-7)	100 mg/g	4-Chlorocatechol, with hydrolysis	Creatinine in urine	*
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Methyl alcohol (CAS 67-56-1)	15 mg/l	Methanol	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Exposure guidelines****US - California OELs: Skin designation**

Methyl alcohol (CAS 67-56-1)

Can be absorbed through the skin.

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

Methyl alcohol (CAS 67-56-1)

Skin designation applies.

Toluene (CAS 108-88-3)

Skin designation applies.

**US - Tennessee OELs: Skin designation**

Methyl alcohol (CAS 67-56-1)

Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation**

Methyl alcohol (CAS 67-56-1)

Can be absorbed through the skin.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Methyl alcohol (CAS 67-56-1)

Can be absorbed through the skin.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Chemical respirator with organic vapor cartridge and full facepiece.

**Skin protection****Hand protection**

Wear appropriate chemical resistant gloves. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.

**Skin protection****Other**

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

**Respiratory protection**

Chemical respirator with organic vapor cartridge and full facepiece.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Liquid.

**Color**

Amber.

**Odor**

Solvent odor.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

Not available.

**Initial boiling point and boiling range**

170 °F (76.7 °C)

**Flash point**

1.0 °F (-17.2 °C) [Test Method:Closed Cup]

**Evaporation rate**

Not available.

**Flammability (solid, gas)**

Not applicable.

## Upper/lower flammability or explosive limits

<b>Flammability limit - lower (%)</b>	1 %
<b>Flammability limit - upper (%)</b>	11 %
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	68 mmHg [@ 68 °F]
<b>Vapor density</b>	Not available.
<b>Relative density</b>	0.82 [@ 77 °F] [Ref Std:WATER=1]
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Negligible.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	1 - 35 cP [@ 73.4 °F ]
<b>Other information</b>	Hazardous Air Pollutants: 35.2 - 45.3 % weight [Test Method:Calculated] and <=15.11 lb HAPS/lb solids [Test Method:Calculated]
<b>Density</b>	0.82 g/ml
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>Percent volatile</b>	95.3 - 97 % weight [Test Method:Estimated]
<b>VOC</b>	781 g/l [Test Method:calculated SCAQMD rule 443.1] [Details:low solids less exempts]

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong acids. Strong oxidizing agents. Halogens. Nitrates.
<b>Hazardous decomposition products</b>	No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	May cause damage to organs by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.
<b>Eye contact</b>	Causes serious eye irritation.
<b>Ingestion</b>	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

### Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

### Information on toxicological effects

<b>Acute toxicity</b>	May be fatal if swallowed and enters airways.
-----------------------	---

Components	Species	Test Results
Chlorobenzene (CAS 108-90-7)		
<b><u>Acute</u></b>		
<b>Inhalation</b>		
LC50	Rat	29.7 mg/l, 4 hours
<b>Oral</b>		
LD50	Rat	> 2000 mg/kg
Cyclohexane (CAS 110-82-7)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	12705 mg/kg
Ethyl acetate (CAS 141-78-6)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Guinea pig	3 g/kg
<b>Inhalation</b>		
LC50	Rat	16000 mg/l, 6 Hours
<b>Oral</b>		
LD50	Rat	5600 mg/kg
Ethyl alcohol (CAS 64-17-5)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rat	> 2000 mg/kg
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Mouse	39 g/m <sup>3</sup> , 4 Hours
<b>Oral</b>		
LD50	Rat	7000 - 11000 mg/kg
Ethylbenzene (CAS 100-41-4)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	15400 mg/kg
<b>Inhalation</b>		
LC50	Rat	17.4 mg/m <sup>3</sup> , 4 Hours
<b>Oral</b>		
LD50	Rat	35000 - 47000 mg/kg
Toluene (CAS 108-88-3)		
<b><u>Acute</u></b>		
<b>Dermal</b>		
LD50	Rabbit	12200 mg/kg
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	28.1 mg/l, 4 Hours
Xylene (CAS 1330-20-7)		
<b><u>Acute</u></b>		
<b>Oral</b>		
LD50	Rat	3523 mg/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	



## Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** Suspected of causing cancer.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylbenzene (CAS 100-41-4)

2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3)

3 Not classifiable as to carcinogenicity to humans.

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

### NTP Report on Carcinogens

Not listed.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

**Reproductive toxicity** Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.

**Specific target organ toxicity - single exposure** Causes damage to organs (central nervous system, optic nerve). May cause respiratory irritation. May cause drowsiness and dizziness.

**Specific target organ toxicity - repeated exposure** May cause damage to organs (hearing organs) through prolonged or repeated exposure.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Components		Species	Test Results
Chlorobenzene (CAS 108-90-7)			
<b>Aquatic</b>			
Crustacea	EC50	Daphnia	19.9 mg/l, 48 hours
Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	7.4 mg/l, 96 hours
		Fathead minnow ( <i>Pimephales promelas</i> )	19.12 mg/l, 96 hours
Cyclohexane (CAS 110-82-7)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	0.9 mg/l, 48 hours
Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	3.961 - 5.181 mg/l, 96 hours
Ethyl acetate (CAS 141-78-6)			
<b>Aquatic</b>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	2306 mg/l, 24 Hours
Fish	LC50	Indian catfish ( <i>Heteropneustes fossilis</i> )	200 - 225 mg/l, 96 Hours
Ethyl alcohol (CAS 64-17-5)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	LC50	Ceriodaphnia dubia	5012 mg/l, 48 hours
		<i>Daphnia magna</i>	454 mg/l, 11 days
Fish	LC50	<i>Pimephales promelas</i>	13480 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	NOEC	Ceriodaphnia dubia	9.6 mg/l, 10 days
Ethylbenzene (CAS 100-41-4)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Water flea ( <i>Daphnia magna</i> )	1.81 - 2.38 mg/l, 48 hours

Components		Species	Test Results
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4.2 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	EC50	Ceriodaphnia dubia	3.6 mg/l, 7 days
Methyl alcohol (CAS 67-56-1)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	> 10000 mg/l, 48 hours
Fish	LC50	Bluegill (Lepomis macrochirus)	15400 mg/l, 96 hours
Toluene (CAS 108-88-3)			
<b>Aquatic</b>			
<i>Acute</i>			
Crustacea	EC50	Daphnia magna	11.5 mg/l, 48 hours
Fish	LC50	Oncorhynchus kisutch	5.5 mg/l, 96 hours
<i>Chronic</i>			
Crustacea	NOEC	Ceriodaphnia dubia	0.74 mg/l, 7 days
Fish	NOEC	Oncorhynchus kisutch	1.4 mg/l, 40 days
Xylene (CAS 1330-20-7)			
<b>Aquatic</b>			
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.6 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

Chlorobenzene (CAS 108-90-7)	2.89
Cyclohexane (CAS 110-82-7)	3.44
Ethyl acetate (CAS 141-78-6)	0.73
Ethyl alcohol (CAS 64-17-5)	-0.31
Ethylbenzene (CAS 100-41-4)	3.15
Methyl alcohol (CAS 67-56-1)	-0.77
Toluene (CAS 108-88-3)	2.73
Xylene (CAS 1330-20-7)	3.12 - 3.2

**Mobility in soil** No data available.

**Other adverse effects** The product contains volatile organic compounds which have a photochemical ozone creation potential.

**13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F  
D021: Waste Chlorobenzene

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

### DOT

UN number	UN1133
UN proper shipping name	Adhesives, containing a flammable liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Label(s)	3
Packing group	II
Environmental hazards	
Marine pollutant	Yes.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	149, B52, IB2, T4, TP1, TP8
Packaging exceptions	150
Packaging non bulk	173
Packaging bulk	242

### IATA

UN number	UN1133
UN proper shipping name	Adhesives containing flammable liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	Yes.
ERG Code	3L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

### IMDG

UN number	UN1133
UN proper shipping name	ADHESIVES containing flammable liquid
Transport hazard class(es)	
Class	3
Subsidiary risk	-
Packing group	II
Environmental hazards	
Marine pollutant	Yes.
EmS	F-E, S-D
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

### CERCLA Hazardous Substance List (40 CFR 302.4)

Chlorobenzene (CAS 108-90-7)	Listed.
Cyclohexane (CAS 110-82-7)	Listed.
Ethyl acetate (CAS 141-78-6)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Methyl alcohol (CAS 67-56-1)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

### SARA 304 Emergency release notification

Not regulated.

### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

### Toxic Substances Control Act (TSCA)

All components on the TSCA 8(b) inventory are designated "active".

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

Not listed.

### SARA 311/312 Hazardous chemical

Yes

**Classified hazard categories**

- Flammable (gases, aerosols, liquids, or solids)
- Skin corrosion or irritation
- Serious eye damage or eye irritation
- Respiratory or skin sensitization
- Carcinogenicity
- Reproductive toxicity
- Specific target organ toxicity (single or repeated exposure)
- Aspiration hazard

### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Cyclohexane	110-82-7	30 - 60
Ethylbenzene	100-41-4	< 11
Methyl alcohol	67-56-1	0.1 - 1
Xylene	1330-20-7	20 - 35

### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

- Chlorobenzene (CAS 108-90-7)
- Ethylbenzene (CAS 100-41-4)
- Methyl alcohol (CAS 67-56-1)
- Toluene (CAS 108-88-3)
- Xylene (CAS 1330-20-7)

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

#### Safe Drinking Water Act (SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

#### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Toluene (CAS 108-88-3) 6594

#### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Toluene (CAS 108-88-3) 35 %WV

#### DEA Exempt Chemical Mixtures Code Number

Toluene (CAS 108-88-3) 594

#### FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Ethyl acetate (CAS 141-78-6) Low priority  
Ethyl alcohol (CAS 64-17-5) Low priority

### US state regulations

#### US. Massachusetts RTK - Substance List

- Chlorobenzene (CAS 108-90-7)
- Cyclohexane (CAS 110-82-7)
- Ethyl acetate (CAS 141-78-6)
- Ethyl alcohol (CAS 64-17-5)
- Ethylbenzene (CAS 100-41-4)
- Methyl alcohol (CAS 67-56-1)
- Toluene (CAS 108-88-3)
- Xylene (CAS 1330-20-7)

#### US. New Jersey Worker and Community Right-to-Know Act

- Chlorobenzene (CAS 108-90-7)
- Cyclohexane (CAS 110-82-7)
- Ethyl acetate (CAS 141-78-6)
- Ethyl alcohol (CAS 64-17-5)
- Ethylbenzene (CAS 100-41-4)
- Methyl alcohol (CAS 67-56-1)
- Toluene (CAS 108-88-3)
- Xylene (CAS 1330-20-7)

## US. Pennsylvania Worker and Community Right-to-Know Law

Chlorobenzene (CAS 108-90-7)  
Cyclohexane (CAS 110-82-7)  
Ethyl acetate (CAS 141-78-6)  
Ethyl alcohol (CAS 64-17-5)  
Ethylbenzene (CAS 100-41-4)  
Methyl alcohol (CAS 67-56-1)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

## US. Rhode Island RTK

Chlorobenzene (CAS 108-90-7)  
Cyclohexane (CAS 110-82-7)  
Ethyl acetate (CAS 141-78-6)  
Ethyl alcohol (CAS 64-17-5)  
Ethylbenzene (CAS 100-41-4)  
Methyl alcohol (CAS 67-56-1)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

## California Proposition 65



**WARNING:** This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer, and Methyl alcohol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004

### California Proposition 65 - CRT: Listed date/Developmental toxin

Methyl alcohol (CAS 67-56-1) Listed: March 16, 2012  
Toluene (CAS 108-88-3) Listed: January 1, 1991

## US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Chlorobenzene (CAS 108-90-7)  
Cyclohexane (CAS 110-82-7)  
Ethyl acetate (CAS 141-78-6)  
Ethylbenzene (CAS 100-41-4)  
Methyl alcohol (CAS 67-56-1)  
Toluene (CAS 108-88-3)  
Xylene (CAS 1330-20-7)

## International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 22-September-2019  
**Revision date** -  
**Version #** 01  
**HMIS® ratings** Health: 2  
Flammability: 3  
Physical hazard: 0

## NFPA ratings



## Disclaimer

Goodrich Corporation cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.