



Revision Number: 004.4

Issue date: 01/25/2021

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE M-CRT 5900 AERO CHROMATE COATING known as ALODINE T 5900
Product type/use: Conversion coating
Restriction of Use: None identified
Company address: Henkel Corporation
 One Henkel Way
 Rocky Hill, Connecticut 06067

IDH number: 756391

Region: United States

Contact information:
 Telephone: +1 (860) 571-5100
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CONTAINS FLUORIDES. MAY CAUSE DELAYED BURNS (NOT IMMEDIATELY PAINFUL OR VISIBLE)! LONG TERM EXPOSURE TO FLUORIDES OVER YEARS MAY CAUSE FLUOROSIS! CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1



Precautionary Statements

Prevention: Wash affected area thoroughly after handling. Wear protective gloves, clothing, eye and face protection.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Wash contaminated clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Hexafluorozirconic acid	12021-95-3	1 - 5
Chromium hydroxide sulfate	12336-95-7	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist. If breathing is difficult, give oxygen. Trained personnel should administer 2.5% calcium gluconate through a nebulizer for 20 minutes.
Skin contact:	Remove contaminated clothing and footwear while rinsing the affected area with large amounts of running water for at least 15 minutes. GET IMMEDIATE MEDICAL ATTENTION. If iced solution of 0.13% aqueous Benzalkonium Chloride (Zephiran) or 2.5% calcium gluconate gel is available, rinsing may be limited to 5 minutes, with the soak solution or gel applied as soon as the rinsing is stopped. Gloves should be worn when applying the gel to prevent transfer of HF and secondary burns. If using calcium gluconate gel, it should be continuously re-applied and massaged into the affected area until pain has been relieved for at least 30 minutes. If Benzalkonium Chloride (Zephiran) or calcium gluconate gel is not available, rinsing must continue until medical treatment is provided.
Eye contact:	Immediately flush affected eye with large amounts of gently flowing water or 0.9% sterile saline solution for at least 15 minutes. Hold eyelid wide open. Get immediate medical attention. Eye flushing should continue during transportation to a doctor.
Ingestion:	Get immediate medical attention. Do not induce vomiting. Attempt immediate administration of a fluoride binding substance: milk, chewable calcium carbonate tablets or 4-8 ounces (120-240 ml) of milk of magnesia or a liquid antacid. Avoid large amounts of liquid as it may induce vomiting. Never give anything by mouth to an unconscious person.
Symptoms:	See Section 11.
Notes to physician:	Treatment of hypocalcemia associated with corrosive fluoride compounds exposure may be corrected by intravenous calcium gluconate or calcium chloride. Treatment of hypomagnesemia may be corrected by intravenous magnesium sulfate.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen fluoride.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear suitable protective clothing, gloves and eye/face protection.
Clean-up methods:	Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Avoid breathing mists or aerosols of this product. IN CASE OF CONTACT OR SUSPICION OF CONTACT, PROMPT MEDICAL ATTENTION IS ABSOLUTELY NECESSARY. Use only with adequate ventilation. Do not take internally. Wash thoroughly after handling. For industrial use only.

Storage: For safe storage, store at or above 40 °F (4.4 °C) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Thaw and mix thoroughly if frozen.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Hexafluorozirconic acid	5 mg/m ³ TWA (as Zr) 10 mg/m ³ STEL (as Zr)	5 mg/m ³ PEL (as Zr)	None	None
Chromium hydroxide sulfate	0.003 mg/m ³ TWA (as Cr(III)) Inhalable fraction. 0.003 mg/m ³ TWA (as Cr(III)) Inhalable fraction. (Respiratory sensitization) (Dermal sensitization)	1 mg/m ³ PEL (as Cr) 0.5 mg/m ³ PEL (as Cr)	None	None

Engineering controls: Use general ventilation and use local exhaust, where possible, in confined or enclosed spaces. Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	dark green
Odor:	Mild
Odor threshold:	Not available.
pH:	1.75 - 2.25
Vapor pressure:	Not determined
Boiling point/range:	> 100 °C (> 212°F)calculated
Melting point/range:	Not determined
Specific gravity:	1.034 - 1.094
Vapor density:	Not determined
Flash point:	Not applicable
Flammable/Explosive limits - lower:	Not applicable
Flammable/Explosive limits - upper:	Not applicable
Autoignition temperature:	Not applicable
Flammability:	Not applicable
Evaporation rate:	Not determined
Solubility in water:	Not available.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	Not applicable
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions of storage and use.
Hazardous reactions:	Will not occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. May liberate hydrogen fluoride.
Incompatible materials:	This product may react with strong acids, bases and oxidizing agents. This material will react with glass, concrete, certain metals, silica containing materials, rubber, leather, and many organics.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:	Mists, vapors or liquid may cause severe irritation or burns. Can cause pulmonary edema; signs and symptoms can be delayed for several hours.
Skin contact:	Corrosive to the skin. Contact with the skin or mucous membranes may cause severe irritation and burns. Following skin exposure to this product, the sensation of irritation or pain may be delayed.
Eye contact:	This product is severely irritating to the eyes and may cause irreversible damage including burns and blindness.
Ingestion:	This product may produce corrosive damage to the gastrointestinal tract if it is swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Hexafluorozirconic acid	None	No Records
Chromium hydroxide sulfate	None	Allergen, Corrosive, Irritant, Respiratory

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Hexafluorozirconic acid	No	No	No
Chromium hydroxide sulfate	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: No data available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:	Corrosive liquid, acidic, inorganic, n.o.s. (Fluorozirconic acid, Chromium sulphate)
Hazard class or division:	8
Identification number:	UN 3264
Packing group:	II

International Air Transportation (ICAO/IATA)

Proper shipping name: Corrosive liquid, acidic, inorganic, n.o.s. (Fluorozirconic acid, Chromium sulphate)
Hazard class or division: 8
Identification number: UN 3264
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Fluorozirconic acid, Chromium sulphate)
Hazard class or division: 8
Identification number: UN 3264
Packing group: II

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Chromium hydroxide sulfate (CAS# 12336-95-7).

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 01/25/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.