



**Revision Date:** 04/28/2004 Issue date: 04/28/2004

#### CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Contact Information:** 

Telephone: 860.571.5100

Product name: Silver Grade Anti-Seize Lubricant Item number: 80209 Product type: Lubricant Region: **United States** 

Company address: Henkel Corporation

1001 Trout Brook Crossing Emergency telephone: 860.571.5100 Rocky Hill, Connecticut 06067 Internet: www.loctite.com

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components Graphite 7782-42-5	<u>%</u> 10-30	ACGIH TLV 2 mg/m³ TWA	OSHA PEL 15 mg/m³ (total), 5 mg/m³ (respirable)	OTHER None
Calcium oxide 1305-78-8	10-30	2 mg/m³ TWA	5 mg/m³ (TWA)	None
Aluminum 7429-90-5	5-10	10 mg/m³ TWA 5 mg/m³ TWA	15 mg/m³ TWA (total), 5 mg/m³( respirable)	None
Silica, quartz 14808-60-7	0.1-1	0.05 mg/m³ TWA	0.1mg/m³ TWA (respirable)	None

### 3. HAZARDS IDENTIFICATION

# **EMERGENCY OVERVIEW**

HMIS:

Physical state: HEALTH: Paste 1 Color: FLAMMABILITY: Silver 1 PHYSICAL HAZARD: Odor: Hydrocarbon-like 1

**Personal Protection:** See Section 8

**WARNING:** CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION

Relevant routes of exposure: Skin, inhalation, eyes

**Potential Health Effects** 

Inhalation: Moderate respiratory tract irritation.

Skin contact: Moderate skin irritation. Eye contact: Moderate eye irritation.

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Principal hazard of

ingestion is aspiration into the lungs and subsequent pneumonitis.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

See Section 11 for additional toxicological information.

Item number: 80209 Product name: Silver Grade Anti-Seize Lubricant

### 4. FIRST AID MEASURES

**Inhalation:** Remove to fresh air. If discomfort persists seek medical attention.

Skin contact: Wash with soap and water. If symptoms persist, obtain medical attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

**Ingestion:** Do not induce vomiting. Get medical attention immediately.

# 5. FIRE-FIGHTING MEASURES

Flash point: >93°C (>200°F) Decomposes before flashing.

Flashback: Not applicable Flame Projection: Not applicable

Autoignition temperature: Not determined

Flammable/Explosive limits-lower %: Not available

Flammable/Explosive limits-upper %: Not available

Extinguishing media: Carbon dioxide (CO2). Foam. Dry chemical.

Special fire fighting procedures: None

Unusual fire or explosion hazards: None

**Hazardous combustion products:** Oxides of carbon. Oxides of nitrogen.

#### 6. ACCIDENTAL RELEASE MEASURES

**Environmental precautions:** Prevent further leakage or spillage.

Clean-up methods: Remove all ignition sources. Soak up with inert absorbent. Store in a closed container until ready for

disposal.

# 7. HANDLING AND STORAGE

Handling: Keep away from heat, spark and flame. Avoid contact with skin and eyes.

Storage: Keep in a cool, well ventilated area.

**Incompatible products:** No special restrictions on storage with other products.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor concentration below

established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Skin protection:** Neoprene or oil resistant gloves

**Eye/face protection:** Safety goggles or safety glasses with side shields.

Item number: 80209 Product name: Silver Grade Anti-Seize Lubricant

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Paste Color: Silver

Odor: Hydrocarbon-like Vapor pressure: 45 mmHg @20°C (68° F)

pH: Not applicable
Boiling point/range: Not available
Melting point/range: Not available
Specific gravity: 1.25

Vapor density:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available
Not available
Insoluble
Not determined

**VOC content:** 12.96%; 162 grams/liter

# 10. STABILITY AND REACTIVITY

Stability: Stable.

Hazardous polymerization: Will not occur.

Hazardous decomposition products: None reasonably foreseeable

**Incompatability:** Strong oxidizing agents.

Conditions to avoid: None known.

# 11. TOXICOLOGICAL INFORMATION

#### Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Graphite	No	No	No
Calcium oxide	No	No	No
Aluminum	No	No	No
Silica, quartz	Known Carcinogen	Group 1	Yes

### Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs		
Graphite	Lung		
Calcium oxide	Irritant, Eyes, Corrosive		
Aluminum	Central nervous system, Irritant, Lung		
Silica, quartz	Some evidence of carcinogenicity, Lung, Immune system		

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available

# 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

**EPA hazardous waste number:** Not a RCRA hazardous waste.

# 14. TRANSPORT INFORMATION

Item number: 80209 Product name: Silver Grade Anti-Seize Lubricant

#### U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None

### International Air Transportation (ICAO/IATA):

Proper shipping name: Unrestricted Hazard class or division: None Identification number: None Packing group: None

#### WaterTransportation (IMO/IMDG):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None
Marine pollutant: None

### 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

TSCA 12 (b) Export Notification: Non

CERCLA/SARA Section 302 EHS: None.

CERCLA/SARA Section 311/312: Immediate Health Hazard CERCLA/SARA 313: Aluminum (CAS# 7429-90-5).

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Domestic Substances List.

WHMIS hazard class: D.2.A, D.2.B

### **16. OTHER INFORMATION**

This material safety data sheet contains changes from the previous version in sections: Revised to new format.

Prepared by: C.J. Michaels, Senior Health & Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Item number: 80209 Product name: Silver Grade Anti-Seize Lubricant