

SAFETY DATA SHEET

E65XXA28960-4311

Section 1. Identification

Product name : E65XX POLANE MACHINE TOOL FINISH PRIMER-SEALER with PHX
Primer Sealer - Dark Gray

Product code : E65XXA28960-4311

Other means of identification : Not available.

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Paint or paint related material.

Manufacturer : THE SHERWIN-WILLIAMS COMPANY
101 W. Prospect Avenue
Cleveland, OH 44115

Emergency telephone number of the company : (216) 566-2917

Product Information Telephone Number : Not available.

Regulatory Information Telephone Number : (216) 566-2902

Transportation Emergency Telephone Number : (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 2
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION - Category 2
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 16.8% (dermal), 7.1% (inhalation)

GHS label elements

Hazard pictograms :



Signal word : Danger

Date of issue/Date of revision : 6/29/2020 **Date of previous issue** : 6/22/2020

Version : 7.01 1/21

E65XXA28960-4311 E65XX POLANE MACHINE TOOL FINISH PRIMER-SEALER with PHX
Primer Sealer - Dark Gray

SHW-85-NA-GHS-US

Section 2. Hazards identification

- Hazard statements** : Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye damage.
May cause respiratory irritation.
May cause drowsiness or dizziness.
May cause cancer.
Suspected of damaging fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure. (lungs)
- Precautionary statements**
- General** : Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
- Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating or lighting equipment. Use non-sparking tools. Take action to prevent static discharges. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.
- Response** : IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.
- Storage** : Store locked up. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Contains solvents which can cause permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. This product must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.

Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
- Hazards not otherwise classified** : None known.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.
- CAS number/other identifiers**

Section 3. Composition/information on ingredients

Ingredient name	% by weight	CAS number
n-Butyl Acetate	≥10 - ≤25	123-86-4
Talc	≥10 - ≤25	14807-96-6
Methyl Ethyl Ketone	≥10 - ≤25	78-93-3
Toluene	≤9.6	108-88-3
Cyclohexanone	≤10	108-94-1
Isopropyl Acetate	≤10	108-21-4
Calcium Carbonate	≤10	1317-65-3
Titanium Dioxide	≤10	13463-67-7
Carbon Black	≤1	1333-86-4
Xylene, mixed isomers	≤0.3	1330-20-7
Crystalline Silica, respirable powder	≤0.3	14808-60-7

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.

Section 4. First aid measures

Ingestion : Can cause central nervous system (CNS) depression.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Section 5. Fire-fighting measures

- Specific hazards arising from the chemical** : Highly flammable liquid and vapor. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
halogenated compounds
metal oxide/oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
n-Butyl Acetate	123-86-4	NIOSH REL (United States, 10/2016). TWA: 150 ppm 10 hours. TWA: 710 mg/m ³ 10 hours. STEL: 200 ppm 15 minutes. STEL: 950 mg/m ³ 15 minutes. OSHA PEL (United States, 5/2018). TWA: 150 ppm 8 hours. TWA: 710 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2019). STEL: 150 ppm 15 minutes. TWA: 50 ppm 8 hours.
Talc	14807-96-6	NIOSH REL (United States, 10/2016). TWA: 2 mg/m ³ 10 hours. Form: Respirable fraction ACGIH TLV (United States, 3/2019). TWA: 2 mg/m ³ 8 hours. Form: Respirable fraction
Methyl Ethyl Ketone	78-93-3	ACGIH TLV (United States, 3/2019). TWA: 200 ppm 8 hours. TWA: 590 mg/m ³ 8 hours. STEL: 300 ppm 15 minutes. STEL: 885 mg/m ³ 15 minutes. NIOSH REL (United States, 10/2016).

Section 8. Exposure controls/personal protection

Toluene	108-88-3	<p>TWA: 200 ppm 10 hours. TWA: 590 mg/m³ 10 hours. STEL: 300 ppm 15 minutes. STEL: 885 mg/m³ 15 minutes. OSHA PEL (United States, 5/2018). TWA: 200 ppm 8 hours. TWA: 590 mg/m³ 8 hours. OSHA PEL Z2 (United States, 2/2013). TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes. NIOSH REL (United States, 10/2016). TWA: 100 ppm 10 hours. TWA: 375 mg/m³ 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m³ 15 minutes. ACGIH TLV (United States, 3/2019). TWA: 20 ppm 8 hours.</p>
Cyclohexanone	108-94-1	<p>ACGIH TLV (United States, 3/2019). Absorbed through skin. TWA: 20 ppm 8 hours. STEL: 50 ppm 15 minutes. NIOSH REL (United States, 10/2016). Absorbed through skin. TWA: 25 ppm 10 hours. TWA: 100 mg/m³ 10 hours. OSHA PEL (United States, 5/2018). TWA: 50 ppm 8 hours. TWA: 200 mg/m³ 8 hours.</p>
Isopropyl Acetate	108-21-4	<p>OSHA PEL (United States, 5/2018). TWA: 250 ppm 8 hours. TWA: 950 mg/m³ 8 hours. ACGIH TLV (United States, 3/2019). TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes.</p>
Calcium Carbonate	1317-65-3	<p>OSHA PEL (United States, 5/2018). TWA: 5 mg/m³ 8 hours. Form: Respirable fraction TWA: 15 mg/m³ 8 hours. Form: Total dust NIOSH REL (United States, 10/2016). TWA: 5 mg/m³ 10 hours. Form: Respirable fraction TWA: 10 mg/m³ 10 hours. Form: Total</p>
Titanium Dioxide	13463-67-7	<p>ACGIH TLV (United States, 3/2019). TWA: 10 mg/m³ 8 hours. OSHA PEL (United States, 5/2018). TWA: 15 mg/m³ 8 hours. Form: Total dust</p>
Carbon Black	1333-86-4	<p>NIOSH REL (United States, 10/2016). TWA: 3.5 mg/m³ 10 hours. TWA: 0.1 mg of PAHs/cm³ 10 hours. ACGIH TLV (United States, 3/2019). TWA: 3 mg/m³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). TWA: 3.5 mg/m³ 8 hours.</p>
Xylene, mixed isomers	1330-20-7	<p>ACGIH TLV (United States, 3/2019). TWA: 100 ppm 8 hours.</p>

Section 8. Exposure controls/personal protection

Crystalline Silica, respirable powder	14808-60-7	<p>TWA: 434 mg/m³ 8 hours. STEL: 150 ppm 15 minutes. STEL: 651 mg/m³ 15 minutes. OSHA PEL (United States, 5/2018). TWA: 100 ppm 8 hours. TWA: 435 mg/m³ 8 hours.</p> <p>OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / (%SiO₂+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / (%SiO₂+2) 8 hours. Form: Respirable</p> <p>OSHA PEL (United States, 5/2018). TWA: 50 µg/m³ 8 hours. Form: Respirable dust</p> <p>ACGIH TLV (United States, 3/2019). TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction</p> <p>NIOSH REL (United States, 10/2016). TWA: 0.05 mg/m³ 10 hours. Form: respirable dust</p>
---------------------------------------	------------	--

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Normal butyl acetate	123-86-4	<p>CA Alberta Provincial (Canada, 6/2018). 15 min OEL: 200 ppm 15 minutes. 15 min OEL: 950 mg/m³ 15 minutes. 8 hrs OEL: 150 ppm 8 hours. 8 hrs OEL: 713 mg/m³ 8 hours.</p> <p>CA British Columbia Provincial (Canada, 5/2019). TWA: 20 ppm 8 hours.</p> <p>CA Ontario Provincial (Canada, 1/2018). TWA: 150 ppm 8 hours. STEL: 200 ppm 15 minutes.</p> <p>CA Quebec Provincial (Canada, 1/2014). TWAEV: 150 ppm 8 hours. TWAEV: 713 mg/m³ 8 hours. STEV: 200 ppm 15 minutes. STEV: 950 mg/m³ 15 minutes.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 200 ppm 15 minutes. TWA: 150 ppm 8 hours.</p>
talc (none asbestiform)	14807-96-6	<p>CA British Columbia Provincial (Canada, 5/2019). TWA: 2 mg/m³ 8 hours. Form: Respirable TWA: 0.1 f/cc 8 hours.</p> <p>CA Quebec Provincial (Canada, 1/2014). TWAEV: 3 mg/m³ 8 hours. Form: Respirable dust.</p> <p>CA Ontario Provincial (Canada, 1/2018). TWA: 2 mg/m³ 8 hours. Form: Respirable fraction. TWA: 2 f/cc 8 hours.</p> <p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 2 mg/m³ 8 hours. Form:</p>

Section 8. Exposure controls/personal protection

Methyl ethyl ketone	78-93-3	<p>Respirable particulate CA Saskatchewan Provincial (Canada, 7/2013). TWA: 2 mg/m³ 8 hours. Form: respirable fraction</p> <p>CA Alberta Provincial (Canada, 6/2018). 15 min OEL: 300 ppm 15 minutes. 8 hrs OEL: 200 ppm 8 hours. 8 hrs OEL: 590 mg/m³ 8 hours. 15 min OEL: 885 mg/m³ 15 minutes.</p> <p>CA British Columbia Provincial (Canada, 5/2019). TWA: 50 ppm 8 hours. STEL: 100 ppm 15 minutes.</p> <p>CA Ontario Provincial (Canada, 1/2018). TWA: 200 ppm 8 hours. STEL: 300 ppm 15 minutes.</p> <p>CA Quebec Provincial (Canada, 1/2014). TWAEV: 50 ppm 8 hours. TWAEV: 150 mg/m³ 8 hours. STEV: 100 ppm 15 minutes. STEV: 300 mg/m³ 15 minutes.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 300 ppm 15 minutes. TWA: 200 ppm 8 hours.</p>
Toluene	108-88-3	<p>CA Alberta Provincial (Canada, 6/2018). Absorbed through skin. 8 hrs OEL: 50 ppm 8 hours. 8 hrs OEL: 188 mg/m³ 8 hours.</p> <p>CA British Columbia Provincial (Canada, 5/2019). TWA: 20 ppm 8 hours.</p> <p>CA Ontario Provincial (Canada, 1/2018). TWA: 20 ppm 8 hours.</p> <p>CA Quebec Provincial (Canada, 1/2014). Absorbed through skin. TWAEV: 50 ppm 8 hours. TWAEV: 188 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 60 ppm 15 minutes. TWA: 50 ppm 8 hours.</p>
Cyclohexanone	108-94-1	<p>CA Alberta Provincial (Canada, 6/2018). Absorbed through skin. 8 hrs OEL: 20 ppm 8 hours. 8 hrs OEL: 80 mg/m³ 8 hours. 15 min OEL: 200 mg/m³ 15 minutes. 15 min OEL: 50 ppm 15 minutes.</p> <p>CA British Columbia Provincial (Canada, 5/2019). Absorbed through skin. TWA: 20 ppm 8 hours. STEL: 50 ppm 15 minutes.</p> <p>CA Ontario Provincial (Canada, 1/2018). Absorbed through skin. TWA: 20 ppm 8 hours. STEL: 50 ppm 15 minutes.</p>

Section 8. Exposure controls/personal protection

Isopropyl acetate	108-21-4	<p>CA Quebec Provincial (Canada, 1/2014). Absorbed through skin. TWAEV: 25 ppm 8 hours. TWAEV: 100 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). Absorbed through skin. STEL: 50 ppm 15 minutes. TWA: 20 ppm 8 hours.</p> <p>CA Alberta Provincial (Canada, 6/2018). 15 min OEL: 200 ppm 15 minutes. 8 hrs OEL: 416 mg/m³ 8 hours. 15 min OEL: 832 mg/m³ 15 minutes. 8 hrs OEL: 100 ppm 8 hours.</p> <p>CA British Columbia Provincial (Canada, 5/2019). TWA: 100 ppm 8 hours. STEL: 200 ppm 15 minutes.</p> <p>CA Ontario Provincial (Canada, 1/2018). TWA: 100 ppm 8 hours. STEL: 200 ppm 15 minutes.</p> <p>CA Quebec Provincial (Canada, 1/2014). TWAEV: 250 ppm 8 hours. TWAEV: 1040 mg/m³ 8 hours. STEV: 310 ppm 15 minutes. STEV: 1290 mg/m³ 15 minutes.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 200 ppm 15 minutes. TWA: 100 ppm 8 hours.</p>
Titanium dioxide	13463-67-7	<p>CA British Columbia Provincial (Canada, 5/2019). TWA: 3 mg/m³ 8 hours. Form: Respirable dust TWA: 10 mg/m³ 8 hours. Form: Total dust</p> <p>CA Quebec Provincial (Canada, 1/2014). TWAEV: 10 mg/m³ 8 hours. Form: Total dust.</p> <p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 10 mg/m³ 8 hours.</p> <p>CA Ontario Provincial (Canada, 1/2018). TWA: 10 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 20 mg/m³ 15 minutes. TWA: 10 mg/m³ 8 hours.</p>
Carbon black	1333-86-4	<p>CA British Columbia Provincial (Canada, 5/2019). TWA: 3 mg/m³ 8 hours. Form: Inhalable</p> <p>CA Ontario Provincial (Canada, 1/2018). TWA: 3 mg/m³ 8 hours. Form: Inhalable fraction.</p> <p>CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 3.5 mg/m³ 8 hours.</p> <p>CA Quebec Provincial (Canada, 1/2014). TWAEV: 3.5 mg/m³ 8 hours.</p> <p>CA Saskatchewan Provincial (Canada, 7/2013). STEL: 7 mg/m³ 15 minutes.</p>

Section 8. Exposure controls/personal protection

Xylene	1330-20-7	<p>TWA: 3.5 mg/m³ 8 hours. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 100 ppm 8 hours. 15 min OEL: 651 mg/m³ 15 minutes. 15 min OEL: 150 ppm 15 minutes. 8 hrs OEL: 434 mg/m³ 8 hours. CA British Columbia Provincial (Canada, 5/2019). TWA: 100 ppm 8 hours. STEL: 150 ppm 15 minutes. CA Quebec Provincial (Canada, 1/2014). TWAEV: 100 ppm 8 hours. TWAEV: 434 mg/m³ 8 hours. STEV: 150 ppm 15 minutes. STEV: 651 mg/m³ 15 minutes. CA Ontario Provincial (Canada, 1/2018). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours. CA Saskatchewan Provincial (Canada, 7/2013). STEL: 150 ppm 15 minutes. TWA: 100 ppm 8 hours.</p>
Quartz	14808-60-7	<p>CA British Columbia Provincial (Canada, 5/2019). TWA: 0.025 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 1/2014). TWAEV: 0.1 mg/m³ 8 hours. Form: Respirable dust. CA Ontario Provincial (Canada, 1/2018). TWA: 0.1 mg/m³ 8 hours. Form: Respirable fraction. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 0.025 mg/m³ 8 hours. Form: Respirable particulate CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m³ 8 hours. Form: respirable fraction</p>

Occupational exposure limits (Mexico)

	CAS #	Exposure limits
n-Butyl Acetate	123-86-4	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 150 ppm 8 hours. STEL: 200 ppm 15 minutes.
Methyl Ethyl Ketone	78-93-3	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 200 ppm 8 hours. STEL: 300 ppm 15 minutes.
Toluene	108-88-3	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 20 ppm 8 hours.
Cyclohexanone	108-94-1	NOM-010-STPS-2014 (Mexico, 4/2016). Absorbed through skin. TWA: 20 ppm 8 hours. STEL: 50 ppm 15 minutes.
Isopropyl Acetate	108-21-4	NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 100 ppm 8 hours.

Section 8. Exposure controls/personal protection

STEL: 200 ppm 15 minutes.

Appropriate engineering controls : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Not available.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Melting point/freezing point** : Not available.
- Boiling point/boiling range** : 78°C (172.4°F)

Section 9. Physical and chemical properties

- Flash point** : Closed cup: -1°C (30.2°F) [Pensky-Martens Closed Cup]
- Evaporation rate** : 5.6 (butyl acetate = 1)
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Lower: 1%
Upper: 10%
- Vapor pressure** : 12.1 kPa (90.6 mm Hg) [at 20°C]
- Vapor density** : 2.48 [Air = 1]
- Relative density** : 1.14
- Solubility** : Not available.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Kinematic (40°C (104°F)): <0.205 cm²/s (<20.5 cSt)
- Molecular weight** : Not applicable.
- Aerosol product**
 - Heat of combustion** : 16.221 kJ/g

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
- Incompatible materials** : Reactive or incompatible with the following materials:
oxidizing materials
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-Butyl Acetate	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
Methyl Ethyl Ketone	LD50 Dermal	Rabbit	6480 mg/kg	-
	LD50 Oral	Rat	2737 mg/kg	-
Toluene	LC50 Inhalation Vapor	Rat	49 g/m ³	4 hours
	LD50 Oral	Rat	636 mg/kg	-
Cyclohexanone	LC50 Inhalation Gas.	Rat	8000 ppm	4 hours
	LD50 Oral	Rat	1800 mg/kg	-
Isopropyl Acetate	LD50 Oral	Rat	6750 mg/kg	-

Section 11. Toxicological information

Carbon Black	LD50 Oral	Rat	>15400 mg/kg	-
Xylene, mixed isomers	LC50 Inhalation Gas.	Rat	5000 ppm	4 hours
	LD50 Oral	Rat	4300 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
n-Butyl Acetate	Eyes - Moderate irritant	Rabbit	-	100 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Talc	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
Methyl Ethyl Ketone	Skin - Mild irritant	Rabbit	-	24 hours 14 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
Toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100 mg	-
	Eyes - Mild irritant	Rabbit	-	870 ug	-
	Eyes - Severe irritant	Rabbit	-	24 hours 2 mg	-
	Skin - Mild irritant	Pig	-	24 hours 250 UI	-
Cyclohexanone	Skin - Mild irritant	Rabbit	-	435 mg	-
	Skin - Moderate irritant	Rabbit	-	24 hours 20 mg	-
	Skin - Moderate irritant	Rabbit	-	500 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 250 ug	-
Isopropyl Acetate	Eyes - Severe irritant	Rabbit	-	20 mg	-
	Skin - Mild irritant	Human	-	48 hours 50 %	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
Titanium Dioxide	Skin - Mild irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Mild irritant	Human	-	72 hours 300 ug l	-
Xylene, mixed isomers	Eyes - Mild irritant	Rabbit	-	87 mg	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 mg	-
	Skin - Mild irritant	Rat	-	8 hours 60 UI	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 mg	-
	Skin - Moderate irritant	Rabbit	-	100 %	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Section 11. Toxicological information

Product/ingredient name	OSHA	IARC	NTP
Talc	-	3	-
Toluene	-	3	-
Cyclohexanone	-	3	-
Titanium Dioxide	-	2B	-
Carbon Black	-	2B	-
Xylene, mixed isomers	-	3	-
Crystalline Silica, respirable powder	-	1	Known to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
n-Butyl Acetate	Category 3	-	Narcotic effects
Methyl Ethyl Ketone	Category 3	-	Respiratory tract irritation
Toluene	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
Cyclohexanone	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
Isopropyl Acetate	Category 3	-	Narcotic effects
Calcium Carbonate	Category 3	-	Narcotic effects
	Category 3	-	Respiratory tract irritation
Xylene, mixed isomers	Category 3	-	Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
Talc	Category 1	inhalation	lungs
Methyl Ethyl Ketone	Category 2	-	-
Toluene	Category 2	-	-
Cyclohexanone	Category 2	-	-
Xylene, mixed isomers	Category 2	-	-
Crystalline Silica, respirable powder	Category 1	inhalation	-

Aspiration hazard

Name	Result
Toluene	ASPIRATION HAZARD - Category 1
Xylene, mixed isomers	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Section 11. Toxicological information

- Inhalation** : Can cause central nervous system (CNS) depression. May cause drowsiness or dizziness. May cause respiratory irritation.
- Skin contact** : Causes skin irritation.
- Ingestion** : Can cause central nervous system (CNS) depression.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:
pain
watering
redness

Inhalation : Adverse symptoms may include the following:
respiratory tract irritation
coughing
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness
reduced fetal weight
increase in fetal deaths
skeletal malformations

Skin contact : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
reduced fetal weight
increase in fetal deaths
skeletal malformations

Ingestion : Adverse symptoms may include the following:
stomach pains
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

- General** : Causes damage to organs through prolonged or repeated exposure.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : Suspected of damaging the unborn child.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Section 11. Toxicological information

[Numerical measures of toxicity](#)

[Acute toxicity estimates](#)

Route	ATE value
Oral	4055.3 mg/kg
Dermal	10743.6 mg/kg
Inhalation (gases)	93862.17 ppm

Section 12. Ecological information

[Toxicity](#)

Product/ingredient name	Result	Species	Exposure
n-Butyl Acetate	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina	48 hours
Methyl Ethyl Ketone	Acute LC50 18000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 >500000 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute EC50 5091000 µg/l Fresh water	Daphnia - Daphnia magna - Larvae	48 hours
Toluene	Acute LC50 3220000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
Cyclohexanone	Acute LC50 5500 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry	96 hours
	Chronic NOEC 1000 µg/l Fresh water	Daphnia - Daphnia magna	21 days
	Acute EC50 32.9 mg/l Fresh water	Algae - Chlamydomonas reinhardtii - Exponential growth phase	72 hours
	Acute LC50 527000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
	Chronic EC10 3.56 mg/l Fresh water	Algae - Chlamydomonas reinhardtii - Exponential growth phase	72 hours
Isopropyl Acetate	Acute LC50 110 mg/l Marine water	Crustaceans - Artemia salina	48 hours
Titanium Dioxide	Acute LC50 >1000000 µg/l Marine water	Fish - Fundulus heteroclitus	96 hours
Xylene, mixed isomers	Acute LC50 8500 µg/l Marine water	Crustaceans - Palaemonetes pugio	48 hours
	Acute LC50 13400 µg/l Fresh water	Fish - Pimephales promelas	96 hours

[Persistence and degradability](#)

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
n-Butyl Acetate	-	-	Readily
Methyl Ethyl Ketone	-	-	Readily
Toluene	-	-	Readily
Xylene, mixed isomers	-	-	Readily

[Bioaccumulative potential](#)

Section 12. Ecological information

Product/ingredient name	LogP _{ow}	BCF	Potential
Toluene	-	90	low
Xylene, mixed isomers	-	8.1 to 25.9	low

Mobility in soil






Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3 	3 	3 	3 
Packing group	II	II	II	II	II
Environmental hazards	No.	No.	No.	No.	No.
Additional information	- ERG No.	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3). ERG No.	- ERG No.	- ERG No.	Emergency schedules F-E, S-E

Section 14. Transport information

	128	128	128		
--	-----	-----	-----	--	--

Special precautions for user : Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according to IMO instruments : Not available.

Proper shipping name : Not available.

Section 15. Regulatory information

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

International lists

- Australia inventory (AICS):** Not determined.
- China inventory (IECSC):** Not determined.
- Japan inventory (ENCS):** Not determined.
- Japan inventory (ISHL):** Not determined.
- Korea inventory (KECI):** Not determined.
- New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- Philippines inventory (PICCS):** Not determined.
- Taiwan Chemical Substances Inventory (TCSI):** Not determined.
- Thailand inventory:** Not determined.
- Turkey inventory:** Not determined.
- Vietnam inventory:** Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		3
Physical hazards		0

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Section 16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

Classification	Justification
FLAMMABLE LIQUIDS - Category 2	On basis of test data
SKIN CORROSION/IRRITATION - Category 2	Calculation method
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1	Calculation method
CARCINOGENICITY - Category 1A	Calculation method
TOXIC TO REPRODUCTION - Category 2	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Narcotic effects) - Category 3	Calculation method
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1	Calculation method

History

Date of printing : 6/29/2020

Date of issue/Date of revision : 6/29/2020

Date of previous issue : 6/22/2020

Version : 7.01

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
N/A = Not available
SGG = Segregation Group
UN = United Nations

✔ Indicates information that has changed from previously issued version.

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

