According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## AeroShell Compound 07

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

#### **SECTION 1. IDENTIFICATION**

Product name : AeroShell Compound 07

Product code : 001A0037

#### Manufacturer or supplier's details

Manufacturer/Supplier : Shell Oil Products US

PO Box 4427

Houston TX 77210-4427

USA

SDS Request : (+1) 877-276-7285

Customer Service

**Emergency telephone number** 

Spill Information : 877-504-9351 Health Information : 877-242-7400

#### Recommended use of the chemical and restrictions on use

Recommended use : Glycol for aircraft de-icing., For further details consult the Aer-

oShell Book on www.shell.com/aviation.

Restrictions on use : This product must be used, handled, and applied in accord-

ance with the requirements of the equipment manufacturer's

manuals, bulletins and other documentation.

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Acute toxicity (Oral) : Category 4

Specific target organ toxicity

- repeated exposure

: Category 2 (Kidney)

#### **GHS** label elements

Hazard pictograms :





Signal word : Warning

Hazard statements : PHYSICAL HAZARDS:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

 Version
 Revision Date:
 SDS Number:
 Print Date: 12/04/2021

 2.0
 12/02/2021
 800001000357
 Date of last issue: 04/26/2021

H226 Flammable liquid and vapour.

HEALTH HAZARDS: H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or re-

peated exposure if swallowed. ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

Precautionary statements :

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P270 Do not eat, drink or smoke when using this product.

#### Response:

P301 + P312 IF SWALLOWED: Call a POISON CENTER/doctor

if you feel unwell.

P370 + P378 In case of fire: Use appropriate media to extin-

guish.

#### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

#### Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Hazardous components which must be listed on the label:

Contains ethanediol.

### Other hazards which do not result in classification

Intentional abuse, misuse or other massive exposure may cause multiple organ damage and or death.

The classification of this material is based on OSHA HCS 2012 criteria.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Mixture of ethylene glycol, water and additives.

### **Hazardous components**

Chemical name	Synonyms	CAS-No.	Concentration (% w/w)
Ethanediol	ethane-1,2-diol	107-21-1	85 - 95
Ethanol	ethanol (Solu-	64-17-5	1 - 5
	tion)		

#### **SECTION 4. FIRST-AID MEASURES**

General advice : Not expected to be a health hazard when used under normal

conditions.

If inhaled : Remove to fresh air. If rapid recovery does not occur,

transport to nearest medical facility for additional treatment.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

In case of skin contact : Remove contaminated clothing. Flush exposed area with wa-

ter and follow by washing with soap if available.

If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : If swallowed, do not induce vomiting: transport to nearest

medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Rinse mouth.

Most important symptoms and effects, both acute and delayed

Kidney toxicity may be recognized by blood in the urine or increased or decreased urine flow. Other signs and symptoms can include nausea, vomiting, abdominal cramps, diarrhoea, lumbar pain shortly after ingestion, and possibly narcosis and death.

Not considered to be an inhalation hazard under normal conditions of use.

Respiratory irritation signs and symptoms may include a temporary burning sensation of the nose and throat, coughing, and/or difficulty breathing.

No specific hazards under normal use conditions.

Eye irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blurred vision.

Skin irritation signs and symptoms may include a burning sen-

sation, redness, swelling, and/or blisters.

Ingestion may result in nausea, vomiting and/or diarrhoea. High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea; continued inhalation may result in unconsciousness and/or death.

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

Indication of any immediate medical attention and special treatment needed

IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT!

Call a doctor or poison control center for guidance.

Treat symptomatically.

May cause significant renal, respiratory, and CNS toxicity.

May cause significant acidosis.

The preferred treatment is immediate transportation to a medical facility and use of appropriate treatment including possible administration of activated charcoal, gastric lavage and or gastric aspiration. If none of the above are immediately available and a delay of more than one hour is anticipated before such medical attention can be obtained, induction of vomiting may be appropriate using IPECAC syrup (Contraindicated if there are any signs of CNS depression). This should be considered on a case by case basis following specialist advice. Specific other treatments may include ethanol therapy, fomepizole, treatment of acidosis and haemodialysis. Seek specialist

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

advice without delay.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon diox-

ide, sand or earth may be used for small fires only.

Unsuitable extinguishing

media

Do not use water in a jet.

Specific hazards during fire-

fighting

Will float and can be reignited on surface water. Hazardous combustion products may include:

A complex mixture of airborne solid and liquid particulates and

gases (smoke).

Carbon monoxide may be evolved if incomplete combustion

occurs.

Unidentified organic and inorganic compounds.

Further information : Keep adjacent containers cool by spraying with water.

Special protective equipment :

for firefighters

Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emer-

gency procedures

Personal precautions, protec: Avoid contact with skin and eyes.

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all

possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bond-

ing and grounding (earthing) all equipment.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth

or other containment material.

Reclaim liquid directly or in an absorbent.

Soak up residue with an absorbent such as clay, sand or other

suitable material and dispose of properly.

Additional advice : For guidance on selection of personal protective equipment

see Section 8 of this Safety Data Sheet.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

Local authorities should be advised if significant spillages cannot be contained.

U.S. regulations may require reporting releases of this material to the environment which exceed the reportable quantity (refer to Section 15) to the National Response Center at (800) 424-8802.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this

material.

Advice on safe handling : Extinguish any naked flames. Do not smoke. Remove ignition

sources. Avoid sparks.

Avoid prolonged or repeated contact with skin.

Avoid inhaling vapour and/or mists. Use only in well-ventilated areas.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used.

Properly dispose of any contaminated rags or cleaning mate-

rials in order to prevent fires.

Avoidance of contact : Strong oxidising agents.

Product Transfer : Wait 2 minutes after tank filling (for tanks such as those on

road tanker vehicles) before opening hatches or manholes. Wait 30 minutes after tank filling (for large storage tanks) before opening hatches or manholes. Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable airvapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (≤ 1 m/s until fill pipe submerged to twice its diameter, then ≤ 7 m/s). Avoid splash filling. Do NOT use compressed air for filling, discharging, or handling operations.

Further information on storage stability

Must be stored in a diked (bunded) well- ventilated area, away from sunlight, ignition sources and other sources of heat.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

 Version
 Revision Date:
 SDS Number:
 Print Date: 12/04/2021

 2.0
 12/02/2021
 800001000357
 Date of last issue: 04/26/2021

Use properly labeled and closable containers.

Keep container tightly closed and in a cool, well-ventilated

place.

Store at ambient temperature.

Packaging material : Suitable material: For containers or container linings, use mild

steel or high density polyethylene.

Suitable material: For container linings, use amine-adduct

cured epoxy paint.

Unsuitable material: Aluminium, PVC.

Container Advice : Polyethylene containers should not be exposed to high tem-

peratures because of possible risk of distortion.

Specific use(s) : See additional references that provide safe handling practices:

American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices

on Static Electricity).

#### SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanediol	107-21-1	TWA (Va- pour)	25 ppm	ACGIH
Ethanediol		STEL (Va- pour)	50 ppm	ACGIH
Ethanediol		STEL (Inhalable fraction, Aerosol only)	10 mg/m3	ACGIH
Ethanol	64-17-5	STEL	1,000 ppm	ACGIH
Ethanol		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1

### **Biological occupational exposure limits**

No biological limit allocated.

#### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Meth-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## AeroShell Compound 07

Revision Date: SDS Number: Print Date: 12/04/2021 Version

12/02/2021 800001000357 Date of last issue: 04/26/2021 2.0

ods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA), Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

#### **Engineering measures**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

### Personal protective equipment

Respiratory protection

No respiratory protection is ordinarily required under normal conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

Where air-filtering respirators are suitable, select an appro-

priate combination of mask and filter.

Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point

>65°C (149°F)].

Hand protection Remarks

Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended.

Skin and body protection : Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Protective measures : Personal protective equipment (PPE) should meet recom-

mended national standards. Check with PPE suppliers.

Thermal hazards : Not applicable

### **Environmental exposure controls**

General advice : Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing

vapour.

Minimise release to the environment. An environmental assessment must be made to ensure compliance with local envi-

ronmental legislation.

Information on accidental release measures are to be found in

section 6.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Liquid at room temperature.

Colour : colourless

Odour : characteristic

Odour Threshold : Data not available

pH : Typical 6.9

Concentration: 100 %

pour point : Method: Unspecified

Not applicable

Melting / freezing point Data not available

Initial boiling point and boiling

range

> 100 °C / 212 °F estimated value(s)

Flash point : 54.4 °C / 129.9 °F

Method: Unspecified

Evaporation rate : Data not available

Flammability (solid, gas) : Data not available

Upper explosion limit / upper

flammability limit

Typical 15 %(V)

Lower explosion limit / Lower

flammability limit

Typical 3 %(V)

Vapour pressure : Data not available

Relative vapour density : Data not available

Relative density :  $1.096 (15 \,^{\circ}\text{C} / 59 \,^{\circ}\text{F})$ 

Density : 1.096 kg/dm3 (15.5 °C / 59.9 °F)

Method: Unspecified

Solubility(ies)

Water solubility : completely soluble

Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

: Data not available

Auto-ignition temperature : > 200 °C / 392 °F

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## AeroShell Compound 07

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

Decomposition temperature : Data not available

Viscosity

Viscosity, dynamic : Data not available

Viscosity, kinematic : 12.8 mm2/s (20 °C / 68 °F)

Method: Unspecified

Explosive properties : Classification Code: Not classified

Oxidizing properties : Data not available

Conductivity : This material is not expected to be a static accumulator.

Decomposition temperature : Data not available

Molecular weight : Not applicable

Particle size : Data not available

#### **SECTION 10. STABILITY AND REACTIVITY**

Chemical stability : Stable.

Possibility of hazardous reac- :

tions

Reacts with strong oxidising agents.

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.

Incompatible materials : Strong oxidising agents.

Hazardous decomposition

products

No decomposition if stored and applied as directed.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Basis for assessment : Information given is based on data on the components and

the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a

whole, rather than for individual component(s).

## Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

### **Acute toxicity**

#### **Product:**

Acute oral toxicity : LD50 (rat): > 500 - 2,000 mg/kg

Remarks: Harmful if swallowed.

Remarks: There is a marked difference in acute oral toxicity

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

between rodents and man, man being more susceptible than rodents. The estimated fatal dose for man is 100 milliliters (1/2 cup). This material has also been shown to be toxic and

potentially lethal by ingestion to cats and dogs. Ingestion may cause drowsiness and dizziness.

Acute inhalation toxicity : LC 50 (Rat): > 5 mg/l

Exposure time: 4 h Remarks: Low toxicity:

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: Low toxicity:

**Components:** 

**Ethanediol:** 

Acute oral toxicity : LD 50 (Rat, male and female): > 2,000 mg/kg

Method: Acceptable non-standard method.

Remarks: Harmful if swallowed.

There is a marked difference in acute oral toxicity between rodents and man, man being more susceptible than rodents. The estimated fatal dose for man is 100 milliliters (1/2 cup). This material has also been shown to be toxic and potentially

lethal by ingestion to cats and dogs.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 2.5 mg/l

Exposure time: 6 h Test atmosphere: Aerosol Method: Literature data

Remarks:  $LC50 > 1.0 - \le 5.0 \text{ mg/l}$ 

LC50 greater than near-saturated vapour concentration. Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD 50 (Mouse, male and female): > 2,000 mg/kg

Method: Literature data

Remarks: Based on available data, the classification criteria

are not met.

Ethanol:

Acute oral toxicity : LD50 Oral (Rat, male and female): > 5,000 mg/kg

Method: Test(s) equivalent or similar to OECD Test Guideline

401

Remarks: Based on available data, the classification criteria

are not met.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: Test(s) equivalent or similar to OECD Test Guideline

403

Remarks: Based on available data, the classification criteria

are not met.

Acute dermal toxicity : Remarks: Based on available data, the classification criteria

are not met.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

#### Skin corrosion/irritation

#### **Product:**

Remarks: Slightly irritating to skin., Based on available data, the classification criteria are not

met.

#### Components:

## Ethanediol:

Species: Rabbit

Method: Acceptable non-standard method.

Remarks: Slightly irritating to skin., Insufficient to classify.

#### **Ethanol:**

Species: Rabbit

Method: Test(s) equivalent or similar to OECD Test Guideline 404

Remarks: Based on data from similar materials, Based on available data, the classification crite-

ria are not met.

#### Serious eye damage/eye irritation

#### **Product:**

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not

met.

### **Components:**

## Ethanediol:

Species: Rabbit

Method: Acceptable non-standard method.

Remarks: Slightly irritating to the eye., Insufficient to classify.

#### **Ethanol:**

Species: Rabbit

Result: Causes serious eye irritation.

Method: Test(s) equivalent or similar to OECD Test Guideline 405

Remarks: Based on data from similar materials

#### Respiratory or skin sensitisation

#### **Product:**

Remarks: Not a skin sensitiser.

Based on available data, the classification criteria are not met.

#### **Components:**

### **Ethanediol:**

Species: Guinea pig Method: Literature data

Remarks: Based on available data, the classification criteria are not met.

#### **Ethanol:**

Species: Mouse

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021 2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

Method: Test(s) equivalent or similar to OECD Test Guideline 406

Remarks: Based on data from similar materials Based on available data, the classification crite-

ria are not met.

### Germ cell mutagenicity

#### **Product:**

: Remarks: Non mutagenic, Based on available data, the classi-

fication criteria are not met.

### **Components:**

#### **Ethanediol:**

: Method: OECD Test Guideline 471

Remarks: Based on data from similar materials

: Method: Acceptable non-standard method. Remarks: Based on data from similar materials

: Method: Literature data

Remarks: Based on data from similar materials

: Test species: Rat Method: Literature data

Remarks: Based on available data, the classification criteria

are not met.

Germ cell mutagenicity- As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

#### **Ethanol:**

: Test species: Mouse

Method: OECD Test Guideline 471

Remarks: Based on data from similar materials, Based on available data, the classification criteria are not met.

Germ cell mutagenicity- As-

sessment

: This product does not meet the criteria for classification in

categories 1A/1B.

#### Carcinogenicity

#### **Product:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

#### Components:

#### **Ethanediol:**

Species: Mouse, (male and female)

Application Route: Oral Method: Literature data

Remarks: Based on available data, the classification criteria are not met.

Carcinogenicity - Assess- : This product does not meet the criteria for classification in

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

ment categories 1A/1B.

**Ethanol:** 

Species: Rat, (male and female) Application Route: Oral

Method: Test(s) equivalent or similar to OECD Test Guideline 453 Remarks: Based on available data, the classification criteria are not met.

Carcinogenicity - Assess-

ment

: This product does not meet the criteria for classification in

categories 1A/1B.

IARC Group 1: Carcinogenic to humans

Ethanol 64-17-5

Group 1: Carcinogenic to humans

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

**Product:** 

:

Remarks: Not a developmental toxicant., Based on available data, the classification criteria are not met., Does not impair

fertility.

**Components:** 

**Ethanediol:** 

Species: Rat

Sex: male and female Application Route: Oral

Method: Literature data

Remarks: Based on available data, the classification criteria

are not met.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

 Version
 Revision Date:
 SDS Number:
 Print Date: 12/04/2021

 2.0
 12/02/2021
 800001000357
 Date of last issue: 04/26/2021

Effects on foetal develop-

ment

: Species: Rat, male and female

Application Route: Oral Method: Literature data

Remarks: Based on available data, the classification criteria are not met., Causes foetotoxicity in animals; considered to be

secondary to maternal toxicity.

Reproductive toxicity - As-

sessment

: This product does not meet the criteria for classification in

categories 1A/1B.

**Ethanol:** 

:

Species: Mouse Sex: male and female Application Route: Oral

Method: Equivalent or similar to OECD Test Guideline 416 Remarks: Based on available data, the classification criteria

are not met.

Effects on foetal develop-

ment

Species: Rat, female

Application Route: Inhalation

Method: Test(s) equivalent or similar to OECD Test Guideline

414

Remarks: Based on available data, the classification criteria are not met., Causes foetotoxicity in animals at doses which are maternally toxic., Ethanol, a component of this material,

may cause birth defects and/or miscarriages.

Reproductive toxicity - As-

sessment

This product does not meet the criteria for classification in

categories 1A/1B.

#### STOT - single exposure

### **Product:**

Remarks: Based on available data, the classification criteria are not met.

#### **Components:**

#### **Ethanediol:**

Remarks: Inhalation of vapours or mists may cause irritation to the respiratory system., Based on available data, the classification criteria are not met., Ingestion may cause drowsiness and dizziness.

#### Ethanol:

Remarks: Based on available data, the classification criteria are not met.

#### STOT - repeated exposure

#### **Product:**

Remarks: Kidney: can cause kidney damage.

### **Components:**

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

#### **Ethanediol:**

Exposure routes: Oral Target Organs: Kidney

Remarks: May cause damage to organs or organ systems through prolonged or repeated expo-

sure.

#### **Ethanol:**

Remarks: Based on available data, the classification criteria are not met.

#### Repeated dose toxicity

#### **Components:**

#### **Ethanediol:**

Species: Rat, male Application Route: Oral

Method: Test(s) equivalent or similar to OECD Test Guideline 408

Target Organs: Kidney

#### **Ethanol:**

Species: Rat, male and female Method: OECD Test Guideline 408

Remarks: No significant adverse effects were reported

#### **Aspiration toxicity**

#### **Product:**

Not an aspiration hazard.

#### **Components:**

#### **Ethanediol:**

Based on available data, the classification criteria are not met.

#### **Further information**

#### **Product:**

Remarks: Slightly irritating to respiratory system.

### **Components:**

#### **Ethanediol:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

#### **SECTION 12. ECOLOGICAL INFORMATION**

Basis for assessment : Ecotoxicological data have not been determined specifically

for this product.

Information given is based on a knowledge of the components

and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual com-

ponent(s).

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

**Ecotoxicity** 

Product:

Toxicity to fish (Acute toxici-

ty)

Remarks: LC/EC/IC50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to daphnia and other aquatic invertebrates (Acute

toxicity)

Remarks: LC/EC/IC50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to algae (Acute tox-

icity)

Remarks: LC/EC/IC50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic tox-

icity)

Remarks: Data not available

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

Remarks: Data not available

Toxicity to microorganisms

(Acute toxicity)

Remarks: Data not available

Components:

**Ethanediol:** 

Toxicity to fish (Acute toxici-

ty)

LC50 (Pimephales promelas (fathead minnow)): 72,860 mg/l

Exposure time: 96 h

Method: Other guideline method. Remarks: Practically non toxic: LC/EC/IC50 > 100 mg/l

Toxicity to daphnia and other : aquatic invertebrates (Acute

toxicity)

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202 Remarks: Practically non toxic:

LC/EC/IC50 > 100 mg/l

Toxicity to algae (Acute tox-

icity)

EC50 (Pseudokirchneriella subcapitata (algae)): 6,500 -

13,000 mg/l

Exposure time: 96 h

Method: Other guideline method. Remarks: Practically non toxic: LC/EC/IC50 > 100 mg/l

LC/EC/1030 > 100 III

Toxicity to fish (Chronic tox-

icity)

NOEC (Pimephales promelas (fathead minnow)): 15,380 mg/l

Exposure time: 7 d

Method: Other guideline method. Remarks: NOEC/NOEL > 100 mg/l

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## AeroShell Compound 07

Revision Date: SDS Number: Print Date: 12/04/2021 Version

12/02/2021 800001000357 Date of last issue: 04/26/2021 2.0

Toxicity to daphnia and other : aquatic invertebrates (Chron-

Exposure time: 7 d

ic toxicity)

Method: Other guideline method. Remarks: NOEC/NOEL > 100 mg/l

NOEC (Chironomus sp. (midge)): 8,590 mg/l

Toxicity to microorganisms

(Acute toxicity)

EC20 (Activated sludge, domestic waste): > 1,995 mg/l

Exposure time: 0.5 h

Method: Other guideline method. Remarks: Practically non toxic: LC/EC/IC50 > 100 mg/l

**Ethanol:** 

Toxicity to fish (Acute toxici-

ty)

LC50 (Pimephales promelas (fathead minnow)): 14,200 mg/l

Exposure time: 96 h

Method: Test(s) equivalent or similar to OECD Guideline 203 Remarks: Based on available data, the classification criteria

are not met.

Toxicity to daphnia and other aquatic invertebrates (Acute

toxicity)

LC50 (Ceriodaphnia dubia (water flea)): 5,012 mg/l

Exposure time: 48 h

Method: Test(s) equivalent or similar to OECD Guideline 202 Remarks: Based on available data, the classification criteria

are not met.

Toxicity to algae (Acute tox-

icity)

EC50 (Chlorella vulgaris (Fresh water algae)): 675 mg/l

Exposure time: 72 h

Method: Test(s) equivalent or similar to OECD Test Guideline

201

Remarks: Based on available data, the classification criteria

are not met.

Toxicity to fish (Chronic tox-

icity)

NOEC: 245 mg/l

Exposure time: 30 d

Method: Based on quantitative structure-activity relationship

(QSAR) modelling

Remarks: NOEC/NOEL > 100 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC (Ceriodaphnia dubia (Water flea)): 2 mg/l

Exposure time: 10 d

Method: Test(s) equivalent or similar to OECD Guideline 211 Remarks: NOEC/NOEL > 1.0 - <=10 mg/l (based on test data)

Toxicity to microorganisms

(Acute toxicity)

Toxic threshold (Pseudomonas putida): 6,500 mg/l

Exposure time: 16 h

Persistence and degradability

**Product:** 

Biodegradability Remarks: Readily biodegradable.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

#### **Components:**

**Ethanediol:** 

Biodegradability : Biodegradation: 90 - 100 %

Exposure time: 10 d

Method: OECD Test Guideline 301A Remarks: Readily biodegradable. Not Persistent per IMO criteria.

International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distils at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or

any subsequent revision thereof."

**Ethanol:** 

Biodegradability : Biodegradation: 84 %

Exposure time: 20 d

Method: Test(s) equivalent or similar to OECD Guideline 301

В

Remarks: Readily biodegradable.

Oxidises rapidly by photo-chemical reactions in air.

#### **Bioaccumulative potential**

**Product:** 

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

**Components:** 

**Ethanediol:** 

Bioaccumulation : Remarks: Does not have the potential to bioaccumulate signif-

icantly.

**Ethanol:** 

Bioaccumulation : Remarks: Does not bioaccumulate significantly.

Partition coefficient: n-

octanol/water

log Pow: < 1

Mobility in soil

**Product:** 

Mobility : Remarks: Liquid under most environmental conditions.

If product enters soil, it will be highly mobile and may contam-

inate groundwater. Dissolves in water.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

#### Components:

**Ethanediol:** 

Mobility : Remarks: Disperses in water.

If product enters soil, one or more constituents will be highly

mobile and may contaminate groundwater.

**Ethanol:** 

Mobility : Remarks: Dissolves in water.

If product enters soil, it will be highly mobile and may contam-

inate groundwater.

#### Other adverse effects

**Product:** 

Additional ecological infor-

mation

Does not have ozone depletion potential, photochemical

ozone creation potential or global warming potential.

#### **Components:**

**Ethanediol:** 

Results of PBT and vPvB

assessment

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

Additional ecological infor-

mation

Does not have ozone depletion potential.

**Ethanol:** 

Results of PBT and vPvB

assessment

The substance does not fulfill all screening criteria for persistence, bioaccumulation and toxicity and hence is not consid-

ered to be PBT or vPvB.

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

#### **Disposal methods**

Waste from residues : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth-

ods in compliance with applicable regulations.

Do not dispose into the environment, in drains or in water

courses

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

collector or contractor should be established beforehand. Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater

contamination.

MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides tech-

nical aspects at controlling pollutions from ships.

Contaminated packaging : Drain container thoroughly.

After draining, vent in a safe place away from sparks and fire.

Do not puncture, cut, or weld uncleaned drums.

Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand.

Local legislation

Remarks : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

#### **SECTION 14. TRANSPORT INFORMATION**

## **National Regulations**

**US Department of Transportation Classification (49 CFR Parts 171-180)** 

UN/ID/NA number : UN 1170

Proper shipping name : Ethanol solutions

Class : 3
Packing group : III
Labels : 3

Reportable quantity Ethylene glycol

(5,000 lb)

ERG Code : 127 Marine pollutant : no

#### **International Regulations**

IATA-DGR

UN/ID No. : UN 1170

Proper shipping name : ETHANOL SOLUTION

Class : 3
Packing group : III
Labels : 3

**IMDG-Code** 

UN number : UN 1170

Proper shipping name : ETHANOL SOLUTION

Class : 3
Packing group : III
Labels : 3
Marine pollutant : no

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## AeroShell Compound 07

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

### Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

**Additional Information**: MARPOL Annex 1 rules apply for bulk shipments by sea.

#### **SECTION 15. REGULATORY INFORMATION**

## **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Component RQ   Calculated product RQ	
		(lbs)	(lbs)	
Ethanediol	107-21-1	5000	*	
Methyl ethyl ketone	78-93-3	5000	*	

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

Calculated RQ exceeds reasonably attainable upper limit., The components with RQs are given for information.

### **SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Specific target organ toxicity (single or repeated exposure)

SARA 313 : The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Ethanediol 107-21-1 >= 70 - < 90 %

### Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

#### **US State Regulations**

### Pennsylvania Right To Know

Ethanediol	107-21-1
Ethanol	64-17-5
Methyl ethyl ketone	78-93-3
Propan-2-ol	67-63-0

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## AeroShell Compound 07

 Version
 Revision Date:
 SDS Number:
 Print Date: 12/04/2021

 2.0
 12/02/2021
 800001000357
 Date of last issue: 04/26/2021

### California Prop. 65

WARNING: This product can expose you to chemicals including Ethanol, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

#### California List of Hazardous Substances

Ethanediol 107-21-1 Ethanol 64-17-5

#### Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

#### The components of this product are reported in the following inventories:

REACH : All components listed or polymer exempt.

TSCA : All components listed.

DSL : All components listed.

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

NFPA Rating (Health, Fire, Reac- 2, 2, 0

tivity)

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit : 8-hour time weighted average

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this docu-

ment can be looked up in reference literature (e.g. scientific

dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## AeroShell Compound 07

Revision Date: SDS Number: Print Date: 12/04/2021 Version

12/02/2021 800001000357 Date of last issue: 04/26/2021 2.0

> DIN = Deutsches Institut für Normung DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicolo-

gy Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the

determination of polycyclic aromatics DMSO-extractables KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No Ob-

served Effect Level

OE HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of Dan-

gerous Goods by Rail

SKIN\_DES = Skin Designation

STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

A vertical bar (I) in the left margin indicates an amendment from the previous version.

There has been a significant change in transport classification in section 14.

Due to a change in detail in Section 15, this document has been released as a significant change.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

## **AeroShell Compound 07**

Version Revision Date: SDS Number: Print Date: 12/04/2021

2.0 12/02/2021 800001000357 Date of last issue: 04/26/2021

Revision Date : 12/02/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN