

Revision date: 2023/01/11 Page: 1/13 Version: 5.0 (30690988/SDS GEN US/EN)

1. Identification

Product identifier used on the label

Ardrox AV 40

Recommended use of the chemical and restriction on use

Recommended use*: Treatment of metal surfaces.

Recommended use*: corrosion inhibitor; Restricted to professional users.

Unsuitable for use: Uses other than recommended

Details of the supplier of the safety data sheet

Company:

Chemetall U.S., Inc. 675 Central Avenue New Providence, NJ 07974 – USA +1 800 526-4473 sds.na-chemetall@basf.com

Emergency telephone number

24 Hour Emergency Response Information CHEMTREC: 800-424-9300, +1-703-527-3887

Other means of identification

Chemical family: organic compounds, polymers

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Sens. 1 Skin sensitization Carc. 1 Carcinogenicity

STOT SE 3 (Vapours may cause Specific target organ toxicity — single exposure

^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Revision date: 2023/01/11 Page: 2/13 Version: 5.0 (30690988/SDS_GEN_US/EN)

drowsiness and

dizziness.)

STOT RE 1 Specific target organ toxicity — repeated

exposure

Aquatic Chronic 3 Hazardous to the aquatic environment - chronic

Flam. Lig. 3 Flammable liquids

Aquatic Acute 3 Hazardous to the aquatic environment - acute

Label elements

Pictogram:







Signal Word:

Danger

Hazard Statement:

H226 Flammable liquid and vapour.
 H317 May cause an allergic skin reaction.
 H336 May cause drowsiness or dizziness.

H350 May cause cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P271 Use only outdoors or in a well-ventilated area.

P201 Obtain special instructions before use. P273 Avoid release to the environment.

P272 Contaminated work clothing should not be allowed out of the workplace.

P270 Do not eat, drink or smoke when using this product.

P202 Do not handle until all safety precautions have been read and

understood.

P240 Ground and bond container and receiving equipment.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P233 Keep container tightly closed.

P243 Take action to prevent static discharges.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P260 Do not breathe mist or vapour or spray.

P264 Wash contaminated body parts thoroughly after handling.

P242 Use only non-sparking tools.

Precautionary Statements (Response):

Revision date: 2023/01/11 Page: 3/13 Version: 5.0 (30690988/SDS GEN US/EN)

P312	Call a POISON CENTER or	physician if	you feel unwell.

P314 Get medical advice/attention if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical attention.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P303 + P361 + P353 IF ON SKIN (or hair): Remove or Take off immediately all contaminated

clothing. Rinse skin with water or shower.

P333 + P313 If skin irritation or rash occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P370 + P378 In case of fire: Use water spray for extinction.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2%aro

CAS Number: 1174921-73-3 Content (W/W): >= 20.0 - < 25.0% Synonym: No data available.

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromat

CAS Number: 64742-82-1 Content (W/W): >= 15.0 - < 20.0%

Synonym: R10-65-48/20-66-67-51/53; H226-304-336-372-411-EUH066

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

CAS Number: 64742-48-9

Content (W/W): >= 10.0 - < 15.0%

Synonym: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2%

aromatics

Sulfonic acids, petroleum, calcium salts

CAS Number: 61789-86-4 Content (W/W): >= 7.0 - < 10.0%

Synonym: Total Base Number (TBN) <300; H317 1B, >=10 - 100%

Calcium bis(dinonylnaphthalenesulphonate)

CAS Number: 57855-77-3 Content (W/W): >= 1.0 - < 3.0% Synonym: No data available.

Revision date: 2023/01/11 Page: 4/13 Version: 5.0 (30690988/SDS GEN US/EN)

Distillates (petroleum), hydro- treated light; Kerosine

CAS Number: 64742-47-8 Content (W/W): >= 1.0 - < 3.0% Synonym: No data available.

butanone oxime

CAS Number: 96-29-7

Content (W/W): >= 0.1 - < 0.2%

Synonym: 2-Butanone, oxime; Methyl ethyl ketoxime

4. First-Aid Measures

Description of first aid measures

General advice:

Keep warm, calm and covered up. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

If inhaled:

Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

If on skin:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

If in eves

If symptoms persist, seek medical advice. Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution.

If swallowed:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: butanone oxime

Symptoms: Overexposure may cause:, corneal injury, skin corrosion, coughing, respiratory disorders, dyspnea, nausea, vomiting, diarrhea

Information on: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Symptoms: Overexposure may cause:, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Ingestion may provoke the following symptoms:, asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse, death

Revision date: 2023/01/11 Page: 5/13 Version: 5.0 (30690988/SDS GEN US/EN)

Information on: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromat

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache,

vomiting, dizziness, diarrhea, abdominal cramps

Information on: Calcium bis(dinonvlnaphthalenesulphonate)

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache,

vomiting, dizziness, diarrhea, abdominal cramps

Information on: Distillates (petroleum), hydro- treated light; Kerosine

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache,

vomiting, dizziness, diarrhea, abdominal cramps

Indication of any immediate medical attention and special treatment needed

Note to physician

Antidote: No known specific antidote.

Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Advice for fire-fighters

Protective equipment for fire-fighting:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

Environmental precautions

Revision date: 2023/01/11 Page: 6/13 Version: 5.0 (30690988/SDS_GEN_US/EN)

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for diposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephtalate (PET), Polypropylene (PP), Stainless steel 1.4301 (V2), Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container dry. Keep away from heat. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions. Store protected against freezing.

Storage stability:

Storage temperature: 5 - 35 °C

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Respiratory protection required if exposure limit (if available) may be exceeded

Revision date: 2023/01/11 Page: 7/13 Version: 5.0 (30690988/SDS GEN US/EN)

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1), nitrile rubber (NBR) - 0.4 mm coating thickness, The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties)., The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

General safety and hygiene measures:

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

Form: liquid

Odour: No data available.

Odour threshold: No applicable information available.

Colour: light brown

pH value: substance/mixture is non-soluble (in

water)

Melting point: not determined Freezing point: not determined Boiling range: not determined

onset of boiling: 145 °C (calculated)

Sublimation point: No applicable information available.

Flash point: 34 °C (ISO 3679)

Flammability: Flammable liquid and vapour.

Lower explosion limit: not determined

Upper explosion limit: No applicable information available.

Vapour pressure: (20 °C)

not determined 0.890 g/cm3

Density: 0.890 g/cm3 (20 °C)

Relative density: No applicable information available. No applicable information available.

Vapour density: Heavier than air.

Partitioning coefficient n- not applicable for mixtures

octanol/water (log Pow):

Thermal decomposition: No decomposition if stored and handled as

prescribed/indicated.

Viscosity, dynamic: No applicable information available.

Viscosity, kinematic: 32.0 mm2/s

(20°C)

Solubility in water: insoluble Miscibility with water: immiscible

Solubility (quantitative): No applicable information available.

Revision date: 2023/01/11 Page: 8/13 Version: 5.0 (30690988/SDS GEN US/EN)

Solubility (qualitative): No applicable information available.

Molar mass: No applicable information available.

Evaporation rate: No applicable information available.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties: not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid heat. Avoid direct sunlight. Avoid freezing.

Incompatible materials

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous decomposition products

Decomposition products:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

Oral

Type of value: ATE Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Revision date: 2023/01/11 Page: 9/13 Version: 5.0 (30690988/SDS GEN US/EN)

Inhalation

Type of value: ATE Value: > 20 mg/l

The product has not been tested. The statement has been derived from the properties of the

individual components.

Dermal

Type of value: ATE Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the

individual components.

Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Based on available data, the classification criteria are not met.

Information on: butanone oxime

Assessment of irritating effects: May cause severe damage to the eyes. Skin contact causes

irritation.

Information on: Calcium bis(dinonylnaphthalenesulphonate)

Assessment of irritating effects: Not irritating to the skin. Eye contact causes irritation.

Information on: Distillates (petroleum), hydro-treated light; Kerosine

Assessment of irritating effects: Skin contact causes irritation. Not irritating to the eyes. The product

has not been tested. The statement has been derived from substances/products of a similar structure or composition.

our dottar of or corription.

<u>Sensitization</u>

Assessment of sensitization: Sensitization after skin contact possible.

Information on: butanone oxime Assessment of sensitization:

Sensitization after skin contact possible.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure to small quantities may affect certain organs.

Information on: butanone oxime

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs.

Information on: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromat

Revision date: 2023/01/11 Page: 10/13 Version: 5.0 (30690988/SDS_GEN_US/EN)

Assessment of repeated dose toxicity: Effects on the kidney of male rats were detected after repeated exposure. These effects are specific for the male rat and are known to be of no relevance to humans. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

EU-classification Repeated exposure to small quantities may affect certain organs. Damages the central nerve system.

Information on: Distillates (petroleum), hydro- treated light; Kerosine

Assessment of repeated dose toxicity: Dermatitis The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: May cause cancer.

Information on: butanone oxime

Assessment of carcinogenicity: Indication of possible carcinogenic effect in animal tests.

Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Harmful to aquatic life. Harmful to aquatic life with long lasting effects. There are no test results available for this product. Do not allow to enter drains or waterways.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

No data available concerning biodegradation and elimination.

Bioaccumulative potential

Bioaccumulation potential

No data available.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Revision date: 2023/01/11 Page: 11/13 Version: 5.0 (30690988/SDS_GEN_US/EN)

13. Disposal considerations

Waste disposal of substance:

Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Container disposal:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Land transport

USDOT

Hazard class: 3 Packing group: III

ID number: UN 1139

Hazard label: 3

Proper shipping name: COATING SOLUTION

Sea transport

IMDG

Hazard class: 3 Packing group: III

ID number: UN 1139

Hazard label: 3
Marine pollutant: NO

Proper shipping name: COATING SOLUTION

Air transport

IATA/ICAO

Hazard class: 3 Packing group: III

ID number: UN 1139

Hazard label: 3

Proper shipping name: COATING SOLUTION

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

CERCLA RQ
100 LBSCAS Number
64742-47-8;Chemical name
Distillates (petrole)

100 LBS 64742-47-8; Distillates (petroleum), hydro- treated light; Kerosine;

64742-48-9; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics,

Revision date: 2023/01/11 Page: 12/13 Version: 5.0 (30690988/SDS_GEN_US/EN)

64742-82-1 < 2% aromatics; Hydrocarbons, C9-C12, n-alkanes,

isoalkanes, cyclics, aromat

State regulations

State RTK	CAS Number	Chemical name
NJ	64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics,
	64742-82-1	< 2% aromatics
	64742-47-8	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromat
		Distillates (petroleum), hydro- treated light; Kerosine
PA	64742-48-9	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics,
	64742-82-1	< 2% aromatics
	64742-47-8	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromat
		Distillates (petroleum), hydro- treated light; Kerosine

NFPA Hazard codes:

Health: 2 Fire: 3 Reactivity: 1 Special:

HMIS III rating

Health: 2^m Flammability: 3 Physical hazard:1

16. Other Information

SDS Prepared by:

Chemetall (now part of BASF Group) NA Product Regulations

SDS Prepared on: 2023/01/11

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.

Revision date: 2023/01/11 Page: 13/13
Version: 5.0 (30690988/SDS_GEN_US/EN)

Restricted to professional users.

END OF DATA SHEET