

Safety Data Sheet

Ardrox® AV8

Revision date: 2023/01/05 Page: 1/11

Version: 5.0 (30690975/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

Ardrox® AV8

Recommended use of the chemical and restriction on use

Recommended use*: corrosion inhibitor

Unsuitable for use: Uses other than recommended

Details of the supplier of the safety data sheet

Company:
Chemetall U.S., Inc.
675 Central Avenue
New Providence, NJ 07974 – USA
+1 800 526-4473
sds.na-chemetall@basf.com

Emergency telephone number

24 Hour Emergency Response Information CHEMTREC: 800-424-9300, +1-703-527-3887

Other means of identification

Chemical family: organic compounds

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Asp. Tox. 1 Aspiration hazard

STOT SE 3 (Vapours may cause Specific target organ toxicity — single exposure

drowsiness and

dizziness.)

Flam. Liq. 3 Flammable liquids

^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Safety Data Sheet

Ardrox® AV8

Revision date: 2023/01/05 Page: 2/11
Version: 5.0 (30690975/SDS GEN US/EN)

Skin Corr./Irrit. 2 Skin corrosion/irritation

Label elements

Pictogram:





Signal Word: Danger

Hazard Statement:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

Precautionary Statements (Prevention):

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P271 Use only outdoors or in a well-ventilated area.

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P240 Ground and bond container and receiving equipment.

P233 Keep container tightly closed.

P243 Take action to prevent static discharges.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P242 Use only non-sparking tools.

P264 Wash contaminated body parts thoroughly after handling.

P261 Avoid breathing mist or vapour or spray.

Precautionary Statements (Response):

P312 Call a POISON CENTER or physician if you feel unwell.

P331 Do NOT induce vomiting.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P303 + P361 + P353 IF ON SKIN (or hair): Remove or Take off immediately all contaminated

clothing. Rinse skin with water or shower.

P332 + P313 If skin irritation occurs: Get medical attention.

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or physician.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P370 + P378 In case of fire: Use water spray for extinction.
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

Precautionary Statements (Storage):

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Revision date: 2023/01/05 Page: 3/11

Version: 5.0 (30690975/SDS_GEN_US/EN)

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Labeling of special preparations (GHS):

Repeated exposure may cause skin dryness or cracking.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

CAS Number: 64742-48-9

Content (W/W): >= 50.0 - < 75.0%

Synonym: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2%

aromatics

Calcium bis(dinonylnaphthalenesulphonate)

CAS Number: 57855-77-3 Content (W/W): >= 3.0 - < 5.0% Synonym: No data available.

barium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate)

CAS Number: 25619-56-1 Content (W/W): >= 3.0 - < 5.0% Synonym: No data available.

Distillates (petroleum), hydrotreated light

CAS Number: 64742-47-8
Content (W/W): >= 1.0 - < 3.0%
Synonym: No data available.

4. First-Aid Measures

Description of first aid measures

General advice:

Keep warm, calm and covered up. Never give anything by mouth to an unconscious person. In case of intoxication, call a poison control center or physician for treatment advice, taking the packaging or the label of the product. Symptoms of poisoning may occur even after several hours, continue medical observation for at least 48 hours after the accident.

If inhaled:

Immediate medical attention required. Remove the affected individual into fresh air and keep the person calm. If breathing is irregular or stopped, administer artificial respiration.

If on skin:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

Revision date: 2023/01/05 Page: 4/11
Version: 5.0 (30690975/SDS GEN US/EN)

If in eyes:

If symptoms persist, seek medical advice. Contact lenses should be removed. Hold eyelids open and flush with copious amounts of clean, fresh water or a special eyewash solution.

If swallowed:

Summon medical aid without delay. Do not induce vomiting due to aspiration hazard. Rinse mouth immediately with water. Keep at rest.

Most important symptoms and effects, both acute and delayed

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Symptoms: Overexposure may cause:, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Ingestion may provoke the following symptoms:, asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse, death

Information on: Calcium bis(dinonylnaphthalenesulphonate)

Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Information on: barium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) Symptoms: Overexposure may cause:, Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Information on: Distillates (petroleum), hydrotreated light

Symptoms: Overexposure may cause:, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Ingestion may provoke the following symptoms:, asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse, death

Hazards: If swallowed, in the event of vomiting, risk of product entering the lungs. When inhaled (e.g. during vomiting) risk of pulmonary oedema and/or pneumonia.

Indication of any immediate medical attention and special treatment needed

Note to physician

Antidote: No known specific antidote.

Treatment: Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons: water jet

Special hazards arising from the substance or mixture

Revision date: 2023/01/05 Page: 5/11 Version: 5.0 (30690975/SDS GEN US/EN)

Hazards during fire-fighting:

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Advice for fire-fighters

Protective equipment for fire-fighting:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid breathing vapours. For non-emergency personnel: Use personal protective clothing. Ensure adequate ventilation. Keep away from sources of ignition. For emergency responders: Advice on product handling can be found in sections 7 and 8 of this safety data sheet. Information regarding personal protective measures, see section 8.

Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for diposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eye-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Conditions for safe storage, including any incompatibilities

Keep away from oxidising agents, from strongly alkaline and strongly acid materials.

Revision date: 2023/01/05 Page: 6/11 Version: 5.0 (30690975/SDS GEN US/EN)

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephtalate (PET), Polypropylene (PP), Stainless steel 1.4301 (V2), Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: Keep container dry. Keep in a cool, well-ventilated place. Avoid direct sunlight. Close containers carefully once opened and store them upright in order to prevent any leakage. No smoking. No admission for unauthorised personnel. Always keep in containers of same material as the original one. Observe label precautions.

Storage stability:

Storage temperature: -20 - 40 °C

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Personal protective equipment

Respiratory protection:

Respiratory protection required if exposure limit (if available) may be exceeded

Hand protection:

Chemical resistant protective gloves (EN ISO 374-1), nitrile rubber (NBR) - 0.4 mm coating thickness, The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties)., The gloves should be replaced immediately in case of damage or signs of wear. It is recommended to use preventative skin protection (skin cream).

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

General safety and hygiene measures:

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Ensure adequate ventilation. This can be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations at the workplace below the occupational exposure limits, appropriate certified respirators must be worn. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

Form: liquid

Odour: of hydrocarbons

Odour threshold: No applicable information available.

Colour: light brown

pH value: substance/mixture is non-

polar/aprotic

Melting point: not determined Freezing point: not determined

Revision date: 2023/01/05 Page: 7/11

Version: 5.0 (30690975/SDS_GEN_US/EN)

onset of boiling: 155 °C (calculated)

Boiling range: not determined

Sublimation point: No applicable information available.

Flash point: 46 °C (ISO 2719)

Flammability: Flammable liquid and vapour.

Lower explosion limit: not determined

Upper explosion limit: No applicable information available.

Vapour pressure: (20 °C)

not determined

Density: 0.890 g/cm3

(20°C)

Relative density: No applicable information available.

Vapour density: Heavier than air.

Partitioning coefficient n- not applicable for mixtures

octanol/water (log Pow):

Thermal decomposition: No decomposition if stored and handled as

prescribed/indicated.

Viscosity, dynamic: No applicable information available.

Viscosity, kinematic: 6.0 mm2/s

(20°C)

% volatiles:

Solubility in water: insoluble Miscibility with water: immiscible

Solubility (quantitative):
Solubility (qualitative):
Molar mass:
Evaporation rate:

No applicable information available.
No applicable information available.
No applicable information available.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Vapours may form ignitable mixture with air.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid direct sunlight.

Incompatible materials

Keep away from highly acidic or alkaline substances as well as oxidants in order to prevent exothermal reactions.

Hazardous decomposition products

Decomposition products:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

Revision date: 2023/01/05 Page: 8/11
Version: 5.0 (30690975/SDS_GEN_US/EN)

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Based on available data, the classification criteria are not met.

Oral

Type of value: ATE Value: 10,552 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Inhalation

Type of value: ATE Value: > 20 mg/l

The product has not been tested. The statement has been derived from the properties of the individual components.

Dermal

Type of value: ATE Value: > 2,000 mg/kg

The product has not been tested. The statement has been derived from the properties of the individual components.

Assessment other acute effects

Assessment of STOT single:

Possible narcotic effects (drowsiness or dizziness).

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation.

Information on: Calcium bis(dinonylnaphthalenesulphonate)

Assessment of irritating effects: Not irritating to the skin. Eye contact causes irritation.

Sensitization

Assessment of sensitization: Based on available data, the classification criteria are not met.

Aspiration Hazard

May also damage the lung at swallowing (aspiration hazard).

Chronic Toxicity/Effects

Revision date: 2023/01/05 Page: 9/11 Version: 5.0 (30690975/SDS GEN US/EN)

Repeated dose toxicity

Assessment of repeated dose toxicity: Based on available data, the classification criteria are not met.

Genetic toxicity

Assessment of mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity: Based on available data, the classification criteria are not met.

Teratogenicity

Assessment of teratogenicity: Based on available data, the classification criteria are not met.

Other Information

Has a degreasing effect on skin.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

There are no test results available for this product. Do not allow to enter drains or waterways. Based on available data, the classification criteria are not met.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

No data available concerning biodegradation and elimination.

Bioaccumulative potential

Bioaccumulation potential

No data available.

Mobility in soil

Assessment transport between environmental compartments

No data available.

13. Disposal considerations

Waste disposal of substance:

Do not discharge into drains/surface waters/groundwater. Observe national and local legal requirements.

Container disposal:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

Revision date: 2023/01/05 Page: 10/11 Version: 5.0 (30690975/SDS_GEN_US/EN)

14. Transport Information

Land transport

USDOT

Hazard class: 3 Packing group: III

ID number: UN 1139

Hazard label: 3

Proper shipping name: COATING SOLUTION

Sea transport

IMDG

Hazard class: 3 Packing group: III

ID number: UN 1139

Hazard label: 3
Marine pollutant: NO

Proper shipping name: COATING SOLUTION

Air transport

IATA/ICAO

Hazard class: 3 Packing group: III

ID number: UN 1139

Hazard label: 3

Proper shipping name: COATING SOLUTION

15. Regulatory Information

VOC content:

490 g/l

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

CAS Number Chemical name

25619-56-1 barium bis(di C8-C10, branched, C9 rich,

alkylnaphthalenesulphonate)

CERCLA RQ CAS Number 64742-48-9; 64742-47-8 Chemical name Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; Distillates (petroleum), hydrotreated light

1000 LBS 25619-56-1 barium bis(di C8-C10, branched, C9 rich,

alkylnaphthalenesulphonate)

State regulations

Revision date: 2023/01/05 Page: 11/11
Version: 5.0 (30690975/SDS_GEN_US/EN)

| State RTK | CAS Number | Chemical name |
|-----------|--|---|
| PA | 8006-54-0 | lanolin |
| | 64742-48-9 25619-56-1 64742-47-8 | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics barium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesulphonate) |

Distillates (petroleum), hydrotreated light

NJ 64742-48-9 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics,

25619-56-1 < 2% aromatics

barium bis(di C8-C10, branched, C9 rich,

alkylnaphthalenesulphonate)

NFPA Hazard codes:

Health: 2 Fire: 2 Reactivity: 1 Special:

HMIS III rating

Health: 2 Flammability: 2 Physical hazard:1

16. Other Information

SDS Prepared by:

Chemetall (now part of BASF Group) NA Product Regulations SDS Prepared on: 2023/01/05

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Ardrox® AV8 IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE. IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. Restricted to professional users.

END OF DATA SHEET