

LIQUID 4145-30

Revision Number 1

# SAFETY DATA SHEET

In accordance with OSHA 29 CFR 1910.1200

Revision date 16-Apr-2021 Supersedes Date: Not applicable

1. Identification		
1.1. Product identifier		
Product Name	LIQUID 4145-30	
Other means of identification Other information	Not applicable	
1.2. Relevant identified uses of the	substance or mixture and uses advised against	
Recommended use Restrictions on use	Adhesive No information available	
1.3. Details of the supplier of the sa	afety data sheet	
Responsible Party Bostik Inc. 11320 W. Watertown Plank Road Wauwatosa, Wisconsin 53226 USA Phone: +1 (800) 843-0844 (Domesti Phone: +1 (414) 774-2250 (Internati Fax: +1 (414) 774-8075		
E-mail	msds@bostik.com	
1.4. Emergency telephone number		
Emergency Telephone	Chemtrec (Transport/Environmental): 1-800-424- 1-703-527-3887 (Outside U.S.) Rocky Mountain Poison Center: 1-866-767-5089	
2. Hazard(s) identification		
2.1. Classification of the substance	e or mixture	
Serious eye damage/eye irritation		Category 2A
Specific target organ toxicity (single e	xposure)	Category 3
Flammable liquids		Category 2

Hazards not otherwise classified (HNOC) Not applicable

## 2.2. Label elements

#### EMERGENCY OVERVIEW

### Danger

Hazard statements Causes serious eye irritation May cause drowsiness or dizziness Highly flammable liquid and vapor

LIQUID 4145-30 Revision Number 1



#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating/ lighting/ equipment Use only non-sparking tools Take precautionary measures against static discharge Wear protective gloves/eye protection/face protection Keep cool

#### **Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower IF INHALED: Remove person to fresh air and keep comfortable for breathing Call a POISON CENTER or doctor if you feel unwell

In case of fire: Use CO2, dry chemical, or foam to extinguish

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/ container to an approved waste disposal plant

15 % of the mixture consists of ingredient(s) of unknown toxicity

#### 2.3. Other Information

In use, may form flammable/explosive vapor-air mixture.

### 3. Composition/information on ingredients

#### 3.1. Substances

Not applicable.

#### Mixture

Chemical name	CAS No	Weight-%
Acetone	67-64-1	30 - 60
Methyl ethyl ketone	78-93-3	10 - 30

\*The exact percentage (concentration) of composition has been withheld as a trade secret

4. First-aid measures	
4.1. Description of first aid measure	es_
General advice	Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician or poison control center immediately.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.
4.2. Most important symptoms and	effects, both acute and delayed
Symptoms	May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
4.3. Indication of any immediate me	edical attention and special treatment needed
Note to physicians	Treat symptomatically.
5. Fire-fighting measures	
5.1. Extinguishing media	
Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam. Move containers
Large Fire	from fire area if you can do it without risk. CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
5.2. Special hazards arising from the	e substance or mixture
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	Carbon oxides.
Explosion data Sensitivity to mechanical impac	<b>et</b> None.

Sensitivity to mechanical impact None.

#### LIQUID 4145-30 Revision Number 1

Sensitivity to static discharge Yes.

#### 5.3. Advice for firefighters

Special protective equipment for	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH
fire-fighters	(approved or equivalent) and full protective gear.

#### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep people away from and upwind of spill/leak. Do not touch or walk through spilled material. Ensure adequate ventilation. Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing.	
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.	
6.2. Environmental precautions		
Environmental precautions	Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point. See Section 12 for additional Ecological Information.	
6.3. Methods and material for containment and cleaning up		
Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).	
Methods for cleaning up	Use personal protective equipment as required. Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly.	
Reference to other sections	See section 8 for more information. See section 13 for more information.	

### 7. Handling and storage

#### 7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Do not breathe vapor or mist. Use with local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

LIQUID 4145-30 Revision Number 1	Revision date 16-Apr-2021 Supersedes Date: 16-Apr-2021
Storage Conditions	Keep/store only in original container. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.
7.3 References to other sections	
Reference to other sections	See Section 12: ECOLOGICAL INFORMATION Section 7: HANDLING AND STORAGE Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8. Exposure controls/personal protection

#### 8.1. Control parameters

#### **Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm
67-64-1	TWA: 250 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 250 ppm
		(vacated) TWA: 750 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 1800 mg/m <sup>3</sup>	_
		(vacated) STEL: 2400 mg/m <sup>3</sup>	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for all	
		other sectors.	
		(vacated) STEL: 1000 ppm	
Methyl ethyl ketone	STEL: 300 ppm	TWA: 200 ppm	IDLH: 3000 ppm
78-93-3	TWA: 200 ppm	TWA: 590 mg/m <sup>3</sup>	TWA: 200 ppm
		(vacated) TWA: 200 ppm	TWA: 590 mg/m <sup>3</sup>
		(vacated) TWA: 590 mg/m <sup>3</sup>	STEL: 300 ppm
		(vacated) STEL: 300 ppm	STEL: 885 mg/m <sup>3</sup>
		(vacated) STEL: 885 mg/m <sup>3</sup>	

Chemical name	Argentina	Brazil	Chile	Colombia
Acetone	TWA: 500 ppm	TWA: 780 ppm	TWA: 438 ppm	STEL: 500ppm
67-64-1	STEL: 750 ppm	TWA: 1870 mg/m <sup>3</sup>	TWA: 1040 mg/m <sup>3</sup>	TWA: 250ppm
Methyl ethyl ketone	TWA: 200 ppm	TWA: 155 ppm	TWA: 175 ppm	STEL: 300ppm
78-93-3	STEL: 300 ppm	TWA: 460 mg/m <sup>3</sup>	TWA: 516 mg/m <sup>3</sup>	TWA: 200ppm

Chemical name	Costa Rica	Peru	Uruguay	Venezuela
Acetone	TWA: 250ppm	STEL: 750ppm	500 ppm STEL	STEL: 750 ppm
67-64-1	STEL: 500ppm	STEL: 1781mg/m <sup>3</sup>	250 ppm TWA	TWA: 500 ppm
		TWA: 500ppm		
		TWA: 1187mg/m <sup>3</sup>		
Methyl ethyl ketone	TWA: 200ppm	STEL: 300ppm	300 ppm STEL	STEL: 300 ppm
78-93-3	STEL: 300ppm	STEL: 885mg/m <sup>3</sup>	200 ppm TWA	TWA: 200 ppm
		TWA: 200ppm		
		TWA: 590mg/m <sup>3</sup>		

#### LIQUID 4145-30 Revision Number 1

#### 8.2. Exposure controls

Appropriate engineering controls	
Engineering controls	Showers Eyewash stations Ventilation systems.
Individual protection measures, su	ch as personal protective equipment
Eye/face protection	Tight sealing safety goggles. Avoid contact with eyes. If splashes are likely to occur:. Face protection shield.
Hand protection	Wear suitable gloves. Impervious gloves.
Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General hygiene considerations	Wear suitable gloves and eye/face protection. Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Keep away from food, drink and animal feeding stuffs. Do not breathe vapor or mist. Avoid contact with skin, eyes or clothing. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Take off contaminated clothing and wash it before reuse. Regular cleaning of equipment, work area and clothing is recommended.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state Appearance Color Odor Odor threshold	Liquid No information available Colorless to yellow Solvent No information available	
Property_	Values_	Remarks • Method
pH	No data available	Not applicable Insoluble in water
pH (as aqueous solution)	No data available	None known
Melting point / freezing point	No data available	None known
Initial boiling point and boiling	56 °C / 132.8 °F	
range		
Flash point	-23 °C / -9.4 °F	
Evaporation rate	No data available	None known
Flammability	Not applicable for liquids .	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	

#### LIQUID 4145-30 Revision Number 1

Revision date 16-Apr-2021 Supersedes Date: 16-Apr-2021

Vapor pressure	No data available	None known	
Relative vapor density	No data available	None known	
Relative density	No data available	None known	
-			
Water solubility	No data available	None known	
Solubility(ies)	No data available	None known	
Partition coefficient	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	No data available	None known	
9.2. Other information			
Explosive properties	No information available		
Oxidizing properties	No information available		
Solvent content (%)	No information available		
	30		
Solid content (%)			
Softening Point	No information available		
Molecular weight	No information available		
VOC Content (%)			
Density	.880 g/ml		
Bulk density	No information available		
10. Stability and reactivity			
10.1. Reactivity			
Reactivity	No information available.		
10.2. Chemical stability			
Chemical stability	Stable under normal conditions.		
10.3. Possibility of hazardous react	<u>ions</u>		

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks.

10.5. Incompatible materials

Incompatible materials

Incompatible with strong acids and bases.

10.6. Hazardous decomposition products

Hazardous decomposition products Carbon oxides

## 11. Toxicological information

11.1. Information on toxicological effects

**Product Information** 

Inhalation Specific test data for the substance or mixture is not available. May cause drowsiness or dizziness.

Specific test data for the substance or mixture is not available. Causes serious eye irritation.

LIQUID 4145-30 Revision Number 1	Revision date 16-Apr-2021 Supersedes Date: 16-Apr-2021		
	(based on components). May cause redness, itching, and pain.		
Skin contact	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.		
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.		
Symptoms related to the physical sector of the sector sect	sical, chemical and toxicological characteristics		
Symptoms	May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.		
<u>Acute toxicity</u> Numerical measures of toxici	ty		

The following values are calculated based on chapter 3.1 of the GHS document . ATEmix (oral) 7,530.70 mg/kg

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Acetone	=5800 mg/kg (Rattus)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
67-64-1 Methyl ethyl ketone	-2482 ma/kg (Bottup)	- 5000 mg/kg (Onvetelegue	-11700 ppm (Pottup) 4 h
78-93-3	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute	Rabbit	eye			irritant
Eye Irritation/Corrosion					

#### Respiratory or skin sensitization

Based on available data, the classification criteria are not met.

Acetone (67-64-1) Methyl ethyl ketone (78-93-3) Method Species Exposure route Results OECD Test No. 406: Skin Guinea pig Dermal No sensitization responses Sensitization were observed Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. STOT - single exposure May cause drowsiness or dizziness. **STOT - repeated exposure** Based on available data, the classification criteria are not met. Central nervous system, Eyes, Skin, Heart, Cardiovascular system, Respiratory system. **Target organ effects** Based on available data, the classification criteria are not met. Aspiration hazard US - EN Page 8/11

Other adverse effects	No information available.
Interactive effects	No information available.

## 12. Ecological information

#### 12.1. Toxicity

### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Acetone 67-64-1	-	LC50 96 h 4.74 - 6.33 mL/L (Oncorhynchus mykiss )	EC50 = 14500 mg/L 15 min	EC50 48 h 10294 - 17704 mg/L (Daphnia magna Static)
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna )

#### 12.2. Persistence and degradability

Persistence and degradability No information available.

### 12.3. Bioaccumulative potential

Bioaccumulation

There is no data for this product.

#### **Component Information**

Chemical name	Partition coefficient
Acetone 67-64-1	-0.24
Methyl ethyl ketone 78-93-3	0.3

#### 12.4. Mobility in soil

Mobility	No information available.
Other adverse effects	
Other adverse effects	No information available.

## 13. Disposal considerations

#### 13.1. Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of waste in accordance with environmental legislation. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Dispose of in accordance with federal, state and local regulations.
US - EN	Page 9/11

## 14. Transport information

Note:	The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments made in non-bulk packages (see regulatory definition) The information shown here, may not always agree with the bill of lading shipping description for the material
DOT UN/ID No Proper Shipping Name Transport hazard class(es) Packing Group DOT reportable quantity - Ibs Reportable Quantity (RQ) Special Provisions Marine Pollutant Description Emergency Response Guide Number	UN1133 Adhesives 3 II Acetone: RQ (lb)= 5000.00, Methyl ethyl ketone: RQ (lb)= 5000.00 (Acetone: RQ (kg)= 2270.00, Methyl ethyl ketone: RQ (kg)= 2270.00) 149, B52, IB2, T4, TP1, TP8 Np UN1133, Adhesives, 3, II 128
IATA UN number or ID number UN proper shipping name Transport hazard class(es) Packing group Special Provisions Description	UN1133 Adhesives 3 II A3 UN1133, Adhesives, 3, II
IMDG UN number or ID number UN proper shipping name Transport hazard class(es) Packing group EmS-No Marine pollutant Description	UN1133 Adhesives 3 II F-E, S-D NP UN1133, Adhesives, 3, II, (-23°C c.c.)

## 15. Regulatory information

#### International Inventories

TSCA	Listed
DSL	Listed

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL** - Canadian Domestic Substances List

Listed - The components of this product are either listed or exempt from listing on inventory.

Not Listed - One or more components of this product are not listed on inventory.

#### **US Federal Regulations**

#### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

## LIQUID 4145-30

Revision Number 1

#### SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

#### Europe

#### Restrictions of Use of Hazardous Substances (RoHS) Directive 2011/65/EU

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation. This document is based on the information given to us by our own suppliers at the date of this document.

#### SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

### 16. Other information

#### Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section a TWA Ceiling	B: EXPOSURE CONTROLS/PERSONAL F TWA (time-weighted average) Maximum limit value	PROTECTION STEL *	STEL (Short Term Exposure Limit) Skin designation
Prepared By	Product Safety & Reg	ulatory Affairs.	
Revision date	16-Apr-2021		
Revision note	No information availab	ole.	

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### **End of Safety Data Sheet**