

ROYCO® 808

ADVANCED SYNTHETIC TURBINE ENGINE OIL

ROYCO® 808 is a synthetic base lubricating oil for gas turbine engines requiring an oil with lower volatility and higher oxidative stability than is obtainable with conventional mineral based turbine oils. ROYCO 808 is formulated using the highest quality polyol ester base stocks compounded with additives to impart higher oxidation and corrosion resistance as well as enhanced antiwear protection. These benefits provide for exceptionally clean engine operation as well as extended drain intervals.

APPLICATIONS

ROYCO® 808 is intended for use in the lubrication of aircraft gas turbine and industrial turboprop engines - especially those operating in extreme cold or hot environs. **ROYCO® 808** is also recommended for use in engines, which require start-up after extended periods of "cold soak" such as aircraft, APU's and railroad industrial snow removal equipment. **ROYCO® 808** may also be used as a control fluid in stationary turbine applications.

ROYCO® 808 is not interchangeable with any other lubricating oils except those qualified under Mil-PRF-7808 or Mil-PRF-23699.

FEATURES AND BENEFITS

Features

- **Excellent Thermal and Oxidative Stability**
- **Low pour point**
- **Excellent corrosion and wear protection**
- **Chemically stable**

Benefits

- **Maintains engine efficiency;**
- **Extends engine life;**
- **Reduces carbon deposits and sludge formation.**
- **Eases start-up in low ambient temperatures.**
- **Extends component life;**
- **Reduces engine maintenance costs.**
- **Lowers oil consumption and losses due to evaporation**

APPROVALS & SPECIFICATIONS

ROYCO® 808 meets all requirements and is qualified under MIL-SPEC: MIL-PRF-7808L Grade 3, NATO Code O-148, UK Joint Service Designation OX-9.



PACKAGING

ROYCO® 808 is available in 55 gallon drums, 5 gallon pails, and twenty-four by 1-quart cans per carton.

PROPERTIES	TEST METHOD	ROYCO® 808
Flash Point, °C (°F)	ASTM D92	220 (428)
Acid Number, mg KOH/gm	ASTM D664	0.13
Trace Sediment, mg/200 ml	Spec.	1.0
Evaporation Loss, 205°C, 6.5 hrs., %	ASTM D972B	22
Kinematic Viscosity, cSt	ASTM D445	
@ 100°C		3.1
@ 40°C		12.05
@ -51°C		7,675
Viscosity Stability, -51°C, 6 hrs., % change	ASTM D2532	0.2
Lead Corrosion, 325°F, 1 hour, g/m ²	FTM 5321	-0.02
Silver-Bronze Corrosion, 232°C	FTM 5305	
Silver, g/m ²		0.00
Bronze, g/m ²		0.13
Accelerated Storage Stability, g/m ²	Spec	
48 hrs, 110°C		-0.05
168 hrs, 110°C		-1.4
Elastomer Compatibility	FTM 3604 FTM 3432	
NBR "H" Rubber, 70°C/168 hrs, %		32
"FA" Rubber, 175°C/72 hrs., % Swell		8
Tensile Strength Change, %		-18
Elongation Change, %		-21
Hardness Change, %		-8
Static Foam Test	FTM 3213	
Foam Volume, ml		27
Foam Collapse Time, seconds		10
Oxidation Corrosion Test, 200°C, 96 hrs.	ASTM D4636	
Metal Coupon Weight Change, mg/cm ²		
Aluminum		-0.05
Silver		-0.03
Bronze		0.05
Steel		0.01
M-50 (steel)		0.02
Magnesium		0.01
Titanium		0.01
Viscosity Change, 40°C, %		11.2
Acid Number Change, mg KOH/g		1.1
Insolubles, mg/100 ml		0.1
Density, 15°C, g/ml	Report	0.952



This information and our technical advice – whether verbal, in writing or by way of trials – is subject to change without notice and given in good faith but without warranty or guarantee, express or implied, and this also applies where proprietary rights of third parties are involved. Our advice does not release you from the obligation to verify the information currently provided - especially that contained in our safety data and technical information sheets - and to test our products as to their suitability for the intended processes and uses. The application, use and processing of our products and the products manufactured by you on the basis of our technical advice are beyond our control and, therefore, entirely your own responsibility. Our products are sold in accordance with the current version of our General Conditions of Sale and Delivery.

©2017 LANXESS and the LANXESS Logo are trademarks of LANXESS Deutschland GmbH or its affiliates. All trademarks are registered in many countries in the world.

North America

+1.833.LANXESS
customer.care@lanxess.com

Europe, Middle East & Africa

+44.161.875.3800
emea.export@lanxess.com

South & Central America

+55.19.3522.5083
atendimento.cliente@lanxess.com

Asia Pacific

+86.21.6109.6666
Orders.apac@lanxess.com

