Rug Pad



We offer rug pads for rugs and runners to prevent slipping, allow extra comfort and extend the rug's life. We recommend rug pads for all wool rugs. Rug pads are used beneath your rug on smooth or hard floors (timber, parquet, laminate, tile, stone, marble, cork, and PVC floor coverings) and on heated floors. It can be used on carpets to prevent rugs from creeping.

Newly sealed floors must be completely dry and cured before laying any rug or rug pad. Measuring ½" (3 mm) in thickness, it provides additional walking comfort while satisfying the highest demands.

| Imperial | Metric | |
|---------------|-------------|--|
| 5'7" x 7'10" | 1.7 × 2.4 m | |
| 6'7" x 9'10" | 2 × 3 m | |
| 8' x 10' | 2.4 × 3 m | |
| 8'2" x 11'6" | 2.5 × 3.5 m | |
| 9' x 12' | 2.7 × 3.6 m | |
| 9'10" x 13'2" | 3 × 4 m | |
| 10' x 14' | 3 × 4.2 m | |
| 11'6" x 14'9" | 3.5 × 4.5 m | |
| 2'7" x 13'2" | 0.8 × 4 m | |

Notes

The rug pad will be 1" (2 $\frac{1}{2}$ cm) smaller than your rug on each side. Custom size available.

| Fiber & construction | Composition | Features and Benefits |
|---|---------------------------------------|---|
| Fiber: Felt and natural rubber | 100% recycled felt and natural rubber | Light adhesive on both sides |
| Height: ¼" (3 mm) | | Enhances walking comfort |
| | | Prevents rugs from creeping |
| | | Grips through fiber |
| Underlay installation guide | | Free of folds |
| 1. Make sure the floor is vacuumed, clean and dry | _ | Easily to cut to size and lay |
| 2. Mark the position of the rug | | Odourless |
| 3. Lay the underlay 1" (2 ½ cm) inside the marks | | Free of harmful substances |
| 4. Place the rug on top of the underlay | | Improves the sound absorption |
| 5. For oversized rugs, the underlay will be comprised | | Residue free |
| of multiple pieces | | Anchors rugs to both soft & hard floors |
| 6. Underlay can be trimmed using scissors if required | | Can be used on heated floors |