PH 80 PORTABLE LAMP

Opal white/high lustre chrome plated, 5744172325, Designed by Poul Henningsen

Type:	
Product:	
Project:	
Modified:	

Technical specifications

Materials
Shades: Injection molded PC.
Top, cone, heat sink, stem top, base: Die-casted aluminum.
Stem: Extruded aluminum.
Diffuser: Injection molded clear PC.

Finishes
White opal shades.
Red or white cone.
Socket house in white or high lustre chrome plated.
Stem top in white or black.
Stem in white or high lustre chrome plated.
Base in black or white.

Mounting
Cord: 1.5 m. USB-C/USB-C.

Light control: Switch on base.

White light indicator on base when charging.

Batteries: 2 x LiPo, rechargeble, replaceable.

Battery lifetime: 5 hours at 100%.

Dim-2-Warm (1800-2700K) Stepless-dim and 4 step-dim (5%,

Information
Please note that the PH 80 Portable Lamp comes with a USB-cable but without an adapter. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

PH 80 PORTABLE LAMP

Opal white/high lustre chrome plated, 5744172325, Designed by Poul Henningsen

20%, 45%, 100%) customer user setting (can switch between the functions). For mounting instructions, see download section on the product detail page.

Variant Options

For particular variant options, please check our online Product Variants Configurator on the product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	DELIVERED LUMEN	FEATURES	CABLE	COLOR, RAL	W / H / L (IN) / W (LB)
5744172325	Integrated LED 1800K-2700K dim-2-warm	5V, 2A/10W	174	-	Without cord	Opal white/high lustre chrome plated	230 / 305 / 230 in / 1.8 lb
5744172338	Integrated LED 1800K-2700K dim-2-warm	5V, 2A/10W	174	-	Without cord	Opal white/white	230 / 305 / 230 in / 1.8 lb