

MODEL 3475

6-LED No-Air Polyurethane-Wrapped Aluminum Blast Light



6 Bright White LEDs



3475 Blast Light
(shown with optional stanchion)

	Product Specifications	3475
Light Output	Lumens	1200 lumens and >40,000 lux at 1 foot with optics
	Beam	25° (Spot Light)
Emitter	Emitter Type	LED
	Color Temperature	6000K (+/-200K)
Power	Power Consumption	18 Watts
	Option to power directly from 12-28V AC/DC source: Also available in 220-V?	Battery clamp option available, Minimum cord length: 10 feet Yes
Optics	Refractive Optic Design?	Yes
Housing	Light Body	Aluminum with Polyurethane handle and halo
	Halo	Shock Absorbing Light Halo
	Dimensions - Length	7"
	Product Weight	Lighthouse 2lbs, 100' System 8.5lbs
	Attachment Methods	Optional Light Stanchion (high or low)
	Lens	Triple lens (outer lens: tempered glass pyrex) and field replaceable polycarbonate
	Primary Cable on systems	100' Extreme Cable standard, other lengths available (min. 10 feet)
	Assembled in USA?	Yes
	No Air:	Yes

Complete System Includes:

- Blast Light
- Power Pack
- Hose Clamp (1)
- 100' (ft.) Extreme Cable
- Stanchion
- Plug



Optional Battery Clamps (used to power directly from a 12VDC Source)

