

88VX Series

Airline Respirator

The Bullard 88VX Series airline respirators offer advancements in comfort and reliable respiratory protection for abrasive blasters and painters. The 88VX Respirator is NIOSH approved as a Type C and CE Continuous Flow Class Respirator (Approval No. TC-19C-293).



Advanced Protection

- Sewn-in neck cuff provides a physical barrier to airborne contaminants
- Double lining in the neck area enhances durability and protection

Comfortable Fit

- Lightweight inner shell with an adjustable headband suspension
- Airflow is channeled directly to the user's breathing zone
- No fit testing required
- Optional cheek pads for increased stability

Head Protection


- Helmet provides top impact and penetration protection
- Helmet and cape help protect the worker's entire head, face, and upper body from abrasive rebound, airborne contaminants and messy overspray

Optimum Visibility

- Wide-angle faceshield lens
- Translucent yellow helmet prevents closed-in feeling among workers
- Optional tinted lenses provide protection from the sun

Climate Control

- Optional climate control devices warm or cool incoming air to maximize comfort and improve productivity



Distributed By:



2717 Tobey • Indianapolis, IN 46219
(317) 545-0665 • FAX (317) 545-0670 • (800) 800-0665
www.idsblast.com



www.bullard.com

88VX Series

Airline Respirator

88VX Parts List

88VXSYS

Includes a 88VX3235 respirator assembly, ADP20 Free -Air® pump, 50 foot (15 m) air supply hose and Frigatron 2000 climate control device.

Respirator Models

For use with breathing air compressors

Includes EVX30 breathing tube assembly with 1/4" Industrial Interchange fitting and belt, inner and outer lenses and cape. Breathing air supply hose not included.

88VX3230	Respirator with 46VX nylon cape – 28" (71 cm) length
88VX3230H	Same as model 88VX3230 with 25' (8m) of starter hose
88VX1330	Same as model 88VX3230 with 13VX nylon cape – 38" (96cm) length

For use with Bullard Free-Air® Pumps

Includes EVX35 breathing tube assembly with 1/2" Industrial Interchange fitting and belt, inner and outer lenses and cape. Breathing air supply hose not included.

88VX3235	Respirator with 46VX nylon cape – 28" (71 cm) length.
88VX3235H100	Same as model 88VX3235 with 100' (32 m) of starter hose

Replacement Capes for 88VX Series Airline Respirators

46VX	Tan Nylon Cape – 28" (71 cm) length
13VX	Tan Nylon Cape – 38" (96 cm) length
21VX	"Golden Gate" Style, Tan Nylon Cape – 38" (96 cm) length
36VX	Hibernia Parka, Tan Nylon Parka with Long Sleeves – 38" (96 cm) length
36LVX	Hibernia Parka, Tan Nylon Parka with Long Sleeves – 38" (96 cm) length, XL

Accessories for 88VX Series Airline Respirators

88VXTGP	Adjustable headband suspension with Plenum
88VXRTT	Adjustable Sure-Lock® ratchet headband suspension with Plenum
88VXAK	Oval Door/Gasket/Latch Kit
88CA	Carrying Strap
88VXBAIL	Replacement Bail for Latch Assembly (10/pkg)
88VXHPP	Replacement Hinge Pins for Latch Assembly (10/pkg)
20NC	Elastic Chin Strap
88CK	Breathing Tube Connector Kit
88FW	Box Front Window Frame
77GLT	Box Front Glass Lens
77LG	Front Box Lens Gasket
G4613	Rectangular Window Gasket
G7713	Oval Window Gasket
GVXCP	Replaceable Cheek Pads, Pair
88VXOLG	Outer lenses .042", Pack of 25 - Tinted Green
88VXOLT	Outer lenses .030", Pack of 25 - Tinted Smoke

Replacement Lenses for 88VX Series (Oval)

P771B/B771B	Inner plastic lens, .040" (1 mm) thick (200/pkg)
B771040	Outer plastic lens, .040" (1 mm) thick (200/pkg)
P771020/B771020	Outer plastic lens, .020" (0.5 mm) thick (400/pkg)
P771R	Outer plastic lens, .015" (0.4 mm) thick (50/pkg)
88VXLC	Clear Mylar lens cover, perforated edges (25/pkg)

Replacement Breathing Tube Assemblies

Includes breathing tube, airflow control, quick-disconnect fitting and belt.

88VXBT	Breathing tube only (fitting not included)
Optional Climate Control Breathing Tube Assemblies	
AC1000	Cool tube with 1/4" Industrial Interchange, steel quick-disconnect fitting. Adjustable airflow. For use with breathing air compressors.
HC2400	Hot/Cold tube with 1/4" Industrial Interchange, steel quick-disconnect fitting. Adjustable airflow. For use with breathing air compressors.
Frigatron 2000	Cool tube with 1/2" Industrial Interchange, steel quick-disconnect fitting. Adjustable airflow. For use with Bullard ADP20 or EDP30 pumps.
DC5040	Dual-Cool with 1/4" Industrial Interchange for use with air compressors. Order Dual-Cool vests separately.
DC70ML	Dual-Cool vest. Size M/L
DC70XLXXL	Dual-Cool vest. Size XL/XXL
CT30	Plastic Cool tube with 1/4" Industrial Steel, quick-disconnect fitting, adjustable airflow. For use with breathing air compressors.
HCT30	Plastic Hot/Cold tube with 1/4" Industrial Interchange, steel quick-disconnect fitting. Adjustable airflow. For use with breathing air compressors.

Air Supply Hoses and Fittings

V10 Series Starter and Extension Hose Kits (For use with Breathing Air Compressors)
Includes 3/8" (10 mm) I.D. rubber hose, V11 hose-to-hose adapter fitting and V13 adapter fitting - 3/8" (10 mm) hose-to-3/8" (10 mm) pipe.

4696	25' (8 m) Starter hose kit with 1/4" Industrial Interchange, steel quick-disconnect fittings
5454	25' (8 m) Extension hose kit
5457	50' (15 m) Extension hose kit
5458	100' (31 m) Extension hose kit

V20 Series Starter Hoses (For use with Free-Air Pumps)

Includes 1/2" (13 mm) I.D. rubber hose with 1/2" Industrial Interchange male/female quick-disconnect coupler.


V2050ST	50' (15 m)
V20100ST	100' (31 m)



Americas:
Bullard
1898 Safety Way
Cynthiana, KY 41031-9303 • USA
Toll-free within USA: 877-BULLARD (285-5273)
Tel: +1-859-234-6616
Fax: +1-859-234-8987

Europe:
Bullard GmbH
Lilienthalstrasse 12
53424 Remagen • Germany
Tel: +49-2642 999980
Fax: +49-2642 9999829

Asia-Pacific:
Bullard Asia Pacific Pte. Ltd.
LHK Building
701, Sims Drive, #04-03
Singapore 387383
Tel: +65-6745-0556
Fax: +65-6745-5176



©2013 Bullard. All rights reserved.
Free-Air is a registered trademark of Bullard.
Mylar is a registered trademark of Dupont Teijin Films.
8017 (0613)