



HURRICANE 800_{EM}

HURRICANE 800EM ELECTRIC EXTREME DUTY SPECIFICATIONS

- **VACUUM SPECIFICATIONS:** Skid Mounted 4" x 8" rectangular tube frame, 6" x 12" fork pockets. 4 point certified lift frame. Sub frame for motor & blower package with vibration isolators.
- **POWER PACKAGE 1:** 200 hp, 460 Volt, 3 Phase hostile duty motor. Direct drive to a Roots 4500 cfm blower capable of 28" of mercury (Hg)
- **POWER PACKAGE 2:** 300 hp, 460 Volt, 3 Phase hostile duty motor. Direct drive to a Roots 5660 cfm blower capable of 28" of mercury (Hg)
- **FILTRATION SYSTEM — 3 STAGE:**
 - Stage 1: Cyclonic separation
 - Stage 2: 37 Teflon coated, quick change filterbags with continuous reverse pulse air cleaning
 - Stage 3: Dual blower safety filters with optional HEPA filtration
- **INSTRUMENT PANEL:** NEMA 4 Soft start package. Push button motor start/stop with indicator light, disconnect lever, filter cleaning on/off, vacuum system on/off.

STANDARD EQUIPMENT

Paint one color with custom lettering/striping
 Wet or dry operation
 Automatic cone vibrator
 Emergency stop button
 10" inspection manhole

OPTIONS

HEPA filtration
 Dirty filter shut down system
 Slide gate discharge
 Toolbox
 Hydraulic lift package
 Air compressor – 120PSI
 Trailer mounted
 Hydraulic auger in cone
 Rotary valve
 Double dump valve

INDUSTRIES

Sandblasting/Painting
 Ship Cleaning
 Foundries
 Factories
 Mining
 Blast Recovery
 Wastewater Treatment




Dimensional Drawing On Reverse Side



Distributed By:



2717 Tobey • Indianapolis, IN 46219
 (317) 545-0665 • FAX (317) 545-0670 • (800) 800-0665
www.idsblast.com



INDUSTRIAL
VACUUM

HURRICANE
800
EM

HURRICANE™

DIMENSIONS

WIDTH 88" WEIGHT 12,500 lbs.

