

Now includes **Prepware software!**

UNLIMITED study sessions and practice tests—FREE with book

2025-2026

Commercial Pilot

TEST PREP



Pass your test the first time

Now includes **Prepware software!**

UNLIMITED study sessions and practice tests—FREE with book

2025-2026 Commercial Pilot TEST PREP

Pass your test the first time



Commercial Pilot Test Prep 2025–2026 Edition

Aviation Supplies & Academics, Inc. 7005 132nd Place SE Newcastle, Washington 98059 asa@asa2fly.com | 425.235.1500 | asa2fly.com

© 2024 Aviation Supplies & Academics, Inc.

Visit asa2fly.com/TPC for additional information and resources related to this book.

Sample Federal Aviation Administration (FAA) questions herein contain information as of: September 2024. Stay informed of changes since the book was printed: asa2fly.com/testupdate

None of the material in this publication supersedes any documents, procedures or regulations issued by the Federal Aviation Administration.

Aviation Supplies & Academics, Inc. (ASA), assumes no responsibility for any errors or omissions. Neither is any liability assumed for damages resulting from the use of the information contained herein.

Cover photo: Viktor Kochetkov/Shutterstock.com

ASA-TP-C-25

ISBN 978-1-64425-428-8

Additional format available: eBook PDF ISBN 978-1-64425-429-5

Printed in the United States of America

2025 2024 5 4 3 2

About the Contributor

Jackie Spanitz

General Manager Aviation Supplies & Academics, Inc.

As ASA General Manager, Jackie Spanitz oversees maintenance and development of the books and pilot supplies in the ASA product line. Ms. Spanitz has worked with airman training and testing for more than 30 years, including participation in the Airman Certification Standards (ACS) committees. Jackie holds a Bachelor of Science in Aviation Technology from Western Michigan University, a Master of Science from Embry-Riddle Aeronautical University, and Instructor and Commercial Pilot certificates. She is the technical editor for ASA's Test Prep and FAR/AIM series.

Aviation Supplies & Academics, Inc. (ASA) is an industry leader in the development and sale of aviation supplies and publications for pilots, flight instructors, aviation mechanics, aircraft dispatchers, air traffic controllers, and drone operators. ASA has provided trusted training materials to millions of aviators resulting in successful airman certification for over 80 years. Visit asa2fly.com to learn more.

Stay informed with ASA online resources.

Website



asa2fly.com

Updates



asa2fly.com /testupdate

Blog



learntoflyblog.com



asapresents.net

Follow, like, share.

- instagram.com/asa2fly
- facebook.com/asa2fly
- youtube.com/asa2fly
- in linkedin.com/company/asa2fly

Contents

Instructions	Propellers	2-9
Updates and Practice Testsv	Cold Weather Operations	2-12
Introductionvi	Rotorcraft Systems	2-13
Description of the Testsvii	Glider Systems	2-29
Knowledge Test Registrationvii	Balloon Operations	2-37
Knowledge Test Eligibilityviii	Airship Operations	2-43
Acceptable Materialsix	Airship IFR Operations	2-45
Testing Procedures for Applicants Requesting Special Accommodationsix		
Test Reportsx	Chapter 3 Flight Instruments	
Retesting Proceduresx	Airspeed Indicator	3-3
Cheating or Other Unauthorized Conductx	Altitudes	
Test-Taking Tipsxii	Magnetic Compass	
Commercial Pilot Certificate Eligibility	Gyroscopic Instruments and Systems	
Requirementsxiii	Attitude Instrument Flying	
Knowledge Exam Referencesxiv	Electronic Flight Instruments	
Acronymsxv	Electionic Flight motiuments	0 10
ASA Test Prep Layoutxvii		
AOA 1031 TOP Layout	Chapter 4 Regulations	
	Pilot Certificate Types and Privileges	4-3
Chapter 1 Basic Aerodynamics	Medical Certificates	
Aerodynamic Terms1–3	Pilot Logbooks	
Axes of Rotation and the Four Forces Acting	High-Performance, Complex, and Tailwheel	/
in Flight1–5	Airplanes	4–8
<i>Lift.</i> 1–6	Recent Flight Experience: Pilot-In-Command	
Weight1-7	Change of Address	
Thrust1–7	Towing	
Drag1-7	Responsibility and Authority of the	
Lift/Drag Ratios1–11	Pilot-In-Command	4-13
The V _G Diagram1–13	Preflight Action	
Stability1–14	Seatbelts	
Turns, Loads, and Load Factors 1–16	Portable Electronic Devices	4–19
Stalls and Spins1–23	Fuel Requirements	4–20
Flaps1–24	Transponder and ADS-B Requirements	
Wing Shapes 1-25	Supplemental Oxygen	
Torque1–26	Instrument and Equipment Requirements	
Ground Effect	Restricted, Limited, and Experimental	
Wake Turbulence 1–28	Aircraft: Operating Limitations	4-24
Glider Aerodynamics	Emergency Locator Transmitter (ELT)	4-25
Gildor / torodynamico	Truth in Leasing	4-25
	Operating Near Other Aircraft and	
Chapter 2 Aircraft Systems	Right-of-Way Rules	
Ignition System2-3	Speed Limits	
Air-Fuel Mixture2–4	Aircraft Lights	
Carburetor Ice2-6	Minimum Altitudes	4–31
Aviation Fuel	Maintenance Responsibility	
Engine Temperatures2–8	Aircraft Inspections	4–33

Maintenance Records4-35	Tropopause Height/Vertical Wind Shear	
Maintenance, Preventative Maintenance,	Prognostic Chart	
Rebuilding, and Alteration4-36	Significant Weather Prognostics 7	
NTSB Part 830 4–38	Lifted Index Chart	7–16
IFR Operations 4–41		
Rotorcraft Regulations4–42	Chapter 9 Airevelt Berleymanes	
Glider Regulations4-43	Chapter 8 Aircraft Performance	
Lighter-Than-Air Regulations4-43	Weight and Balance	
LTA Fundamentals of Instructing 4-46	Computing Weight and Balance	
	Graph Weight and Balance Problems	
Chapter F Proceedures and	Weight Change	
Chapter 5 Procedures and Airport Operations	Weight Shift	
	Rotorcraft Weight and Balance	
Airspace	Glider Weight and Balance	
Basic VFR Weather Minimums	Headwind and Crosswind Components	
Operations on Wet or Slippery Runways 5–15	Density Altitude	
Land and Hold Short Operations (LAHSO) 5–16	Takeoff and Landing Considerations	
Airport Marking Aids and Signs5–17	Takeoff and Landing Distance	
VFR Cruising Altitudes	Fuel Consumption vs. Brake Horsepower 8	
Collision Avoidance	Time, Fuel, and Distance to Climb	
Fitness Physiology	Table Method	
Aeronautical Decision Making (ADM)5-29	Graph Method	
	Cruise Performance Table	
Chapter 6 Weether	Cruise and Range Performance Table	
Chapter 6 Weather	Maximum Rate of Climb	
The Earth's Atmosphere	Glide Distance	
Temperature	Rotorcraft Performance	
Wind6-7	Glider Performance	
Moisture	Balloon Performance	3–43
Stable and Unstable Air6-10		
Clouds	Chantes O. Novinction	
Air Masses and Fronts6–16	Chapter 9 Navigation	
Turbulence	The Flight Computer	
lcing	Finding True Course, Time, Rate, Distance,	
Thunderstorms	and Fuel	
Fog	Finding Density Altitude	
Wind Shear	Finding Wind Direction and Velocity	
Soaring Weather6-30	VHF Omni-Directional Range (VOR)	
	Horizontal Situation Indicator (HSI)	9–18
Chapter 7 Weather Services		
Aviation Routine Weather Report (METAR)7–3	Cross References	
,	A: Question Number and Page Number	Λ 1
Pilot Report (UA)	G	Λ-ι
· · ·	B: Airman Knowledge Test Report Codes and Question Numbers	R_1
Graphical Forecasts for Aviation (GFA)	Codes and Question Numbers	D-1
Winds and Temperatures Aloft Forecast (FB) 7–10		
Inflight Weather Advisories (WA, WS, WST) 7–10	FAA Figures	
Surface Analysis Chart 7–12	•	
Constant Pressure Chart7-13	Airman Knowledge Testing Supplement for Commercial Pilot (FAA-CT-8080-1E)	

Updates and Practice Tests

Free Test Updates for the Life Cycle of Test Prep Books

The FAA modifies tests as needed throughout the year. ASA keeps abreast of changes to the tests and posts free Test Updates on the ASA website. Before taking your test, be certain you have the most current information by visiting the ASA Test Updates webpage: asa2fly.com/testupdate. Additionally, sign up for free email notifications, which are sent when new Test Updates are available.

We Invite Your Feedback

After you take your FAA exam, let us know how you did. Were you prepared? Did ASA's products meet your needs and exceed your expectations? We want to continue to improve these products to ensure applicants are prepared and become safe aviators. Send your feedback to: cfi@asa2fly.com.



prepware.com

See inside front cover for FREE account!

Online practice to prepare for written exams.

As the experts in FAA Knowledge Exam preparation, we want you to have the confidence needed before heading to the testing center, and help eliminate the hassle and expense of retaking exams.

Realistic Test Simulation

Test maps and time allowed mirror the official FAA exams

Performance Graphs

Review explanations for missed questions and track your performance

Gain Confidence

Go into your exam fully prepared after practicing up to 5 simulated tests

Succeed

Pass your exam and review your airman knowledge test report to prepare for your checkride

Remote Pilot | Sport Pilot | Private Pilot | Instrument Rating | Commercial Pilot | Flight Instructor | Ground Instructor Fundamentals of Instructing | Flight Engineer | Airline Transport Pilot | Aviation Mechanic General | Airframe | Powerplant

Practice tests and flashcards are also available as an app for your mobile devices! asa2fly.com/apps

Introduction

Welcome to the Aviation Supplies & Academics, Inc., (ASA) Test Prep Series. This series has been helping pilots prepare for the FAA Knowledge Tests for more than 60 years with great success. We are confident that with proper use of this book you will score very well on your Commercial Pilot certificate test.

Begin your studies with a classroom or home-study ground school course, which will involve reading a comprehensive textbook. Visit the Reader Resources for this Test Prep (asa2fly.com/TPC) and become familiar with the FAA guidance materials available for this certification exam. Then use this Test Prep to prepare for your exam: read the question, select your choice for the correct answer, and then read the explanation. Use the references that conclude each explanation to identify additional resources for further study of a subject. Upon completion of your studies, take practice tests at prepware.com (see inside the front cover for your activation code).

The questions in this book have been arranged into chapters based on subject matter to promote better understanding, aid recall, and provide a more efficient study guide. Place emphasis on questions most likely to be included in your test (identified by the aircraft category above each question). For example, a pilot preparing for the Commercial Airplane test would focus on the questions marked "ALL" and "AIR," and a pilot preparing for the Commercial Helicopter test would focus on the guestions marked "ALL" and "RTC."

Prior to taking an FAA Airman Knowledge Test, all applicants must establish an FAA Tracking Number (FTN) by creating a profile in the Integrated Airman Certification and Rating Application (IACRA) system at iacra.faa.gov. Then visit faa.psiexams.com to register for your exam and take FAA-created practice tests to become familiar with the computer testing platform.

It is important to answer every question assigned on your FAA Knowledge Test. If in their ongoing review, the FAA decides a question has no correct answer, is no longer applicable, or is otherwise defective, your answer will be marked correct no matter which one you chose. However, you will not be given the automatic credit if you have not marked an answer. Unlike some other exams you may have taken, there is no penalty for guessing in this instance.

The FAA exams are "closed tests" which means the exact database of questions is not available to the public. The question and answer choices in this book are based on our extensive history and experience with the FAA testing and airman certification process. You might see similarly worded questions on your official FAA exam, or answer stems might be rearranged from the order you see in this book. Therefore, be sure to fully understand the intent of each question and corresponding answer while studying, rather than memorizing the letter associated with the correct response. You may be asked a question that has unfamiliar wording; studying and understanding the information in this book and the associated references will give you the tools to answer question variations with confidence.

If your study leads you to guestion an answer choice, we recommend you seek the assistance of a local instructor. We welcome your questions, recommendations, and concerns—send them to:

Aviation Supplies & Academics, Inc.

7005 132nd Place SE Newcastle, WA 98059-3153

Phone: 425.235.1500 Email: cfi@asa2fly.com Website: asa2fly.com

The FAA appreciates testing experience feedback. You can contact them at:

Federal Aviation Administration

Training & Certification Group, **Testing Standards Section** PO Box 25082 Oklahoma City, OK 73125

Email: TestingStandardsComments@faa.gov

Description of the Tests

The FAA Knowledge Exam is an objective, multiple choice test. Each question can be answered by one of the three choices. Each test question is independent of the others—a correct response to one question does not depend on the correct response to another. You must score at least 70 percent to pass the test.

As stated in 14 CFR §61.63, an applicant need not take an additional knowledge test provided the applicant holds an airplane, rotorcraft, powered-lift, or airship rating at that pilot certificate level. For example, an applicant transitioning from gliders to airplanes will need to take the 100-question test. But an applicant transitioning from airplanes to gliders, or airplanes to helicopters, will not be required to take the Knowledge Exam.

Military applicants should refer to the Commercial Pilot – Military Competence Airman Certification Standards (FAA-S-ACS-12) for information on the expected knowledge in preparation for the Military Competence Knowledge Exam. Additionally, applicants should review §61.73. Military pilots or former military pilots: Special rules, which provides information to military pilots who are interested in acquiring their civilian pilot certificate.

The table below lists the number of questions and the allotted time for each test. Each question in this book is preceded by a category. Use these categories to study the content that may appear on your test. Study all the guestions first, then refer to the following table, placing emphasis on those guestions most likely to be included on your test (identified by the test prep category above each question number).

Test Code	Test Name	Test Prep Study	Number of Questions	Min. Age	Allotted Time (hrs)
CAX	Commercial Pilot — Airplane	ALL, AIR	100	16	2.5
CRH	Commercial Pilot — Helicopter	ALL, RTC	100	16	3.0
CRG	Commercial Pilot—Gyroplane	ALL, RTC	100	16	3.0
CGX	Commercial Pilot—Glider	ALL, GLI	100	16	3.0
СВН	Commercial Pilot — Balloon-Hot Air	ALL, LTA	100	16	3.0
CLA	Commercial Pilot — Airship	ALL, LTA	100	16	3.0
CBG	Commercial Pilot — Balloon-Gas	ALL, LTA	60	16	2.5
MCN	Military Competency— Non-Category	MIL	50	18	2.0
CCP	Commercial Pilot—Airplane Canadian Conversion*	ALL, AIR	40	18	2.0
CCH	Commercial Pilot—Helicopter Canadian Conversion*	ALL, RTC	40	18	2.0

^{*} This test focuses on U.S. regulations, procedures, and operations.

Knowledge Test Registration

The FAA testing providier authorizes hundreds of test center locations that offer a full range of airman knowledge tests. For information on authorized testing centers and to register for the knowledge test, visit faa.psiexams.com.

When you contact a knowledge testing center, be prepared to select a test date and make payment. You may register for test(s) several weeks in advance online or by phone, and you may cancel in accordance with the testing center's cancellation policy.

Regardless of your registration method, you will need an FAA Tracking Number (FTN) prior to registering for the FAA Airman Knowledge Test. This FTN will follow you throughout your aviation career. You will obtain your FTN as part of the test registration process, by creating a profile in the Integrated Airman Certificate and Rating Application (IACRA) system at iacra.faa.gov/IACRA. This FTN will be printed on your Airman Knowledge Test Report (AKTR).

The test registration process includes collection of this information: name, FTN, physical address, date of birth, email address, photo identification, phone number, test authorization (credentials of the individual such as an instructor endorsement), and previous number of test attempts.

- Step 1: Create a profile using the IACRA system and login to obtain your FTN.
- Step 2: Register for your knowledge test with PSI by phone or online.

For more information, contact: **PSI Services LLC** 844-704-1487 or examschedule@psionline.com faa.psiexams.com

Knowledge Test Eligibility

All Commercial Pilot Tests

You will be required to show proper identification and the following:

- 1. Certificate of graduation or a statement of accomplishment certifying the satisfactory completion of the ground school portion of a course for the certificate or rating sought. The certificate or statement may be issued by a Federal Aviation Administration certified pilot school or an agency such as a high school, college, adult education program, Civil Air Patrol, or Reserve Officers Training Corp (ROTC) flight training school.
- 2. Written statement or logbook endorsement from an authorized ground or flight instructor certifying that the applicant completed an applicable ground training or home study course and is prepared for the knowledge test.

Ground schools will issue an endorsement when you complete their course. If you choose to homestudy, you can either get an endorsement from your instructor or submit your home-study materials to an FAA Office for review and approval prior to taking the test.

Complete two Prepware practice tests with scores of 80% or higher to get your knowledge test endorsement for any pilot rating directly from ASA. Visit asa2fly.com/prepware or prepware.com for more details.

If a flight or ground instructor is providing your endorsement, you may use the following template:

Commercial i not Endorsement
I certify that (First name, MI, Last name

Commercial Pilot Endorsement

I certify that (First name, MI, Last name) $_$	has received
the required training of 14 CFR §61.125. I	have determined he/she is prepared for the (Test name; e.g.
Commercial Pilot – Airplane)	knowledge test.
Signed	Date
CFI Number	Expires

Military Competency Tests

Requires *no* instructor endorsements or other form of written authorization.

Acceptable Materials

The applicant may use test aids and materials within the guidelines listed below during the test, if actual test questions or answers are not revealed.

Acceptable Materials	Unacceptable Materials	Notes
Supplement book provided by proctor.	Written materials that are hand- written, printed, or electronic.	Testing centers may provide calculators and/or deny the use of personal calculators.
All models of aviation-oriented calculators or small electronic calculators that perform only arithmetic functions.	Electronic calculators incorporating permanent or continuous type memory circuits without erasure capability.	Test proctor may prohibit the use of your calculator if he or she is unable to determine the calculator's erasure capability.
Calculators with simple programma- ble memories, which allow addition to, subtraction from, or retrieval of one number from the memory; or simple functions, such as square root and percentages.	Magnetic cards, magnetic tapes, modules, computer chips, or any other device upon which pre-written programs or information related to the test can be stored and retrieved.	Printouts of data must be sur- rendered at the completion of the test if the calculator incorpo- rates this design feature.
Scales, straight-edges, protractors, plotters, navigation computers, blank log sheets, holding pattern entry aids, and electronic or mechanical calculators that are directly related to the test.	Dictionaries.	Before, and upon completion of the test, while in the presence of the test proctor, actuate the ON/ OFF switch or RESET button, and perform any other function that ensures erasure of any data stored in memory circuits.
Manufacturer's permanently inscribed instructions on the front and back of such aids, such as formulas, conversions, regulations, signals, weather data, holding pattern diagrams, frequencies, weight and balance formulas, and ATC procedures.	Any booklet or manual containing instructions related to use of test aids.	Test proctor makes the final determination regarding aids, reference materials, and test materials.

Testing Procedures for Applicants Requesting Special Accommodations

If you are an applicant with a learning or reading disability, you may request approval from the local FAA office to take an airman knowledge test, using the special accommodations procedures outlined in the most current version of FAA Order 8080.6 Conduct of Airman Knowledge Tests.

Prior to approval of any option, the FAA Aviation Safety Inspector must advise you of the regulatory certification requirement of being able to read, write, speak, and understand the English language.

Test Reports

Your test will be graded immediately upon completion and your score will display on the computer screen. You will receive your Airman Knowledge Test Report (AKTR), which will state your score. See sample AKTR on the next page.

Visit **faa.psiexams.com** to request a duplicate or replacement AKTR due to loss or destruction.

Airman Knowledge Test Reports are valid for 24 calendar months. If the AKTR expires before completion of the practical test, you must retake the knowledge test.

The AKTR lists the Airman Certification Standard (ACS) code (if an Airman Certification Standard is available for the certificate and rating specific to the test) or Learning Statement Code (LSC) (if a Practical Test Standard is in effect for the certificate and rating specific to the test) for questions answered incorrectly. The total number of ACSs/LSCs shown on the AKTR is not necessarily an indication of the total number of questions answered incorrectly. Study these knowledge areas to improve your understanding of the subject matter. See Cross-Reference B in the back of this book for a listing of ACSs/LSCs and their associated questions.

Your instructor is required to provide instruction on each of the knowledge areas listed on your AKTR and to complete an endorsement of this instruction. You must present this to the examiner prior to taking the practical test. During the oral portion of the practical test, the examiner is required to evaluate the noted areas of deficiency.

Retesting Procedures

Applicants retesting after failure are required to submit the applicable AKTR indicating failure, along with an endorsement (on the test report) from an authorized instructor, who gave the applicant the additional training, certifying the applicant is competent to pass the test. The original failed AKTR and retest endorsement presented as authorization shall be retained by the proctor and attached to the applicable sign-in/out log. The latest test taken will reflect the official score.

Applicants retesting in an attempt to achieve a higher passing score may retake the same test for a better grade after 30 days. The latest test taken will reflect the official score. Applicants are required to submit the original applicable AKTR indicating previous passing score to the testing center prior to testing. Testing center personnel must collect and destroy this report prior to issuing the new test report.

Cheating or Other Unauthorized Conduct

Computer testing centers must follow strict security procedures to avoid test compromise. These procedures are established by the FAA and are covered in FAA Order 8080.6 Conduct of Airman Knowledge Tests. The FAA has directed testing centers to terminate a test at any time a test proctor suspects a cheating incident has occurred. An FAA investigation will then be conducted. If the investigation determines that cheating or unauthorized conduct has occurred, then any airman certificate or rating that you hold may be revoked, and you will be prohibited for one year from applying for or taking any test for a certificate or rating under 14 CFR Part 61.

U.S. DEPARTMENT OF TRANSPORTATION **Federal Aviation Administration** Airman Knowledge Test Report

NAME: TAYLOR SMITH

FAA TRACKING NUMBER (FTN): C1234567 EXAM ID: 98765432109876543

Commercial Pilot - Airplane (CAX) **EXAM:**

EXAM DATE: 09/15/2024 **EXAM SITE:** ABC12345

SCORE: 88% **GRADE:** Pass TAKE:

The Airman Certification Standards (ACS) codes listed below represent incorrectly answered questions. These ACS codes and their associated Areas of Operation/Tasks/Elements may be found in the appropriate ACS document at http://www.faa.gov/training_testing/testing/acs.

A single code may represent more than one incorrect response.

CA.I.F.K3 CA.I.G.R1 CA.III.A.K8 CA.IV.A.R2d CA.V.A.K2e CA.VII.B.K1 CA.IX.D.K3c

EXPIRATION DATE: 09/30/2026

DO NOT LOSE THIS REPORT

AUTHORIZED INSTRUCTOR'S STATEMENT: (if applicable)	
On (date) I gave the above named applicant shown to be deficient, and consider the applicant competent to	
Name	
Cert. No	(print clearly)
Type of instructor certificate	
Signature	

FRAUDULENT ALTERATION OF THIS FORM BY ANY PERSON IS A BASIS FOR SUSPENSION OR REVOCATION OF ANY CERTIFICATES OR RATINGS HELD BY THAT PERSON. **ISSUED BY: PSI Services LLC**

FEDERAL AVIATION ADMINISTRATION

THIS INFORMATION IS PROTECTED BY THE PRIVACY ACT. FOR OFFICIAL USE ONLY.

Sample Airman Knowledge Test Report

Test-Taking Tips

Prior to launching the actual test, the test proctor's testing software will provide you with an opportunity to practice navigating through the test. This practice (or tutorial) session may include a "sample" question(s). These sample questions have no relation to the content of the test, but are meant to familiarize you with the look and feel of the system screens, including selecting an answer, marking a question for later review, time remaining for the test, and other features of the testing software.

Follow these time-proven tips, which will help you develop a skillful, smooth approach to test-taking:

- Visit faa.psiexams.com to take a small sample test to become familiar with the latest PSI exam interface you will see on your actual FAA knowledge test.
- Be careful to fully understand the intent of each question and corresponding answer while studying, rather than memorize the A, B, C answer choice—answer stems may appear in a different order than you studied and have some wording differences.
- Take with you to the testing center a sign-off from an instructor (except for military competency test candidates), photo I.D., the testing fee, calculator, flight computer (ASA's E6-B or CX-3 Flight Computer), plotter, magnifying glass, and a sharp pointer, such as a safety pin.
- Your first action when you sit down should be to write on the scratch paper the weight and balance and any other formulas and information you can remember from your study. Remember, some of the formulas may be on your E6-B.
- Answer each question in accordance with the latest regulations and guidance publications.
- Read each question carefully before looking at the possible answers. You should clearly understand the problem before attempting to solve it.
- · After formulating an answer, determine which answer choice corresponds the closest with your answer. The answer chosen should completely resolve the problem.
- From the answer choices given, it may appear that there is more than one possible answer. However, there is only one answer that is correct and complete. The other answers are either incomplete, erroneous, or represent popular misconceptions.
- Answer each question in accordance with the latest regulations and guidance publications.
- If a certain question is difficult for you, it is best to mark it for REVIEW and proceed to the other questions. After you answer the less difficult questions, return to those which you marked for review and answer them. The review marking procedure will be explained to you prior to starting the test. Although the computer should alert you to unanswered questions, make sure every question has an answer recorded. This procedure will enable you to use the available time to the maximum advantage.
- Perform each math calculation twice to confirm your answer. If adding or subtracting a column of numbers, reverse your direction the second time to reduce the possibility of error.
- When solving a calculation problem, select the answer nearest to your solution. The problem has been checked with various types of calculators; therefore, if you have solved it correctly, your answer will be closer to the correct answer than any of the other choices.
- Remember that information is provided in the Legends and Figures contained within the Airman Knowledge Testing Supplement (FAA-CT-8080 document) you'll be using during the test.
- Remember to answer every question, even the ones with no completely correct answer, to ensure the FAA gives you credit for a bad question.
- Take your time and be thorough but relaxed. Take a minute off every half-hour or so to relax the brain and the body. Stay hydrated.
- Your test will be graded immediately upon completion.

Commercial Pilot Certificate Eligibility Requirements

The general prerequisites for a Commercial Pilot Certificate require that the applicant have a combination of experience, knowledge, risk management, and skill. For specific information pertaining to certification, an applicant should carefully review the appropriate sections of Part 61 for Commercial Pilot Certification, including 14 CFR §61.23 "Medical Certificates: Requirement and Duration," and §61.35, "Knowledge Test: Prerequisites and Passing Grades."

Additionally, to be eligible for a Commercial Pilot Certificate, applicants must:

- Be at least 18 years of age (16 to take the knowledge test).
- Be able to read, speak, write, and understand English or have a limitation placed on the certificate.
- Hold a current medical certificate issued under Part 67. No medical certificate is required for a glider or balloon rating.
- Pass a knowledge test appropriate to the aircraft rating sought on the subjects in which ground instruction is required. Applicants for a knowledge test must show evidence of completing ground training or a home study course and be prepared for the knowledge test.
- Pass an oral and flight test appropriate to the rating they seek, covering items selected by the inspector or examiner from those on which training is required.
- Hold at least a Private Pilot Certificate.
- Comply with the provisions of Part 61 which apply to the rating they seek.

Knowledge Exam References

The FAA references the following documents to write the FAA Knowledge Exam questions. You should be familiar with all of these as part of your ground school studies, which you should complete before starting test preparation.

FAA-H-8083-1 Aircraft Weight and Balance Handbook

FAA-H-8083-3 Airplane Flying Handbook

FAA-H-8083-11 Balloon Flying Handbook

FAA-H-8083-13 Glider Flying Handbook

FAA-H-8083-15 Instrument Flying Handbook

FAA-H-8083-21 Helicopter Flying Handbook

FAA-H-8083-25 Pilot's Handbook of Aeronautical Knowledge

FAA-H-8083-28 Aviation Weather Handbook

(Note: LTA applicants should also review FAA-H-8083-9 Aviation Instructor's Handbook, How to Fly a Balloon, Balloon Digest, Balloon Ground School, Powerline Excerpts, and Goodyear Airship Operations Manual)

FAA-S-ACS-7 Commercial Pilot Airplane Airman Certification Standards

FAA-S-ACS-12 Commercial Pilot Military Competence Airman Certification Standards

FAA-S-ACS-16 Commercial Pilot Helicopter Airman Certification Standards

AC 00-30 Atmospheric Turbulence Avoidance

AC 60-22 Aeronautical Decision Making

AC 90-48 Pilot's Role in Collision Avoidance

AC 91-13 Cold Weather Operation of Aircraft

AC 91-51 Effect of Icing on Aircraft Control and Airplane Deice and Anti-Ice Systems

Chart Supplement U.S.

Sectional Aeronautical Chart (SAC)

U.S. Terminal Procedures

Aeronautical Information Manual (AIM)

14 CFR Part 1, 23, 29, 39, 43, 61, 68, 71, 73, 91, 117, 119

49 CFR Part 830 (NTSB)

Visit asa2fly.com for these and many more titles and pilot supplies for your aviation endeavors. Visit asa2fly.com/TPC for reader resources useful to commercial pilots.

Acronyms

For reference, acronyms appearing in this book are defined below.

AC Convective Outlook AD Airworthiness Directive AD Airworthiness Directive ADC air data computer ADM aeronautical decision making ADS-B Automatic Dependent Surveillance—Broadcast AGL above ground level AGL above ground level AGL air traffic control ATIC Automatic Terminal Information Service AWC aviation weather center AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CGC center of gravity CCL center Garten CWA Center Weather Advisory ELT emergency locator transmitter FA end Automatic Information CAMI Center Weather Advisory ELT emergency locator transmitter FA error outload cannot are forecast Alert CWA Center Weather Advisory ELT emergency locator transmitter ADM E air date decision making L/D lift-to-drag ratio LAHSO land and hold short operation LHAS knots indicated airspeed L/D lift-to-drag ratio LHASO land and hold short operation LHASO Low-Level Wind Shear Alert System LLWAS Low-Level Wind Shear Alert System LLWAS land and hold short operation LHASO land and hold short operation LHASO land and hold short operation AME above ground level LOC localizer (LS) Low-Level Wind Shear Alert System LLWAS
ADC air data computer ADM aeronautical decision making ADS-B Automatic Dependent Surveillance—Broadcast AGL above ground level AGL above ground level AIRMET AIRMET AME aviation medical examiner ATIC air traffic control AUTO aviation weather center AWOS Automatic Terminal Information Service AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CEL center of indicated airspeed LAHSO land and hold short operation LLWAS Low-Level Wind Shear Alert System LOC localizer (ILS) LTA lighter than air LTE loss of tail rotor effectiveness manifold pressure maximum elevation figure aviation routine weather report aviation routine weather report AWOA Memorandum of Agreement MOA Memorandum of Agreement MSL mean sea level MIIItary Operation Area mean sea level MTR Military Training Route NMAC near midair collision NOTAM Notice to Air Missions NOTAM Notice to Air Missions NOTAM Notice to Air Missions NATSB National Transportation Safety Board OAT outside air temperature OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service PATWAS pilots' automatic telephone weather answering service PATWAS pilots' automatic telephone weather answering service
ADM aeronautical decision making ADS-B Automatic Dependent Surveillance—Broadcast AGL above ground level AGL above ground level AGL above ground level AGL above ground level AGR AIRMET airman's meteorological information AME aviation medical examiner ARTCC air traffic control center ATIS Automatic Terminal Information Service AWC aviation weather center AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CATI clear air turbulence CDI course deviation indicator CG center of gravity CCL center of Iffances. AILWAS Low-Level Wind Shear Alert System LLWAS Low-Level Wind Short operation LLWAS Low-Level Wind Shear Alert Spytem MAP manifold pressure MET Anishort operation of MET was introduced of MET anishort operation operation of MET anishort operation ope
ADS-B Automatic Dependent Surveillance—Broadcast AGL above ground level AGL Automatic marin severable was a severable with a a sever
AGL above ground level LOA Letter of Agreement AGL above ground level LOC localizer (ILS) AIRMET airman's meteorological information AME aviation medical examiner ATCC air traffic control center ATC air traffic control ATIS Automatic Terminal Information Service AWC aviation weather center AWOS Automated Surface Weather Observing System AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS Continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter EA AUSO Automated Surface Surface States CWA Center Weather Advisory ELT emergency locator transmitter LLWAS Low-Level Wind Shear Alert System LOA Letter of Agreement LOC localizer (ILS) Local
AGL above ground level AIRMET airman's meteorological information AME aviation medical examiner ARTCC air traffic control center ATC air traffic control ATIS Automatic Terminal Information Service AWC aviation weather center AWOS Automated Surface Weather Observing System AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS Continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter LOC localizer (ILS) Localizer (IS) Localizer (IS) Localizer (IS)
AGL above ground level AIRMET airman's meteorological information AME aviation medical examiner ARTCC air traffic control center ATC air traffic control ATIS Automatic Terminal Information Service AWC aviation weather center AWOS Automated Surface Weather Observing System AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS CONTINENTAL AUTOMATIC Area surant flags and the surant flags are forecast. AWOS Correct Weather Advisory ELT emergency locator transmitter AWOS Automated Surface Weather Observing MAP manifold pressure METAR aviation routine weather report METAR aviation routine weather anison figure METAR aviation routine weather figure METAR aviation routine weather anison figure METAR aviation routine weather air viation routine weather leaves of tail rotor effectiveness METAR aviation routine weather anison figure METAR aviation routine weather anison figure METAR aviation routine weather leaves of tail rotor effectiveness METAR aviation routine weather language METAR aviation routine weather anison figure METAR aviation routine weather anison figure METAR aviation routine weather air viation routine weather anison figure METAR aviation routi
AIRMET airman's meteorological information AME aviation medical examiner ARTCC air traffic control center ATC air traffic control AUC aviation weather center AWC aviation weather center AWOS Automated Surface Weather Observing System AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS CONUS CWA Center Weather Advisory ELT emergency locator transmitter AWAP manifold pressure MAP manifold pressure METAR aviation routine weather report MOA Memorandum of Agreement MOA Military Operation Area MSL mean sea level MTR Military Training Route NMTR Military Training Route NMAC near midair collision NOTAM Notice to Air Missions NOTAM Notice to Air Missions NATSB National Transportation Safety Board OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service PATWAS pilots' automatic telephone weather answering service PATWAS printers are forecast.
AME aviation medical examiner ARTCC air traffic control center ATC air traffic control ATS Automatic Terminal Information Service AWC aviation weather center AWOS Automated Surface Weather Observing System AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Cereter Weather Advisory ELT emergency locator transmitter EAC air turbulence maximum elevation figure MAP manifold pressure MAP manifold pressure manifold pressure manifold pressure manifold pressure maximum elevation figure maximum elevation figure METAR aviation routine weather report METAR aviation routine weather aviation routine weather answering selector primary flight display
ARTCC air traffic control center ATC air traffic control ATIS Automatic Terminal Information Service AWC aviation weather center AWOS Automated Surface Weather Observing System AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter EA aviation routine weather in aviation figure META aviation routine weather report MAP maximum elevation figure METAR aviation routine weather report MOA Memorandum of Agreement MOA Military Operation Area MSL mean sea level MTR Military Training Route MTR Military Training Route NIMAC near midair collision NOTAM Notice to Air Missions NTSB National Transportation Safety Board OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service ELT emergency locator transmitter PFD primary flight display
ATC air traffic control ATIS Automatic Terminal Information Service AWC aviation weather center AWOS Automated Surface Weather Observing System AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter EA aviation routine weather figure METAR aviation routine weather report MOA Memorandum of Agreement MOA Military Operation Area MSL mean sea level MTR Military Training Route NMAC near midair collision NOTAM Notice to Air Missions NTSB National Transportation Safety Board OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service ELT emergency locator transmitter EA area foregot.
ATIS Automatic Terminal Information Service AWC aviation weather center AWOS Automated Surface Weather Observing System AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter METAR aviation routine weather report MOA Military Operation Area MSL mean sea level MTR Military Training Route MTR MILITARY M
AWC aviation weather center AWOS Automated Surface Weather Observing System AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter MOA Memorandum of Agreement MOA Military Operation Area MSL mean sea level MTR Military Training Route NTR Military Training Route NTR Military Training Route NTR Military Operation Area MSL mean sea level MTR Military Operation Area MSL mean sea level MTR Military Operation Area MSL mean sea level NTR Military Training Route NTR Military Training Route NTR Military Operation Area MSL mean sea level NTR Military Training Route NTR Military Operation Area MSL mean sea level
AWOS Automated Surface Weather Observing System AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter MMAC mean sea level MTR Military Training Route MMAC near midair collision NOTAM Notice to Air Missions NTSB National Transportation Safety Board OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service PFD primary flight display
AWW Severe Weather Forecast Alert BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter MSL mean sea level MTR Military Training Route NMAC near midair collision NOTAM Notice to Air Missions NTSB National Transportation Safety Board OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service PFD primary flight display
BHP brake horsepower BTU British thermal unit CAMI Civil Aeromedical Institute CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter BTR Military Training Route NMAC near midair collision NMAC near midair collision NOTAM Notice to Air Missions NTSB National Transportation Safety Board OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service PFD primary flight display
BTU British thermal unit CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter NMAC near midair collision NOTAM Notice to Air Missions NTSB National Transportation Safety Board OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service PFD primary flight display
CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter NMAC near midair collision NOTAM Notice to Air Missions NTSB National Transportation Safety Board OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service PFD primary flight display
CAMI Civil Aeromedical Institute CAT clear air turbulence CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter NOTAM Notice to Air Missions NTSB National Transportation Safety Board OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service PFD primary flight display
CDI course deviation indicator CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter NTSB National Transportation Safety Board OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service PFD primary flight display
CG center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter CONUS course deviation indicator OAT outside air temperature OBS omni bearing selector PA pressure altitude PATWAS pilots' automatic telephone weather answering service PFD primary flight display
CL center of gravity CL center of lift CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter PA pressure altitude PATWAS pilots' automatic telephone weather answering service PFD primary flight display
CONUS continental/contiguous United States CWA Center Weather Advisory ELT emergency locator transmitter PA pressure altitude PATWAS pilots' automatic telephone weather answering service PFD primary flight display
CWA Center Weather Advisory ELT emergency locator transmitter PATWAS pilots' automatic telephone weather answering service PFD primary flight display
ELT emergency locator transmitter PFD primary flight display
FA area forecast
FA area forecast PIC pilot-in-command
FAR Federal Aviation Regulation PIREP pilot report
FB winds and temperatures aloft forecast PT procedure turn
FL flight level RAIM receiver autonomous integrity monitoring
FSDO Flight Standards District Office SIC second-in-command
FSS Flight Service Station SIGMET significant meteorological information
GFA Graphical Forecasts for Aviation SM statute mile
GMT Greenwich Mean Time TAF terminal aerodrome forecast
GPH gallons per hour TAS true airspeed
GPS Global Positioning System TC true course
HIS horizontal situation indicator TH true heading

thermal index ΤI

TIBS Telephone Information Briefing Service TIS-B Traffic Information Service-Broadcast

UAT Universal Access Transceiver

VFR visual flight rules

VHF Omnidirectional Range VOR

VOR Test Facility VOT Visual Route (MTR) VR wind correction angle WCA

WSFO Weather Service Forecast Office


ASA Test Prep Layout

Sample FAA questions have been sorted into chapters according to subject matter. Within each chapter, similar questions are grouped together following introductory chapter text. Figures referenced in the chapter text are numbered with the appropriate chapter number, e.g., "Figure 1-1" is Chapter 1's first chapter text figure.

Some sample FAA questions refer to Figures or Legends immediately following the question number, e.g., "5201. (Refer to Figure 14.)." These are FAA Figures and Legends from the Airman Knowledge Testing Supplement (FAA-CT-8080-1E) that can be found at the back of this book. This supplement will be provided to you as a separate booklet when you take your FAA test.

Following each sample FAA test question is ASA's explanation in italics. The last line of the explanation contains a Learning Statement Code (LSC), for those tests referencing an FAA Practical Test Standard (PTS), or Airman Certification Standards (ACS) code, for those tests with an ACS, as well as a reference for further study. Some questions include an explanation for the incorrect answers for added clarity. When you encounter a difficult question, find the LSC or ACS code in Cross-Reference B, and then look for material relating to the subject description within the given reference(s). Refer to Cross-Reference B for more information on how to use LSCs or ACS codes for effective studying.

Answers to each question are found at the bottom of each page.



Chapter 2 **Aircraft Systems**

Ignition System 2-3

Air-Fuel Mixture 2-4

Carburetor Ice 2-6

Aviation Fuel 2-7

Engine Temperatures 2-8

Propellers 2-9

Cold Weather Operations 2–12

Rotorcraft Systems 2-13

Glider Systems 2-29

Balloon Operations 2-37

Airship Operations 2–43

Airship IFR Operations 2-45

Ignition System

Most reciprocating engines used to power small aircraft incorporate two separate magneto ignition systems. The primary advantages of the dual ignition system are increased safety and improved engine performance.

A magneto ("mag") is a self-contained source of electrical energy, so even if an aircraft loses total electric power, the engine will continue to run. For electrical energy, magnetos depend upon a rotating magnet and a coil.

When checking for magneto operation prior to flight, the engine should run smoothly when operating with the magneto selector set on BOTH, and should experience a slight drop in revolutions per minute (RPM) when running on only one or the other magneto. The drop in RPM is caused by reduced efficiency of a single spark plug, as opposed to two.

If the ground wire between the magneto and the ignition switch becomes disconnected or broken, the engine cannot be shut down by turning off the ignition switch.

AIR. RTC

5169. Before shutdown, while at idle, the ignition key is momentarily turned OFF. The engine continues to run with no interruption; this

- A—is normal because the engine is usually stopped by moving the mixture to idle cut-off.
- B—should not normally happen. Indicates a magneto not grounding in OFF position.
- C—is an undesirable practice, but indicates that nothing is wrong.

If the magneto switch ground wire is disconnected, the magneto is ON even though the ignition switch is in the OFF position. The engine could fire if the propeller is moved from outside the airplane. (PLT478, CA.I.G.R1, CH.I.G.R1) — FAA-H-8083-25

Answer (A) is incorrect because the engine should stop when the ignition key is turned to the OFF position. Answer (C) is incorrect because this indicates there is a faulty ground wire.

AIR, RTC

5171. A way to detect a broken magneto primary grounding lead is to

- A—idle the engine and momentarily turn the ignition off.
- B—add full power, while holding the brakes, and momentarily turn off the ignition.
- C—run on one magneto, lean the mixture, and look for a rise in manifold pressure.

If the magneto switch ground wire is disconnected, the magneto is ON even though the ignition switch is in the OFF position. The engine could fire if the propeller is moved from outside the airplane. (PLT343, CA.I.G.R1, CH.I.G.R1) — FAA-H-8083-25

Answer (B) is incorrect because it is not necessary to add full power when performing the check. Answer (C) is incorrect because the way to detect a broken magneto ground wire is to turn the ignition to the OFF position; if the engine continues to run, the problem is confirmed.

AIR, RTC

5173. The most probable reason an engine continues to run after the ignition switch has been turned off is

- A—carbon deposits glowing on the spark plugs.
- B—a magneto ground wire is in contact with the engine casing.
- C—a broken magneto ground wire.

If the magneto switch ground wire is disconnected, the magneto is ON even though the ignition switch is in the OFF position. The engine could fire if the propeller is moved from outside the airplane. (PLT343, CA.I.G.R1, CH.I.G.R1) — FAA-H-8083-25

Answer (A) is incorrect because glowing carbon deposits is a result of preignition. Answer (B) is incorrect because a magneto ground wire should be in contact with the engine casing to provide grounding.

AIR, RTC

5174. If the ground wire between the magneto and the ignition switch becomes disconnected, the engine

A-will not operate on one magneto.

- B—cannot be started with the switch in the BOTH position.
- C—could accidentally start if the propeller is moved with fuel in the cylinder.

If the magneto switch ground wire is disconnected, the magneto is ON even though the ignition switch is in the OFF position. The engine could fire if the propeller is moved from outside the airplane. (PLT343, CA.I.G.R1, CH.I.G.R1) — FAA-H-8083-25

Answer (A) is incorrect because both magnetos remain on when the ground wire is disconnected. Answer (B) is incorrect because the engine can still be started, and the magnetos cannot be turned off.

Air-Fuel Mixture

Carburetors are normally set to deliver the correct air-fuel mixture (air-fuel ratio) at sea level. This air-fuel ratio is the ratio of the weight of fuel to the weight of air entering the cylinder. The ratio is determined by the setting of the mixture control in both fuel injection and carburetor-equipped engines.

When climbing, the mixture control allows the pilot to decrease fuel flow as altitude increases (air density decreases), thus maintaining the correct air-fuel ratio. If fuel flow is allowed to remain constant by not leaning the mixture, the air-fuel ratio will become too rich as the density of air decreases with increased altitude, resulting in a loss of efficiency. Operating with an excessively rich mixture may cause fouling of spark plugs.

When descending, air density increases. Unless fuel flow is increased, the mixture may become excessively lean; i.e., the weight of fuel will be too low for the weight of air reaching the cylinders. This may result in the creation of high engine temperatures and pressures.

The best power mixture is the air-fuel ratio from which the most power can be obtained for any given throttle setting.

AIR, RTC, LTA

5172. Fouling of spark plugs is more apt to occur if the aircraft

A—gains altitude with no mixture adjustment.

B—descends from altitude with no mixture adjustment.

C—throttle is advanced very abruptly.

If the air-fuel mixture is too rich, excessive fuel consumption, rough engine operation, and appreciable loss of power will occur. Because of excessive fuel, a cooling effect takes place which causes below normal temperatures in the combustion chambers. This cooling results in spark plug fouling. Unless the mixture is leaned with a gain in altitude, the mixture becomes excessively rich. (PLT343, CA.I.G.R1, CH.I.G.R1) — FAA-H-8083-25

Answer (B) is incorrect because descending without a mixture adjustment (operating with an excessively lean mixture) would result in overheating, rough engine operation, a loss of power, and detonation. Answer (C) is incorrect because advancing the throttle abruptly may cause the engine to hesitate or stop.

AIR, RTC, LTA

5176. The pilot controls the air-fuel ratio with the

A—throttle

B—manifold pressure

C-mixture control

The air-fuel ratio of the combustible mixture delivered to the engine is controlled by the mixture control. (PLT249, CA.I.G.K1e, CH.I.G.K1e) — FAA-H-8083-25

Answer (A) is incorrect because the throttle regulates the total volume of fuel and air entering the combustion chamber. Answer (B) is incorrect because the manifold pressure indicates the engine's power output.

Answers

5174 [C]

5172 [A]

5176 [C]

AIR, RTC, LTA

5187. Air-fuel ratio is the ratio between the

- A—volume of air and volume of fuel entering the cylinder.
- B—weight of air and weight of fuel entering the cylinder.
- C—weight of air and weight of fuel entering the carburetor.

The mixture control is used to change the air to fuel mixture entering the combustion chamber (cylinder). Air-fuel ratio is the weight of air to a given weight of fuel. (PLT249, CA.I.G.K1e, CH.I.G.K1e) — FAA-H-8083-25

Answer (A) is incorrect because, as altitude increases, the amount of air in a fixed volume decreases. Answer (C) is incorrect because the carburetor is where the air-fuel ratio is established prior to entering the cylinders.

AIR, RTC, LTA

5188. The mixture control can be adjusted, which

- A—prevents the air-fuel combination from becoming too rich at higher altitudes.
- B—regulates the amount of air flow through the carburetor's venturi.
- C—prevents the air-fuel combination from becoming lean as the airplane climbs.

As the aircraft climbs, the air-fuel mixture becomes richer and the excessive fuel causes the engine to lose power and to run rougher. The mixture control provides a means for the pilot to decrease fuel to compensate for this imbalance in mixture as altitude increases. (PLT343, CA.I.G.R1, CH.I.G.R1) — FAA-H-8083-25

Answer (B) is incorrect because the throttle regulates the airflow through the carburetor's venturi. Answer (C) is incorrect because the air-fuel ratio becomes richer as the aircraft climbs.

AIR, RTC, LTA

5298. The best power mixture is that air-fuel ratio at which

- A—cylinder head temperatures are the coolest.
- B—the most power can be obtained for any given throttle setting.
- C—a given power can be obtained with the highest manifold pressure or throttle setting.

The throttle setting determines the amount of air flowing into the engine. The mixture control is then adjusted to get the best air-fuel ratio, resulting in the best power the engine can develop at this particular throttle setting. (PLT249, CA.I.G.K1c, CH.I.G.K1b) — FAA-H-8083-25

Answer (A) is incorrect because the cylinder heads will be the coolest when mixture is richest. Answer (C) is incorrect because this describes the highest power setting.

AIR, RTC, LTA

5608. What will occur if no leaning is made with the mixture control as the flight altitude increases?

- A—The volume of air entering the carburetor decreases and the amount of fuel decreases.
- B—The density of air entering the carburetor decreases and the amount of fuel increases.
- C—The density of air entering the carburetor decreases and the amount of fuel remains constant.

Fuel flow remains constant if no adjustments are made. The same volume of air goes into the carburetor, but the weight and density of the air is less, causing an excessively rich mixture, which causes spark plug fouling and decreased power. (PLT249, CA.I.G.K1c, CH.I.G.K1b) — FAA-H-8083-25

AIR, RTC, LTA

5609. Unless adjusted, the air-fuel mixture becomes richer with an increase in altitude because the amount of fuel

- A—decreases while the volume of air decreases.
- B—remains constant while the volume of air decreases.
- C—remains constant while the density of air decreases.

Fuel flow remains constant if no adjustments are made. The same volume of air goes into the carburetor, but the weight and density of the air is less, causing an excessively rich mixture, which causes spark plug fouling and decreased power. (PLT249, CA.I.G.K1c, CH.I.G.K1b) — FAA-H-8083-25

AIR, RTC, LTA

5610. The basic purpose of adjusting the air-fuel mixture control at altitude is to

- A—decrease the fuel flow to compensate for decreased air density.
- B—decrease the amount of fuel in the mixture to compensate for increased air density.
- C—increase the amount of fuel in the mixture to compensate for the decrease in pressure and density of the air.

Fuel flow remains constant if no adjustments are made. The same volume of air goes into the carburetor, but the weight and density of the air is less, causing an excessively rich mixture, which causes spark plug fouling and decreased power. (PLT249, CA.I.G.K1c, CH.I.G.K1b) — FAA-H-8083-25

Answers

5187 [B]

5188 [A]

5298 [B]

5608 [C]

5609 [C]

5610 [A]

AIR, RTC, LTA

5611. At high altitudes, an excessively rich mixture will cause the

A—engine to overheat.

B—fouling of spark plugs.

C—engine to operate smoother even though fuel consumption is increased.

Fuel flow remains constant if no adjustments are made. The same volume of air goes into the carburetor, but the weight and density of the air is less, causing an excessively rich mixture, which causes spark plug fouling and decreased power. (PLT343, CA.I.G.K1c, CH.I.G.K1b) — FAA-H-8083-25

Answer (A) is incorrect because a lean mixture will cause the engine to overheat. Answer (C) is incorrect because an engine runs smoother when the mixture is adjusted for the altitude.

Carburetor Ice

As air flows through a carburetor, it expands rapidly. At the same time, fuel entering the airstream is vaporized. Expansion of the air and vaporization of the fuel causes a sudden cooling of the mixture which may cause ice to form inside the carburetor. The possibility of icing should always be considered when operating in conditions where the outside air temperature is between 20°F and 70°F and the relative humidity is high.

Carburetor heat preheats the air before it enters the carburetor and either prevents carburetor ice from forming or melts any ice which may have formed. When carburetor heat is applied, the heated air that enters the carburetor is less dense. This causes the air-fuel mixture to become enriched, and this in turn decreases engine output (less engine horsepower) and increases engine operating temperatures.

During engine run-up, prior to departure from a high-altitude airport, the pilot may notice a slight engine roughness which is not affected by the magneto check but grows worse during the carburetor heat check. In this case the air-fuel mixture may be too rich due to the lower air density at the high altitude, and applying carburetor heat decreases the air density even more. A leaner setting of the mixture control may correct this problem.

In an airplane with a fixed-pitch propeller, the first indication of carburetor ice will likely be a decrease in RPM as the air supply is choked off. Application of carburetor heat will decrease air density, causing the RPM to drop even lower. Then, as the carburetor ice melts, the RPM will rise gradually.

Fuel injection systems, which do not utilize a carburetor, are generally considered to be less susceptible to icing than carburetor systems are.

AIR, RTC, LTA

5170. Leaving the carburetor heat on while taking off

A—leans the mixture for more power on takeoff.

B—will decrease the takeoff distance.

C—will increase the ground roll.

Use of carburetor heat enriches the mixture, which tends to reduce the output of the engine and also increases the operating temperature. Therefore, the heat should not be used when full power is required (such as during takeoff) or during normal engine operations except to check for the presence of, or removal of carburetor ice. A decrease in engine output will increase distance required to reach lift off speed. Therefore, it will increase ground roll. (PLT189, CA.I.G.K1e, CH.I.G.K1e) — FAA-H-8083-25

AIR, RTC, LTA

5189. Which statement is true concerning the effect of the application of carburetor heat?

A—It enriches the air-fuel mixture.

B—It leans the air-fuel mixture.

C—It has no effect on the air-fuel mixture.

Use of carburetor heat enriches the mixture which tends to reduce the output of the engine and also increases the operating temperature. (PLT189, CA.I.G.K1e, CH.I.G.K1e) — FAA-H-8083-25

Answers

5611 [B]

AIR, RTC, LTA

5606. Applying carburetor heat will

A—not affect the mixture.

B—lean the air-fuel mixture.

C—enrich the air-fuel mixture.

Use of carburetor heat enriches the mixture which tends to reduce the output of the engine and also increases the operating temperature. (PLT343, CA.I.G.K1e, CH.I.G.K1e) — FAA-H-8083-25

Aviation Fuel

Fuel does two things for the engine; it acts both as an agent for combustion and as an agent for cooling (based on the mixture setting of the engine).

Aviation fuel is available in several grades. The proper grade for a specific engine will be listed in the aircraft flight manual. If the proper grade of fuel is not available, it is possible to use the next higher grade. A lower grade of fuel should never be used.

The use of low-grade fuel or a too lean air-fuel mixture may cause detonation, which is the uncontrolled spontaneous explosion of the mixture in the cylinder, instead of burning progressively and evenly. Detonation produces extreme heat.

Preignition is the premature uncontrolled firing of the air-fuel mixture. It is caused by an incandescent area (such as a carbon or lead deposit heated to a red hot glow) serving as an ignitor in advance of normal ignition.

Fuel can be contaminated by water and/or dirt. The air inside the aircraft fuel tanks can cool at night, which allows formation of water droplets (through condensation) on the insides of the fuel tanks. These droplets then fall into the fuel. To avoid this problem, always fill the tanks completely when parking overnight.

Thoroughly drain all of the aircraft's sumps, drains, and strainers before a flight to get rid of any water that may have collected.

Dirt can get into the fuel if refueling equipment is poorly maintained or if the refueling operation is sloppy. Use care when refueling an aircraft.

On aircraft equipped with fuel pumps, the practice of running a fuel tank dry before switching tanks is considered unwise because the engine-driven fuel pump or electric fuel boost pump may draw air into the fuel system and cause vapor lock.

AIR, RTC, LTA

5185-1. Detonation may occur at high-power settings when

- A—the fuel mixture ignites instantaneously instead of burning progressively and evenly.
- B—an excessively rich fuel mixture causes an explosive gain in power.
- C—the fuel mixture is ignited too early by hot carbon deposits in the cylinder.

Detonation or knock is a sudden explosion or shock to a small area of the piston top, rather than the normal smooth burn in the combustion chamber. (PLT115, CA.I.G.K1e, CH.I.G.K1e) — FAA-H-8083-25

Answer (B) is incorrect because detonation may occur with an excessively lean fuel mixture and a loss in power. Answer (C) is incorrect because this describes preignition.

5606 [C]

5185-1 [A]

2025-2026

Commercial Pilot TEST PREP

Tests are hard. Studying doesn't need to be.

Join millions of pilots and mechanics who chose ASA and passed their tests the first time, using the most trusted resource in FAA test preparation. Test material is expertly organized into chapters based on subject matter and includes introductory text and illustrations, questions, answer choices, answers, explanations (for correct and incorrect answers), and references for further study. Use the book to become familiar with the FAA Knowledge Exam, then use Prepware for unlimited study sessions and practice tests, and receive your test authorization (endorsement) at no additional cost!

The ASA Test Prep and Prepware software include the figures, legends, and full-color charts you'll see at the testing center. Questions cover all Commercial Pilot and Military Competency FAA Knowledge Exams and are identified by test: airplane, rotorcraft, glider, and lighter-than-air. You can also count on ASA to monitor FAA test changes and update you through a free email service.

ASA's Commercial Pilot Test Prep is the pilot's best resource for successful test-taking.

- Includes Prepware software for your computer and a 24-month subscription to Prepware Online with access from any internet-connected device
- Explanations for correct and incorrect answers, FAA references for further study, and airman test report codes for remedial study
- Figures from the FAA Airman Knowledge Testing Supplement
- Test-taking tips and quick crossreferences for easy question-finding
- Free online updates and subscription service to stay informed of test changes





Aviation Supplies & Academics, Inc. 7005 132nd Place SE Newcastle, Washington 98059 425-235-1500 | asa2fly.com

ASA-TP-C-25



Get the PREPWARE mobile app for Apple and Android devices