

SILVER STORM™ WASHABLE KEYBOARD

Model: STK503, STWK503, STK503P,
STK503RED & STWK503P

Specialized Silver Storm™ Washable, Waterproof Keyboards from Seal Shield.™ Keyboard with a natural look and feel that makes typing smooth and comfortable. Washable & dishwasher-safe keyboard is IP66-certified, compatible with medical-grade cleaners & disinfectants. USB quick connect cable with Seal Cap for easy plug and play. Laser etched keycaps enhance durability and product longevity throughout regular and vigorous cleaning.

FEATURES:



100% Waterproof
& Dishwasher Safe



Silicone Keyboard is
IP66 Certified



Contains an antimicrobial
agent to prevent microorganisms
from degrading the product



USB Quick Connect Cable
with Seal Cap™



Full-Size Numeric
Keypad and
Laser Etched Keycaps



Compatible with
Hospital Cleaners &
Disinfectants



STK503, STK503P



STK503RED



STWK503, STWK503P

MEDICAL-GRADE CLEANING CAPABILITIES

- Dishwasher-Safe (Hot & Cold settings)
- Bleach compatible. Clorox® approved.
(including Clorox HealthCare Products)
- Disinfectants & Sporicides
(including Lysol® products EPA-certified to kill COVID-19)
- Solvents, Corrosives and Acids
- Alcohol and H. Peroxide





PRODUCT DATASHEET

"25% of hospital keyboards harbor MRSA, but daily disinfecting of the keyboards could reduce risk of cross-contamination."

- Dr. William Rutala, Professor,
Division of Infectious Diseases

SILVER STORM™ WASHABLE KEYBOARD

Model: STK503, STWK503, STK503P,
STK503RED & STWK503P

TECHNICAL DATA

Compatibility:	Windows®, Mac® (USB Models)
Key Layout:	104 (US) 105 (International)
Net Dimension:	17.9in x 7.3in x 1in (45.5cm x 18.6cm x 2.6cm)
Weight:	1.32 lbs (.6 kg)
Cable Length:	6.0 feet (1.8m) with Seal Cap™
Connection Type:	Gold-plated USB (STK503, STWK503) Gold-plated PS/2 (STK503P, STWK503P)
Key Switch:	Membrane key switch with tactile feedback
Key Switch Life Cycle:	Greater than 10 million keystrokes
Key Switch Operating Force:	55 ± 10 gf
Keycaps Type:	Laser etched
Total Key Travel:	.157 ± .019 in (4 ± 0.5mm)
Operating Voltage:	+5VDC ± 5%
EMI - RFI:	Conforms to FCC Rules for Class B Computing Device
Approvals/Certifications:	IP 66, NEMA 4X, RoHS, WEEE, CE, FCC
Operating Temperature & Humidity:	Temperature: 0°C to 40° C (32°F to 104° F) Humidity: 85% RH or Less
Storage Temperature & Humidity:	Temperature: -15°C to 60° C (5°F to 104° F) Humidity: 85% RH or Less



Copyright© 2020, Seal Shield, LLC. All rights reserved. All other trademarks and trade names are those of their respective owners.

Limited 2-Year Warranty