

Specifications

Light source	650 nm Laser Diode
Scan range	Up To 500mm
Scan speed	100 scans/sec
Best resolution	0.1mm (4mils) - Code 39
Print contrast	45% or more
Reading angle	38°
Reading indicator	Green / Red LED & Beeper
Auto-sense Range	Up to 180 mm
Interface	USB or Keyboard Wedge or RS232
Symbologies	UPC/EAN/JAN, Code 39, Codabar, ITF 2/5, Code 128, Code 11, Code 93, MSI ...
Input voltage	5 VDC ± 0.5V
Current - operating	65mA max
Dimensions (L*W*H)	90 X 60 X 160 mm
Weight	110 g +/- 5 g (No cable)
Temperature-operation	0° to 50° (32° to 122°)
Temperature-storage	-20° to 60° (-4° to 140°)
Humidity-operation	10% to 85% relative humidity, non-condensing
Humidity-storage	5% to 95% relative humidity, non-condensing
Ambient Light	Sun light up to 36000 Lux
Drop Resistance	1.5m drop
Scan Range:	
4 mils	40 ~ 70 mm
5 mils	45 ~ 120 mm
13 mils	30 ~250 mm
20 mils	40 ~ 320 mm
40 mils	65 ~ 500 mm