

OPN2001

Pocket memory scanner



+ Related products



OPN2002

- Data Collector
- Pocket memory scanner
- USB, Bluetooth



OPL9725

- Data Collector
- Barcode laser scanner
- IrDA
- 1 key operation



DCL1530

- Data Collector
- Barcode laser scanner
- USB, IrDA
- Dry cell battery

Operation

- CPU: ARM7 32 bits
- O/S: Proprietary
- RTC: Supports year, month, day, hour, minute, second (leap year supported)

Memory

- FlashROM: 512 kB (Program storage + >15.000 barcodes + time stamp)
- RAM: 64 kB

Operating indicators

- Visual: 1 LEDbar (red/green/orange)
- Non-visual: Buzzer

Operating keys

- Entry options: 2 keys total,
1 clear key,
1 scan key

Communication

- USB: MiniUSB, Ver. 1.1, VCP

Power

- Rechargeable battery: Lithium-Ion 3.7 V DC, 150 mAh
- Operating time: 10.000 scans (every scan 4 sec. laser beam on / 1 sec. good read LED on)
- Data retention time: Ca. 72 hours
- Charging method: Enclosed USB cable

Barcode scanner Optics

- Light source: 650 nm visible laser diode
- Scan method: Vibrating mirror
- Scan rate: 100 scans/sec
- Reading pitch angle: -35 to 0°, 0 to +35°
- Reading skew angle: -50 to -8°, +8 to +50°
- Reading tilt angle: -20 to 0°, 0 to +20°
- Curvature: R>15 mm (EAN8), R>20 mm (EAN13)
- Min. PCS value: 0.45
- Depth of field: At PCS 0.9 UPC
60 - 570 mm / 2.36 - 22.44 in (1.0 mm / 39 mil),
40 - 360 mm / 1.57 - 14.17 in (0.5 mm / 20 mil),
40 - 220 mm / 1.57 - 8.66 in (0.25 mm / 10 mil),
40 - 120 mm / 1.57 - 4.72 in (0.15 mm / 6 mil),
50 - 100 mm / 1.97 - 3.94 in (0.127 mm / 5 mil)

Supported Symbolologies

- Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GSI-128 (EAN-128), GSI DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISMN-ISSN, Matrix 2of5, MSI/Plessey-UK/Plessey, S-Code, Telepen, Tri-Optic
- Postal code: Chinese Post, Korean Postal Authority code
- 2D code: MicroPDF417, PDF417

Durability

- Temperature in operation: -10 to 40 °C / 14 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Ambient light immunity: White 4,000 lx max, Fluorescent 4,000 lx max, Direct sun 80,000 lx max

Physical

- Dimensions (w x h x d):
30 x 62 x 16 mm / 1.18 x 2.44 x 0.63 in
- Weight body: Ca. 28 g / 1 oz (incl. battery)
- Case: ABS, Black

Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS, JIS-C-6802 Class 2, IEC 60825-1 Class 2, FDA CDRH Class II

Enclosed items

- USB cable
- Neck strap

Copyright Opticon. All rights reserved. This information is subject to change without prior notice.

Authorised Australian Distributor:
Goodson Imports Pty Ltd
142 Wicks Road
North Ryde NSW 2113
Ph: 02-8875 4544
Fax: 02-8875 4588
www.goodson.com.au

Opticon Sensors Europe B.V.
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com

OPTICON
WWW.OPTICON.COM