

Technical drawing of a square plate with the following dimensions and features:

- Overall Dimensions:** 8.00 (203.2) by 9.00 (228.6).
- Central Feature:** A large circular hole with a diameter of 4.33, which fits both 10.8 and 11.0 cm stage adapters.
- Edge Features:** 40 threaded thru holes (1/4-20 (M6)) are distributed around the perimeter.
- Internal Features:** 20 clearance holes for 1/4-20 (M6) cap screws are located in the center.
- Dimensions:**
 - Top edge: 3.00 (76.2) from left corner to first hole; 1.00 (25.4) TYP. between holes; 1.00 (25.4) TYP. from last hole to right corner.
 - Right edge: 4.50 (114.3) from top corner to first hole; 1.00 (25.4) TYP. between holes; 1.00 (25.4) TYP. from last hole to bottom corner.
 - Bottom edge: 6.00 (152.4) from right corner to last hole; 1.00 (25.4) TYP. between holes; 1.00 (25.4) TYP. from first hole to left corner.
 - Left edge: 1.00 (25.4) TYP. from top corner to first hole; 1.00 (25.4) TYP. between holes; 1.00 (25.4) TYP. from last hole to bottom corner.

Technical drawing of a square plate with various dimensions and features. The drawing includes the following specifications:

- Dimensions in parentheses reflect metric assembly features.**
- Overall dimensions:** 8.00 (14.1) by 9.00 (14.3).
- Central hole:** 1.00 (25.0) TYP.
- Outer hole:** 1.00 (25.0) TYP.
- Inner hole:** 1.00 (25.0) TYP.
- Corner hole:** 1.00 (25.0) TYP.
- Edge hole:** 1.00 (25.0) TYP.
- Threaded hole:** 1/4-20 (M6) THREADED THRU HOLE, 40 PLACES.
- Clearance:** CLEARANCE FOR 1/4-20 (M6) CAP SCREW, 20 PLACES.
- Fit:** ϕ 4.33 FITS BOTH 10.8 AND 11.0 cm STAGE ADAPTERS.
- Other dimensions:** 3.00, 4.50, 6.00 (151.59), 1.00 (25.0) TYP., .50 (14.1), .50 (14.3), .50.

Technical drawing of a square plate with various dimensions and features. The drawing includes the following specifications:

- Dimensions in parentheses reflect metric assembly features.**
- Overall dimensions:** 8.00 (14.1) by 9.00 (14.3).
- Central hole:** 1.00 (25.0) TYP.
- Outer hole:** 1.00 (25.0) TYP.
- Inner hole:** 1.00 (25.0) TYP.
- Corner hole:** 1.00 (25.0) TYP.
- Edge hole:** 1.00 (25.0) TYP.
- Threaded hole:** 1/4-20 (M6) THREADED THRU HOLE, 40 PLACES.
- Clearance:** CLEARANCE FOR 1/4-20 (M6) CAP SCREW, 20 PLACES.
- Fit:** ϕ 4.33 FITS BOTH 10.8 AND 11.0 cm STAGE ADAPTERS.
- Other dimensions:** 3.00, 4.50, 6.00 (151.59), 1.00 (25.0) TYP., .50 (14.1), .50 (14.3), .50.

Technical drawing of a square plate with various dimensions and features. The drawing includes the following specifications:

- Dimensions in parentheses reflect metric assembly features.**
- Overall dimensions:** 8.00 (14.1) by 9.00 (14.3).
- Central hole:** 1.00 (25.0) TYP.
- Outer hole:** 1.00 (25.0) TYP.
- Inner hole:** 1.00 (25.0) TYP.
- Corner hole:** 1.00 (25.0) TYP.
- Edge hole:** 1.00 (25.0) TYP.
- Threaded hole:** 1/4-20 (M6) THREADED THRU HOLE, 40 PLACES.
- Clearance:** CLEARANCE FOR 1/4-20 (M6) CAP SCREW, 20 PLACES.
- Fit:** ϕ 4.33 FITS BOTH 10.8 AND 11.0 cm STAGE ADAPTERS.
- Other dimensions:** 3.00, 4.50, 6.00 (151.59), 1.00 (25.0) TYP., .50 (14.1), .50 (14.3), .50.

Technical drawing of a square plate with various dimensions and features. The drawing includes the following specifications:

- Dimensions in parentheses reflect metric assembly features.**
- Overall dimensions:** 8.00 (14.1) by 9.00 (14.3).
- Central hole:** 1.00 (25.0) TYP.
- Outer hole:** 1.00 (25.0) TYP.
- Inner hole:** 1.00 (25.0) TYP.
- Corner hole:** 1.00 (25.0) TYP.
- Edge hole:** 1.00 (25.0) TYP.
- Threaded hole:** 1/4-20 (M6) THREADED THRU HOLE, 40 PLACES.
- Clearance:** CLEARANCE FOR 1/4-20 (M6) CAP SCREW, 20 PLACES.
- Fit:** ϕ 4.33 FITS BOTH 10.8 AND 11.0 cm STAGE ADAPTERS.
- Other dimensions:** 3.00, 4.50, 6.00 (151.59), 1.00 (25.0) TYP., .50 (14.1), .50 (14.3), .50.