

Isometric drawing of the Laser Diode Mounting Bracket with dimensions and labels:

- 2.19 x 2.19
- .25
- .63
- 2.13
- .88 SQUARE
- YAW ADJUSTMENT SCREW, FIT OR 2.0mm
- $\phi .21$ THRU HOLE BEHIND COVER, 1. UP FROM BOTTOM SURFACE CENTER FROM BACKSIDE B SIZE $\phi .632 \times 1.04$ D POCKET TO HOLD LASER DIODE.
- .51
- 2.13

Isometric drawing of the Laser Diode Mounting Bracket with dimensions and labels:

- 2.19 x 2.19
- .25
- .63
- 2.13
- .88 SQUARE
- YAW ADJUSTMENT SCREW, FIT OR 2.0mm
- $\phi .21$ THRU HOLE BEHIND COVER, 1. UP FROM BOTTOM SURFACE CENTER FROM BACKSIDE B SIZE $\phi .632 \times 1.04$ D POCKET TO HOLD LASER DIODE.
- .51
- 2.13

Isometric drawing of the Laser Diode Mounting Bracket with dimensions and labels:

- 2.19 x 2.19
- .25
- .63
- 2.13
- .88 SQUARE
- YAW ADJUSTMENT SCREW, FIT OR 2.0mm
- $\phi .21$ THRU HOLE BEHIND COVER, 1. UP FROM BOTTOM SURFACE CENTER FROM BACKSIDE B SIZE $\phi .632 \times 1.04$ D POCKET TO HOLD LASER DIODE.
- .51
- 2.13

Isometric drawing of the Laser Diode Mounting Bracket with dimensions and labels:

- 2.19 x 2.19
- .25
- .63
- 2.13
- .88 SQUARE
- YAW ADJUSTMENT SCREW, FIT OR 2.0mm
- $\phi .21$ THRU HOLE BEHIND COVER, 1. UP FROM BOTTOM SURFACE CENTER FROM BACKSIDE B SIZE $\phi .632 \times 1.04$ D POCKET TO HOLD LASER DIODE.
- .51
- 2.13

Isometric drawing of the Laser Diode Mounting Bracket with dimensions and labels:

- 2.19 x 2.19
- .25
- .63
- 2.13
- .88 SQUARE
- YAW ADJUSTMENT SCREW, FIT OR 2.0mm
- $\phi .21$ THRU HOLE BEHIND COVER, 1. UP FROM BOTTOM SURFACE CENTER FROM BACKSIDE B SIZE $\phi .632 \times 1.04$ D POCKET TO HOLD LASER DIODE.
- .51
- 2.13

Isometric drawing of the Laser Diode Mounting Bracket with dimensions and labels:

- 2.19 x 2.19
- .25
- .63
- 2.13
- .88 SQUARE
- YAW ADJUSTMENT SCREW, FIT OR 2.0mm
- $\phi .21$ THRU HOLE BEHIND COVER, 1. UP FROM BOTTOM SURFACE CENTER FROM BACKSIDE B SIZE $\phi .632 \times 1.04$ D POCKET TO HOLD LASER DIODE.
- .51
- 2.13

Isometric drawing of the Laser Diode Mounting Bracket with dimensions and labels:

- 2.19 x 2.19
- .25
- .63
- 2.13
- .88 SQUARE
- YAW ADJUSTMENT SCREW, FIT OR 2.0mm
- $\phi .21$ THRU HOLE BEHIND COVER, 1. UP FROM BOTTOM SURFACE CENTER FROM BACKSIDE B SIZE $\phi .632 \times 1.04$ D POCKET TO HOLD LASER DIODE.
- .51
- 2.13

Isometric drawing of the Laser Diode Mounting Bracket with dimensions and labels:

- 2.19 x 2.19
- .25
- .63
- 2.13
- .88 SQUARE
- YAW ADJUSTMENT SCREW, FIT OR 2.0mm
- $\phi .21$ THRU HOLE BEHIND COVER, 1. UP FROM BOTTOM SURFACE CENTER FROM BACKSIDE B SIZE $\phi .632 \times 1.04$ D POCKET TO HOLD LASER DIODE.
- .51
- 2.13

Isometric drawing of the Laser Diode Mounting Bracket with dimensions and labels:

- 2.19 x 2.19
- .25
- .63
- 2.13
- .88 SQUARE
- YAW ADJUSTMENT SCREW, FIT OR 2.0mm
- $\phi .21$ THRU HOLE BEHIND COVER, 1. UP FROM BOTTOM SURFACE CENTER FROM BACKSIDE B SIZE $\phi .632 \times 1.04$ D POCKET TO HOLD LASER DIODE.
- .51
- 2.13