

UFF0200

**UFF0200A**

W 19.7" D 26" H 37.5"
W 50.0 D 66.0 H 95.3 cm
*257 lbs / 117 kg daily at 70/50°F
*198 lbs / 90 kg daily at 90/70°F

Model	Ice type	Cooling	Electrical	Shipping Weight	Replaces Model
UFF0200A-161	Flake	Air	115v/60hz/1	168 lbs / 76 kg	RF0266A-161
UFF0200AZ-251	Flake	Air	230v/50hz/1	168 lbs / 76 kg	RF0266AZ-251

Application Storage Capacity: 50 lbs/ 23kg. Cubic volume 1.7. Storage capacity is AHRI certified.

Application storage capacity measured 90% of total volume in cu. ft x 22 lbs/ft3

Includes 6 ft / 1.8 m power cord with NEMA 5-15P plug.

Use cleaner (000000084) only with this model.

Not compatible with iAuCS® or LuminIce II.

Price list performance rating is 60hz data.

50 Hz Electric Connection: Add Z for Bare Lead cord.

UFF0350

**UFF0350A**

W 29" D 27" H 39.5"
W 73.8 D 69.0 H 100.4 cm
*350 lbs / 159 kg daily at 70/50°F
273 lbs / 125 kg daily at 90/70°F

UFF0350A-161	Flake	Air	115v/60Hz/1	224 lbs / 102 kg	RF0385A-161
UFF0350AZ-251	Flake	Air	230v/50hz/1	224 lbs / 102 kg	RF0385AZ-251

Application Ice Storage Capacity: 60 lbs/27 kg. Measured cubic volume 2.04 Storage Capacity is AHRI certified

Application storage capacity measured 90% of total volume in cu. ft x 22 lbs/ft3

Includes 6 ft / 1.8 m power cord with NEMA 5-15P plug.


Use cleaner (000000084) only with this model.

Not compatible with iAuCS or LuminIce II.

Price list performance rating is 60hz data.

50 Hz Electric Connection: Add Z for Bare Lead cord.

RFF0320



W 22" D 23.6" H 26"
W 55.9 D 59.9 H 66.0 cm

*370 lbs / 168 kg daily at 70/50°F
*287 lbs / 130 kg daily at 90/70°F

Model	Ice type	Cooling	Electrical	Shipping Weight	Replaces Model
RFF0320A-161	Flake	Air	115v/60hz/1	174 lbs / 79 kg	RFS0300A-161
RFF0320AZ-251	Flake	Air	230v/50hz/1	174 lbs / 79 kg	RFS0300AZ-251



Recommended Bins: D320 or D420 (See page 19).

See pages 22-23 for required adapters.


Use cleaner (000000084) only with this model.

Price list performance rating is 60hz data.

Not compatible with SPA/SFA dispensers, iAuCS, or LuminIce II. **Not Stackable**

50 Hz Electric Connection: Add Z for Bare Lead cord.

RFF0620



W 22" D 23.6" H 26"
W 55.9 D 59.9 H 66.0 cm

*730 lbs / 331 kg daily at 70/50°F
*530 lbs / 240 kg daily at 90/70°F

RFF0620A-161	Flake	Air	115v/60Hz/1	230 lbs / 104 kg	RFS0650A-161
RFF0620W-161	Flake	Water	115v/60Hz/1	230 lbs / 104 kg	RFS0650W-161
RFF0620AZ-251	Flake	Air	230v/50hz/1	230 lbs / 104 kg	RFS0650AZ-251
RFF0620WZ-251	Flake	Water	230v/50hz/1	230 lbs / 104 kg	RFS0650WZ-251



Recommended Bins: D320 or D420 (see page 19).

See pages 22-23 for required adapters.

Use cleaner (000000084) only with this model.

Not compatible with SPA/SFA dispensers, iAuCS, or LuminIce II. **Not Stackable**

50 Hz Electric Connection: Add Z for Bare Lead cord.

★ **ENERGY STAR® Qualified Model**

*Daily ice production based on air-cooled condenser model at air temperature/water temperature.