IC1	ΓΟ	RY.
ULT	RAS	PEC

PROJECT:	
ITEM #	_
MODEL #	

AIA # .

___ QTY: _

SIS #

EXTRA WIDE HALF-DOOR REACH-IN REFRIGERATOR

RSA-2D-S1-EW-HDHC





- **3 Year Parts & Labor Warranty**
 - Plus An Additional 4 Year Compressor Warranty
- **Exclusive 2 Year Warranty On Magnetic Door Gaskets**
- Lifetime Warranty On Handles & Hinges (Parts Only)

OPTIONS & ACCESSORIES

3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 fax: (800) 253-5168

- Secure-Temp[™] Technology
- Stainless Steel Case Back
- Stainless Steel Kick Plate
- Exterior Door Laminate
- Glass Half-Door Models
- · Door Swing Orientation (at time of order)
- Additional Shelves
- Heat Shield (left, right)
- Tray Slides (type A & A/C)
 - 3", 6" Casters Or 6" Seismic Legs

CABINET CONSTRUCTION

- Stainless Steel Exterior
- Aluminum Interior
- Stay-Open Door Feature For Easy Product Loading
- 20 Gauge Stainless Steel Door
- Magnetic Door Switch Automatically Activates Interior LED Light
- Heavy-Duty Cylinder Locks
- Stainless Steel Interior Door Liner
- One Piece, Snap-In Magnetic Door Gaskets
- Low Profile Vertical Door Handles
- **Hinged Front Shroud**
- **Energy Saving Thermal Breaker**
- Stainless Steel Breaker Caps
- Silver Freeze Wire Shelves Per Section
- 6" High Adjustable Stainless Steel Legs
- 8' Cord And Plug (see electrical data for details)

FEATURES

- Full Electronic Control With Touchpoint Interface
- **Expansion Valve Technology**
- Manager's Lockout Feature
- Anti-Condensate Door Perimeter Heaters
- Variable Speed Compressor Technology

REFRIGERATION

- Refrigeration System Uses R-290 Refrigerant To Comply With All **Environmental Concerns**
- Hot Gas Condensate Evaporator
- Adaptive Defrost For Reduced Energy Consumption And More **Consistent Product Temperatures**
- Epoxy Coated Evaporator Coil, Located Out Of The Food Zone
- Refrigerator Capable Of Maintaining Product Temperature 36°F to 38°F





Please verify qualifying units by visiting: www.energystar.gov/cfs


- FlexTemp Models Maintain Between 28°F And 38°F
- **Correctional Package**
- Remote Models* (6" legs only) (refrigerant must be specified at time of order, see note)



RSA-2D-S1-EW-HDHC







We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment. Dimensional tolerances +/- 1/4". Metric dimensions (MM)

12" Top and 3" rear clearance is required

CHARACTERISTICS		ELECTRICAL DATA		SHIPPING DETAILS	
Net Capacity	49.02	Cabinet Voltage	115/60/1	Height	88″
Width, Overall (in.)	58 3/8″	Total Amperes	6.5	Width	66″
Depth, Overall (with handles)	34 7/8″	NEMA Plug* (8' cord)	5-15P	Depth	41"
Height Overall (6" legs)	84 1/8″	REFRIGERATION DATA		Crated Weight	542 lbs
Depth, Door Open 90°	59 1/8″	Condensing Unit Size, HP*	1/3	*NOTE: Remote units are field wired and comes with 6' legs. Refrigerant must be specified at time of order.	
Door Opening (in.)	23" x 25 1/4"	Refrigerant*	R-290		
No. Of Shelves	6	Capacity (BTU/HR) (100°F/20°F)	Variable Speed Technology		

3779 Champion Blvd, Winston-Salem, NC 27105 ph: (888) 845-9800 fax: (800) 253-5168

Sales@VictoryRefrigeration.com VictoryRefrigeration.com

Rev. 6/4/20 Printed in U.S.A.

an Ali Group Company

