

FT-A+	FT-A	CTR	LEADING EDGE CONTRACTOR	CONTRACTOR
<b>The Ultimate SRL</b>	<b>The No Compromise SRL</b>	<b>Serious Workhorse. Serious Value.</b>	<b>No Frills Compliant</b>	<b>No Frills Compliant</b>
 <b>AXIS</b> AXIS-Enabled	 <b>AXIS</b> AXIS-Enabled	—	—	—
 <b>Field Repairable</b> Field repairable cable assembly	—	—	—	—
 <b>Length</b> 30' (20' and 60' to follow)	 <b>Length</b> 20' / 30' / 60'	 <b>Length</b> 20' / 30' / 60'	 <b>Length</b> 20' / 30' / 50'	 <b>Length</b> 20' / 30' / 50'
 <b>ANSI</b> Class 2	 <b>ANSI</b> Class 2	 <b>ANSI</b> Class 2	 <b>ANSI</b> Class 2	 <b>ANSI</b> Class 1
 <b>User Capacity</b> 420 lb user capacity	 <b>User Capacity</b> 420 lb user capacity	 <b>User Capacity</b> 310 lb user capacity	 <b>User Capacity</b> 310 lb user capacity	 <b>User Capacity</b> 310 lb user capacity
 <b>Housing Material</b> Composite	 <b>Housing Material</b> Composite	 <b>Housing Material</b> Composite	 <b>Housing Material</b> Glass-filled nylon	 <b>Housing Material</b> Glass-filled nylon
 <b>Lifeline</b> 7/32" galvanized wire rope	 <b>Lifeline</b> 7/32" galvanized wire rope	 <b>Lifeline</b> 7/32" galvanized wire rope	 <b>Lifeline</b> 7/32" galvanized wire rope	 <b>Lifeline</b> 3/16" galvanized wire rope
 <b>Energy Absorber</b> Ultra compact, water and UV resistant external EA	 <b>Energy Absorber</b> Ultra compact, water and UV resistant external EA	 <b>Energy Absorber</b> External EA with WrapPack Cover	 <b>Energy Absorber</b> External EA with WrapPack Cover	 <b>Energy Absorber</b> Internal brake
 <b>Label</b> UV, scratch-resistant	 <b>Label</b> UV, scratch-resistant	 <b>Label</b> Wear-resistant	 <b>Label</b> Wear-resistant	 <b>Label</b> Wear-resistant
 <b>Handle</b> Integrated / rigid carry handle	 <b>Handle</b> Integrated / rigid carry handle	 <b>Handle</b> Composite textile with integrated wire rope	 <b>Handle</b> Textile handle	 <b>Handle</b> Textile handle
 <b>Anchorage</b> Aluminum swivel anchorage	 <b>Anchorage</b> Aluminum swivel anchorage	 <b>Anchorage</b> Steel swivel anchorage	 <b>Anchorage</b> Fixed anchorage	 <b>Anchorage</b> Fixed anchorage
 <b>Worker UX</b> Optimized working / walking speed. No nuisance lock up.	 <b>Worker UX</b> Optimized working / walking speed. No nuisance lock up.	 <b>Worker UX</b> Optimized working / walking speed. No nuisance lock up.	 <b>Worker UX</b> Consistent and reliable payout	 <b>Worker UX</b> Consistent and reliable payout
 <b>Lifeline Orifice</b> Wear-resistant composite	 <b>Lifeline Orifice</b> Wear-resistant composite	 <b>Lifeline Orifice</b> Wear-resistant composite	 <b>Lifeline Orifice</b> Metal	 <b>Lifeline Orifice</b> Metal
 <b>Lifeline handle</b> Shock resistant grab handle	 <b>Lifeline handle</b> Shock resistant grab handle	 <b>Lifeline handle</b> Shock resistant grab handle	 <b>Lifeline handle</b> Shock resistant grab handle	 <b>Lifeline handle</b> Spring / Shock grab handle
 <b>Weight</b> Industry leading light weight	 <b>Weight</b> Industry leading light weight	 <b>Weight</b> Industry leading light weight	—	—