Model: WBB2224969

# Flotec Submersible Water Removal Utility Pump 1/4 HP, 1600 GPH

★★★★★ (0)




Ships within 1 Business Day

## Product Description

Multi-purpose pump for a variety of household dewatering tasks including sump draining, emptying ponds and aquariums.

**Key Features:**

- Multipurpose pump for emergency basement and sump draining, emptying ponds, appliances, wash down and roof dewatering
- Draws water down to 3/16"
- Corrosion-resistant, continuous duty submersible pump

- Switch for automatic operation sold separately

## Specifications

### Weights & Dimensions

| | |
|---|---|
| Length | 6.5 in |
| Width | 6.5 in |
| Height | 9.875 in |
| Weight | 7 lbs |
| Cord Length | 8 ft |
| Discharge Connection Size | 1 in |

### Product Details

| | |
|---|---|
| Max Fluid Temperature | 77 °F |
| Gallons per Minute | 26 gal/min |
| Float Switch | No |
| Impeller Material | Noryl |
| Material | Thermoplastic |
| Phase | 1 |
| Discharge Connection Type | Female W/ Garden Hose Adapter |
| Manufacturers Part Number | FP0S1600X-08 |
| Submersible | Yes |
| Temperature of Liquid Pumped | 77 |
| Continuous Operation | Yes |
| Brand | Flotec |

| | |
|---|---|
| Type | Submersible Utility Pump |
| Horsepower | 1/4 HP |
| Color | Black |
| Amperage | 15 A |
| Hertz | 60 Hz |
| Switch Type | Manual |
| Voltage | 115 V |
| Gallons per Hour | 1790 gal/hr |
| Includes | Garden Hose Adapter |
| Shaft Seal Material | Silicone Carbide |
| Max Pressure | 50.82 psi |

## Warranty

| | |
|---|---|
| Warranty | 1 yr |

## Compliance & Certifications

| | |
|---|---|
| Certifications | CSA, UL |