Workspace Business • Education • Facility Supplies FilingSupplies.com

we can supply that.®

Model: WBB831467

Vibration/Shock Absorption Mount, Threaded Stud, 1.00" Dia, .75"H, 1/4-20 Thread

★★★★★ (6)



Ships within 1 Business Day

Product Description

Vibration / shock absorption mounts, also known as vibration isolation mounts, anti-vibration mounts, vibration bobbins or rubber bumpers, are used as end-stop bumpers, e.g., for conveyor trolleys. They absorb most of the accumulated kinetic energy on impact. They act as dampers and prevent damaging shock and rebound. They also act as sound dampers. These mounts are also used as leveling feet.

Specifications

Weights & Dimensions

Height	0.75 in
Weight Capacity	140 Ft. Lbs. lb-ft
Spring Rate	993 Ft. Lbs./In.
Stud Length	0.50 in
Load Capacity Range	100 - 250 Ft. Lbs. lb-ft
Thread	1/4-20 in
Max Travel	0.15"
Unit of Measurement	Inch (Imperial)
Base Diameter	1.00 in

Product Details

Body Mount Material	Natural rubber (NR), Vulcanized
Color	Black
Durometer	55
Country of Origin	Import
Insert Material	Steel, Zinc Plated, Blue Passivated, Molded In
Manufacturers Part Number	352.1-25-19-1/4-55
Cover Plate Material	Steel, Zinc Plated, Blue Passivated, Molded In
Brand	J.W. Winco