Model: WBB3186064

EXCLUSIVE BRANDS | BESTSELLER

Global Industrial™ Emergency Mixing Valve, 1/2" Inlet Connection, Brass, 28 GPM

★★★★★ (0)





Ships within 1 Business Day

Product Description

✓ Precisely blends hot & cold water to deliver consistent tepid temperature
✓ Maintains a high rate in both normal and bypass modes
✓ Compatible with eyewash stations, drench showers, & dual-purpose eyewash/drench hose assemblies

Provide safer, more controlled water temperatures during emergency rinse applications with

the Global Industrial® Emergency Mixing Valve. Constructed from durable brass, this valve is designed to supply emergency wash fixtures, such as drench showers and eyewash stations, with tempered water. It delivers a high flow rate in both normal and bypass modes-even during a hot water failure-and automatically shuts off completely if cold water is lost to help prevent scalding. This unit features a wide inlet temperature range and a low minimum flow requirement, making it reliable across different climates and ideal for use in industrial facilities, warehouses, manufacturing plants, laboratories, and more.

- 125 PSI max operating pressure
- Multi-fixture compatibility
- Inlet and outlet connection: 1/2" x 14 NPT
- Ideal for facility maintenance teams, safety/EHS managers, plumbing contractors, and plant managers

Specifications

Weights & Dimensions

Inlet Connection	1/2" x 14 NPT in
Outlet Connection	1/2" x 14 NPT in

Product Details

Flow Rate	28 gal/min
Type	Emergency Valves
Material	Brass
Package Quantity	1
Color	Brass
Temperature Range Min	65°F
Manufacturers Part Number	B3186064
Temperature Range Max	95°F
Brand	Global Industrial
Max Pressure	125 psi