Model: WBB3128685

Zurn® Aquaflush® Exposed Manual Diaphragm Flush Valve w/ Sweat Solder Kit, 3.5 GPF, Chrome

★★★★★ (0)







In Stock, Ships in 3-4 days

Product Description

Manual flush valve Z6000 is ADA compliant with a non-hold-open and no leak handle feature, high back pressure vacuum breaker, one piece hex coupling nut, adjustable tailpiece, spud coupling and flange for top spud connection. Internal flush valve seals are made of chloramine resistant materials.

Engineered for performance, Zurn's Aquaflush® Exposed Manual Diaphragm Flush Valves provide consistent and reliable water closet operation. The Z6000-YB-YC features a streamlined design while providing high-level performance, unsurpassed water conservation, and long-lasting savings. Each flush valve contains a quiet GO BLUE® dual-

seal diaphragm with a clog-resistant bypass and chloramine-resistant seals for an extended lifespan and lower maintenance costs. The durable Aquaflush® series comes with a sweat solder kit and a cast wall flange. The Z6000-YB-YC has optional flush rates ranging from a boosted 4.5 gpf full flush to a water-saving 1.6 gpf. This model offers a water-saving solution for any commercial retrofit or new construction project.

Exposed, quiet diaphragm-type, chrome plated flushometer valve with a polished exterior. Complete with Zurn's AquaVantage® TPE, chloramine resistant, dual seal diaphragm with a clog resistant, triple filtered by-pass. The valve is ADA compliant with a non-hold open and no leak handle feature. Internal seals are made of chloramine resistant materials.

Features:

- Clog-resistant triple filter diaphragm
- Chemical resistant gaskets and seals for extended service life with lower maintenance costs
- Manual ADA compliant handle with no-leak seal technology
- 3-year warranty
- Proprietary Dezincification resistant low lead brass alloy
- Control Stop has internal siphon-guard protection and vandal resistant stop cap, Sweat solder kit, wall flange with set screw.
- High back pressure Vacuum Breaker with one piece hex coupling nut
- Chloramine resistant Internal seals
- Adjustable tailpiece
- Spud coupling and flange for top spud connection

Compliance and Certification:

- ADA Compliant

Specifications

Weights & Dimensions

Weight	6 lbs
Spud Size	1-1/2 in
Inlet Size	1 in

Product Details

Gallons per Flush	3.5 gal/flush
Type	Flush Valve
Color	Silver
Series	Aquaflush
For Use With	Top Spud Connection
Pressure Range	10 to 100 psi
Power Source	Manual
Country of Origin	United States
Finish	Chrome Plated
Material	Brass
Flush Type	Manual
Manufacturers Part Number	Z6000-YB-YC
Installation Type	Exposed
Spud Placement	Top
Brand	Zurn

Compliance & Certifications

ADA Compliant	Yes