
## **OVERVIEW**

Easily set the mood and enjoy your living spaces more by adjusting the brightness of fixtures containing 3-way sockets through these versatile lamps. Available in an A19 option, our 2700K bulbs deliver varying intensities of warm-hued, welcoming light by a simple twist or pull of the fixture's switch. Featuring a 25,000-hour lifespan, you'll save energy and lower bills in fixtures including ceiling fans and table lamps for years to come.

## **FEATURES**

- Versatile Use
  - Use in ceiling, decorative, and even entirely closed fixtures to deliver 3 different intensities of evenly diffused, omni-directional light
- Purable and Reliable
  Rated for use in all conditions
  including damp, indoors, and outdoors





SIMPLYCONSERVE®







DAMP-RATED



BEAM ANGLE

	2700 K	3000 K	3500 K	4000 K	5000 K	6500 K
COLOR TEMPERATURE						
GHT TYPE WARM WHITE 2700K-3000K		COOL WHITE/BRIGHT WHITE 3100 - 4500K		<b>DAYLIGHT</b> 5000K		
Light Coloration	Hues ranging from orange to yellow-white		A more neutral white light may have a slightly blue tint		Blue-white light mimicking daylight	
Ambiance Created	Cozy and inviting		Warm and welcoming		Crisp and invigorating	
Ideal Rooms/Locations	Living rooms, kitchens, and bedrooms		Bathrooms, entryways, outdoors		Basements and garages	
Ideal Applications  Table and floor lamps, p and chandeliers			Vanities and overhead lighting Task and secu			urity lighting











# 3-Way LED Lamp

L12A1927K3WAY-11



Savings Start Here™


## **ORDERING INFORMATION**


Model #	Source	WattS	Lamp Type	Operation Type	ССТ
L12A1927K3WAY-11	L = LED	4/8/12w	A19	3WAY = 3WAY Socket compatibility	2700K = 2700K

#### **SPECIFICATIONS**

	MODEL #	LUMENS	CRI	VOLTAGE	INCAND. EQUIV.	BASE
L12A	1927K3WAY-11	500/1,000/1,500	≥80	120VAC	40/75/100	E26 Med. Base

## **DIMENSIONS**





## **PRODUCT**

MODEL#	w	н
L12A1927K3WAY-11	2.36"	4.61"

## **CASE**

MODEL #	Н	W	L	Case QTY	Gross WT
L12A1927K3WAY-11	12.6"	12.6"	10.6"	50	9.4 lbs.

## **5-YEAR LIMITED WARRANTY**



AM Conservation warrants that this product is free from defects in material and workmanship for a period of 5 years from the date of the first purchase or the original distribution of the product under an energy conservation program, subject to the proper installation and/or use of the product. For full standard limited product warranty, please visit amconservation.com/warranties.