L20/30-TF22-35/50-D-ADJ-2PK L34/45-TF24-35/50-D-ADJ-2PK

OVERVIEW

The Simply Conserve® Field-Adjustable LED Troffers offer an energyefficient, modern replacement for traditional fluorescent fixtures in standard drop ceilings. Designed to fit 1" T-bar grid systems, these troffers feature selectable lumen output and color temperature to meet a range of lighting needs with a single SKU. Their sleek centerbasket design provides uniform, low-glare illumination and blends seamlessly into commercial environments such as offices, schools, healthcare facilities, and municipal buildings—delivering reliable, high-quality performance with a clean architectural look.

FEATURES

- Adjustable Output & Color Temperature Selectable lumen and CCT settings allow for on-site flexibility and simplified specification and stocking.
- · Architectural Center-Basket Design Modern center-basket housing delivers advanced light distribution with a clean aesthetic suited for visible ceiling applications.
- · Drop Ceiling Compatible

Engineered to fit standard 1" T-bar grid ceilings for quick, secure integration in new construction or retrofit installations.

· Efficient & Long-Lasting

L70-rated lifetime of 50,000 hours with high efficacy, excellent color rendering, and support for 0-10V dimming to maximize energy savings and comfort.















DIMMABLE



FLICKER-**FREE**

LIGHT TYPE	WARM W 2700K-30		COOL WHITE/B			IGHT
COLOR TEMPERATURE						
	2700 K	3000 K	3500 K	4000 K	5000 K	6500 K

Hues ranging from A more neutral white light Blue-white light **Light Coloration** orange to yellow-white may have a slightly blue tint mimicking daylight

Ambiance Created Cozy and inviting Warm and welcoming Crisp and invigorating













1701 Charleston Regional Parkway, Suite A Charleston, SC 29492 (843) 971-1414 www.AMConservation.com

Field-Adjustable LED Troffers

L20/30-TF22-35/50-D-ADJ-2PK L34/45-TF24-35/50-D-ADJ-2PK



Savings Start Here™


ORDERING INFORMATION


SOURCE	WATTAGE	LAMP TYPE	SIZE	ССТ	INC. OPTIONS
L = LED	20/30 = 20W, 25W, 30W	TF = TROFFER	22 = 2' x 2'	35/50 = 3500K, 4000K, 5000K	D = 0-10V Dimming, ADJ = Adjustable
L = LED	34/45 = 34W, 38W, 45W	TF = TROFFER	24 = 2' x 4'	35/50 = 3500K, 4000K, 5000K	D = 0-10V Dimming, ADJ = Adjustable

SPECIFICATIONS

MODEL #	WATTS	ССТ	LUMENS	VOLTAGE	CRI	DIM
L20/30-TF22-35/50-D-ADJ-2PK	20/25/30	5000K	2500/3125/3750	120-277V	≥80	0-10V
L34/45-TF24-35/50-D-ADJ-2PK	34/38/45	5000K	4250/4750/5000	120-277V	≥80	0-10V

DIMENSIONS





PRODUCT

MODEL#	L	w	н
L20/30-TF22-35/50-D-ADJ-2PK	24.3"	24"	5"
L34/45-TF24-35/50-D-ADJ-2PK	48.7"	24"	5"

CASE

MODEL #	L	W	Н	GROSS WEIGHT	CASE QTY
L20/30-TF22-35/50-D-ADJ-2PK	24.4"	24.0"	4.92"	17.4 lbs.	2
L34/45-TF24-35/50-D-ADJ-2PK	48.4"	24.0"	4.92"	27.7 lbs.	2

5-YEAR LIMITED WARRANTY



AM Conservation warrants that this product is free from defects in material and workmanship for a period of 5 years from the date of the first purchase or the original distribution of the product under an energy conservation program, subject to the proper installation and/or use of the product. For full standard limited product warranty, please visit amconservation.com/warranties.

For warranty claims, please contact: customercare@amconservation.com

To learn more, please visit: www.AMConservation.com

