

SIMPLYCONSERVE

LED LINEAR HIGH BAY

L135HBL250D



The LED Linear High Bay Series offers leading-edge efficacy and scalability for high-ceiling applications such as warehouses, distribution centers, manufacturing facilities and big box retailers. Measuring just 12 5/8" x 24", the LED luminaires deliver the high lumen output associated with traditional fluorescent and HID high bays in a form factor one-quarter the size.



PRODUCT FEATURES OVERVIEW



BEAM ANGLE



50,000 HOURS



EASY TO INSTALL



FLICKER FREE



SLIM DESIGN



5-YEAR LIMITED WARRANTY*

*AM Conservation Group, Inc. guarantees to the original purchaser or recipient of this lamp that it is free from defects in material and workmanship for five years from the date of purchase. Warranty is limited to repair or replacement of the lamp. Lamps being returned must include proof of purchase.

| | |
|------------------------|---------------|
| Rated Power (W): | 135W |
| Color Temp (CCT): | 5000K |
| Typical Lumens (lm): | 18,000 lm |
| Efficacy (lm/w): | 133 lm/w |
| Beam Angle: | 100° |
| Operation Temperature: | -4°F to 104°F |
| Storage Temperature: | -4°F to 104°F |
| Input Voltage (V): | 120-277V |
| Power Factor: | >0.9 |
| THD: | 5.44% |
| Ignition Time: | Instant On |
| Line Frequency: | 60 Hz |
| Dimmable: | 0-10V |
| Safety Certification: | ETL |

- Over 130 lumens / watt
- Indoor damp-rated
- Mounting hardware included
- This product is rated for indoor use only
- 100-277VAC 50-60Hz
- Lightweight slim design
- Operates at 130 lumens per watt
- Mounting hardware included (whip, hangers and chain)
- Driver standard with 0-10V dimming (pre-wired)
- 5000K color temperature with 80+ CRI
- Sensors are available

LED LINEAR HIGH BAY | L135HBL250D

SPECIFICATIONS BY MODEL

| ITEM # | WATTS | CCT | LM | CRI | VOLT | LIFETIME | DLC LISTED | CASE QTY |
|-------------|-------|-------|-------|-----|----------|-------------|------------|----------|
| L135HBL250D | 135W | 5000K | 18000 | >80 | 120-277v | 50,000 Hrs. | Yes | 1 |

MODEL SELECTION

| FAMILY | WATTAGE | TYPE | SIZE | CCT. | OPERATION |
|---------|--|---|--------------------|--|--------------|
| L = LED | 135 = 135W 174 = 174W 223 = 223W | HBL = High Bay Linear HBU = High Bay UFO | 2 = 2FT 4 = 4FT | 30 = 3000K 40 = 4000K 50 = 5000K | D = Dimmable |

DIMENSIONS

| PRODUCT | PACKAGING |
|---------|--|
| | <p>Case</p> <p>12 13/16"</p> <p>25 7/16"</p> <p>2 1/2"</p> <p>1/Master Case</p> <p>Net WT: 9.5 LBS Gross WT: 9.5 LBS</p> |