

ADJUSTABLE STRIP LIGHT

OVERVIEW

Simply Conserve's field-adjustable linear strip fixture includes two switches inside the unit which allow for adjustment of the input power, 30W/40W/50W and color temperature 3500K/4000K/5000K. Push-button lens cover releases allow for tool-free access to adjust settings and wire connections. Lens is supported with aircraft cable to prevent the lens from falling. This versatile product is suitable for a variety of applications including retail, offices, warehouses, stairwells, and garages.

KEY FEATURES

- Field-adjustable lumen and CCT
- L70-rated lifetime of 50,000 hours
- 0-10V dimmable
- 3/4" knockouts for easy daisy-chaining or control addition
- Toll-less lens cover removal
- UL-damp location listed







EASY TO

FIELD-**ADJUSTABLE**

L30/50-STRP-35/50-4FT-D-ADJ-120/277

0-4-1	Type
Catalog #	
Project	
Comments	Date
Prepared by	











ORDERING INFORMATION

SOURCE	WATTAGE	FIXTURE TYPE	ССТ	SIZE	INC. OPTIONS	VOLTAGE
L = LED	30/50 = 30W,	STRP = Strip	35/50 = 3500K,	4FT = 4 Ft.	D = Dimmable	120/277 =
	40W, 50W	Fixture	4000K, 5000K	Nominal	ADJ = Adjustable	120-277V



ADJUSTABLE STRIP LIGHT

SPECIFICATIONS

L30/50-STRP-35/50-4FT-D-ADJ-120/277


CATALOG #	WATTS	CCT	LUMENS	EFFICACY	CRI	VOLTAGE	DIM
L30/50-STRP-35/50-4FT- D-ADJ-120/277	30/40/50	35/40/50K	3900/5200/6500	130 LPW	>80	120-277V	0-10V

SPECIFICATIONS


IMAGE	CATALOG #	DESCRIPTION			
	N/A	Surface mounting kit (included)			
	STRP-SKIT-4FT	4-ft suspended mounting kit, 5-ft adjustable length			

DIMENSIONS

PRODUCT



CASE



CATALOG #	L	W	Н	
L30/50-STRP-35/50-	48"	3"	3.3"	
4FT-120/277-D-ADJ	40			

CATALOG #	L	W	Н	CASE QTY	GROSS WT
L30/50-STRP-35/50-D- ADJ-4FT-120/277	49.4"	10.8"	8.66"	6	26.5 lbs.

5 -Year Limited Warranty



AM Conservation Group ("AMCG") warrants this product to be free from manufacturing defects for a period of five years from the date of consumer purchase or distribution by an energy conservation program, and has been properly installed, AMCG will replace the strip light free of charge.

For warranty claims, please contact:

customercare@amconservationgroup.com

To learn more, please visit:

www.amconservationgroup.com

