SIMPLYCONSERVE®

OVERVIEW

Our LED Globe Lamps replace incandescent bulbs to reduce energy use by 75% while maintaining decorative appeal. Ideally suited for residential, hospitality, and commercial environments, these lamps produce soft, evenly diffused light—creating a gentle and ambient glow for adding elegance to bathrooms, bars, and restaurants. Use in chandeliers, decorative fixtures, wall sconces, and vanity fixtures for years of beauty, energy savings, and lower utility bills.

FEATURES

· 25,000-Hour Lifespan

This lamp's rated average life expectancy is equal to 23 years when used 3 hours/day.

• Dimmable To Create The Perfect Atmosphere

Adjust brightness levels to set the ideal mood when paired with a dimmer switch.

· Quick Install Contractor Packs

Available in larger quantity case and bulk packs to make installations economical, quick, and convenient for contractors.

· Welcoming Light For Every Occasion

2700K temperature provides a soft-white (yellowish) glow ideal for living rooms, dining rooms, bedrooms, and bathrooms. Or select our 5000K bulb for a more invigorating, daylight option.







25,000 HOURS

DIMMABLE

MERCURY FREE

2700 K

COLOR TEMPERATURE				
LIGHT TYPE	WARM WHITE 2700K-3000K	COOL WHITE/BRIGHT WHITE 3100 - 4500K	DAYLIGHT 5000K	
Light Coloration	Hues ranging from orange to yellow-white	A more neutral white light may have a slightly blue tint	Blue-white light mimicking daylight	
Ambiance Created	Cozy and inviting	Warm and welcoming	Crisp and invigorating	
Ideal Rooms/Locations	Living rooms, kitchens, and bedrooms	Bathrooms, entryways, outdoors	Basements and garages	
Ideal Applications	Table and floor lamps, pendants, and chandeliers	Vanities and overhead lighting	Task and security lighting	

3500 K

4000 K

5000 K

3000 K











6500 K

LED Globe Lamps



Savings Start Here™


ORDERING INFORMATION


SOURCE	WATTAGE	LAMP TYPE	сст
L = LED	06 = 6W	G25 = G25 GLOBE LAMP	27K = 2700K 50K = 5000K

SPECIFICATIONS

MODEL #	WATTS	ССТ	LUMENS	INCAND EQUIV.	CRI	VOLTAGE
LH06G252700K	6W	2700K	450	40W	≥80	120
LH06G252700KC60	6W	2700K	450	40W	≥80	120
L06G252700KC60-7	6W	2700K	450	40W	≥80	120
L06G2527K-7	6W	2700K	450	40W	≥80	120
L06G2550K-7	6W	5000K	450	40W	≥80	120

DIMENSIONS





PRODUCT

MODEL #	н	w
LH06G252700K	5"	3.1"
LH06G252700KC60	5"	3.1"
L06G252700KC60-7	5"	3.1"
L06G2527K-7	5"	3.1"
L06G2550K-7	5"	3.1"

CASE

MODEL#	L	w	н	GROSS WEIGHT	CASE QTY	CONTRACTOR PACKS
LH06G252700K	14"	11.1"	10.7"	5.55 lbs.	24	
LH06G252700KC60	19.9"	16.7"	10.7"	10.15 lbs.	60	√
L06G252700KC60-7	19.9"	16.7"	10.7"	10.15 lbs.	60	✓
L06G2527K-7	14"	10.7"	10.7"	5.55 lbs.	24	
L06G2550K-7	14"	10.7"	10.7"	5.55 lbs.	24	

LIMITED 5-YEAR WARRANTY



AM Conservation warrants that this product is free from defects in material and workmanship for the lifetime of the product from the date of the first purchase or the original distribution of the product under an energy conservation program, subject to the proper installation and/or use of the product. For full standard limited product warranty, please visit amconservation.com/warranties.

