LED PAR Lamps

OVERVIEW

Whether you're spotlighting art, landscaping, or creating a warm, inviting atmosphere, Simply Conserve® PAR 30 LED bulbs are your go-to solution for reliable and beautiful illumination. With concentrated 40° beam angles, they deliver precise illumination, directing focused, even light exactly where it's desired. Pair with a dimmer switch for additional dramatic effect. Medium bases with both standard and short neck options ensure easy installation and proper fitment in both shallow and deeply recessed fixtures without compromising aesthetics.

FEATURES

- Long-Lasting Convenience
 Boasting a 25,000-hour lifespan, you'll forget when you installed them.
- Suitable For All Your Lighting Needs
 Ideal for ceiling lighting—even in damp locations.
- Customize Your Lighting
 Pair with a dimmer switch to adjust room ambiance while saving even more energy.







DIMMABLE



MERCURY FREE



	2700 K	3000 K	3500 K	4000 K	5000 K	6500 K	
COLOR TEMPERATURE							
LIGHT TYPE	WARM WHITE 2700K-3000K		COOL WHITE/BI 3100 - 4		DAYLIGHT 5000K		
Light Coloration	Hues ranging from orange to yellow-white		A more neutral may have a slig	0	Blue-white light mimicking daylight		
Ambiance Created	Cozy and inviting		Warm and w	elcoming	Crisp and invigorating		
Ideal Rooms/Locations	Living rooms, kitchens, and bedrooms		Bathrooms, entry	ways, outdoors	Basements and garages		
Ideal Applications	Table and floor lamps, pendants, and chandeliers		Vanities and ove	rhead lighting	Task and security lighting		











1701 Charleston Regional Parkway, Suite A Charleston, SC 29492 (843) 971-1414 www.AMConservation.com

LED PAR Lamps





Savings Start Here™

SPECIFICATIONS

MODEL #	BASE TYPE	NECK TYPE	WATTS	ССТ	LUMENS	CRI	DIMMABLE	INCAN. EQUIV.	VOLTAGE	UL LISTING
LPAR20D7W27KV11	E26	STANDARD	7W	2700K	500	≥80	\checkmark	50W	120V	DAMP LOCATION
LPAR30DSN11W-27	E26	SHORT	11W	2700K	850	≥80	✓	75W	120V	DAMP LOCATION
LPAR30DW11W-27K	E26	STANDARD	11W	2700K	850	≥80	✓	75W	120V	DAMP LOCATION
LPAR30DW11W-50K	E26	STANDARD	11W	5000K	850	≥80	✓	75W	120V	DAMP LOCATION
LPAR38D15W-27K	E26	STANDARD	15W	2700K	1250	≥80	✓	120W	120V	WET LOCATION
LPAR38D15W-50K	E26	STANDARD	15W	5000K	1250	≥80	✓	120W	120V	WET LOCATION

DIMENSIONS





PRODUCT

MODEL #	н	w
LPAR20D7W27KV11	3.4"	2.5"
LPAR30DSN11W-27	3.7"	3.8"
LPAR30DW11W-27K	4.7"	3.9"
LPAR30DW11W-50K	4.7"	3.9"
LPAR38D15W-27K	5.08"	4.72"
LPAR38D15W-50K	5.08"	4.72"

CASE

MODEL #	L.	w	н	GROSS WEIGHT	CASE QTY
LPAR20D7W27KV11	13.6"	13.4"	7.8"	8.8 lbs	50
LPAR30DSN11W-27	12"	15.8"	8.6"	8.35 lbs.	24
LPAR30DW11W-27K	15.9"	11.9"	10.2"	10.16 lbs	24
LPAR30DW11W-50K	15.7"	11.8"	8.3"	8.35 lbs	24
LPAR38D15W-27K	15.5"	20.6"	13.2"	24 lbs.	24
LPAR38D15W-50K	15.5"	20.6"	13.2"	24 lbs.	24

5-YEAR LIMITED WARRANTY



AM Conservation warrants that this product is free from defects in material and workmanship for a period of 5 years from the date of the first purchase or the original distribution of the product under an energy conservation program, subject to the proper installation and/or use of the product. For full standard limited product warranty, please visit amconservation.com/warranties.