LED T5 Type A

L25T5G40A-25PK L25T5G50A-25PK

25W 54W T5HO REPLACEMENT



Simply Conserve® T5 Type A LEDs offers a true plug-and-play retrofit solution for upgrading linear fluorescent fixtures—no rewiring or additional labor required. Engineered for compatibility with T5HO program start electronic ballasts, it delivers over 3,500 lumens of bright, efficient light. Its reliable construction ensures safe installation while helping reduce maintenance and overall operating costs.



FEATURES

· Durable Glass Tube Construction

Built with high-quality glass for enhanced durability, optical clarity, and resistance to warping or discoloration over time.

· Plug-and-Play T5HO Replacement

Designed for direct compatibility with existing T5HO systems using program start electronic ballasts—no rewiring needed.

· Long 50,000-Hour Rated Life

Delivers lasting performance and reduced maintenance costs with an extended service life of up to 50,000 hours.

Versatile for Dry and Damp Locations

Rated for use in both dry and damp environments, offering installation flexibility across a variety of settings.

UL Compliant for Safety and Reliability

Meets UL1993 and UL8750 standards, ensuring safe performance and compliance with industry regulations.



BFAM

ANGLE



50,000 HOURS



TRUE COLOR



FLICKER-FREE



EASY TO INSTALL

ORDERING INFORMATION

MODEL#	SOURCE	WATTAGE	LAMP TYPE	сст
L25T5G40A-25PK	L = LED Linear	25 = 25W	T5 = T5 Tube	40 = 4000K
L25T5G50A-25PK	L = LED Linear	25 = 25W	T5 = T5 Tube	50 = 5000K













LED T5 Type A

L25T5G40A-25PK L25T5G50A-25PK





Savings Start Here™

SPECIFICATIONS

MODEL#	WATTS	сст	LUMENS	EFFICACY	CRI	VOLTAGE	DIM
L25T5G40A-25PK	25W	4000K	3500	125 LPW	≥80	120-277V	No
L25T5G50A-25PK	25W	5000K	3500	125 LPW	≥80	120-277V	No

DIMENSIONS





PRODUCT

MODEL #	L	DIA
L25T5G40A-25PK	45.8"	0.7"
L25T5G50A-25PK	45.8"	0.7"

CASE

MODEL #	L	w	Н	GROSS WEIGHT	CASE QTY
L25T5G40A-25PK	47.3"	5.1"	5.1"	8 lbs.	25
L25T5G50A-25PK	47.3"	5.1"	5.1"	8 lbs.	25

5-YEAR LIMITED WARRANTY



AM Conservation warrants that this product is free from defects in material and workmanship for a period of 5 years from the date of the first purchase or the original distribution of the product under an energy conservation program, subject to the proper installation and/or use of the product. For full standard limited product warranty, please visit amconservation.com/warranties.