Illuminate your path to safety and savings with our dependable, versatile, 120/277 volt Simply Conserve Exit Sign. Featuring LED technology to reduce energy use by 90%, selectable red or green illumination options, a battery backup lasting 90 minutes, and flame-resistant construction, this sign is sure to shine when you need it most. Flexible single and dual sided mounting options for wall and ceiling applications combined with selectable directional arrows enable easy installation just about anywhere. Durably designed for greater reliability, the Simply Conserve LED Exit Sign is backed with a 3-year warranty.



SIMPLYCONSERVE®

FEATURES

- +90% Energy Savings
 Significant savings vs. 18W CFL exit signs.
- Single or Dual Sided, Red or Green Illumination
 Ultra bright RED or GREEN LEDs can be displayed as a single or double face.
- Versatile Installation Options
 Universal JBox attachment and selectable directional arrows for ceiling or wall mount applications.
- Integrated Backup Battery
 90-minute runtime for continuous illumination when the power goes out.
- Durable Design
 120/277 Volt. Impact and flame-resistant construction.
 32° F 100° F environmental operating range for indoor use.

ORDERING INFORMATION

MODEL#	SOURCE	FIXTURE TYPE	FEATURE	LETTER COLOR	EMERGENCY MODE	PACKAGING
LEDEXT-DF-RED/GRN-BB-US	LED = Light Emitting Diode	EXT = Exit Sign	DF = Dual Face Option	RED = Red Letters, GRN = Green Letters	BB = 90min Battery Backup	US = Retail Color Packaging

















Savings Start Here™

SPECIFICATIONS

MODEL #	INPUT POWER	INDICATORS	VOLTAGE	MOUNTING	BATTERY BACKUP
LEDEXT-DF-RED/ GRN-BB-US	1W	Left, Right, Both, Or Neither	120/277V	Ceiling or Wall	90 minutes

DIMENSIONS





PRODUCT

MODEL #	L	w	н
LEDEXT-DF-RED/ GRN-BB-US	11.6"	1.8"	7.2"

CASE

MODEL #	L	w	н	GROSS WT	CASE QTY.	
LEDEXT-DF-RED/ GRN-BB-US	15.6"	12.8"	8.9"	14.1 lbs	6	

3-YEAR WARRANTY



AM Conservation warrants that this product is free from defects in material and workmanship for a period of 3 years from the date of the first purchase or the original distribution of the product under an energy conservation program, subject to the proper installation and/or use of the product. For full standard limited product warranty, please visit amconservation.com/warranties.

For warranty claims, please contact: customercare@amconservation.com

To learn more, please visit: www.amconservation.com

