

Application Instructions for Flamecheck All Weather



DIRECTIONS FOR USE: Flamecheck All Weather is a universal flame retardant for exterior wooden surfaces. Flamecheck All Weather is similar to Flamecheck M-111 but has an added waterproofing agent. Flamecheck All Weather is non-toxic, non-allergenic and environmentally friendly.

Application Instructions: Spray onto absorbent wooden surface, before it dries, apply 2nd coat. Flamecheck M-111 may be used for the 1st coat then use Flamecheck All Weather as your 2nd coat if it dries too quickly. You must apply 2 coats of flame-retardant to give a “Class A” fire-retardant finish by ASTM E-84 standards. Always test to verify the best application procedure for your intended use. Use application instructions for a semi-transparent stain, so that overlapping marks are not left on the surface being treated.

Coverage: 300 sq. ft. per gallon.

Tools: Hand sprayer or airless spray gun (0.15” orifice) is recommended. A professional paintbrush, roller or dipping the wood are acceptable application techniques.

Surface Prep: Material should be clean and dry, free from grease. Test the wood for absorbency, All Weather must absorb into the surface to be effective.

Safety: Use common sense precautions, dust mask, eye protection, rubber gloves/apron.

Dry time: Similar to water depending on temperature and humidity.

Certification: May require application by a certified applicator; CA, NY, and MA.

Test: Always test to verify your application is successful. On a test piece of wood, treat and let dry. Hold a flame to the wood to verify that your application has allowed enough Flamecheck All Weather to absorb in and does not support any flame spread and self-extinguishes when flame is removed. Test waterproof barrier annually, retreat if necessary.

Disclaimer: Flamecheck makes no guarantee, nor any express or implied warranty of merchantability or fitness for a particular use regarding the suitability of this product for any particular purpose or use, nor does it assume any liability arising out of the application or mis-use of this product. Application techniques vary; therefore, it is the end user’s responsibility to test and verify the application techniques and suitability of this product for the intended use. Always test after application. Flamecheck International LLC only warrants the quality control of this product. For the complete disclaimer regarding this product, visit www.flamecheck.com

Keep out of the reach of children. Ingestion of this product, or contact with eyes or skin, can result in serious injury. Use in a well-ventilated area. If swallowed CONTACT A MEDICAL PROFESSIONAL IMMEDIATELY. Contact with eyes or skin, flush with copious amounts of water for 15 minutes. If irritation persists, seek medical attention. **Never give anything by mouth to an unconscious person.**

REFER TO OUR WEBSITE AT www.flamecheck.com FOR ADDITIONAL IMPORTANT INFORMATION.

CERTIFICATES

Flamecheck All Weather meets or exceeds a “Class A” finish when properly applied for these test standards:

- ✓ ASTM E-84
- ✓ ASTM E-108

