

# Application Instructions for Flamecheck™ M-111PA



Flamecheck™ M-111PA is a paint additive for latex/acrylic paint.

*Flamecheck M-111PA meets or exceeds ASTM E-84 test with a “Class A” rating; ZERO flame spread and ZERO Smoke*

## DIRECTIONS FOR USE:

**Coverage:** Approximately 350-400 sq. ft. per coat per gallon. Two coats or 2 mils thickness is required to achieve “Class A” finish.

**Mix:** One 8-ounce bottle of Flamecheck™ M-111PA with 1 (US) Gallon of latex paint. It may be necessary to use a larger container to mix the full 8 ounces into a gallon of paint. **Do Not Dilute. Mix thoroughly.**

**Tools:** Airless spray gun is recommended. Smaller applications may use a high-quality paint brush, or a professional paint roller.

**Surface Preparations:** Be sure the substrate you are treating is clean and free of dust, grease and unsightly spots. Surface area must be a paintable surface. Flamecheck M-111PA passes ASTM E-84 as “Class A” with ZERO flame spread and ZERO smoke over nonflammable substrate. Treat flammable substrates (if porous) with Flamecheck M-111 and allow to dry before painting for additional protection.

**Dry Time:** 2 hours to touch. May take up to 24-48 hours depending on humidity, temperature and thickness of coating to cure.

**Always test before using:** If Flamecheck™ M-111PA changes the consistency of the paint (thick or curdled) it is incompatible with that paint, do not use. Metallic paints may change color weeks after being treated.

**SAFETY:** Use common sense precautions, dust mask, eye protection, rubber gloves/apron. Cover electrical devices and heating and cooling vents.

**Disclaimer:** Flamecheck makes no guarantee, nor any express or implied warranty of merchantability or fitness for a particular use regarding the suitability of this product for any particular purpose or use, nor does it assume any liability arising out of the application or mis-use of this product. Application techniques vary; therefore, it is the end user’s responsibility to test and verify the application techniques and suitability of this product for the intended use. Always test after application. Flamecheck International LLC only warrants the quality control of this product. For the complete disclaimer regarding this product, visit [www.flamecheck.com](http://www.flamecheck.com).

**Keep out of the reach of children.** Ingestion of this product, or contact with eyes or skin, can result in serious injury. Use in a well-ventilated area. If swallowed CONTACT A MEDICAL PROFESSIONAL IMMEDIATELY. Contact with eyes or skin, flush with copious amounts of water for 15 minutes. If irritation persists, seek medical attention. Never give anything by mouth to an unconscious person.

**REFER TO OUR WEBSITE AT [www.flamecheck.com](http://www.flamecheck.com) FOR ADDITIONAL IMPORTANT INFORMATION.**



## CERTIFICATES

Flamecheck™ M-111PA meets or exceeds a “Class A” finish when properly applied for this test standard:

- ✓ ASTM E-84
  - ZERO Smoke
  - Zero Flame Spread

